



An Object Oriented Finite Element Library

Reference Guide

Release 4.0.0

Rachid Touzani
Laboratoire de Mathématiques Blaise Pascal
Université Clermont Auvergne, France
e-mail: rachid.touzani@uca.fr

Contents

1	Module Index	3
1.1	Modules	3
2	Namespace Index	5
2.1	Namespace List	5
3	Hierarchical Index	7
3.1	Class Hierarchy	7
4	Class Index	11
4.1	Class List	11
5	Module Documentation	17
5.1	General Purpose Equations	17
5.2	Conservation Law Equations	22
5.3	Electromagnetics	23
5.4	Fluid Dynamics	24
5.5	Interface Problems	25
5.6	Laplace equation	26
5.7	Porous Media problems	27
5.8	Solid Mechanics	28
5.9	Heat Transfer	29
5.10	Input/Output	30
5.11	Utilities	31
5.12	Vector and Matrix	66
5.13	Physical properties of media	77
5.14	Global Variables	78
5.15	Finite Element Mesh	81
5.16	Shape Function	100
5.17	Solver	101
5.18	OFELI	117
6	Namespace Documentation	163
6.1	OFELI Namespace Reference	163
7	Class Documentation	187
7.1	AbsEqua< T_ > Class Template Reference	187
7.2	Bar2DL2 Class Reference	191
7.3	Beam3DL2 Class Reference	195
7.4	BiotSavart Class Reference	198
7.5	BMatrix< T_ > Class Template Reference	203
7.6	Brick Class Reference	207
7.7	Circle Class Reference	209

7.8	DC1DL2 Class Reference	210
7.9	DC2DT3 Class Reference	213
7.10	DC2DT6 Class Reference	218
7.11	DC3DAT3 Class Reference	221
7.12	DC3DT4 Class Reference	224
7.13	DG Class Reference	228
7.14	DMatrix< T_ > Class Template Reference	229
7.15	Domain Class Reference	240
7.16	DSMatrix< T_ > Class Template Reference	245
7.17	EC2D1T3 Class Reference	253
7.18	EC2D2T3 Class Reference	255
7.19	Edge Class Reference	256
7.20	EdgeList Class Reference	259
7.21	EigenProblemSolver Class Reference	260
7.22	Elas2DQ4 Class Reference	266
7.23	Elas2DT3 Class Reference	269
7.24	Elas3DH8 Class Reference	273
7.25	Elas3DT4 Class Reference	275
7.26	Element Class Reference	277
7.27	ElementList Class Reference	285
7.28	Ellipse Class Reference	286
7.29	Equa_Electromagnetics< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference	287
7.30	Equa_Fluid< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference	288
7.31	Equa_Laplace< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference	290
7.32	Equa_Porous< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference	292
7.33	Equa_Solid< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference	295
7.34	Equa_Therm< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference	297
7.35	Equation< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference	300
7.36	Estimator Class Reference	310
7.37	FastMarching2D Class Reference	314
7.38	FEShape Class Reference	315
7.39	Figure Class Reference	317
7.40	FMM2D Class Reference	318
7.41	FMM3D Class Reference	320
7.42	FMMSolver Class Reference	322
7.43	Funct Class Reference	324
7.44	Gauss Class Reference	326
7.45	Grid Class Reference	328
7.46	HelmholtzBT3 Class Reference	330
7.47	Hexa8 Class Reference	331
7.48	ICPG1D Class Reference	333
7.49	ICPG2DT Class Reference	338
7.50	ICPG3DT Class Reference	342
7.51	Integration Class Reference	345
7.52	IOField Class Reference	347
7.53	IPF Class Reference	349
7.54	Iter< T_ > Class Template Reference	358
7.55	Laplace1DL2 Class Reference	359
7.56	Laplace1DL3 Class Reference	361
7.57	Laplace2DT3 Class Reference	363
7.58	Laplace2DT6 Class Reference	366
7.59	LaplaceDG2DP1 Class Reference	368
7.60	LCL1D Class Reference	370
7.61	LCL2DT Class Reference	374

7.62	LCL3DT Class Reference	376
7.63	Line2 Class Reference	379
7.64	Line3 Class Reference	381
7.65	LinearSolver< T_ > Class Template Reference	382
7.66	LocalMatrix< T_, NR_, NC_ > Class Template Reference	388
7.67	LocalVect< T_, N_ > Class Template Reference	394
7.68	LPSolver Class Reference	400
7.69	Material Class Reference	403
7.70	Matrix< T_ > Class Template Reference	405
7.71	Mesh Class Reference	415
7.72	MeshAdapt Class Reference	434
7.73	Muscl Class Reference	439
7.74	Muscl1D Class Reference	443
7.75	Muscl2DT Class Reference	444
7.76	Muscl3DT Class Reference	445
7.77	MyNLAS Class Reference	446
7.78	MyOpt Class Reference	448
7.79	NLASSolver Class Reference	449
7.80	Node Class Reference	455
7.81	NodeList Class Reference	459
7.82	NSP2DQ41 Class Reference	461
7.83	ODESolver Class Reference	463
7.84	OFELIException Class Reference	473
7.85	OptSolver Class Reference	473
7.86	Partition Class Reference	481
7.87	Penta6 Class Reference	485
7.88	PhaseChange Class Reference	487
7.89	Point< T_ > Class Template Reference	488
7.90	Point2D< T_ > Class Template Reference	491
7.91	Polygon Class Reference	494
7.92	Prec< T_ > Class Template Reference	495
7.93	Prescription Class Reference	500
7.94	Quad4 Class Reference	502
7.95	Reconstruction Class Reference	504
7.96	Rectangle Class Reference	505
7.97	Side Class Reference	507
7.98	SideList Class Reference	513
7.99	SkMatrix< T_ > Class Template Reference	514
7.100	SkSMMatrix< T_ > Class Template Reference	522
7.101	Sphere Class Reference	531
7.102	SpMatrix< T_ > Class Template Reference	533
7.103	SteklovPoincare2DBE Class Reference	536
7.104	Tabulation Class Reference	538
7.105	Tetra4 Class Reference	539
7.106	Timer Class Reference	541
7.107	TimeStepping Class Reference	542
7.108	TINS2DT3S Class Reference	548
7.109	TINS3DT4S Class Reference	550
7.110	Triang3 Class Reference	552
7.111	Triang6S Class Reference	554
7.112	Triangle Class Reference	556
7.113	triangle Class Reference	558
7.114	TrMatrix< T_ > Class Template Reference	559
7.115	Vect< T_ > Class Template Reference	561

7.116WaterPorous2D Class Reference	589
--	-----

Chapter 1

Module Index

1.1 Modules

Here is a list of all modules:

OFELI	117
General Purpose Equations	17
Conservation Law Equations	22
Electromagnetics	23
Fluid Dynamics	24
Interface Problems	25
Laplace equation	26
Porous Media problems	27
Solid Mechanics	28
Heat Transfer	29
Input/Output	30
Utilities	31
Physical properties of media	77
Global Variables	78
Finite Element Mesh	81
Shape Function	100
Solver	101
Vector and Matrix	66

Chapter 2

Namespace Index

2.1 Namespace List

Here is a list of all documented namespaces with brief descriptions:

OFELI	A namespace to group all library classes, functions, ..	163
-------	---	-----

Chapter 3

Hierarchical Index

3.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

AbsEqua< T_ >	187
Equation< T_, NEN_, NEE_, NSN_, NSE_ >	300
Equa_Electromagnetics< T_, NEN_, NEE_, NSN_, NSE_ >	287
Equa_Fluid< T_, NEN_, NEE_, NSN_, NSE_ >	288
Equa_Laplace< T_, NEN_, NEE_, NSN_, NSE_ >	290
Equa_Porous< T_, NEN_, NEE_, NSN_, NSE_ >	292
Equa_Solid< T_, NEN_, NEE_, NSN_, NSE_ >	295
Equa_Therm< T_, NEN_, NEE_, NSN_, NSE_ >	297
AbsEqua< complex.t >	187
Equation< complex.t, NEN_, NEE_, NSN_, NSE_ >	300
Equa_Electromagnetics< complex.t, 3, 3, 2, 2 >	287
EC2D1T3	253
HelmholtzBT3	330
AbsEqua< double >	187
Equation< double, NEN_, NEE_, NSN_, NSE_ >	300
Equa_Solid< double, 8, 24, 4, 12 >	295
Elas3DH8	273
AbsEqua< real.t >	187
Equation< real.t, 3, 3, 2, 2 >	300
DG	228
LaplaceDG2DP1	368
Equation< real.t, NEN_, NEE_, NSN_, NSE_ >	300
Equa_Electromagnetics< real.t, 3, 6, 2, 4 >	287
EC2D2T3	255
Equa_Fluid< real.t, 3, 6, 2, 4 >	288
TINS2DT3S	548
Equa_Fluid< real.t, 4, 12, 3, 9 >	288
TINS3DT4S	550
Equa_Fluid< real.t, 4, 8, 2, 4 >	288
NSP2DQ41	461
Equa_Laplace< real.t, 2, 2, 1, 1 >	290
Laplace1DL2	359
Equa_Laplace< real.t, 3, 3, 1, 1 >	290

Laplace1DL3	361
Equa_Laplace< real_t, 3, 3, 2, 2 >	290
Laplace2DT3	363
Equa_Laplace< real_t, 4, 4, 3, 3 >	290
Equa_Laplace< real_t, 6, 6, 3, 3 >	290
Laplace2DT6	366
Equa_Porous< real_t, 2, 2, 1, 1 >	292
Equa_Porous< real_t, 3, 3, 2, 2 >	292
WaterPorous2D	589
Equa_Solid< real_t, 2, 12, 1, 6 >	295
Beam3DL2	195
Equa_Solid< real_t, 2, 4, 1, 2 >	295
Bar2DL2	191
Equa_Solid< real_t, 3, 6, 2, 4 >	295
Elas2DT3	269
Equa_Solid< real_t, 4, 12, 3, 9 >	295
Elas3DT4	275
Equa_Solid< real_t, 4, 8, 2, 4 >	295
Elas2DQ4	266
Equa_Therm< real_t, 2, 2, 1, 1 >	297
DC1DL2	210
Equa_Therm< real_t, 3, 3, 2, 2 >	297
DC2DT3	213
DC3DAT3	221
Equa_Therm< real_t, 4, 4, 3, 3 >	297
DC3DT4	224
Equa_Therm< real_t, 6, 6, 3, 3 >	297
DC2DT6	218
SteklovPoincare2DBE	536
BiotSavart	198
Domain	240
Edge	256
EdgeList	259
EigenProblemSolver	260
Element	277
ElementList	285
Estimator	310
FastMarching2D	314
FEShape	315
Hexa8	331
Line2	379
Line3	381
Penta6	485
Quad4	502
Tetra4	539
triangle	558
Triang3	552
Triang6S	554
Figure	317
Brick	207
Circle	209

Ellipse	286
Polygon	494
Rectangle	505
Sphere	531
Triangle	556
FMM2D	318
FMM3D	320
FMMSolver	322
Funct	324
Gauss	326
Grid	328
Integration	345
IOField	347
IPF	349
Iter< T_ >	358
Iter< real.t >	358
LinearSolver< T_ >	382
LinearSolver< real.t >	382
LocalMatrix< T_, NR_, NC_ >	388
LocalMatrix< real.t, 2, 2 >	388
LocalVect< T_, N_ >	394
LocalVect< OFELI::Point< real.t >, 3 >	394
LocalVect< real.t, 3 >	394
LocalVect< size.t, 2 >	394
LocalVect< size.t, 3 >	394
LPSolver	400
Material	403
Matrix< T_ >	405
BMatrix< T_ >	203
DMatrix< T_ >	229
DSMatrix< T_ >	245
SkMatrix< T_ >	514
SkSMatrix< T_ >	522
SpMatrix< T_ >	533
TrMatrix< T_ >	559
Matrix< real.t >	405
BMatrix< real.t >	203
DMatrix< real.t >	229
DSMatrix< real.t >	245
SpMatrix< real.t >	533
Mesh	415
MeshAdapt	434
Muscl	439
Muscl1D	443
ICPG1D	333
LCL1D	370
Muscl2DT	444
ICPG2DT	338
LCL2DT	374
Muscl3DT	445
ICPG3DT	342
LCL3DT	376

MyNLAS	446
MyOpt	448
NLASSolver	449
Node	455
NodeList	459
ODESolver	463
OFELIException	473
OptSolver	473
Partition	481
PhaseChange	487
Point< T_ >	488
Point2D< T_ >	491
Point< int >	488
Point< real_t >	488
Point< size_t >	488
Prec< T_ >	495
Prec< real_t >	495
Prescription	500
Reconstruction	504
Side	507
SideList	513
Tabulation	538
Timer	541
TimeStepping	542
Vect< T_ >	561
Vect< complex_t >	561
Vect< fct >	561
Vect< int >	561
Vect< OFELI::Point< real_t > >	561
Vect< Pt >	561
Vect< real_t >	561
Vect< size_t >	561

Chapter 4

Class Index

4.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

AbsEqua< T_ >	Mother abstract class to describe equation	187
Bar2DL2	To build element equations for Planar Elastic Bar element with 2 DOF (Degrees of Freedom) per node	191
Beam3DL2	To build element equations for 3-D beam equations using 2-node lines	195
BiotSavart	Class to compute the magnetic induction from the current density using the Biot-Savart formula	198
BMatrix< T_ >	To handle band matrices	203
Brick	To store and treat a brick (parallelepiped) figure	207
Circle	To store and treat a circular figure	209
DC1DL2	Builds finite element arrays for thermal diffusion and convection in 1-D using 2-Node elements	210
DC2DT3	Builds finite element arrays for thermal diffusion and convection in 2-D domains using 3-Node triangles	213
DC2DT6	Builds finite element arrays for thermal diffusion and convection in 2-D domains using 6-Node triangles	218
DC3DAT3	Builds finite element arrays for thermal diffusion and convection in 3-D domains with axisymmetry using 3-Node triangles	221
DC3DT4	Builds finite element arrays for thermal diffusion and convection in 3-D domains using 4-Node tetrahedra	224
DG	Enables preliminary operations and utilities for the Discontinuous Galerkin method	228

DMatrix< T_ >	To handle dense matrices	229
Domain	To store and treat finite element geometric information	240
DSMatrix< T_ >	To handle symmetric dense matrices	245
EC2D1T3	Eddy current problems in 2-D domains using solenoidal approximation	253
EC2D2T3	Eddy current problems in 2-D domains using transversal approximation . . .	255
Edge	To describe an edge	256
EdgeList	Class to construct a list of edges having some common properties	259
EigenProblemSolver	Class to find eigenvalues and corresponding eigenvectors of a given matrix in a generalized eigenproblem, <i>i.e.</i> Find scalars λ and non-null vectors v such that $[K]\{v\} = \lambda[M]\{v\}$ where $[K]$ and $[M]$ are symmetric matrices. The eigenproblem can be originated from a PDE. For this, we will refer to the matrices K and M as <i>Stiffness</i> and <i>Mass</i> matrices respectively	260
Elas2DQ4	To build element equations for 2-D linearized elasticity using 4-node quadrilaterals	266
Elas2DT3	To build element equations for 2-D linearized elasticity using 3-node triangles	269
Elas3DH8	To build element equations for 3-D linearized elasticity using 8-node hexahedra	273
Elas3DT4	To build element equations for 3-D linearized elasticity using 4-node tetrahedra	275
Element	To store and treat finite element geometric information	277
ElementList	Class to construct a list of elements having some common properties	285
Ellipse	To store and treat an ellipsoidal figure	286
Equa_Electromagnetics< T_, NEN_, NEE_, NSN_, NSE_ >	Abstract class for Electromagnetics Equation classes	287
Equa_Fluid< T_, NEN_, NEE_, NSN_, NSE_ >	Abstract class for Fluid Dynamics Equation classes	288
Equa_Laplace< T_, NEN_, NEE_, NSN_, NSE_ >	Abstract class for classes about the Laplace equation	290
Equa_Porous< T_, NEN_, NEE_, NSN_, NSE_ >	Abstract class for Porous Media Finite Element classes	292
Equa_Solid< T_, NEN_, NEE_, NSN_, NSE_ >	Abstract class for Solid Mechanics Finite Element classes	295
Equa_Therm< T_, NEN_, NEE_, NSN_, NSE_ >	Abstract class for Heat transfer Finite Element classes	297
Equation< T_, NEN_, NEE_, NSN_, NSE_ >	Abstract class for all equation classes	300
Estimator	To calculate an a posteriori estimator of the solution	310
FastMarching2D	To run a Fast Marching Method on 2-D structured uniform grids	314

FEShape	Parent class from which inherit all finite element shape classes	315
Figure	To store and treat a figure (or shape) information	317
FMM2D	Class for the fast marching 2-D algorithm	318
FMM3D	Class for the 3-D fast marching algorithm	320
FMMSolver	The Fast Marching Method solver	322
Funct	A simple class to parse real valued functions	324
Gauss	Calculate data for Gauss integration	326
Grid	To manipulate structured grids	328
HelmholtzBT3	Builds finite element arrays for Helmholtz equations in a bounded media using 3-Node triangles	330
Hexa8	Defines a three-dimensional 8-node hexahedral finite element using Q1-isoparametric interpolation	331
ICPG1D	Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 1-D	333
ICPG2DT	Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 2-D	338
ICPG3DT	Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 3-D	342
Integration	Class for numerical integration methods	345
IOField	Enables working with files in the XML Format	347
IPF	To read project parameters from a file in IPF format	349
Iter< T_ >	Class to drive an iterative process	358
Laplace1DL2	To build element equation for a 1-D elliptic equation using the 2-Node line element (P ₁)	359
Laplace1DL3	To build element equation for the 1-D elliptic equation using the 3-Node line (P ₂)	361
Laplace2DT3	To build element equation for the Laplace equation using the 2-D triangle element (P ₁)	363
Laplace2DT6	To build element equation for the Laplace equation using the 2-D triangle element (P ₂)	366
LaplaceDG2DP1	To build and solve the linear system for the Poisson problem using the DG P ₁ 2-D triangle element	368

LCL1D	Class to solve the linear conservation law (Hyperbolic equation) in 1-D by a MUSCL Finite Volume scheme	370
LCL2DT	Class to solve the linear hyperbolic equation in 2-D by a MUSCL Finite Volume scheme on triangles	374
LCL3DT	Class to solve the linear conservation law equation in 3-D by a MUSCL Finite Volume scheme on tetrahedra	376
Line2	To describe a 2-Node planar line finite element	379
Line3	To describe a 3-Node quadratic planar line finite element	381
LinearSolver< T_ >	Class to solve systems of linear equations by iterative methods	382
LocalMatrix< T_, NR_, NC_ >	Handles small size matrices like element matrices, with a priori known size . .	388
LocalVect< T_, N_ >	Handles small size vectors like element vectors	394
LPSolver	To solve a linear programming problem	400
Material	To treat material data. This class enables reading material data in material data files. It also returns these informations by means of its members	403
Matrix< T_ >	Virtual class to handle matrices for all storage formats	405
Mesh	To store and manipulate finite element meshes	415
MeshAdapt	To adapt mesh in function of given solution	434
Muscl	Parent class for hyperbolic solvers with Muscl scheme	439
Muscl1D	Class for 1-D hyperbolic solvers with Muscl scheme	443
Muscl2DT	Class for 2-D hyperbolic solvers with Muscl scheme	444
Muscl3DT	Class for 3-D hyperbolic solvers with Muscl scheme using tetrahedra	445
MyNLAS	Abstract class to define by user specified function	446
MyOpt	Abstract class to define by user specified optimization function	448
NLASSolver	To solve a system of nonlinear algebraic equations of the form $f(u) = 0$	449
Node	To describe a node	455
NodeList	Class to construct a list of nodes having some common properties	459
NSP2DQ41	Builds finite element arrays for incompressible Navier-Stokes equations in 2-D domains using Q_1/P_0 element and a penalty formulation for the incompressibility condition	461
ODESolver	To solve a system of ordinary differential equations	463

OFELIException	To handle exceptions in OFELI	473
OptSolver	To solve an optimization problem with bound constraints	473
Partition	To partition a finite element mesh into balanced submeshes	481
Penta6	Defines a 6-node pentahedral finite element using P_1 interpolation in local coordinates $(s.x, s.y)$ and Q_1 isoparametric interpolation in local coordinates $(s.x, s.z)$ and $(s.y, s.z)$	485
PhaseChange	This class enables defining phase change laws for a given material	487
Point< T_ >	Defines a point with arbitrary type coordinates	488
Point2D< T_ >	Defines a 2-D point with arbitrary type coordinates	491
Polygon	To store and treat a polygonal figure	494
Prec< T_ >	To set a preconditioner	495
Prescription	To prescribe various types of data by an algebraic expression. Data may consist in boundary conditions, forces, tractions, fluxes, initial condition. All these data types can be defined through an enumerated variable	500
Quad4	Defines a 4-node quadrilateral finite element using Q_1 isoparametric interpolation	502
Reconstruction	To perform various reconstruction operations	504
Rectangle	To store and treat a rectangular figure	505
Side	To store and treat finite element sides (edges in 2-D or faces in 3-D)	507
SideList	Class to construct a list of sides having some common properties	513
SkMatrix< T_ >	To handle square matrices in skyline storage format	514
SkSMatrix< T_ >	To handle symmetric matrices in skyline storage format	522
Sphere	To store and treat a sphere	531
SpMatrix< T_ >	To handle matrices in sparse storage format	533
SteklovPoincare2DBE	Solver of the Steklov Poincare problem in 2-D geometries using piecewise constant boundary element	536
Tabulation	To read and manipulate tabulated functions	538
Tetra4	Defines a three-dimensional 4-node tetrahedral finite element using P_1 interpolation	539
Timer	To handle elapsed time counting	541

TimeStepping	To solve time stepping problems, i.e. systems of linear ordinary differential equations of the form $[A2]\{y''\} + [A1]\{y'\} + [A0]\{y\} = \{b\}$	542
TINS2DT3S	Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 2-D domains. Numerical approximation uses stabilized 3-node triangle finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration	548
TINS3DT4S	Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 3-D domains. Numerical approximation uses stabilized 4-node tetrahedral finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration	550
Triang3	Defines a 3-Node (P_1) triangle	552
Triang6S	Defines a 6-Node straight triangular finite element using P_2 interpolation . . .	554
Triangle	To store and treat a triangle	556
triangle	Defines a triangle. The reference element is the rectangle triangle with two unit edges	558
TrMatrix< T_ >	To handle tridiagonal matrices	559
Vect< T_ >	To handle general purpose vectors	561
WaterPorous2D	To solve water flow equations in porous media (1-D)	589

Chapter 5

Module Documentation

5.1 General Purpose Equations

Gathers equation related classes.

Classes

- class [AbsEqua< T_ >](#)
Mother abstract class to describe equation.
- class [Equation< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for all equation classes.
- class [Estimator](#)
To calculate an a posteriori estimator of the solution.

Functions

- `template<class T_ , size_t N_ , class E_ >`
`void element_assembly (const E_ &e, const LocalVect< T_ , N_ > &be, Vect< T_ > &b)`
Assemble local vector into global vector.
- `template<class T_ , size_t N_ , class E_ >`
`void element_assembly (const E_ &e, const LocalMatrix< T_ , N_ , N_ > &ae, Vect< T_ > &b)`
Assemble diagonal local vector into global vector.
- `template<class T_ , size_t N_ , class E_ >`
`void element_assembly (const E_ &e, const LocalMatrix< T_ , N_ , N_ > &ae, Matrix< T_ > *A)`
Assemble local matrix into global matrix.
- `template<class T_ , size_t N_ , class E_ >`
`void element_assembly (const E_ &e, const LocalMatrix< T_ , N_ , N_ > &ae, SkMatrix< T_ > &A)`
Assemble local matrix into global skyline matrix.
- `template<class T_ , size_t N_ , class E_ >`
`void element_assembly (const E_ &e, const LocalMatrix< T_ , N_ , N_ > &ae, SkSMatrix< T_ > &A)`
Assemble local matrix into global symmetric skyline matrix.
- `template<class T_ , size_t N_ , class E_ >`
`void element_assembly (const E_ &e, const LocalMatrix< T_ , N_ , N_ > &ae, SpMatrix< T_ > &A)`

Assemble local matrix into global sparse matrix.

- `template<class T_, size_t N_>`
`void side_assembly (const Element &e, const LocalMatrix< T_, N_, N_ > &ae, SpMatrix< T_ > &A)`

Side assembly of local matrix into global matrix (as instance of class [SpMatrix](#)).

- `template<class T_, size_t N_>`
`void side_assembly (const Element &e, const LocalMatrix< T_, N_, N_ > &ae, SkSMatrix< T_ > &A)`

Side assembly of local matrix into global matrix (as instance of class [SkSMatrix](#)).

- `template<class T_, size_t N_>`
`void side_assembly (const Element &e, const LocalMatrix< T_, N_, N_ > &ae, SkMatrix< T_ > &A)`

Side assembly of local matrix into global matrix (as instance of class [SkMatrix](#)).

- `template<class T_, size_t N_>`
`void side_assembly (const Element &e, const LocalVect< T_, N_ > &be, Vect< T_ > &b)`

Side assembly of local vector into global vector.

- `ostream & operator<< (ostream &s, const Estimator &r)`

Output estimator vector in output stream.

5.1.1 Detailed Description

Gathers equation related classes.

5.1.2 Function Documentation

`void element_assembly (const E_ &e, const LocalVect< T_, N_ > &be, Vect< T_ > &b)`

Assemble local vector into global vector.

Parameters

in	<i>e</i>	Reference to local entity (Element or Side)
in	<i>be</i>	Local vector
in,out	<i>b</i>	Global vector

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`void element_assembly (const E_ &e, const LocalMatrix< T_, N_, N_ > &ae, Vect< T_ > &b)`

Assemble diagonal local vector into global vector.

Parameters

in	e	Reference to local entity (Element or Side)
in	ae	Local matrix
in,out	b	Global vector

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void element_assembly (const E_ & e , const LocalMatrix< T_, N_, N_ > & ae , Matrix< T_ > * A)

Assemble local matrix into global matrix.

This function is to be called with an abstract pointer to matrix (class [Matrix](#))

Parameters

in	e	Reference to local entity (Element or Side)
in	ae	Local matrix
in,out	A	Pointer to global matrix

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void element_assembly (const E_ & e , const LocalMatrix< T_, N_, N_ > & ae , SkMatrix< T_ > & A)

Assemble local matrix into global skyline matrix.

Parameters

in	e	Reference to local entity (Element or Side)
in	ae	Local matrix
in,out	A	Global matrix

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void element_assembly (const E_ & e , const LocalMatrix< T_, N_, N_ > & ae , SkSMMatrix< T_ > & A)

Assemble local matrix into global symmetric skyline matrix.

Parameters

<code>in</code>	e	Reference to local entity (Element or Side)
<code>in</code>	ae	Local matrix
<code>in,out</code>	A	Global matrix

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void element_assembly (const E_ & e , const LocalMatrix< T_, N_, N_ > & ae , SpMatrix< T_ > & A)

Assemble local matrix into global sparse matrix.

Parameters

<code>in</code>	e	Reference to local entity (Element or Side)
<code>in</code>	ae	Local matrix
<code>in,out</code>	A	Global matrix

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void side_assembly (const Element & e , const LocalMatrix< T_, N_, N_ > & ae , SpMatrix< T_ > & A)

Side assembly of local matrix into global matrix (as instance of class [SpMatrix](#)).

Parameters

<code>in</code>	e	Reference to local Element
<code>in</code>	ae	Local matrix
<code>in,out</code>	A	Global matrix

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void side_assembly (const Element & e , const LocalMatrix< T_, N_, N_ > & ae , SkSMatrix< T_ > & A)

Side assembly of local matrix into global matrix (as instance of class [SkSMatrix](#)).

Parameters

in	e	Reference to local Element
in	ae	Local matrix
in,out	A	Global matrix

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void side_assembly (const [Element](#) & e , const [LocalMatrix](#)< $T_$, $N_$, $N_$ > & ae , [SkMatrix](#)< $T_$ > & A)

[Side](#) assembly of local matrix into global matrix (as instance of class [SkMatrix](#)).

Parameters

in	e	Reference to local Element
in	ae	Local matrix
in,out	A	Global matrix

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void side_assembly (const [Element](#) & e , const [LocalVect](#)< $T_$, $N_$ > & be , [Vect](#)< $T_$ > & b)

Side assembly of local vector into global vector.

Parameters

in	e	Reference to local Element
in	be	Local vector
in,out	b	Global vector

Author

Rachid Touzani

Copyright

GNU Lesser Public License

5.2 Conservation Law Equations

Conservation law equations.

Classes

- class [ICPG1D](#)
Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 1-D.
- class [ICPG2DT](#)
Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 2-D.
- class [ICPG3DT](#)
Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 3-D.
- class [LCL1D](#)
Class to solve the linear conservation law (Hyperbolic equation) in 1-D by a MUSCL Finite Volume scheme.
- class [LCL2DT](#)
Class to solve the linear hyperbolic equation in 2-D by a MUSCL Finite Volume scheme on triangles.
- class [LCL3DT](#)
Class to solve the linear conservation law equation in 3-D by a MUSCL Finite Volume scheme on tetrahedra.
- class [Muscl](#)
Parent class for hyperbolic solvers with Muscl scheme.
- class [Muscl1D](#)
Class for 1-D hyperbolic solvers with [Muscl](#) scheme.
- class [Muscl2DT](#)
Class for 2-D hyperbolic solvers with [Muscl](#) scheme.
- class [Muscl3DT](#)
Class for 3-D hyperbolic solvers with [Muscl](#) scheme using tetrahedra.

5.2.1 Detailed Description

Conservation law equations.

5.3 Electromagnetics

Electromagnetic equations.

Classes

- class [BiotSavart](#)
Class to compute the magnetic induction from the current density using the Biot-Savart formula.
- class [EC2D1T3](#)
Eddy current problems in 2-D domains using solenoidal approximation.
- class [EC2D2T3](#)
Eddy current problems in 2-D domains using transversal approximation.
- class [Equa_Electromagnetics](#)< [T_](#), [NEN_](#), [NEE_](#), [NSN_](#), [NSE_](#) >
Abstract class for Electromagnetics [Equation](#) classes.
- class [HelmholtzBT3](#)
Builds finite element arrays for Helmholtz equations in a bounded media using 3-Node triangles.

5.3.1 Detailed Description

Electromagnetic equations.

5.4 Fluid Dynamics

Fluid Dynamics equations.

Classes

- class [Equa_Fluid](#)[< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for Fluid Dynamics [Equation](#) classes.
- class [NSP2DQ41](#)
Builds finite element arrays for incompressible Navier-Stokes equations in 2-D domains using Q_1/P_0 element and a penalty formulation for the incompressibility condition.
- class [TINS2DT3S](#)
Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 2-D domains. Numerical approximation uses stabilized 3-node triangle finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.
- class [TINS3DT4S](#)
Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 3- \leftrightarrow D domains. Numerical approximation uses stabilized 4-node tetrahedral finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.

5.4.1 Detailed Description

Fluid Dynamics equations.

5.5 Interface Problems

Interface problems, including image processing.

Classes

- class [FastMarching2D](#)
To run a Fast Marching Method on 2-D structured uniform grids.
- class [FMMSolver](#)
The Fast Marching Method solver.

5.5.1 Detailed Description

Interface problems, including image processing.

5.6 Laplace equation

Laplace and Poisson equations.

Classes

- class [Equa.Laplace< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for classes about the Laplace equation.
- class [Laplace1DL2](#)
To build element equation for a 1-D elliptic equation using the 2-Node line element (P_1).
- class [Laplace1DL3](#)
To build element equation for the 1-D elliptic equation using the 3-Node line (P_2).
- class [Laplace2DT3](#)
To build element equation for the Laplace equation using the 2-D triangle element (P_1).
- class [Laplace2DT6](#)
To build element equation for the Laplace equation using the 2-D triangle element (P_2).
- class [LaplaceDG2DP1](#)
To build and solve the linear system for the Poisson problem using the [DG](#) P_1 2-D triangle element.
- class [SteklovPoincare2DBE](#)
Solver of the Steklov Poincare problem in 2-D geometries using piecewise constant boundary elemen.

5.6.1 Detailed Description

Laplace and Poisson equations.

5.7 Porous Media problems

Porous Media equation classes.

Classes

- class `Equa_Porous< T_, NEN_, NEE_, NSN_, NSE_ >`
Abstract class for Porous Media Finite Element classes.

5.7.1 Detailed Description

Porous Media equation classes.

5.8 Solid Mechanics

Solid Mechanics finite element equations.

Classes

- class [Bar2DL2](#)
To build element equations for Planar Elastic Bar element with 2 DOF (Degrees of Freedom) per node.
- class [Beam3DL2](#)
To build element equations for 3-D beam equations using 2-node lines.
- class [Elas2DQ4](#)
To build element equations for 2-D linearized elasticity using 4-node quadrilaterals.
- class [Elas2DT3](#)
To build element equations for 2-D linearized elasticity using 3-node triangles.
- class [Elas3DH8](#)
To build element equations for 3-D linearized elasticity using 8-node hexahedra.
- class [Elas3DT4](#)
To build element equations for 3-D linearized elasticity using 4-node tetrahedra.
- class [Equa_Solid< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for Solid Mechanics Finite Element classes.

5.8.1 Detailed Description

Solid Mechanics finite element equations.

5.9 Heat Transfer

Heat Transfer equations.

Classes

- class [DC1DL2](#)
Builds finite element arrays for thermal diffusion and convection in 1-D using 2-Node elements.
- class [DC2DT3](#)
Builds finite element arrays for thermal diffusion and convection in 2-D domains using 3-Node triangles.
- class [DC2DT6](#)
Builds finite element arrays for thermal diffusion and convection in 2-D domains using 6-Node triangles.
- class [DC3DAT3](#)
Builds finite element arrays for thermal diffusion and convection in 3-D domains with axisymmetry using 3-Node triangles.
- class [DC3DT4](#)
Builds finite element arrays for thermal diffusion and convection in 3-D domains using 4-Node tetrahedra.
- class [Equa_Therm](#)< T_, NEN_, NEE_, NSN_, NSE_ >
Abstract class for Heat transfer Finite Element classes.
- class [PhaseChange](#)
This class enables defining phase change laws for a given material.

5.9.1 Detailed Description

Heat Transfer equations.

5.10 Input/Output

Input/Output utility classes.

Classes

- class [IOField](#)
Enables working with files in the XML Format.
- class [IPF](#)
To read project parameters from a file in [IPF](#) format.
- class [Prescription](#)
To prescribe various types of data by an algebraic expression. Data may consist in boundary conditions, forces, tractions, fluxes, initial condition. All these data types can be defined through an enumerated variable.

Macros

- `#define MAX_NB_PAR 50`
Maximum number of parameters.
- `#define MAX_ARRAY_SIZE 100`
Maximum array size.
- `#define MAX_INPUT_STRING_LENGTH 100`
Maximum string length.
- `#define FILENAME_LENGTH 150`
Length of a string defining a file name.
- `#define MAX_FFT_SIZE 15`
Maximal size for the FFT Table This table can be used by the FFT for any number of points from 2 up to [MAX_FFT_SIZE](#). For example, if [MAX_FFT_SIZE](#) = 14, then we can transform anywhere from 2 to 2^{15} = 32,768 points, using the same sine and cosine table.

5.10.1 Detailed Description

Input/Output utility classes.

5.10.2 Macro Definition Documentation

`#define MAX_NB_PAR 50`

Maximum number of parameters.
Used in class IPF

`#define MAX_ARRAY_SIZE 100`

Maximum array size.
Used in class IPF

`#define MAX_INPUT_STRING_LENGTH 100`

Maximum string length.
Used in class IPF

5.11 Utilities

Utility functions and classes.

Files

- file [OFELI.h](#)
Header file that includes all kernel classes of the library.
- file [OFELI.Config.h](#)
File that contains some macros.
- file [constants.h](#)
File that contains some widely used constants.

Classes

- class [Funct](#)
A simple class to parse real valued functions.
- class [Tabulation](#)
To read and manipulate tabulated functions.
- class [Point< T_ >](#)
Defines a point with arbitrary type coordinates.
- class [Point2D< T_ >](#)
Defines a 2-D point with arbitrary type coordinates.
- class [OFELIException](#)
To handle exceptions in [OFELI](#).
- class [Gauss](#)
Calculate data for Gauss integration.
- class [Timer](#)
To handle elapsed time counting.

Macros

- `#define OFELI_E 2.71828182845904523536028747135`
- `#define OFELI_PI 3.14159265358979323846264338328`
- `#define OFELI_THIRD 0.33333333333333333333333333333333`
- `#define OFELI_SIXTH 0.16666666666666666666666666666667`
- `#define OFELI_TWELVETH 0.08333333333333333333333333333333`
- `#define OFELI_SQRT2 1.41421356237309504880168872421`
- `#define OFELI_SQRT3 1.73205080756887729352744634151`
- `#define OFELI_ONEOVERPI 0.31830988618379067153776752675`
- `#define OFELI_GAUSS2 0.57735026918962576450914878050196`
- `#define OFELI_EPSMCH DBL_EPSILON`
- `#define OFELI_TOLERANCE OFELI_EPSMCH*10000`
- `#define VLG 1.e10`
- `#define OFELI_IMAG std::complex<double>(0.,1.);`
- `#define CATCH_EXCEPTION`

Typedefs

- typedef unsigned long `lsize_t`
This type stands for type `unsigned long`.
- typedef double `real_t`
This type stands for `double`.
- typedef std::complex< double > `complex_t`
This type stands for type `std::complex<double>`

Functions

- ostream & `operator<<` (ostream &s, const `complex_t` &x)
Output a complex number.
- ostream & `operator<<` (ostream &s, const std::string &c)
Output a string.
- template<class T_ >
ostream & `operator<<` (ostream &s, const vector< T_ > &v)
Output a vector instance.
- template<class T_ >
ostream & `operator<<` (ostream &s, const std::list< T_ > &l)
Output a vector instance.
- template<class T_ >
ostream & `operator<<` (ostream &s, const std::pair< T_, T_ > &a)
Output a pair instance.
- void `saveField` (Vect< `real_t` > &v, string output_file, int opt)
Save a vector to an output file in a given file format.
- void `saveField` (const Vect< `real_t` > &v, const Mesh &mesh, string output_file, int opt)
Save a vector to an output file in a given file format.
- void `saveField` (Vect< `real_t` > &v, const Grid &g, string output_file, int opt)
Save a vector to an output file in a given file format, for a structured grid data.
- void `saveGnuplot` (string input_file, string output_file, string mesh_file, int f=1)
Save a vector to an input `Gnuplot` file.
- void `saveGnuplot` (Mesh &mesh, string input_file, string output_file, int f=1)
Save a vector to an input `Gnuplot` file.
- void `saveTecplot` (string input_file, string output_file, string mesh_file, int f=1)
Save a vector to an output file to an input `Tecplot` file.
- void `saveTecplot` (Mesh &mesh, string input_file, string output_file, int f=1)
Save a vector to an output file to an input `Tecplot` file.
- void `saveVTK` (string input_file, string output_file, string mesh_file, int f=1)
Save a vector to an output `VTK` file.
- void `saveVTK` (Mesh &mesh, string input_file, string output_file, int f=1)
Save a vector to an output `VTK` file.
- void `saveGmsh` (string input_file, string output_file, string mesh_file, int f=1)
Save a vector to an output `Gmsh` file.
- void `saveGmsh` (Mesh &mesh, string input_file, string output_file, int f=1)
Save a vector to an output `Gmsh` file.
- ostream & `operator<<` (ostream &s, const Tabulation &t)
Output Tabulated function data.

- `template<class T_>`
`bool operator==(const Point< T_> &a, const Point< T_> &b)`
Operator ==
- `template<class T_>`
`Point< T_> operator+ (const Point< T_> &a, const Point< T_> &b)`
Operator +
- `template<class T_>`
`Point< T_> operator+ (const Point< T_> &a, const T_ &x)`
Operator +
- `template<class T_>`
`Point< T_> operator- (const Point< T_> &a)`
Unary Operator -
- `template<class T_>`
`Point< T_> operator- (const Point< T_> &a, const Point< T_> &b)`
Operator -
- `template<class T_>`
`Point< T_> operator- (const Point< T_> &a, const T_ &x)`
Operator -
- `template<class T_>`
`Point< T_> operator* (const T_ &a, const Point< T_> &b)`
*Operator **
- `template<class T_>`
`Point< T_> operator* (const int &a, const Point< T_> &b)`
*Operator *.*
- `template<class T_>`
`Point< T_> operator* (const Point< T_> &b, const T_ &a)`
Operator /
- `template<class T_>`
`Point< T_> operator* (const Point< T_> &b, const int &a)`
*Operator **
- `template<class T_>`
`T_ operator* (const Point< T_> &a, const Point< T_> &b)`
*Operator **
- `template<class T_>`
`Point< T_> operator/ (const Point< T_> &b, const T_ &a)`
Operator /
- `bool areClose (const Point< double> &a, const Point< double> &b, double toler=OFELI.TOLERANCE)`
Return true if both instances of class Point<double> are distant with less then toler
- `double SqrDistance (const Point< double> &a, const Point< double> &b)`
Return squared euclidean distance between points a and b
- `double Distance (const Point< double> &a, const Point< double> &b)`
Return euclidean distance between points a and b
- `bool operator< (const Point< size_t> &a, const Point< size_t> &b)`
Comparison operator. Returns true if all components of first vector are lower than those of second one.
- `template<class T_>`
`std::ostream & operator<< (std::ostream &s, const Point< T_> &a)`
Output point coordinates.

- `template<class T_>`
`bool operator==(const Point2D< T_> &a, const Point2D< T_> &b)`
Operator ==.
- `template<class T_>`
`Point2D< T_> operator+ (const Point2D< T_> &a, const Point2D< T_> &b)`
Operator +.
- `template<class T_>`
`Point2D< T_> operator+ (const Point2D< T_> &a, const T_ &x)`
Operator +.
- `template<class T_>`
`Point2D< T_> operator- (const Point2D< T_> &a)`
Unary Operator -
- `template<class T_>`
`Point2D< T_> operator- (const Point2D< T_> &a, const Point2D< T_> &b)`
Operator -
- `template<class T_>`
`Point2D< T_> operator- (const Point2D< T_> &a, const T_ &x)`
Operator -
- `template<class T_>`
`Point2D< T_> operator* (const T_ &a, const Point2D< T_> &b)`
*Operator *.*
- `template<class T_>`
`Point2D< T_> operator* (const int &a, const Point2D< T_> &b)`
- `template<class T_>`
`Point2D< T_> operator* (const Point2D< T_> &b, const T_ &a)`
Operator /
- `template<class T_>`
`Point2D< T_> operator* (const Point2D< T_> &b, const int &a)`
*Operator **
- `template<class T_>`
`T_ operator* (const Point2D< T_> &b, const Point2D< T_> &a)`
*Operator *.*
- `template<class T_>`
`Point2D< T_> operator/ (const Point2D< T_> &b, const T_ &a)`
Operator /
- `bool areClose (const Point2D< real_t> &a, const Point2D< real_t> &b, real_t toler=OFELI.TOLERANCE)`
Return true if both instances of class Point2D<real_t> are distant with less then toler [Default: OFELI.EPSMCH].
- `real_t SqrDistance (const Point2D< real_t> &a, const Point2D< real_t> &b)`
Return squared euclidean distance between points a and b
- `real_t Distance (const Point2D< real_t> &a, const Point2D< real_t> &b)`
Return euclidean distance between points a and b
- `template<class T_>`
`std::ostream & operator<< (std::ostream &s, const Point2D< T_> &a)`
Output point coordinates.
- `real_t Discrepancy (Vect< real_t> &x, const Vect< real_t> &y, int n, int type=1)`
Return discrepancy between 2 vectors x and y
- `real_t Discrepancy (Vect< complex_t> &x, const Vect< complex_t> &y, int n, int type=1)`

- Return discrepancy between 2 vectors x and y*
- void `getMesh` (string file, ExternalFileFormat form, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a mesh file stored in an external file format.
 - void `getBamg` (string file, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a mesh file stored in `Bamg` format.
 - void `getEasymesh` (string file, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a mesh file stored in `Easymesh` format.
 - void `getGambit` (string file, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a mesh file stored in `Gambit` neutral format.
 - void `getGmsh` (string file, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a mesh file stored in `Gmsh` format.
 - void `getMatlab` (string file, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a Matlab mesh data.
 - void `getNetgen` (string file, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a mesh file stored in `Netgen` format.
 - void `getTetgen` (string file, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a mesh file stored in `Tetgen` format.
 - void `getTriangle` (string file, Mesh &mesh, size_t nb_dof=1)
Construct an instance of class `Mesh` from a mesh file stored in `Triangle` format.
 - void `saveMesh` (const string &file, const Mesh &mesh, ExternalFileFormat form)
This function saves mesh data a file for a given external format.
 - void `saveGmsh` (const string &file, const Mesh &mesh)
This function outputs a `Mesh` instance in a file in `Gmsh` format.
 - void `saveGnuplot` (const string &file, const Mesh &mesh)
This function outputs a `Mesh` instance in a file in `Gmsh` format.
 - void `saveMatlab` (const string &file, const Mesh &mesh)
This function outputs a `Mesh` instance in a file in `Matlab` format.
 - void `saveTecplot` (const string &file, const Mesh &mesh)
This function outputs a `Mesh` instance in a file in `Tecplot` format.
 - void `saveVTK` (const string &file, const Mesh &mesh)
This function outputs a `Mesh` instance in a file in `VTK` format.
 - void `saveBamg` (const string &file, Mesh &mesh)
This function outputs a `Mesh` instance in a file in `Bamg` format.
 - void `BSpline` (size_t n, size_t t, Vect< Point< `real_t` > > &control, Vect< Point< `real_t` > > &output, size_t num_output)
Function to perform a B-spline interpolation.
 - void `banner` (const string &prog=" ")
Outputs a banner as header of any developed program.
 - template<class T_ >
void `QuickSort` (std::vector< T_ > &a, int begin, int end)
Function to sort a vector.
 - template<class T_ >
void `qksort` (std::vector< T_ > &a, int begin, int end)
Function to sort a vector.
 - template<class T_ , class C_ >
void `qksort` (std::vector< T_ > &a, int begin, int end, C_ compare)
Function to sort a vector according to a key function.

- `int Sgn (real_t a)`
Return sign of a : -1 or 1 .
- `real_t Abs2 (complex_t a)`
Return square of modulus of complex number a
- `real_t Abs2 (real_t a)`
Return square of real number a
- `real_t Abs (real_t a)`
Return absolute value of a
- `real_t Abs (complex_t a)`
Return modulus of complex number a
- `real_t Abs (const Point< real_t > &p)`
Return Norm of vector a
- `real_t Conjg (real_t a)`
Return complex conjugate of real number a
- `complex_t Conjg (complex_t a)`
Return complex conjugate of complex number a
- `real_t Max (real_t a, real_t b, real_t c)`
Return maximum value of real numbers a , b and c
- `int Max (int a, int b, int c)`
Return maximum value of integer numbers a , b and c
- `real_t Min (real_t a, real_t b, real_t c)`
Return minimum value of real numbers a , b and c
- `int Min (int a, int b, int c)`
Return minimum value of integer numbers a , b and c
- `real_t Max (real_t a, real_t b, real_t c, real_t d)`
Return maximum value of integer numbers a , b , c and d
- `int Max (int a, int b, int c, int d)`
Return maximum value of integer numbers a , b , c and d
- `real_t Min (real_t a, real_t b, real_t c, real_t d)`
Return minimum value of real numbers a , b , c and d
- `int Min (int a, int b, int c, int d)`
Return minimum value of integer numbers a , b , c and d
- `real_t Arg (complex_t x)`
Return argument of complex number x
- `complex_t Log (complex_t x)`
Return principal determination of logarithm of complex number x
- `template<class T_ >`
`T_ Sqr (T_ x)`
Return square of value x
- `template<class T_ >`
`void Scale (T_ a, const vector< T_ > &x, vector< T_ > &y)`
Multiply vector x by a and save result in vector y
- `template<class T_ >`
`void Scale (T_ a, const Vect< T_ > &x, Vect< T_ > &y)`
Multiply vector x by a and save result in vector y
- `template<class T_ >`
`void Scale (T_ a, vector< T_ > &x)`

- Multiply vector x by a*

 - `template<class T_ >`
`void Xpy (size_t n, T_ *x, T_ *y)`
Add array x to y
 - `template<class T_ >`
`void Xpy (const vector< T_ > &x, vector< T_ > &y)`
Add vector x to y
 - `template<class T_ >`
`void Axy (size_t n, T_ a, T_ *x, T_ *y)`
Multiply array x by a and add result to y
 - `template<class T_ >`
`void Axy (T_ a, const vector< T_ > &x, vector< T_ > &y)`
Multiply vector x by a and add result to y
 - `template<class T_ >`
`void Axy (T_ a, const Vect< T_ > &x, Vect< T_ > &y)`
Multiply vector x by a and add result to y
 - `template<class T_ >`
`void Copy (size_t n, T_ *x, T_ *y)`
Copy array x to y n is the arrays size.
 - `real_t Error2 (const vector< real_t > &x, const vector< real_t > &y)`
Return absolute L2 error between vectors x and y
 - `real_t RError2 (const vector< real_t > &x, const vector< real_t > &y)`
Return absolute L^2 error between vectors x and y
 - `real_t ErrorMax (const vector< real_t > &x, const vector< real_t > &y)`
Return absolute Max. error between vectors x and y
 - `real_t RErrorMax (const vector< real_t > &x, const vector< real_t > &y)`
Return relative Max. error between vectors x and y
 - `template<class T_ >`
`T_ Dot (size_t n, T_ *x, T_ *y)`
Return dot product of arrays x and y
 - `real_t Dot (const vector< real_t > &x, const vector< real_t > &y)`
Return dot product of vectors x and y .
 - `template<class T_ >`
`T_ Dot (const Point< T_ > &x, const Point< T_ > &y)`
Return dot product of x and y
 - `real_t exprep (real_t x)`
Compute the exponential function with avoiding over and underflows.
 - `template<class T_ >`
`void Assign (vector< T_ > &v, const T_ &a)`
Assign the value a to all entries of a vector v
 - `template<class T_ >`
`void clear (vector< T_ > &v)`
Assign 0 to all entries of a vector.
 - `template<class T_ >`
`void clear (Vect< T_ > &v)`
Assign 0 to all entries of a vector.
 - `real_t Nrm2 (size_t n, real_t *x)`
Return 2-norm of array x

- `real.t Nrm2` (const vector< `real.t` > &x)
Return 2-norm of vector x
- template<class T_ >
`real.t Nrm2` (const Point< T_ > &a)
Return 2-norm of a
- bool `Equal` (`real.t` x, `real.t` y, `real.t` toler=`OFELLEPSMCH`)
Function to return true if numbers x and y are close up to a given tolerance $toler$
- char `itoc` (int i)
Function to convert an integer to a character.
- template<class T_ >
T_ `stringTo` (const std::string &s)
Function to convert a string to a template type parameter.

5.11.1 Detailed Description

Utility functions and classes.

5.11.2 Macro Definition Documentation

#define OFELI_E 2.71828182845904523536028747135

Value of e or exp (with 28 digits)

#define OFELI_PI 3.14159265358979323846264338328

Value of Pi (with 28 digits)

#define OFELI_THIRD 0.333333333333333333333333333333

Value of $1/3$ (with 28 digits)

#define OFELI_SIXTH 0.166666666666666666666666666667

Value of $1/6$ (with 28 digits)

#define OFELI_TWELVETH 0.083333333333333333333333333333

Value of $1/12$ (with 28 digits)

#define OFELI_SQRT2 1.41421356237309504880168872421

Value of $\sqrt{2}$ (with 28 digits)

#define OFELI_SQRT3 1.73205080756887729352744634151

Value of $\sqrt{3}$ (with 28 digits)

#define OFELI_ONEOVERPI 0.31830988618379067153776752675

Value of $1/Pi$ (with 28 digits)

#define OFELI_GAUSS2 0.57735026918962576450914878050196

Value of $1/\sqrt{3}$ (with 32 digits)

#define OFELI_EPSMCH DBL_EPSILON

Value of Machine Epsilon

#define OFELI_TOLERANCE OFELI_EPSMCH*10000

Default tolerance for an iterative process = OFELI_EPSMCH * 10000

#define VLG 1.e10

Very large number: A real number for penalty

#define OFELI_IMAG std::complex<double>(0.,1.);

= Unit imaginary number (i)

#define CATCH_EXCEPTION

Value:

```
catch(OFELIException &e) {
    std::cout << "OFELI error: " << e.what() << endl;
    return 1;
}
catch(runtime_error &e) {
    std::cout << "OFELI Runtime error: " << e.what() << endl;
    return 1;
}
catch( ... ) {
    std::cout << "OFELI Unexpected error: " << endl;
    return 1;
}
```

This macro can be inserted after a try loop to catch a thrown exception.

5.11.3 Function Documentation**ostream & operator<< (ostream & s, const complex_t & x)**

Output a complex number.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const std::string & c)

Output a string.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const vector< T_ > & v)

Output a vector instance.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const std::list< T_ > & l)

Output a vector instance.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const std::pair< T_, T_ > & a)

Output a pair instance.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveField (Vect< real_t > & v, string output_file, int opt)

Save a vector to an output file in a given file format.

Case where the vector contains mesh information

Parameters

in	<i>v</i>	Vect instance to save
in	<i>output_file</i>	Output file where to save the vector
in	<i>opt</i>	Option to choose file format to save. This is to be chosen among enumerated values: GMSH GNUPLOT MATLAB TECPLOT V↔TK

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveField (const Vect< real_t > & v, const Mesh & mesh, string output_file, int opt)

Save a vector to an output file in a given file format.

Case where the vector does not contain mesh information

Parameters

in	<i>v</i>	Vect instance to save
in	<i>mesh</i>	Mesh instance
in	<i>output_file</i>	Output file where to save the vector
in	<i>opt</i>	Option to choose file format to save. This is to be chosen among enumerated values: GMSH, GNUPLOT, MATLAB, TECPLOT, VTK

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveField (Vect< real.t > &v, const Grid &g, string output_file, int opt = VTK)

Save a vector to an output file in a given file format, for a structured grid data.

Parameters

in	<i>v</i>	Vect instance to save
in	<i>g</i>	Grid instance
in	<i>output_file</i>	Output file where to save the vector
in	<i>opt</i>	Option to choose file format to save. This is to be chosen among enumerated values: GMSH, VTK

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveGnuplot (string input_file, string output_file, string mesh_file, int f = 1)

Save a vector to an input [Gnuplot](#) file.

Gnuplot is a command-line driven program for producing 2D and 3D plots. It is under the GNU General Public License. Available information can be found in the site:

<http://www.gnuplot.info/>

Parameters

in	<i>input_file</i>	Input file (OFELI XML file containing a field).
in	<i>output_file</i>	Output file (gnuplot format file)
in	<i>mesh_file</i>	File containing mesh data
in	<i>f</i>	Field is stored each <i>f</i> time step [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveGnuplot (Mesh & *mesh*, string *input_file*, string *output_file*, int *f* = 1)

Save a vector to an input **Gnuplot** file.

Gnuplot is a command-line driven program for producing 2D and 3D plots. It is under the GNU General Public License. Available information can be found in the site:

<http://www.gnuplot.info/>

Parameters

in	<i>mesh</i>	Reference to Mesh instance
in	<i>input_file</i>	Input file (OFELI XML file containing a field).
in	<i>output_file</i>	Output file (gnuplot format file)
in	<i>f</i>	Field is stored each <i>f</i> time step [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveTecplot (string *input_file*, string *output_file*, string *mesh_file*, int *f* = 1)

Save a vector to an output file to an input **Tecplot** file.

Tecplot is high quality post graphical commercial processing program developed by **Amtec**. Available information can be found in the site: <http://www.tecplot.com>

Parameters

in	<i>input_file</i>	Input file (OFELI XML file containing a field).
in	<i>output_file</i>	Output file (gnuplot format file)
in	<i>mesh_file</i>	File containing mesh data
in	<i>f</i>	Field is stored each <i>f</i> time step [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveTecplot (Mesh & *mesh*, string *input_file*, string *output_file*, int *f* = 1)

Save a vector to an output file to an input **Tecplot** file.

Tecplot is high quality post graphical commercial processing program developed by **Amtec**. Available information can be found in the site: <http://www.tecplot.com>

Parameters

in	<i>mesh</i>	Reference to Mesh instance
in	<i>input_file</i>	Input file (OFELI XML file containing a field).
in	<i>output_file</i>	Output file (gnuplot format file)
in	<i>f</i>	Field is stored each <i>f</i> time step [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

saveVTK (string *input_file*, string *output_file*, string *mesh_file*, int *f* = 1)

Save a vector to an output **VTK** file.

The Visualization ToolKit (VTK) is an open source, freely available software system for 3D computer graphics. Available information can be found in the site:

<http://public.kitware.com/VTK/>

Parameters

in	<i>input_file</i>	Input file (OFELI XML file containing a field).
in	<i>output_file</i>	Output file (VTK format file)
in	<i>mesh_file</i>	File containing mesh data
in	<i>f</i>	Field is stored each <i>f</i> time step [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

saveVTK (Mesh & *mesh*, string *input_file*, string *output_file*, int *f* = 1)

Save a vector to an output **VTK** file.

The Visualization ToolKit (VTK) is an open source, freely available software system for 3D computer graphics. Available information can be found in the site:

<http://public.kitware.com/VTK/>

Parameters

in	<i>mesh</i>	Reference to Mesh instance
in	<i>input_file</i>	Input file (OFELI XML file containing a field).
in	<i>output_file</i>	Output file (VTK format file)
in	<i>f</i>	Field is stored each <i>f</i> time step [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveGmsh (string *input_file*, string *output_file*, string *mesh_file*, int *f* = 1)

Save a vector to an output **Gmsh** file.

Gmsh is a free mesh generator and postprocessor that can be downloaded from the site:

<http://www.geuz.org/gmsh/>

Parameters

in	<i>input_file</i>	Input file (OFELI XML file containing a field).
in	<i>output_file</i>	Output file (Gmsh format file)
in	<i>mesh_file</i>	File containing mesh data
in	<i>f</i>	Field is stored each <i>f</i> time step [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveGmsh (Mesh & mesh, string input_file, string output_file, int f = 1)

Save a vector to an output [Gmsh](#) file.

[Gmsh](#) is a free mesh generator and postprocessor that can be downloaded from the site:
<http://www.geuz.org/gmsh/>

Parameters

in	<i>mesh</i>	Reference to Mesh instance
in	<i>input_file</i>	Input file (OFELI XML file containing a field).
in	<i>output_file</i>	Output file (Gmsh format file)
in	<i>f</i>	Field is stored each <i>f</i> time step [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

bool operator== (const Point< T_ > & a, const Point< T_ > & b)

Operator ==

Return true if a=b, false if not.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator+ (const Point< T_ > & a, const Point< T_ > & b)

Operator +

Return sum of two points a and b

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator+ (const Point< T_ > & a, const T_ & x)

Operator +

Translate a by x

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator- (const Point< T_ > & a)

Unary Operator -

Return minus a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator- (const Point< T_ > & a, const Point< T_ > & b)

Operator -

Return point a minus point b

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator- (const Point< T_ > & a, const T_ & x)

Operator -

Translate a by -x

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator* (const T_ & a, const Point< T_ > & b)

Operator *

Return point b premultiplied by constant a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator* (const int & a, const Point< T_ > & b)

Operator *.

Return point b divided by integer constant a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator* (const Point< T_ > & b, const T_ & a)

Operator /

Return point b multiplied by constant a

Point< T_ > operator* (const Point< T_ > & b, const int & a)

Operator *

Return point b postmultiplied by constant a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

T_ operator* (const Point< T_ > & b, const Point< T_ > & a)

Operator *

Return inner (scalar) product of points a and b

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< T_ > operator/ (const Point< T_ > & b, const T_ & a)

Operator /

Return point b divided by constant a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

bool areClose (const Point< double > & a, const Point< double > & b, double toler = OFELI_TOLERANCE)

Return true if both instances of class Point<double> are distant with less then toler

Author

Rachid Touzani

Copyright

GNU Lesser Public License

double SqrDistance (const Point< double > & a, const Point< double > & b)

Return squared euclidean distance between points a and b

Author

Rachid Touzani

Copyright

GNU Lesser Public License

double Distance (const Point< double > & a, const Point< double > & b)

Return euclidean distance between points a and b

Author

Rachid Touzani

Copyright

GNU Lesser Public License

bool operator< (const Point< size_t > & a, const Point< size_t > & b)

Comparison operator. Returns true if all components of first vector are lower than those of second one.

Return minus a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (std::ostream & s, const Point< T_ > & a)

Output point coordinates.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

bool operator== (const Point2D< T_ > & a, const Point2D< T_ > & b)

Operator ==.

Return true if a=b, false if not.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point2D< T_ > operator+ (const Point2D< T_ > & a, const Point2D< T_ > & b)

Operator +.

Return sum of two points a and b

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point2D< T_ > operator+ (const Point2D< T_ > & a, const T_ & x)

Operator +.
Translate a by x

Author
Rachid Touzani

Copyright
GNU Lesser Public License

Point2D< T_ > operator- (const Point2D< T_ > & a)

Unary Operator -
Return minus a

Author
Rachid Touzani

Copyright
GNU Lesser Public License

Point2D< T_ > operator- (const Point2D< T_ > & a, const Point2D< T_ > & b)

Operator -
Return point a minus point b

Author
Rachid Touzani

Copyright
GNU Lesser Public License

Point2D< T_ > operator- (const Point2D< T_ > & a, const T_ & x)

Operator -
Translate a by -x

Author
Rachid Touzani

Copyright
GNU Lesser Public License

Point2D< T_ > operator* (const T_ & a, const Point2D< T_ > & b)

Operator *.

Return point b premultiplied by constant a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point2D< T_ > operator* (const int & a, const Point2D< T_ > & b)

Operator *.

Return point b divided by integer constant a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point2D< T_ > operator* (const Point2D< T_ > & b, const T_ & a)

Operator /

Return point b postmultiplied by constant a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point2D< T_ > operator* (const Point2D< T_ > & b, const int & a)

Operator *

Return point b postmultiplied by constant a

Author

Rachid Touzani

Copyright

GNU Lesser Public License

T_ operator* (const Point2D< T_ > & b, const Point2D< T_ > & a)

Operator *.

Return point *b* postmultiplied by integer constant *a*.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point2D< T_ > operator/ (const Point2D< T_ > & b, const T_ & a)

Operator /

Return point *b* divided by constant *a*

Author

Rachid Touzani

Copyright

GNU Lesser Public License

real_t SqrDistance (const Point2D< real_t > & a, const Point2D< real_t > & b)

Return squared euclidean distance between points *a* and *b*

Author

Rachid Touzani

Copyright

GNU Lesser Public License

real_t Distance (const Point2D< real_t > & a, const Point2D< real_t > & b)

Return euclidean distance between points *a* and *b*

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (std::ostream & s, const Point2D< T_ > & a)

Output point coordinates.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

real_t Discrepancy (Vect< real_t > & x, const Vect< real_t > & y, int n, int type = 1)

Return discrepancy between 2 vectors x and y

Parameters

in,out	x	First vector (Instance of class Vect). On output, x is assigned the vector y
in	y	Second vector (Instance of class Vect)
in	n	Type of norm <ul style="list-style-type: none"> • 1: Weighted 1-Norm • 2: Weighted 2-Norm • 0: Max-Norm
in	$type$	Discrepancy type (0: Absolute, 1: Relative [Default])

Returns

Computed discrepancy value

```
real_t Discrepancy ( Vect< complex_t > &  $x$ , const Vect< complex_t > &  $y$ , int  $n$ , int  $type = 1$  )
```

Return discrepancy between 2 vectors x and y

Parameters

in,out	x	First vector (Instance of class Vect). On output, x is assigned the vector y
in	y	Second vector (Instance of class Vect)
in	n	Type of norm <ul style="list-style-type: none"> • 1: Weighted 1-Norm • 2: Weighted 2-Norm • 0: Max-Norm
in	$type$	Discrepancy type (0: Absolute, 1: Relative [Default])

Returns

Computed discrepancy value

void getMesh (string *file*, ExternalFileFormat *form*, Mesh & *mesh*, size_t *nb_dof* = 1)

Construct an instance of class [Mesh](#) from a mesh file stored in an external file format.

Parameters

in	<i>file</i>	Input mesh file name.
in	<i>form</i>	<p>Format of the mesh file. This one can be chosen among the enumerated values:</p> <ul style="list-style-type: none"> • GMSH: Mesh generator Gmsh, see site: http://www.geuz.org/gmsh/ • MATLAB: Matlab file, see site: http://www.mathworks.com/products/matlab/ • EASYMESH: Easymesh is a 2-D mesh generator, see site: http://web.mit.edu/easymesh_v1.4/www/easymesh.html • GAMBIT: Gambit is a mesh generator associated to Fluent http://www.stanford.edu/class/me469b/gambit_download.html • BAMG: Mesh generator Bamg, see site: http://raweb.inria.fr/rapportsactivite/R%2002/gamma/uid25.html • NETGEN: Netgen is a 3-D mesh generator, see site: http://www.hpfem.jku.at/netgen/ • TETGEN: Tetgen is a 3-D mesh generator, see site: http://tetgen.berlios.de/ • TRIANGLE_FF: Triangle is a 2-D mesh generator, see site: http://www.cs.cmu.edu/~quake/triangle.html
out	<i>mesh</i>	Mesh instance created by the function.
in	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. Its default value here is 1.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void getBamg (string *file*, Mesh & *mesh*, size_t *nb_dof* = 1)

Construct an instance of class [Mesh](#) from a mesh file stored in [Bamg](#) format.

Parameters

<code>in</code>	<i>file</i>	Name of a file written in the Bamg format.
-----------------	-------------	--

Note

Bamg is a 2-D mesh generator. It allows to construct adapted meshes from a given metric. It was developed at INRIA, France. Available information can be found in the site:
<http://raweb.inria.fr/rapportsactivite/RA2002/gamma/uid25.html>

Parameters

<code>out</code>	<i>mesh</i>	Mesh instance created by the function.
<code>in</code>	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. Its default value here is 1.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void getEasymesh (string *file*, Mesh & *mesh*, size_t *nb_dof* = 1)

Construct an instance of class [Mesh](#) from a mesh file stored in **Easymesh** format.

Parameters

<code>in</code>	<i>file</i>	Name of a file (without extension) written in Easymesh format. Actually, the function <code>Easymesh2MDF</code> attempts to read mesh data from files <code>file.e</code> , <code>file.n</code> and <code>file.s</code> produced by Easymesh .
-----------------	-------------	--

Note

Easymesh is a free program that generates 2-D, unstructured, Delaunay and constrained Delaunay triangulations in general domains. It can be downloaded from the site:
<http://www.dinma.univ.trieste.it/nirftc/research/easymesh/Default.htm>

Parameters

<code>in</code>	<i>mesh</i>	Mesh instance created by the function.
<code>in</code>	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. Its default value here is 1.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void getGambit (string *file*, Mesh & *mesh*, size_t *nb_dof* = 1)

Construct an instance of class [Mesh](#) from a mesh file stored in **Gambit** neutral format.

Note

Gambit is a commercial mesh generator associated to the CFD code **Fluent**. Informations about **Gambit** can be found in the site:

<http://www.fluent.com/software/gambit/>

Parameters

in	<i>file</i>	Name of a file written in the Gambit neutral format.
out	<i>mesh</i>	Mesh instance created by the function.
in	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. Its default value here is 1.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void getGmsh (string *file*, Mesh & *mesh*, size_t *nb_dof* = 1)

Construct an instance of class [Mesh](#) from a mesh file stored in **Gmsh** format.

Note

Gmsh is a free mesh generator that can be downloaded from the site:

<http://www.geuz.org/gmsh/>

Parameters

in	<i>file</i>	Name of a file written in the Gmsh format.
out	<i>mesh</i>	Mesh instance created by the function.
in	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. Its default value here is 1.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void getMatlab (string *file*, Mesh & *mesh*, size_t *nb_dof* = 1)

Construct an instance of class [Mesh](#) from a Matlab mesh data.

Note

Matlab is a language of scientific computing including visualization. It is developed by **MathWorks**. Available information can be found in the site:

<http://www.mathworks.com/products/matlab/>

Parameters

in	<i>file</i>	Name of a file created by Matlab by executing the script file <code>Matlab20FELI.m</code>
out	<i>mesh</i>	Mesh instance created by the function.
in	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. Its default value here is 1.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void getNetgen (string *file*, Mesh & *mesh*, size_t *nb_dof* = 1)

Construct an instance of class [Mesh](#) from a mesh file stored in [Netgen](#) format.

Note

Netgen is a tetrahedral mesh generator that can be downloaded from the site:

<http://www.hpfem.jku.at/netgen/>

Parameters

in	<i>file</i>	Name of a file written in the Netgen format.
out	<i>mesh</i>	Mesh instance created by the function.
in	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. [default = 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void getTetgen (string *file*, Mesh & *mesh*, size_t *nb_dof* = 1)

Construct an instance of class [Mesh](#) from a mesh file stored in [Tetgen](#) format.

Note

Tetgen is a free three-dimensional mesh generator that can be downloaded in the site:

<http://tetgen.berlios.de/>

Parameters

in	<i>file</i>	Name of a file written in the Tetgen format.
out	<i>mesh</i>	Mesh instance created by the function.
in	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. Its default value here is 1.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
void getTriangle ( string file, Mesh & mesh, size_t nb_dof = 1 )
```

Construct an instance of class [Mesh](#) from a mesh file stored in [Triangle](#) format.

Note

TRIANGLE is a C program that can generate meshes, Delaunay triangulations and Voronoi diagrams for 2D pointsets that can be downloaded in the site:

http://people.scs.fsu.edu/~burkardt/c_src/triangle/triangle.html/

Parameters

in	<i>file</i>	Name of a file written in the Tetgen format.
out	<i>mesh</i>	Mesh instance created by the function.
in	<i>nb_dof</i>	Number of degrees of freedom for each node. This information is not provided, in general, by mesh generators. Its default value here is 1.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
void saveMesh ( const string & file, const Mesh & mesh, ExternalFileFormat form )
```

This function saves mesh data a file for a given external format.

Parameters

in	<i>file</i>	File where to store mesh
in	<i>mesh</i>	Mesh instance to save
in	<i>form</i>	Format of the mesh file. This one can be chosen among the enumerated values: <ul style="list-style-type: none"> • GMSH: Mesh generator and graphical postprocessor Gmsh: http://www.geuz.org/gmsh/ • GNUPLOT: Well known graphics software: http://www.gnuplot.info/ • MATLAB: Matlab file: http://www.mathworks.com/products/matlab/ • TECPLOT: Commercial graphics software: http://www.tecplot.com • VTK: Graphics format for the free postprocessor ParaView: http://public.kitware.com/VTK/

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
void saveGmsh ( const string &file, const Mesh & mesh )
```

This function outputs a [Mesh](#) instance in a file in **Gmsh** format.

Note

Gmsh is a free mesh generator that can be downloaded from the site: <http://www.geuz.org/gmsh/>

Parameters

out	<i>file</i>	Output file in Gmsh format.
in	<i>mesh</i>	Mesh instance to save.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveGnuplot (const string & *file*, const Mesh & *mesh*)

This function outputs a [Mesh](#) instance in a file in [Gmsh](#) format.

Note

Gnuplot is a command-line driven program for producing 2D and 3D plots. It is under the GNU General Public License. Available information can be found in the site:

<http://www.gnuplot.info/>

Parameters

out	<i>file</i>	Output file in Gnuplot format.
in	<i>mesh</i>	Mesh instance to save.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveMatlab (const string & *file*, const Mesh & *mesh*)

This function outputs a [Mesh](#) instance in a file in [Matlab](#) format.

Note

Matlab is a language of scientific computing including visualization. It is developed by [MathWorks](#). Available information can be found in the site:

<http://www.mathworks.com/products/matlab/>

Parameters

out	<i>file</i>	Output file in Matlab format.
in	<i>mesh</i>	Mesh instance to save.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveTecplot (const string & *file*, const Mesh & *mesh*)

This function outputs a [Mesh](#) instance in a file in [Tecplot](#) format.

Note

Tecplot is high quality post graphical commercial processing program developed by [Amtec](#). Available information can be found in the site:

<http://www.tecplot.com>

Parameters

out	<i>file</i>	Output file in Tecplot format.
in	<i>mesh</i>	Mesh instance to save.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveVTK (const string & *file*, const Mesh & *mesh*)

This function outputs a [Mesh](#) instance in a file in **VTK** format.

Note

The Visualization ToolKit (VTK) is an open source, freely available software system for 3D computer graphics. Available information can be found in the site:

<http://public.kitware.com/VTK/>

Parameters

out	<i>file</i>	Output file in VTK format.
in	<i>mesh</i>	Mesh instance to save.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void saveBamg (const string & *file*, Mesh & *mesh*)

This function outputs a [Mesh](#) instance in a file in **Bamg** format.

Parameters

in	<i>file</i>	Name of a file written in the Bamg format.
----	-------------	--

Note

Bamg is a 2-D mesh generator. It allows to construct adapted meshes from a given metric. It was developed at INRIA, France. Available information can be found in the site:

<http://raweb.inria.fr/rapportsactivite/RA2002/gamma/uid25.html>

Parameters

in	<i>mesh</i>	Mesh instance.
-----------	-------------	--------------------------------

Author

Rachid Touzani

Copyright

GNU Lesser Public License

BSpline (size_t n, size_t t, Vect< Point< real_t > > & control, Vect< Point< real_t > > & output, size_t num_output)

Function to perform a B-spline interpolation.

This program is adapted from a free program distributed by Keith Vertanen (vertankd@cda.↵mrs.umn.edu) in 1994.

Parameters

in	<i>n</i>	Number of control points minus 1.
in	<i>t</i>	Degree of the polynomial plus 1.
in	<i>control</i>	Control point array made up of Point structure.
out	<i>output</i>	Vector in which the calculated spline points are to be put.
in	<i>num_output</i>	How many points on the spline are to be calculated.

Note

Condition: $n+2 > t$ (No curve results if $n+2 \leq t$) Control vector contains the number of points specified by *n* Output array is the proper size to hold *num_output* point structures

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void banner (const string & prog = " ")

Outputs a banner as header of any developed program.

Parameters

in	<i>prog</i>	Calling program name. Enables writing a copyright notice accompanying the program.
-----------	-------------	--

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void QuickSort (std::vector< T_ > & a, int begin, int end)

Function to sort a vector.

qksort uses the famous quick sorting algorithm.

Parameters

in,out	<i>a</i>	Vector to sort.
in	<i>begin</i>	index of starting iterator
in	<i>end</i>	index of ending iterator

The calling program must provide an overloading of the operator < for the type T_.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void qksort (std::vector< T_ > & a, int begin, int end)

Function to sort a vector.

qksort uses the famous quick sorting algorithm.

Parameters

in,out	<i>a</i>	Vector to sort.
in	<i>begin</i>	index of starting index (default value is 0)
in	<i>end</i>	index of ending index (default value is the vector size - 1)

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void qksort (std::vector< T_ > & a, int begin, int end, C_ compare)

Function to sort a vector according to a key function.

qksort uses the famous quick sorting algorithm.

Parameters

in,out	<i>a</i>	Vector to sort.
in	<i>begin</i>	index of starting index (0 for the beginning of the vector)
in	<i>end</i>	index of ending index
in	<i>compare</i>	A function object that implements the ordering. The user must provide this function that returns a boolean function that is true if the first argument is less than the second and false if not.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void Scale (T_ a, const vector< T_ > & x, vector< T_ > & y)

Multiply vector x by a and save result in vector y
x and y are instances of class vector<T_>

void Scale (T_ a, const Vect< T_ > & x, Vect< T_ > & y)

Multiply vector x by a and save result in vector y
x and y are instances of class Vect<T_>

void Scale (T_ a, vector< T_ > & x)

Multiply vector x by a
x is an instance of class vector<T_>

void Xpy (const vector< T_ > & x, vector< T_ > & y)

Add vector x to y
x and y are instances of class vector<T_>

void Apxy (size_t n, T_ a, T_ * x, T_ * y)

Multiply array x by a and add result to y
n is the arrays size.

void Apxy (T_ a, const vector< T_ > & x, vector< T_ > & y)

Multiply vector x by a and add result to y
x and y are instances of class vector<T_>

void Apxy (T_ a, const Vect< T_ > & x, Vect< T_ > & y)

Multiply vector x by a and add result to y
x and y are instances of class Vect<T_>

T_ Dot (size_t n, T_ * x, T_ * y)

Return dot product of arrays x and y
n is the arrays size.

double Dot (const vector< real_t > & x, const vector< real_t > & y)

Return dot product of vectors x and y.
x and y are instances of class vector<double>

void clear (vector< T_ > & v)

Assign 0 to all entries of a vector.
Parameters

in	v	Vector to clear
----	---	-----------------

void clear (Vect< T_ > & v)

Assign 0 to all entries of a vector.

Parameters

<code>in</code>	<code>v</code>	Vector to clear
-----------------	----------------	-----------------

`real_t Nrm2 (size_t n, real_t * x)`

Return 2-norm of array `x`

Parameters

<code>in</code>	<code>n</code>	is Array length
<code>in</code>	<code>x</code>	Array to treat

`bool Equal (real_t x, real_t y, real_t toler = OFELI_EPSMCH)`

Function to return true if numbers `x` and `y` are close up to a given tolerance `toler`

Default value of tolerance is the constant `OFELI_EPSMCH`

5.12 Vector and Matrix

Vector and matrix classes.

Classes

- class `BMatrix< T_ >`
To handle band matrices.
- class `DMatrix< T_ >`
To handle dense matrices.
- class `DSMatrix< T_ >`
To handle symmetric dense matrices.
- class `LocalMatrix< T_, NR_, NC_ >`
Handles small size matrices like element matrices, with a priori known size.
- class `LocalVect< T_, N_ >`
Handles small size vectors like element vectors.
- class `SkMatrix< T_ >`
To handle square matrices in skyline storage format.
- class `SkSMatrix< T_ >`
To handle symmetric matrices in skyline storage format.
- class `SpMatrix< T_ >`
To handle matrices in sparse storage format.
- class `TrMatrix< T_ >`
To handle tridiagonal matrices.
- class `Vect< T_ >`
To handle general purpose vectors.

Functions

- `template<class T_ >`
`Vect< T_ > operator* (const BMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_ >`
`BMatrix< T_ > operator* (T_ a, const BMatrix< T_ > &A)`
*Operator * (Premultiplication of matrix by constant)*
- `template<class T_ >`
`ostream & operator<< (ostream &s, const BMatrix< T_ > &a)`
Output matrix in output stream.
- `template<class T_ >`
`Vect< T_ > operator* (const DMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_ >`
`ostream & operator<< (ostream &s, const DMatrix< T_ > &a)`
Output matrix in output stream.
- `template<class T_ >`
`Vect< T_ > operator* (const DSMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_ >`
`ostream & operator<< (ostream &s, const DSMatrix< T_ > &a)`

Output matrix in output stream.

- `template<class T_, size_t NR_, size_t NC_>`
`LocalMatrix< T_, NR_, NC_ > operator* (T_ a, const LocalMatrix< T_, NR_, NC_ > &x)`

*Operator * (Multiply matrix x by scalar a)*

- `template<class T_, size_t NR_, size_t NC_>`
`LocalVect< T_, NR_ > operator* (const LocalMatrix< T_, NR_, NC_ > &A, const LocalVect< T_, NC_ > &x)`

*Operator * (Multiply matrix A by vector x)*

- `template<class T_, size_t NR_, size_t NC_>`
`LocalMatrix< T_, NR_, NC_ > operator/ (T_ a, const LocalMatrix< T_, NR_, NC_ > &x)`

Operator / (Divide matrix x by scalar a)

- `template<class T_, size_t NR_, size_t NC_>`
`LocalMatrix< T_, NR_, NC_ > operator+ (const LocalMatrix< T_, NR_, NC_ > &x, const LocalMatrix< T_, NR_, NC_ > &y)`

Operator + (Add matrix x to y)

- `template<class T_, size_t NR_, size_t NC_>`
`LocalMatrix< T_, NR_, NC_ > operator- (const LocalMatrix< T_, NR_, NC_ > &x, const LocalMatrix< T_, NR_, NC_ > &y)`

Operator - (Subtract matrix y from x)

- `template<class T_, size_t NR_, size_t NC_>`
`ostream & operator<< (ostream &s, const LocalMatrix< T_, NR_, NC_ > &A)`

Output vector in output stream.

- `template<class T_, size_t N_>`
`LocalVect< T_, N_ > operator+ (const LocalVect< T_, N_ > &x, const LocalVect< T_, N_ > &y)`

Operator + (Add two vectors)

- `template<class T_, size_t N_>`
`LocalVect< T_, N_ > operator- (const LocalVect< T_, N_ > &x, const LocalVect< T_, N_ > &y)`

Operator - (Subtract two vectors)

- `template<class T_, size_t N_>`
`LocalVect< T_, N_ > operator* (T_ a, const LocalVect< T_, N_ > &x)`

*Operator * (Premultiplication of vector by constant)*

- `template<class T_, size_t N_>`
`LocalVect< T_, N_ > operator/ (T_ a, const LocalVect< T_, N_ > &x)`

Operator / (Division of vector by constant)

- `template<class T_, size_t N_>`
`real.t Dot (const LocalVect< T_, N_ > &a, const LocalVect< T_, N_ > &b)`

Calculate dot product of 2 vectors (instances of class [LocalVect](#))

- `template<class T_, size_t N_>`
`void Scale (T_ a, const LocalVect< T_, N_ > &x, LocalVect< T_, N_ > &y)`

Multiply vector x by constant a and store result in y.

- `template<class T_, size_t N_>`
`void Scale (T_ a, LocalVect< T_, N_ > &x)`

Multiply vector x by constant a and store result in x.

- `template<class T_, size_t N_>`
`void Axpy (T_ a, const LocalVect< T_, N_ > &x, LocalVect< T_, N_ > &y)`

*Add a*x to vector y.*

- `template<class T_, size_t N_>`
`void Copy (const LocalVect< T_, N_ > &x, LocalVect< T_, N_ > &y)`
Copy vector x into vector y.
- `template<class T_, size_t N_>`
`ostream & operator<< (ostream &s, const LocalVect< T_, N_ > &v)`
Output vector in output stream.
- `template<class T_>`
`Vect< T_ > operator* (const SkMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_>`
`ostream & operator<< (ostream &s, const SkMatrix< T_ > &a)`
Output matrix in output stream.
- `template<class T_>`
`Vect< T_ > operator* (const SkSMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_>`
`ostream & operator<< (ostream &s, const SkSMatrix< T_ > &a)`
Output matrix in output stream.
- `template<class T_>`
`Vect< T_ > operator* (const SpMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_>`
`ostream & operator<< (ostream &s, const SpMatrix< T_ > &A)`
Output matrix in output stream.
- `template<class T_>`
`Vect< T_ > operator* (const TrMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_>`
`TrMatrix< T_ > operator* (T_ a, const TrMatrix< T_ > &A)`
*Operator * (Premultiplication of matrix by constant)*
- `template<class T_>`
`ostream & operator<< (ostream &s, const TrMatrix< T_ > &A)`
Output matrix in output stream.
- `template<class T_>`
`Vect< T_ > operator+ (const Vect< T_ > &x, const Vect< T_ > &y)`
Operator + (Addition of two instances of class Vect)
- `template<class T_>`
`Vect< T_ > operator- (const Vect< T_ > &x, const Vect< T_ > &y)`
Operator - (Difference between two vectors of class Vect)
- `template<class T_>`
`Vect< T_ > operator* (const T_ &a, const Vect< T_ > &x)`
*Operator * (Premultiplication of vector by constant)*
- `template<class T_>`
`Vect< T_ > operator* (const Vect< T_ > &x, const T_ &a)`
*Operator * (Postmultiplication of vector by constant)*
- `template<class T_>`
`Vect< T_ > operator/ (const Vect< T_ > &x, const T_ &a)`
Operator / (Divide vector entries by constant)

- `template<class T_>`
`T_ Dot (const Vect< T_> &x, const Vect< T_> &y)`
Calculate dot product of two vectors.
- `void Modulus (const Vect< complex.t> &x, Vect< real.t> &y)`
Calculate modulus of complex vector.
- `void Real (const Vect< complex.t> &x, Vect< real.t> &y)`
Calculate real part of complex vector.
- `void Imag (const Vect< complex.t> &x, Vect< real.t> &y)`
Calculate imaginary part of complex vector.
- `template<class T_>`
`istream & operator>> (istream &s, Vect< T_> &v)`
- `template<class T_>`
`ostream & operator<< (ostream &s, const Vect< T_> &v)`
Output vector in output stream.
- `real.t operator* (const vector< real.t> &x, const vector< real.t> &y)`
*Operator * (Dot product of 2 vector instances)*

Friends

- `template<class TT_>`
`ostream & operator<< (ostream &s, const SpMatrix< TT_> &A)`

5.12.1 Detailed Description

Vector and matrix classes.

5.12.2 Function Documentation

`Vect< T_> operator* (const BMatrix< T_> & A, const Vect< T_> & b)`

Operator * (Multiply vector by matrix and return resulting vector.

Parameters

in	<i>A</i>	BMatrix instance to multiply by vector
in	<i>b</i>	Vect instance

Returns

Vect instance containing $A*b$

`BMatrix< T_> operator* (T_ a, const BMatrix< T_> & A)`

Operator * (Premultiplication of matrix by constant)

Returns

$a*A$

`Vect< T_> operator* (const DMatrix< T_> & A, const Vect< T_> & b)`

Operator * (Multiply vector by matrix and return resulting vector.

Parameters

in	A	DMatrix instance to multiply by vector
in	b	Vect instance

Returns

[Vect](#) instance containing $A*b$ **`Vect< T_ > operator* (const DMatrix< T_ > & A, const Vect< T_ > & b)`**

Operator * (Multiply vector by matrix and return resulting vector.

Parameters

in	A	DMatrix instance to multiply by vector
in	b	Vect instance

Returns

[Vect](#) instance containing $A*b$ **`LocalMatrix< T_, NR_, NC_ > operator* (T_ a, const LocalMatrix< T_, NR_, NC_ > & x)`**

Operator * (Multiply matrix x by scalar a)

Returns

 $a*x$ **`LocalVect< T_, NR_, NC_ > operator* (const LocalMatrix< T_, NR_, NC_ > & x, const LocalVect< T_, NC_ > & y)`**

Operator * (Multiply matrix A by vector x)

This function performs a matrix-vector product and returns resulting vector as a reference to [LocalVect](#) instance

Returns

 $A*x$ **`LocalMatrix< T_, NR_, NC_ > operator/ (T_ a, const LocalMatrix< T_, NR_, NC_ > & x)`**

Operator / (Divide matrix x by scalar a)

Returns

 x/a **`LocalMatrix< T_, NR_, NC_ > operator+ (const LocalMatrix< T_, NR_, NC_ > & x, const LocalMatrix< T_, NR_, NC_ > & y)`**

Operator + (Add matrix x to y)

Returns

 $x+y$

LocalMatrix< T_, NR_, NC_ > operator- (const LocalMatrix< T_, NR_, NC_ > & x, const LocalMatrix< T_, NR_, NC_ > & y)

Operator - (Subtract matrix y from x)

Returns

$x-y$

LocalVect< T_, N_ > operator+ (const LocalVect< T_, N_ > & x, const LocalVect< T_, N_ > & y)

Operator + (Add two vectors)

Returns

$x+y$

LocalVect< T_, N_ > operator- (const LocalVect< T_, N_ > & x, const LocalVect< T_, N_ > & y)

Operator - (Subtract two vectors)

Returns

$x-y$

LocalVect< T_, N_ > operator* (T_ a, const LocalVect< T_, N_ > & x)

Operator * (Premultiplication of vector by constant)

Returns

$a*x$

LocalVect< T_, N_ > operator/ (T_ a, const LocalVect< T_, N_ > & x)

Operator / (Division of vector by constant)

Returns

x/a

double Dot (const LocalVect< T_, N_ > & a, const LocalVect< T_, N_ > & b)

Calculate dot product of 2 vectors (instances of class [LocalVect](#))

Returns

Dot product

Vect< T_ > operator* (const SkMatrix< T_ > & A, const Vect< T_ > & b)

Operator * (Multiply vector by matrix and return resulting vector.

Parameters

<code>in</code>	A	SkMatrix instance to multiply by vector
<code>in</code>	b	Vect instance

Returns

[Vect](#) instance containing $A*b$

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`ostream & operator<< (ostream & s, const SkMatrix< T_ > & a)`

Output matrix in output stream.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`Vect< T_ > operator* (const SkSMatrix< T_ > & A, const Vect< T_ > & b)`

Operator * (Multiply vector by matrix and return resulting vector.

Parameters

<code>in</code>	A	SkSMatrix instance to multiply by vector
<code>in</code>	b	Vect instance

Returns

[Vect](#) instance containing $A*b$

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const SkSMatrix< T_ > & a)

Output matrix in output stream.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Vect< T_ > operator* (const SpMatrix< T_ > & A, const Vect< T_ > & b)

Operator * (Multiply vector by matrix and return resulting vector.

Parameters

in	A	SpMatrix instance to multiply by vector
in	b	Vect instance

Returns

[Vect](#) instance containing A*b

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const SpMatrix< T_ > & A)

Output matrix in output stream.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Vect< T_ > operator* (const TrMatrix< T_ > & A, const Vect< T_ > & b)

Operator * (Multiply vector by matrix and return resulting vector.

Parameters

in	A	TrMatrix instance to multiply by vector
----	---	---

<code>in</code>	<code>b</code>	Vect instance
-----------------	----------------	-------------------------------

Returns

[Vect](#) instance containing $A*b$

Author

Rachid Touzani

Copyright

GNU Lesser Public License

TrMatrix< T_ > operator* (T_ a, const TrMatrix< T_ > & A)

Operator * (Premultiplication of matrix by constant)

Returns

$a*A$

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const TrMatrix< T_ > & a)

Output matrix in output stream.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Vect< T_ > operator+ (const Vect< T_ > & x, const Vect< T_ > & y)

Operator + (Addition of two instances of class [Vect](#))

Returns

$x + y$

Vect< T_ > operator- (const Vect< T_ > & x, const Vect< T_ > & y)

Operator - (Difference between two vectors of class [Vect](#))

Returns

$x - y$

Vect< T_ > operator* (const T_ & a, const Vect< T_ > & x)

Operator * (Premultiplication of vector by constant)

Returns

$a*x$

Vect< T_ > operator* (const Vect< T_ > & x, const T_ & a)

Operator * (Postmultiplication of vector by constant)

Returns

$x*a$

Vect< T_ > operator/ (const Vect< T_ > & x, const T_ & a)

Operator / (Divide vector entries by constant)

Returns

x/a

T_ Dot (const Vect< T_ > & x, const Vect< T_ > & y)

Calculate dot product of two vectors.

Returns

Dot (inner or scalar) product Calculate dot (scalar) product of two vectors

void Modulus (const Vect< complex.t > & x, Vect< real.t > & y)

Calculate modulus of complex vector.

Parameters

in	x	Vector with complex value entries
out	y	Vector containing moduli of entries of x

void Real (const Vect< complex.t > & x, Vect< real.t > & y)

Calculate real part of complex vector.

Parameters

in	x	Vector with complex value entries
out	y	Vector containing real parts of entries of x

void Imag (const Vect< complex.t > & x, Vect< real.t > & y)

Calculate imaginary part of complex vector.

Parameters

in	x	Vector with complex value entries
out	y	Vector containing imaginary parts of entries of x

istream & operator>> (istream & s, Vect< T_ > & a)

Read vector from input stream

ostream & operator<< (ostream & s, const Vect< T_ > & v)

Output vector in output stream.

Level of vector output depends on the global variable `Verbosity`

- If `Verbosity=0`, this function outputs vector size only.
- If `Verbosity>0`, this function outputs vector size, vector name, value of time, and number of components
- If `Verbosity>1`, this function outputs in addition the first 10 entries in vector
- If `Verbosity>2`, this function outputs in addition the first 50 entries in vector
- If `Verbosity>3`, this function outputs in addition the first 100 entries in vector
- If `Verbosity>4`, this function outputs all vector entries

Author

Rachid Touzani

Copyright

GNU Lesser Public License

real_t operator* (const vector< real_t > & x, const vector< real_t > & y)

Operator * (Dot product of 2 vector instances)

Returns

$x \cdot y$

5.12.3 Friends

ostream & operator<< (ostream & s, const SpMatrix< TT_ > & A) [friend]

Output matrix in output stream

5.13 Physical properties of media

Physical properties of materials and media.

Classes

- class [Material](#)

To treat material data. This class enables reading material data in material data files. It also returns these informations by means of its members.

5.13.1 Detailed Description

Physical properties of materials and media.

5.14 Global Variables

All global variables in the library.

Variables

- Node * [theNode](#)
A pointer to [Node](#).
- Element * [theElement](#)
A pointer to [Element](#).
- Side * [theSide](#)
A pointer to [Side](#).
- Edge * [theEdge](#)
A pointer to [Edge](#).
- int [Verbosity](#)
Verbosity parameter.
- int [theStep](#)
Time step counter.
- int [theIteration](#)
Iteration counter.
- int [NbTimeSteps](#)
Number of time steps.
- int [MaxNbIterations](#)
Maximal number of iterations.
- real.t [theTimeStep](#)
Time step label.
- real.t [theTime](#)
Time value.
- real.t [theFinalTime](#)
Final time value.
- real.t [theTolerance](#)
Tolerance value for convergence.
- real.t [theDiscrepancy](#)
Value of discrepancy for an iterative procedure Its default value is 1.0.
- bool [Converged](#)
Boolean variable to say if an iterative procedure has converged.
- bool [InitPetsc](#)

5.14.1 Detailed Description

All global variables in the library.

5.14.2 Variable Documentation

Node* [theNode](#)

A pointer to [Node](#).

Useful for loops on nodes

Element* theElement

A pointer to [Element](#).

Useful for loops on elements

Side* theSide

A pointer to [Side](#).

Useful for loops on sides

Edge* theEdge

A pointer to [Edge](#).

Useful for loops on edges

int Verbosity

Verbosity parameter.

Parameter for verbosity of message outputting.

The value of Verbosity can be modified anywhere in the calling programs. It allows outputting messages in function of the used class or function. To see how this parameter is used in any class, the [OFELI](#) user has to read corresponding documentation.

Its default value is 1

int theStep

Time step counter.

This counter must be initialized by the user if the macro `timeLoop` is not used

Remarks

May be used in conjunction with the macro `TimeLoop`. In this case, it has to be initialized before. Its default value is 1

int theIteration

Iteration counter.

This counter must be initialized by the user

Remarks

May be used in conjunction with the macro `IterationLoop`. Its default value is 1

int NbTimeSteps

Number of time steps.

Remarks

May be used in conjunction with the macro `TimeLoop`.

int MaxNbIterations

Maximal number of iterations.

Remarks

May be used in conjunction with the macro `IterationLoop`. Its default value is 1000

real_t theTimeStep

Time step label.

Remarks

May be used in conjunction with the macro `TimeLoop`. In this case, it has to be initialized before

real_t theTime

Time value.

Remarks

May be used in conjunction with the macro `TimeLoop`. Its default value is 0.0

real_t theFinalTime

Final time value.

Remarks

May be used in conjunction with the macro `TimeLoop`. In this case, it has to be initialized before

real_t theTolerance

Tolerance value for convergence.

Remarks

May be used within an iterative procedure. Its default value is $1.e-8$

bool Converged

Boolean variable to say if an iterative procedure has converged.

Its default value is `false`

bool InitPetsc

Boolean to say if PETSc use was initialized. Useful only if PETSc is used

5.15 Finite Element Mesh

Mesh management classes

Classes

- class [Domain](#)
To store and treat finite element geometric information.
- class [Edge](#)
To describe an edge.
- class [Element](#)
To store and treat finite element geometric information.
- class [Figure](#)
To store and treat a figure (or shape) information.
- class [Rectangle](#)
To store and treat a rectangular figure.
- class [Brick](#)
To store and treat a brick (parallelepiped) figure.
- class [Circle](#)
To store and treat a circular figure.
- class [Sphere](#)
To store and treat a sphere.
- class [Ellipse](#)
To store and treat an ellipsoidal figure.
- class [Triangle](#)
To store and treat a triangle.
- class [Polygon](#)
To store and treat a polygonal figure.
- class [Grid](#)
To manipulate structured grids.
- class [Mesh](#)
To store and manipulate finite element meshes.
- class [MeshAdapt](#)
To adapt mesh in function of given solution.
- class [NodeList](#)
Class to construct a list of nodes having some common properties.
- class [ElementList](#)
Class to construct a list of elements having some common properties.
- class [SideList](#)
Class to construct a list of sides having some common properties.
- class [EdgeList](#)
Class to construct a list of edges having some common properties.
- class [Node](#)
To describe a node.
- class [Partition](#)
To partition a finite element mesh into balanced submeshes.
- class [Side](#)
To store and treat finite element sides (edges in 2-D or faces in 3-D)

Macros

- `#define GRAPH_MEMORY 1000000`
Memory necessary to store matrix graph.
- `#define MAX_NB_ELEMENTS 10000`
Maximal Number of elements.
- `#define MAX_NB_NODES 10000`
Maximal number of nodes.
- `#define MAX_NB_SIDES 30000`
Maximal number of sides in.
- `#define MAX_NB_EDGES 30000`
Maximal Number of edges.
- `#define MAX_NBDOF_NODE 6`
Maximum number of DOF supported by each node.
- `#define MAX_NBDOF_SIDE 6`
Maximum number of DOF supported by each side.
- `#define MAX_NBDOF_EDGE 2`
Maximum number of DOF supported by each edge.
- `#define MAX_NB_ELEMENT_NODES 20`
Maximum number of nodes by element.
- `#define MAX_NB_ELEMENT_EDGES 10`
Maximum number of edges by element.
- `#define MAX_NB_SIDE_NODES 9`
Maximum number of nodes by side.
- `#define MAX_NB_ELEMENT_SIDES 8`
Maximum number of sides by element.
- `#define MAX_NB_ELEMENT_DOF 27`
Maximum number of dof by element.
- `#define MAX_NB_SIDE_DOF 4`
Maximum number of dof by side.
- `#define MAX_NB_INT_PTS 20`
Maximum number of integration points in element.
- `#define MAX_NB_MATERIALS 10`
Maximum number of materials.
- `#define TheNode (*theNode)`
- `#define TheElement (*theElement)`
- `#define TheSide (*theSide)`
- `#define TheEdge (*theEdge)`
- `#define ElementLoop(m) for ((m).topElement(); (theElement=(m).getElement());)`
- `#define ActiveElementLoop(m) for ((m).topElement(); (theElement=(m).getActiveElement());)`
- `#define SideLoop(m) for ((m).topSide(); (theSide=(m).getSide());)`
- `#define EdgeLoop(m) for ((m).topEdge(); (theEdge=(m).getEdge());)`
- `#define NodeLoop(m) for ((m).topNode(); (theNode=(m).getNode());)`
- `#define BoundaryNodeLoop(m) for ((m).topBoundaryNode(); (theNode=(m).getBoundaryNode());)`
- `#define BoundarySideLoop(m) for ((m).topBoundarySide(); (theSide=(m).getBoundarySide());)`
- `#define theNodeLabel theNode->n()`

- #define `theSideLabel` `theSide->n()`
A macro that returns side label in a loop using macro `MeshSides`
- #define `theSideNodeLabel`(i) `theSide->getNodeLabel(i)`
*A macro that returns label of *i*-th node of side using macro `MeshSides`*
- #define `theElementLabel` `theElement->n()`
A macro that returns element label in a loop using macro `MeshElements`
- #define `theElementNodeLabel`(i) `theElement->getNodeLabel(i)`
*A macro that returns label of *i*-th node of element using macro `MeshElements`*

Functions

- ostream & `operator<<` (ostream &s, const Edge &ed)
Output edge data.
- ostream & `operator<<` (ostream &s, const Element &el)
Output element data.
- Figure `operator&&` (const Figure &f1, const Figure &f2)
Function to define a `Figure` instance as the intersection of two `Figure` instances.
- Figure `operator||` (const Figure &f1, const Figure &f2)
Function to define a `Figure` instance as the union of two `Figure` instances.
- Figure `operator-` (const Figure &f1, const Figure &f2)
Function to define a `Figure` instance as the set subtraction of two `Figure` instances.
- ostream & `operator<<` (ostream &s, const Material &m)
Output material data.
- ostream & `operator<<` (ostream &s, const Mesh &ms)
Output mesh data.
- ostream & `operator<<` (ostream &s, const MeshAdapt &a)
Output `MeshAdapt` class data.
- ostream & `operator<<` (ostream &s, const NodeList &nl)
Output `NodeList` instance.
- ostream & `operator<<` (ostream &s, const ElementList &el)
Output `ElementList` instance.
- ostream & `operator<<` (ostream &s, const SideList &sl)
Output `SideList` instance.
- ostream & `operator<<` (ostream &s, const EdgeList &el)
Output `EdgeList` instance.
- size_t `Label` (const Node &nd)
Return label of a given node.
- size_t `Label` (const Element &el)
Return label of a given element.
- size_t `Label` (const Side &sd)
Return label of a given side.
- size_t `Label` (const Edge &ed)
Return label of a given edge.
- size_t `NodeLabel` (const Element &el, size_t n)
Return global label of node local label in element.
- size_t `NodeLabel` (const Side &sd, size_t n)
Return global label of node local label in side.

- `Point< real_t > Coord` (const Node &nd)
Return coordinates of a given node.
- `int Code` (const Node &nd, size_t i=1)
Return code of a given (degree of freedom of) node.
- `int Code` (const Element &el)
Return code of a given element.
- `int Code` (const Side &sd, size_t i=1)
Return code of a given (degree of freedom of) side.
- `bool operator==` (const Element &el1, const Element &el2)
Check equality between 2 elements.
- `bool operator==` (const Side &sd1, const Side &sd2)
Check equality between 2 sides.
- `void DeformMesh` (Mesh &mesh, const Vect< real_t > &u, real_t rate=0.2)
Calculate deformed mesh using a displacement field.
- `void MeshToMesh` (Mesh &m1, Mesh &m2, const Vect< real_t > &u1, Vect< real_t > &u2, size_t nx, size_t ny=0, size_t nz=0, size_t dof=1)
Function to redefine a vector defined on a mesh to a new mesh.
- `void MeshToMesh` (const Vect< real_t > &u1, Vect< real_t > &u2, size_t nx, size_t ny=0, size_t nz=0, size_t dof=1)
Function to redefine a vector defined on a mesh to a new mesh.
- `void MeshToMesh` (Mesh &m1, Mesh &m2, const Vect< real_t > &u1, Vect< real_t > &u2, const Point< real_t > &xmin, const Point< real_t > &xmax, size_t nx, size_t ny, size_t nz, size_t dof=1)
Function to redefine a vector defined on a mesh to a new mesh.
- `real_t getMaxSize` (const Mesh &m)
Return maximal size of element edges for given mesh.
- `real_t getMinSize` (const Mesh &m)
Return minimal size of element edges for given mesh.
- `real_t getMinElementMeasure` (const Mesh &m)
Return minimal measure (length, area or volume) of elements of given mesh.
- `real_t getMaxElementMeasure` (const Mesh &m)
Return maximal measure (length, area or volume) of elements of given mesh.
- `real_t getMinSideMeasure` (const Mesh &m)
Return minimal measure (length or area) of sides of given mesh.
- `real_t getMaxSideMeasure` (const Mesh &m)
Return maximal measure (length or area) of sides of given mesh.
- `real_t getMeanElementMeasure` (const Mesh &m)
Return average measure (length, area or volume) of elements of given mesh.
- `real_t getMeanSideMeasure` (const Mesh &m)
Return average measure (length or area) of sides of given mesh.
- `void setNodeCodes` (Mesh &m, const string &exp, int code, size_t dof=1)
Assign a given code to all nodes satisfying a boolean expression using node coordinates.
- `void setBoundaryNodeCodes` (Mesh &m, const string &exp, int code, size_t dof=1)
Assign a given code to all nodes on boundary that satisfy a boolean expression using node coordinates.
- `int NodeInElement` (const Node *nd, const Element *el)
Say if a given node belongs to a given element.
- `int NodeInSide` (const Node *nd, const Side *sd)

- *Say if a given node belongs to a given side.*
 • `int SideInElement (const Side *sd, const Element *el)`
Say if a given side belongs to a given element.
- `ostream & operator<< (ostream &s, const Node &nd)`
Output node data.
- `ostream & operator<< (ostream &s, const Side &sd)`
Output side data.

5.15.1 Detailed Description

Mesh management classes

5.15.2 Macro Definition Documentation

#define GRAPH_MEMORY 1000000

Memory necessary to store matrix graph.

This value is necessary only if nodes are to be renumbered.

#define TheNode (*theNode)

A macro that gives the instance pointed by *theNode*

#define TheElement (*theElement)

A macro that gives the instance pointed by *theElement*

#define TheSide (*theSide)

A macro that gives the instance pointed by *theSide*

#define TheEdge (*theEdge)

A macro that gives the instance pointed by *theEdge*

#define ElementLoop(m) for ((m).topElement(); (theElement=(m).getElement());

A macro to loop on mesh elements *m* : Instance of Mesh

Note

: Each iteration updates the pointer *theElement* to current Element

**#define ActiveElementLoop(m) for ((m).topElement(); (theElement=(m).getActive↵
Element());**

A macro to loop on mesh active elements *m* : Instance of Mesh

Note

: Each iteration updates the pointer *theElement* to current Element

: This macro is necessary only if adaptive meshing is used

```
#define SideLoop( m ) for ((m).topSide(); (theSide=(m).getSide());)
```

A macro to loop on mesh sides m : Instance of Mesh

Note

: Each iteration updates the pointer `theSide` to current Element

```
#define EdgeLoop( m ) for ((m).topEdge(); (theEdge=(m).getEdge());)
```

A macro to loop on mesh edges m : Instance of Mesh

Note

: Each iteration updates the pointer `theEdge` to current Edge

```
#define NodeLoop( m ) for ((m).topNode(); (theNode=(m).getNode());)
```

A macro to loop on mesh nodes m : Instance of Mesh

Note

: Each iteration updates the pointer `theNode` to current Node

```
#define BoundaryNodeLoop( m ) for ((m).topBoundaryNode(); (theNode=(m).getBoundaryNode());)
```

A macro to loop on mesh nodes m : Instance of Mesh

Note

: Each iteration updates the pointer `theNode` to current Node

```
#define BoundarySideLoop( m ) for ((m).topBoundarySide(); (theSide=(m).getBoundary↵Side());)
```

A macro to loop on mesh boundary sides m : Instance of Mesh

Note

: Each iteration updates the pointer `theSide` to current Node

```
#define theNodeLabel theNode->n()
```

A macro that returns node label in a loop using macro *MeshNodes*

5.15.3 Function Documentation

Figure operator&& (const Figure & $f1$, const Figure & $f2$)

Function to define a [Figure](#) instance as the intersection of two [Figure](#) instances.

Parameters

<code>in</code>	<code>f1</code>	First Figure instance
<code>in</code>	<code>f2</code>	Second Figure instance

Returns

Updated resulting [Figure](#) instance

Figure operator|| (`const Figure & f1`, `const Figure & f2`)

Function to define a [Figure](#) instance as the union of two [Figure](#) instances.

Parameters

<code>in</code>	<code>f1</code>	First Figure instance
<code>in</code>	<code>f2</code>	Second Figure instance

Returns

Updated resulting [Figure](#) instance

Figure operator- (`const Figure & f1`, `const Figure & f2`)

Function to define a [Figure](#) instance as the set subtraction of two [Figure](#) instances.

Parameters

<code>in</code>	<code>f1</code>	First Figure instance to subtract from
<code>in</code>	<code>f2</code>	Second Figure instance to subtract

Returns

Updated resulting [Figure](#) instance

ostream & operator<< (`ostream & s`, `const Mesh & ms`)

Output mesh data.

Level of mesh output depends on the global variable `Verbosity`

- If `Verbosity=0` or `Verbosity=1`, this function outputs only principal mesh parameters: number of nodes, number of elements, ...
- If `Verbosity>1`, this function outputs in addition the list of 10 first nodes, elements and sides
- If `Verbosity>2`, this function outputs in addition the list of 50 first nodes, elements and sides
- If `Verbosity>3`, this function outputs all mesh data

ostream & operator<< (`ostream & s`, `const NodeList & nl`)

Output [NodeList](#) instance.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const ElementList & el)

Output [ElementList](#) instance.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const SideList & sl)

Output [SideList](#) instance.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, const EdgeList & el)

Output [EdgeList](#) instance.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

size_t Label (const Node & nd)

Return label of a given node.

Parameters

<i>in</i>	<i>nd</i>	Reference to Node instance
-----------	-----------	--

Returns

Label of node

Author

Rachid Touzani

Copyright

GNU Lesser Public License

size_t Label (const Element & el)

Return label of a given element.

Parameters

<code>in</code>	<code>el</code>	Reference to Element instance
-----------------	-----------------	---

Returns

Label of element

Author

Rachid Touzani

Copyright

GNU Lesser Public License

size_t Label (const Side & *sd*)

Return label of a given side.

Parameters

<code>in</code>	<code>sd</code>	Reference to Side instance
-----------------	-----------------	--

Returns

Label of side

Author

Rachid Touzani

Copyright

GNU Lesser Public License

size_t Label (const Edge & *ed*)

Return label of a given edge.

Parameters

<code>in</code>	<code>ed</code>	Reference to Edge instance
-----------------	-----------------	--

Returns

Label of edge

Author

Rachid Touzani

Copyright

GNU Lesser Public License

size_t NodeLabel (const Element & *el*, size_t *n*)

Return global label of node local label in element.

Parameters

<code>in</code>	<code>el</code>	Reference to Element instance
<code>in</code>	<code>n</code>	Local label of node in element

Returns

Global label of node

Author

Rachid Touzani

Copyright

GNU Lesser Public License

size_t NodeLabel (const Side & *sd*, size_t *n*)

Return global label of node local label in side.

Parameters

<code>in</code>	<code>sd</code>	Reference to Side instance
<code>in</code>	<code>n</code>	Local label of node in side

Returns

Global label of node

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Point< real.t > Coord (const Node & *nd*)

Return coordinates of a given node.

Parameters

<code>in</code>	<code>nd</code>	Reference to Node instance
-----------------	-----------------	--

Returns

Coordinates of node

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int Code (const Node & *nd*, size_t *i* = 1)

Return code of a given (degree of freedom of) node.

Parameters

<code>in</code>	<code>nd</code>	Reference to Node instance
<code>in</code>	<code>i</code>	Label of dof [Default: 1]

Returns

Code of dof of node

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int Code (const Element & *el*)

Return code of a given element.

Parameters

<code>in</code>	<code>el</code>	Reference to Element instance
-----------------	-----------------	---

Returns

Code of element

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int Code (const Side & *sd*, size_t *i* = 1)

Return code of a given (degree of freedom of) side.

Parameters

<code>in</code>	<code>sd</code>	Reference to Side instance
<code>in</code>	<code>i</code>	Label of dof [Default: 1]

Returns

Code of dof of side

Author

Rachid Touzani

Copyright

GNU Lesser Public License

operator== (const Element & *el1*, const Element & *el2*)

Check equality between 2 elements.

Parameters

<code>in</code>	<code>el1</code>	Reference to first Side instance
<code>in</code>	<code>el2</code>	Reference to second Side instance

Returns

`true` is elements are equal, *i.e.* if they have the same nodes, `false` if not.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`bool operator==(const Side & sd1, const Side & sd2)`

Check equality between 2 sides.

Parameters

<code>in</code>	<code>sd1</code>	Reference to first Side instance
<code>in</code>	<code>sd2</code>	Reference to second Side instance

Returns

`true` is sides are equal, *i.e.* if they have the same nodes, `false` if not.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`void DeformMesh (Mesh & mesh, const Vect< real.t > & u, real.t a = 0.2)`

Calculate deformed mesh using a displacement field.

Parameters

<code>in, out</code>	<code>mesh</code>	Mesh instance. On output, node coordinates are modified to take into account the displacement
<code>in</code>	<code>u</code>	Displacement field at nodes
<code>in</code>	<code>a</code>	Maximal deformation rate. [Default: 1]. A typical value is 0.2 (<i>i.e.</i> 20%).

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
void MeshToMesh ( Mesh & m1, Mesh & m2, const Vect< real.t > & u1, Vect< real.t > & u2, size.t nx, size.t ny = 0, size.t nz = 0, size.t dof = 1 )
```

Function to redefine a vector defined on a mesh to a new mesh.

The program interpolates (piecewise linear) first the vector on a finer structured grid. Then the values on the new mesh nodes are computed.

Remarks

For efficiency the number of grid cells must be large enough so that interpolation provides efficient accuracy

Parameters

in	<i>m1</i>	Reference to the first mesh instance
out	<i>m2</i>	Reference to the second mesh instance
in	<i>u1</i>	Input vector of nodal values defined on first mesh
out	<i>u2</i>	Output vector of nodal values defined on second mesh
in	<i>nx</i>	Number of cells in the x-direction in the fine structured grid
in	<i>ny</i>	Number of cells in the y-direction in the fine structured grid The default value of ny is 0, i.e. a 1-D grid
in	<i>nz</i>	Number of cells in the z-direction in the fine structured grid The default value of nz is 0, i.e. a 1-D or 2-D grid
in	<i>dof</i>	Label of degree of freedom of vector u. Only this dof is considered. [Default: 1]

Note

The input vector *u1* is a one degree of freedom per node vector, i.e. its size must be equal (or greater than) the total number of nodes of mesh *m1*. The size of vector *u2* is deduced from the mesh *m2*

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
void MeshToMesh ( const Vect< real.t > & u1, Vect< real.t > & u2, size.t nx, size.t ny = 0, size.t nz = 0, size.t dof = 1 )
```

Function to redefine a vector defined on a mesh to a new mesh.

The program interpolates (piecewise linear) first the vector on a finer structured grid. Then the values on the new mesh nodes are computed.

Remarks

For efficiency the number of grid cells must be large enough so that interpolation provides efficient accuracy

Parameters

in	<i>u1</i>	Input vector of nodal values defined on first mesh. This vector instance must contain Mesh instance
out	<i>u2</i>	Output vector of nodal values defined on second mesh. This vector instance must contain Mesh instance
in	<i>nx</i>	Number of cells in the x-direction in the fine structured grid
in	<i>ny</i>	Number of cells in the y-direction in the fine structured grid The default value of ny is 0, i.e. a 1-D grid
in	<i>nz</i>	Number of cells in the z-direction in the fine structured grid The default value of nz is 0, i.e. a 1-D or 2-D grid
in	<i>dof</i>	Label of degree of freedom of vector u. Only this dof is considered. [Default: 1]

Note

The input vector *u1* is a one degree of freedom per node vector, i.e. its size must be equal (or greater than) the total number of nodes of mesh *m1*. The size of vector *u2* is deduced from the mesh *m2*

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
void MeshToMesh ( Mesh & m1, Mesh & m2, const Vect< real.t > & u1, Vect< real.t > & u2, const Point< real.t > & xmin, const Point< real.t > & xmax, size.t nx, size.t ny, size.t nz, size.t dof = 1 )
```

Function to redefine a vector defined on a mesh to a new mesh.

The program interpolates (piecewise linear) first the vector on a finer structured grid. Then the values on the new mesh nodes are computed. In this function the grid rectangle is defined so that this one can cover only a submesh of *m1*.

Remarks

For efficiency the number of grid cells must be large enough so that interpolation provides efficient accuracy

Parameters

in	<i>m1</i>	Reference to the first mesh instance
out	<i>m2</i>	Reference to the second mesh instance
in	<i>u1</i>	Input vector of nodal values defined on first mesh
out	<i>u2</i>	Output vector of nodal values defined on second mesh
in	<i>xmin</i>	Point instance containing minimal coordinates of the rectangle that defines the grid

<code>in</code>	<code>xmax</code>	Point instance containing maximal coordinates of the rectangle that defines the grid
<code>in</code>	<code>nx</code>	Number of cells in the x-direction in the fine structured grid
<code>in</code>	<code>ny</code>	Number of cells in the y-direction in the fine structured grid The default value of <code>ny</code> is 0, i.e. a 1-D grid
<code>in</code>	<code>nz</code>	Number of cells in the z-direction in the fine structured grid The default value of <code>nz</code> is 0, i.e. a 1-D or 2-D grid
<code>in</code>	<code>dof</code>	Label of degree of freedom of vector <code>u</code> . Only this <code>dof</code> is considered. [Default: 1]

Note

The input vector `u1` is a one degree of freedom per node vector, i.e. its size must be equal (or greater than) the total number of nodes of mesh `m1`. The size of vector `u2` is deduced from the mesh `m2`

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`real.t getMaxSize (const Mesh & m)`

Return maximal size of element edges for given mesh.

Parameters

<code>in</code>	<code>m</code>	Reference to mesh instance
-----------------	----------------	----------------------------

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`real.t getMinSize (const Mesh & m)`

Return minimal size of element edges for given mesh.

Parameters

<code>in</code>	<code>m</code>	Reference to mesh instance
-----------------	----------------	----------------------------

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`real.t getMinElementMeasure (const Mesh & m)`

Return minimal measure (length, area or volume) of elements of given mesh.

Parameters

<code>in</code>	<code>m</code>	Reference to mesh instance
-----------------	----------------	----------------------------

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`real.t getMaxElementMeasure (const Mesh & m)`

Return maximal measure (length, area or volume) of elements of given mesh.

Parameters

<code>in</code>	<code>m</code>	Reference to mesh instance
-----------------	----------------	----------------------------

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`real.t getMinSideMeasure (const Mesh & m)`

Return minimal measure (length or area) of sides of given mesh.

Parameters

<code>in</code>	<code>m</code>	Reference to mesh instance
-----------------	----------------	----------------------------

Note

Use this function only if sides are present in the mesh and for 2-D meshes

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`real.t getMaxSideMeasure (const Mesh & m)`

Return maximal measure (length or area) of sides of given mesh.

Parameters

<code>in</code>	<code>m</code>	Reference to mesh instance
-----------------	----------------	----------------------------

Note

Use this function only if sides are present in the mesh and for 2-D meshes

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`real_t getMeanElementMeasure (const Mesh & m)`

Return average measure (length, area or volume) of elements of given mesh.

Parameters

<code>in</code>	<code>m</code>	Reference to mesh instance
-----------------	----------------	----------------------------

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`real_t getMeanSideMeasure (const Mesh & m)`

Return average measure (length or area) of sides of given mesh.

Parameters

<code>in</code>	<code>m</code>	Reference to mesh instance
-----------------	----------------	----------------------------

Note

Use this function only if sides are present in the mesh and for 2-D meshes

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`void setNodeCodes (Mesh & m, const string & exp, int code, size_t dof = 1)`

Assign a given code to all nodes satisfying a boolean expression using node coordinates.

Parameters

in	<i>m</i>	Reference to mesh instance
in	<i>exp</i>	Regular expression using x, y, and z coordinates of nodes, according to <code>exprtk</code> parser
in	<i>code</i>	Code to assign
in	<i>dof</i>	Degree of freedom for which code is assigned [Default: 1]

void setBoundaryNodeCodes (Mesh & *m*, const string & *exp*, int *code*, size_t *dof* = 1)

Assign a given code to all nodes on boundary that satisfy a boolean expression using node coordinates.

Parameters

in	<i>m</i>	Reference to mesh instance
in	<i>exp</i>	Regular expression using x, y, and z coordinates of nodes, according to <code>exprtk</code> parser
in	<i>code</i>	Code to assign
in	<i>dof</i>	Degree of freedom for which code is assigned [Default: 1]

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int NodeInElement (const Node * *nd*, const Element * *el*)

Say if a given node belongs to a given element.

Parameters

in	<i>nd</i>	Pointer to Node
in	<i>el</i>	Pointer to Element

Returns

Local label of the node if this one is found, 0 if not.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int NodeInSide (const Node * *nd*, const Side * *sd*)

Say if a given node belongs to a given side.

Parameters

<code>in</code>	<code>nd</code>	Pointer to Node
<code>in</code>	<code>sd</code>	Pointer to Side

Returns

Local label of the node if this one is found, 0 if not.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int SideInElement (const Side * *sd*, const Element * *el*)

Say if a given side belongs to a given element.

Parameters

<code>in</code>	<code>sd</code>	Pointer to Side
<code>in</code>	<code>el</code>	Pointer to Element

Returns

Local label of the side if this one is found, 0 if not.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & *s*, const Node & *nd*)

Output node data.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & *s*, const Side & *sd*)

Output side data.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

5.16 Shape Function

Shape function classes.

Classes

- class [FEShape](#)
Parent class from which inherit all finite element shape classes.
- class [triangle](#)
Defines a triangle. The reference element is the rectangle triangle with two unit edges.
- class [Hexa8](#)
Defines a three-dimensional 8-node hexahedral finite element using Q_1 -isoparametric interpolation.
- class [Line2](#)
To describe a 2-Node planar line finite element.
- class [Line3](#)
To describe a 3-Node quadratic planar line finite element.
- class [Penta6](#)
Defines a 6-node pentahedral finite element using P_1 interpolation in local coordinates $(s.x, s.y)$ and Q_1 isoparametric interpolation in local coordinates $(s.x, s.z)$ and $(s.y, s.z)$.
- class [Quad4](#)
Defines a 4-node quadrilateral finite element using Q_1 isoparametric interpolation.
- class [Tetra4](#)
Defines a three-dimensional 4-node tetrahedral finite element using P_1 interpolation.
- class [Triang3](#)
Defines a 3-Node (P_1) triangle.
- class [Triang6S](#)
Defines a 6-Node straight triangular finite element using P_2 interpolation.

5.16.1 Detailed Description

Shape function classes.

5.17 Solver

Solver functions and classes.

Classes

- class [Reconstruction](#)
To perform various reconstruction operations.
- class [EigenProblemSolver](#)
Class to find eigenvalues and corresponding eigenvectors of a given matrix in a generalized eigenproblem, i.e. Find scalars λ and non-null vectors v such that $[K]\{v\} = \lambda[M]\{v\}$ where $[K]$ and $[M]$ are symmetric matrices. The eigenproblem can be originated from a PDE. For this, we will refer to the matrices K and M as Stiffness and Mass matrices respectively.
- class [Integration](#)
Class for numerical integration methods.
- class [Iter< T_ >](#)
Class to drive an iterative process.
- class [LinearSolver< T_ >](#)
Class to solve systems of linear equations by iterative methods.
- class [LPSolver](#)
To solve a linear programming problem.
- class [MyNLAS](#)
Abstract class to define by user specified function.
- class [MyOpt](#)
Abstract class to define by user specified optimization function.
- class [NLASSolver](#)
To solve a system of nonlinear algebraic equations of the form $f(u) = 0$.
- class [ODESolver](#)
To solve a system of ordinary differential equations.
- class [OptSolver](#)
To solve an optimization problem with bound constraints.
- class [Prec< T_ >](#)
To set a preconditioner.
- class [TimeStepping](#)
To solve time stepping problems, i.e. systems of linear ordinary differential equations of the form $[A2]\{y''\} + [A1]\{y'\} + [A0]\{y\} = \{b\}$.

Macros

- `#define MAX_NB_INPUT_FIELDS 3`
Maximum number of fields for an equation.
- `#define MAX_NB_MESHES 10`
Maximum number of meshes.
- `#define TIME_LOOP(ts, t, ft, n)`
A macro to loop on time steps to integrate on time ts : Time step t : Initial time value updated at each time step ft : Final time value n : Time step index.
- `#define TimeLoop`
A macro to loop on time steps to integrate on time.
- `#define IterationLoop while (++theIteration<MaxNbIterations && Converged==false)`
A macro to loop on iterations for an iterative procedure.

Functions

- ostream & **operator<<** (ostream &s, const Muscl3DT &m)
Output mesh data as calculated in class [Muscl3DT](#).
- template<class T_ >
int **BiCG** (const SpMatrix< T_ > &A, const Prec< T_ > &P, const Vect< T_ > &b, Vect< T_ > &x, int max_it, [real_t](#) &toler)
Biconjugate gradient solver function.
- template<class T_ >
int **BiCG** (const SpMatrix< T_ > &A, int prec, const Vect< T_ > &b, Vect< T_ > &x, int max_it, [real_t](#) toler)
Biconjugate gradient solver function.
- template<class T_ >
int **BiCGStab** (const SpMatrix< T_ > &A, const Prec< T_ > &P, const Vect< T_ > &b, Vect< T_ > &x, int max_it, [real_t](#) toler)
Biconjugate gradient stabilized solver function.
- template<class T_ >
int **BiCGStab** (const SpMatrix< T_ > &A, int prec, const Vect< T_ > &b, Vect< T_ > &x, int max_it, [real_t](#) toler)
Biconjugate gradient stabilized solver function.
- template<class T_ >
int **CG** (const SpMatrix< T_ > &A, const Prec< T_ > &P, const Vect< T_ > &b, Vect< T_ > &x, int max_it, [real_t](#) toler)
Conjugate gradient solver function.
- template<class T_ >
int **CG** (const SpMatrix< T_ > &A, int prec, const Vect< T_ > &b, Vect< T_ > &x, int max_it, [real_t](#) toler)
Conjugate gradient solver function.
- template<class T_ >
int **CGS** (const SpMatrix< T_ > &A, const Prec< T_ > &P, const Vect< T_ > &b, Vect< T_ > &x, int max_it, [real_t](#) toler)
Conjugate Gradient Squared solver function.
- template<class T_ >
int **CGS** (const SpMatrix< T_ > &A, int prec, const Vect< T_ > &b, Vect< T_ > &x, int max_it, [real_t](#) toler)
Conjugate Gradient Squared solver function.
- ostream & **operator<<** (ostream &s, const EigenProblemSolver &es)
Output eigenproblem information.
- template<class T_ >
int **GMRes** (const SpMatrix< T_ > &A, const Prec< T_ > &P, const Vect< T_ > &b, Vect< T_ > &x, size_t m, int max_it, [real_t](#) toler)
GMRes solver function.
- template<class T_ >
int **GMRes** (const SpMatrix< T_ > &A, int prec, const Vect< T_ > &b, Vect< T_ > &x, size_t m, int max_it, [real_t](#) toler)
GMRes solver function.
- template<class T_ >
int **GS** (const SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x, [real_t](#) omega, int max_it, [real_t](#) toler)
Gauss-Seidel solver function.

- `template<class T_ >`
`int Jacobi (const SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x, real.t omega,`
`int max_it, real.t toler)`
Jacobi solver function.
- `ostream & operator<< (ostream &s, const LPSolver &s)`
Output solver information.
- `ostream & operator<< (ostream &s, const NLASSolver &nl)`
Output nonlinear system information.
- `ostream & operator<< (ostream &s, const ODESolver &de)`
Output differential system information.
- `ostream & operator<< (ostream &s, const OptSolver &os)`
Output differential system information.
- `template<class T_ , class M_ >`
`int Richardson (const M_ &A, const Vect< T_ > &b, Vect< T_ > &x, real.t omega, int max_it,`
`real.t toler, int verbose)`
Richardson solver function.
- `template<class T_ >`
`void Schur (SkMatrix< T_ > &A, SpMatrix< T_ > &U, SpMatrix< T_ > &L, SpMatrix< T_`
`> &D, Vect< T_ > &b, Vect< T_ > &c)`
Solve a linear system of equations with a 2x2-block matrix.
- `template<class T_ , class M_ >`
`int SSOR (const M_ &A, const Vect< T_ > &b, Vect< T_ > &x, int max_it, real.t toler)`
SSOR solver function.
- `ostream & operator<< (ostream &s, TimeStepping &ts)`
Output differential system information.

5.17.1 Detailed Description

Solver functions and classes.

5.17.2 Macro Definition Documentation

#define MAX_NB_INPUT_FIELDS 3

Maximum number of fields for an equation.
 Useful for coupled problems

#define MAX_NB_MESHES 10

Maximum number of meshes.
 Useful for coupled problems

#define TimeLoop

Value:

```
OFELI::NbTimeSteps = int(OFELI::theFinalTime/
  OFELI::theTimeStep); \
  for (OFELI::theTime=OFELI::theTimeStep,
  theStep=1; \
    theTime<OFELI::theFinalTime+0.001*
  OFELI::theTimeStep; \
    OFELI::theTime+=OFELI::theTimeStep, ++
  OFELI::theStep)
```

A macro to loop on time steps to integrate on time.

It uses the following global variables defined in **OFELI**: `theStep`, `theTime`, `theTimeStep`, `theFinalTime`

#define IterationLoop while (++theIteration<MaxNbIterations && Converged==false)

A macro to loop on iterations for an iterative procedure.

It uses the following global variables defined in **OFELI**: `theIteration`, `MaxNbIterations`, `Converged`

Warning

The variable `theIteration` must be zeroed before using this macro

5.17.3 Function Documentation

int BiCG (const SpMatrix< T_ > & A, const Prec< T_ > & P, const Vect< T_ > & b, Vect< T_ > & x, int max_it, real_t & toler)

Biconjugate gradient solver function.

This function uses the preconditioned Biconjugate Conjugate Gradient algorithm to solve a linear system with a sparse matrix.

The global variable `Verbosity` enables choosing output message level

- `Verbosity < 2` : No output message
- `Verbosity > 1` : Notify executing the function CG
- `Verbosity > 2` : Notify convergence with number of performed iterations or divergence
- `Verbosity > 3` : Output each iteration number and residual
- `Verbosity > 6` : Print final solution if convergence
- `Verbosity > 10` : Print obtained solution at each iteration

Parameters

in	<i>A</i>	Problem matrix (Instance of class SpMatrix).
in	<i>P</i>	Preconditioner (Instance of class Prec).
in	<i>b</i>	Right-hand side vector (class Vect)
in,out	<i>x</i>	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	<i>max_it</i>	Maximum number of iterations.
	<i>toler</i>	[in] Tolerance for convergence (measured in relative weighted 2-Norm).

Returns

Number of performed iterations,

Template Parameters

<code><T_></code>	Data type (double, float, complex<double>, ...)
-------------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int BiCG (const SpMatrix< T_ > &A, int prec, const Vect< T_ > &b, Vect< T_ > &x, int max_it, real_t toler)

Biconjugate gradient solver function.

This function uses the preconditioned Biconjugate Conjugate Gradient algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	<i>A</i>	Problem matrix (Instance of class SpMatrix).
in	<i>prec</i>	Enum variable selecting a preconditioner, among the values ID← ENT_PREC, DIAG_PREC, ILU_PREC or SSOR_PREC
in	<i>b</i>	Right-hand side vector (class Vect)
in,out	<i>x</i>	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	<i>max_it</i>	Maximum number of iterations.
	<i>toler</i>	[in] Tolerance for convergence (measured in relative weighted 2-Norm).

Returns

Number of performed iterations,

Template Parameters

<code><T_></code>	Data type (double, float, complex<double>, ...)
-------------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
int BiCGStab ( const SpMatrix< T_ > & A, const Prec< T_ > & P, const Vect< T_ > & b,  
Vect< T_ > & x, int max_it, real_t toler )
```

Biconjugate gradient stabilized solver function.

This function uses the preconditioned Conjugate Gradient Stabilized algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	A	Problem matrix (Instance of class SpMatrix).
in	P	Preconditioner (Instance of class Prec).
in	b	Right-hand side vector (class Vect)
in,out	x	Vect instance containing initial solution guess on input and solution of the linear system on output (If iterations have succeeded).
in	max_it	Maximum number of iterations.
in	$toler$	Tolerance for convergence (measured in relative weighted 2- \leftrightarrow Norm).

Returns

Number of performed iterations,

Template Parameters

$\langle T_- \rangle$	Data type (double, float, complex<double>, ...)
-----------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
int BiCGStab ( const SpMatrix< T_ > & A, int prec, const Vect< T_ > & b, Vect< T_ > & x,  
int max_it, real_t toler )
```

Biconjugate gradient stabilized solver function.

This function uses the preconditioned Conjugate Gradient Stabilized algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG

- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	A	Problem matrix (Instance of class SpMatrix).
in	$prec$	Enum variable selecting a preconditioner, among the values ID← ENT_PREC, DIAG_PREC, ILU_PREC or SSOR_PREC
in	b	Right-hand side vector (class Vect)
in,out	x	Vect instance containing initial solution guess in input and solu- tion of the linear system in output (If iterations have succeeded).
in	max_it	Maximum number of iterations.
in	$toler$	Tolerance for convergence (measured in relative weighted 2-← Norm).

Returns

Number of performed iterations,

Template Parameters

$\langle T_ \rangle$	Data type (double, float, complex<double>, ...)
-----------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
int CG ( const SpMatrix< T_ > & A, const Prec< T_ > & P, const Vect< T_ > & b, Vect< T_ > & x, int max_it, real_t toler )
```

Conjugate gradient solver function.

This function uses the preconditioned Conjugate Gradient algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	A	Problem matrix (Instance of class SpMatrix).
in	P	Preconditioner (Instance of class Prec).
in	b	Right-hand side vector (class Vect)
in, out	x	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	max_it	Maximum number of iterations.
in	$toler$	Tolerance for convergence (measured in relative weighted 2- \leftrightarrow Norm).

Returns

Number of performed iterations,

Template Parameters

$\langle T_ \rangle$	Data type (double, float, complex<double>, ...)
-----------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int CG (const [SpMatrix](#)< T_ > & A, int *prec*, const [Vect](#)< T_ > & b, [Vect](#)< T_ > & x, int *max_it*, real_t *toler*)

Conjugate gradient solver function.

This function uses the preconditioned Conjugate Gradient algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	A	Problem matrix (Instance of abstract class SpMatrix).
in	<i>prec</i>	Enum variable selecting a preconditioner, among the values ID \leftrightarrow ENT_PREC, DIAG_PREC, ILU_PREC or SSOR_PREC

in	b	Right-hand side vector (class Vect)
in,out	x	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	max_it	Maximum number of iterations.
in	$toler$	Tolerance for convergence (measured in relative weighted 2-Norm).

Returns

Number of performed iterations,

Template Parameters

$\langle T_ \rangle$	Data type (double, float, complex<double>, ...)
-----------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
int CGS ( const SpMatrix< T_ > & A, const Prec< T_ > & P, const Vect< T_ > & b, Vect< T_ > & x, int max_it, real_t toler )
```

Conjugate Gradient Squared solver function.

This function uses the preconditioned Conjugate Gradient Squared algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	A	Problem matrix (Instance of class SpMatrix).
in	P	Preconditioner (Instance of class Prec).
in	b	Right-hand side vector (class Vect)
in,out	x	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).

in	<i>max_it</i>	Maximum number of iterations.
in	<i>toler</i>	Tolerance for convergence (measured in relative weighted 2- \leftrightarrow Norm).

Returns

Number of performed iterations

Template Parameters

$\langle T_ \rangle$	Data type (real_t, float, complex \langle real_t \rangle , ...)
-----------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int CGS (const SpMatrix \langle T_ \rangle & A, int prec, const Vect \langle T_ \rangle & b, Vect \langle T_ \rangle & x, int max_it, real_t toler)

Conjugate Gradient Squared solver function.

This function uses the preconditioned Conjugate Gradient Squared algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	<i>A</i>	Problem matrix (Instance of class SpMatrix).
in	<i>prec</i>	Enum variable selecting a preconditioner, among the values ID \leftrightarrow ENT_PREC, DIAG_PREC, ILU_PREC or SSOR_PREC
in	<i>b</i>	Right-hand side vector (class Vect)
in,out	<i>x</i>	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	<i>max_it</i>	Maximum number of iterations.
in	<i>toler</i>	Tolerance for convergence (measured in relative weighted 2- \leftrightarrow Norm).

Returns

Number of performed iterations

Template Parameters

<code><T_></code>	Data type (real.t, float, complex<real.t>, ...)
-------------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int GMRes (const SpMatrix< T_ > &A, const Prec< T_ > &P, const Vect< T_ > &b, Vect< T_ > &x, size.t m, int max.it, real.t toler)

GMRes solver function.

This function uses the preconditioned GMRES algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	<i>A</i>	Problem matrix (Instance of class SpMatrix).
in	<i>P</i>	Preconditioner (Instance of class Prec).
in	<i>b</i>	Right-hand side vector (class Vect)
in,out	<i>x</i>	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	<i>m</i>	Number of subspaces to generate for iterations.
in	<i>max.it</i>	Maximum number of iterations.
in	<i>toler</i>	Tolerance for convergence (measured in relative weighted 2-↔ Norm).

Returns

Number of performed iterations,

Template Parameters

<code><T_></code>	Data type (double, float, complex<double>, ...)
-------------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
int GMRes ( const SpMatrix< T_ > & A, int prec, const Vect< T_ > & b, Vect< T_ > & x,  
size_t m, int max_it, real_t toler )
```

GMRes solver function.

This function uses the preconditioned GMRES algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message
- Verbosity > 1 : Notify executing the function CG
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	<i>A</i>	Problem matrix (Instance of class SpMatrix).
in	<i>prec</i>	Enum variable selecting a preconditioner, among the values ID← ENT_PREC, DIAG_PREC, ILU_PREC or SSOR_PREC
in	<i>b</i>	Right-hand side vector (class Vect)
in,out	<i>x</i>	Vect instance containing initial solution guess in input and solu- tion of the linear system in output (If iterations have succeeded).
in	<i>m</i>	Number of subspaces to generate for iterations.
in	<i>max_it</i>	Maximum number of iterations.
in	<i>toler</i>	Tolerance for convergence (measured in relative weighted 2-← Norm).

Returns

Number of performed iterations,

Template Parameters

<T_>	Data type (double, float, complex<double>, ...)
------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
int GS ( const SpMatrix< T_ > & A, const Vect< T_ > & b, Vect< T_ > & x, real_t omega, int  
max_it, real_t toler )
```

Gauss-Seidel solver function.

This function uses the relaxed Gauss-Seidel algorithm to solve a linear system with a sparse matrix.

The global variable Verbosity enables choosing output message level

- Verbosity < 2 : No output message

- Verbosity > 1 : Notify executing the function GS
- Verbosity > 2 : Notify convergence with number of performed iterations or divergence
- Verbosity > 3 : Output each iteration number and residual
- Verbosity > 6 : Print final solution if convergence
- Verbosity > 10 : Print obtained solution at each iteration

Parameters

in	A	Problem matrix (Instance of class SpMatrix).
in	b	Right-hand side vector (class Vect)
in,out	x	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	ω	Relaxation parameter.
in	max_it	Maximum number of iterations.
in	$toler$	Tolerance for convergence (measured in relative weighted 2- \leftrightarrow Norm).

Returns

Number of performed iterations

Template Parameters

$\langle T_ \rangle$	Data type (real_t, float, complex<real_t>, ...)
-----------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

```
int Jacobi ( const SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x, real_t omega,  
int max_it, real_t toler )
```

Jacobi solver function.

Parameters

in	A	Problem matrix (Instance of class SpMatrix).
in	b	Right-hand side vector (class Vect)
in,out	x	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	ω	Relaxation parameter.
in	max_it	Maximum number of iterations.
in,out	$toler$	Tolerance for convergence (measured in relative weighted 2- \leftrightarrow Norm).

Returns

Number of performed iterations,

Template Parameters

<code><T_></code>	Data type (real.t, float, complex<real.t>, ...)
<code><M_></code>	Matrix storage class

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int Richardson (const *M_* & *A*, const Vect< T_ > & *b*, Vect< T_ > & *x*, real.t *omega*, int *max_it*, real.t *toler*, int *verbose*)

Richardson solver function.

Parameters

in	<i>A</i>	Problem matrix problem (Instance of abstract class <i>M_</i>).
in	<i>b</i>	Right-hand side vector (class Vect)
	<i>x</i>	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	<i>omega</i>	Relaxation parameter.
in	<i>max_it</i>	Maximum number of iterations.
in	<i>toler</i>	Tolerance for convergence (measured in relative weighted 2- \leftrightarrow Norm).
in	<i>verbose</i>	Information output parameter (0: No output, 1: Output iteration information, 2 and greater: Output iteration information and solution at each iteration.

Returns

nb_it Number of performed iterations,

Template Parameters

<code><T_></code>	Data type (real.t, float, complex<real.t>, ...)
<code><M_></code>	Matrix storage class

Author

Rachid Touzani

Copyright

GNU Lesser Public License

void Schur (SkMatrix< T_ > & *A*, SpMatrix< T_ > & *U*, SpMatrix< T_ > & *L*, SpMatrix< T_ > & *D*, Vect< T_ > & *b*, Vect< T_ > & *c*)

Solve a linear system of equations with a 2x2-block matrix.

The linear system is of the form

$$\begin{bmatrix} A & U \\ L & D \end{bmatrix} \begin{bmatrix} x \\ y \end{bmatrix} = \begin{bmatrix} b \\ c \end{bmatrix}$$

Parameters

in	A	Instance of class SkMatrix class for the first diagonal block. The matrix must be invertible and factorizable (Do not use SpMatrix class) where A, U, L, D are instances of matrix classes,
in	U	Instance of class SpMatrix for the upper triangle block. The matrix can be rectangular
in	L	Instance of class SpMatrix for the lower triangle block. The matrix can be rectangular
in	D	Instance of class SpMatrix for the second diagonal block. The matrix must be factorizable (Do not use SpMatrix class)
in,out	b	Vector (Instance of class Vect) that contains the first block of right-hand side on input and the first block of the solution on output. b must have the same size as the dimension of A .
in,out	c	Vect instance that contains the second block of right-hand side on output and the first block of the solution on output. c must have the same size as the dimension of D .

Template Argument:

Template Parameters

$\langle T_ \rangle$	data type (real_t, float, ...)
-----------------------	--------------------------------

Author

Rachid Touzani

Copyright

GNU Lesser Public License

int SSOR (const $M_$ & A , const $Vect< T_ \rangle$ & b , $Vect< T_ \rangle$ & x , int max_it , real_t $toler$)

SSOR solver function.

Parameters

in	A	Problem matrix (Instance of abstract class $M_$).
in	b	Right-hand side vector (class Vect)
in,out	x	Vect instance containing initial solution guess in input and solution of the linear system in output (If iterations have succeeded).
in	max_it	Maximum number of iterations.
in	$toler$	Tolerance for convergence (measured in relative weighted 2- \leftrightarrow Norm).

Returns

Number of performed iterations,

Template Arguments:

- $T_$ data type (double, float, ...)
- $M_$ Matrix storage class

Author

Rachid Touzani

Copyright

GNU Lesser Public License

ostream & operator<< (ostream & s, TimeStepping & ts)

Output differential system information.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

5.18 OFELI

Modules

- [General Purpose Equations](#)
Gathers equation related classes.
- [Conservation Law Equations](#)
Conservation law equations.
- [Electromagnetics](#)
Electromagnetic equations.
- [Fluid Dynamics](#)
Fluid Dynamics equations.
- [Interface Problems](#)
Interface problems, including image processing.
- [Laplace equation](#)
Laplace and Poisson equations.
- [Porous Media problems](#)
Porous Media equation classes.
- [Solid Mechanics](#)
Solid Mechanics finite element equations.
- [Heat Transfer](#)
Heat Transfer equations.
- [Input/Output](#)
Input/Output utility classes.
- [Utilities](#)
Utility functions and classes.
- [Physical properties of media](#)
Physical properties of materials and media.
- [Global Variables](#)
All global variables in the library.
- [Finite Element Mesh](#)
Mesh management classes
- [Shape Function](#)
Shape function classes.
- [Solver](#)
Solver functions and classes.
- [Vector and Matrix](#)
Vector and matrix classes.

Files

- file [AbsEqua.h](#)
Definition file for abstract class AbsEqua.
- file [ICPG1D.h](#)
Definition file for class ICPG1D.
- file [ICPG2DT.h](#)
Definition file for class ICPG2DT.
- file [ICPG3DT.h](#)

- *Definition file for class ICPG3DT.*
- file [LCL1D.h](#)
- *Definition file for class LCL1D.*
- file [LCL2DT.h](#)
- *Definition file for class LCL2DT.*
- file [LCL3DT.h](#)
- *Definition file for class LCL3DT.*
- file [Muscl.h](#)
- *Definition file for class Muscl.*
- file [Muscl1D.h](#)
- *Definition file for class Muscl1D.*
- file [Muscl2DT.h](#)
- *Definition file for class Muscl2DT.*
- file [Muscl3DT.h](#)
- *Definition file for class Muscl3DT.*
- file [BiotSavart.h](#)
- *Definition file for class BiotSavart.*
- file [EC2D1T3.h](#)
- *Definition file for class EC2D1T3.*
- file [EC2D2T3.h](#)
- *Definition file for class EC2D2T3.*
- file [Equa_Electromagnetics.h](#)
- *Definition file for class FE_Electromagnetics.*
- file [HelmholtzBT3.h](#)
- *Definition file for class HelmholtzBT3.*
- file [Equation.h](#)
- *Definition file for class Equation.*
- file [Equa_Fluid.h](#)
- *Definition file for class Equa_Fluid.*
- file [NSP2DQ41.h](#)
- *Definition file for class NSP2DQ41.*
- file [TINS2DT3S.h](#)
- *Definition file for class TINS2DT3S.*
- file [TINS3DT4S.h](#)
- *Definition file for class TINS3DT4S.*
- file [Equa_Laplace.h](#)
- *Definition file for class Equa_Laplace.*
- file [Laplace1DL2.h](#)
- *Definition file for class Laplace1DL2.*
- file [Laplace1DL3.h](#)
- *Definition file for class Laplace1DL3.*
- file [Laplace2DT3.h](#)
- *Definition file for class Laplace2DT3.*
- file [Laplace2DT6.h](#)
- *Definition file for class Laplace2DT6.*
- file [Laplace3DT4.h](#)

- Definition file for class Laplace3DT4.*
- file [SteklovPoincare2DBE.h](#)
 - Definition file for class SteklovPoincare2DBE.*
- file [Equa_Porous.h](#)
 - Definition file for class Equa_Porous.*
- file [WaterPorous1D.h](#)
 - Definition file for class WaterPorous1D.*
- file [WaterPorous2D.h](#)
 - Definition file for class WaterPorous2D.*
- file [Bar2DL2.h](#)
 - Definition file for class Bar2DL2.*
- file [Beam3DL2.h](#)
 - Definition file for class Beam3DL2.*
- file [Elas2DQ4.h](#)
 - Definition file for class Elas2DQ4.*
- file [Elas2DT3.h](#)
 - Definition file for class Elas2DT3.*
- file [Elas3DH8.h](#)
 - Definition file for class Elas3DH8.*
- file [Elas3DT4.h](#)
 - Definition file for class Elas3DT4.*
- file [Equa_Solid.h](#)
 - Definition file for class Equa_Solid.*
- file [DC1DL2.h](#)
 - Definition file for class DC1DL2.*
- file [DC2DT3.h](#)
 - Definition file for class DC2DT3.*
- file [DC2DT6.h](#)
 - Definition file for class DC2DT6.*
- file [DC3DAT3.h](#)
 - Definition file for class DC3DAT3.*
- file [DC3DT4.h](#)
 - Definition file for class DC3DT4.*
- file [Equa_Therm.h](#)
 - Definition file for class Equa_Therm.*
- file [PhaseChange.h](#)
 - Definition file for class PhaseChange and its parent abstract class.*
- file [Funct.h](#)
 - Definition file for class Funct.*
- file [IOField.h](#)
 - Definition file for class IOField.*
- file [IPF.h](#)
 - Definition file for class IPF.*
- file [output.h](#)
 - File that contains some output utility functions.*
- file [Prescription.h](#)

- *Definition file for class Prescription.*
- file [saveField.h](#)
 - *Prototypes for functions to save mesh in various file formats.*
- file [saveField.h](#)
 - *Prototypes for functions to save mesh in various file formats.*
- file [Tabulation.h](#)
 - *Definition file for class Tabulation.*
- file [BMatrix.h](#)
 - *Definition file for class BMatrix.*
- file [DMatrix.h](#)
 - *Definition file for class DMatrix.*
- file [DSMatrix.h](#)
 - *Definition file for abstract class DSMatrix.*
- file [LocalMatrix.h](#)
 - *Definition file for class LocalMatrix.*
- file [LocalVect.h](#)
 - *Definition file for class LocalVect.*
- file [Matrix.h](#)
 - *Definition file for abstract class Matrix.*
- file [Point.h](#)
 - *Definition file and implementation for class Point.*
- file [Point2D.h](#)
 - *Definition file for class Point2D.*
- file [SkMatrix.h](#)
 - *Definition file for class SkMatrix.*
- file [SkSMatrix.h](#)
 - *Definition file for class SkSMatrix.*
- file [SpMatrix.h](#)
 - *Definition file for class SpMatrix.*
- file [TrMatrix.h](#)
 - *Definition file for class TrMatrix.*
- file [Domain.h](#)
 - *Definition file for class Domain.*
- file [Edge.h](#)
 - *Definition file for class Edge.*
- file [Element.h](#)
 - *Definition file for class Element.*
- file [Figure.h](#)
 - *Definition file for figure classes.*
- file [getMesh.h](#)
 - *Definition file for mesh conversion functions.*
- file [Grid.h](#)
 - *Definition file for class Grid.*
- file [Material.h](#)
 - *Definition file for class Material.*
- file [Mesh.h](#)

- Definition file for class Mesh.*
- file [MeshAdapt.h](#)
 - Definition file for class MeshAdapt.*
- file [MeshExtract.h](#)
 - Definition file for classes for extracting submeshes.*
- file [MeshUtil.h](#)
 - Definitions of utility functions for meshes.*
- file [Node.h](#)
 - Definition file for class Node.*
- file [saveMesh.h](#)
 - Prototypes for functions to save mesh in various file formats.*
- file [Side.h](#)
 - Definition file for class Side.*
- file [FEShape.h](#)
 - Definition file for class FEShape.*
- file [Hexa8.h](#)
 - Definition file for class Hexa8.*
- file [Line2.h](#)
 - Definition file for class Line2.*
- file [Line3.h](#)
 - Definition file for class Line3.*
- file [Penta6.h](#)
 - Definition file for class Penta6.*
- file [Quad4.h](#)
 - Definition file for class Quad4.*
- file [Tetra4.h](#)
 - Definition file for class Tetra4.*
- file [Triang3.h](#)
 - Definition file for class Triang3.*
- file [Triang6S.h](#)
 - Definition file for class Triang6S.*
- file [BiCG.h](#)
 - Solves an unsymmetric linear system of equations using the BiConjugate Gradient method.*
- file [BSpline.h](#)
 - Function to perform a B-spline interpolation.*
- file [CG.h](#)
 - Functions to solve a symmetric positive definite linear system of equations using the Conjugate Gradient method.*
- file [CGS.h](#)
 - Solves an unsymmetric linear system of equations using the Conjugate Gradient Squared method.*
- file [EigenProblemSolver.h](#)
 - Definition file for class EigenProblemSolver.*
- file [GMRes.h](#)
 - Function to solve a linear system of equations using the Generalized Minimum Residual method.*
- file [GS.h](#)
 - Function to solve a linear system of equations using the Gauss-Seidel method.*
- file [Integration.h](#)

- Definition file for numerical integration class.*
- file [Jacobi.h](#)
 - Function to solve a linear system of equations using the Jacobi method.*
- file [MyNLAS.h](#)
 - Definition file for abstract class MyNLAS.*
- file [MyOpt.h](#)
 - Definition file for abstract class MyOpt.*
- file [ODESolver.h](#)
 - Definition file for class ODESolver.*
- file [Prec.h](#)
 - Definition file for preconditioning classes.*
- file [Richardson.h](#)
 - Function to solve a linear system of equations using the Richardson method.*
- file [SSOR.h](#)
 - Function to solve a linear system of equations using the Symmetric Successive Over Relaxation method.*
- file [TimeStepping.h](#)
 - Definition file for class TimeStepping.*
- file [constants.h](#)
 - File that contains some widely used constants.*
- file [Gauss.h](#)
 - Definition file for struct Gauss.*
- file [qksort.h](#)
 - File that contains template quick sorting function.*
- file [Timer.h](#)
 - Definition file for class Timer.*
- file [util.h](#)
 - File that contains various utility functions.*

Classes

- class [AbsEqua< T_ >](#)
 - Mother abstract class to describe equation.*
- class [LocalVect< T_, N_ >](#)
 - Handles small size vectors like element vectors.*
- class [ICPG1D](#)
 - Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 1-D.*
- class [ICPG2DT](#)
 - Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 2-D.*
- class [ICPG3DT](#)
 - Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 3-D.*
- class [LCL1D](#)
 - Class to solve the linear conservation law (Hyperbolic equation) in 1-D by a MUSCL Finite Volume scheme.*
- class [LCL2DT](#)
 - Class to solve the linear hyperbolic equation in 2-D by a MUSCL Finite Volume scheme on triangles.*
- class [LCL3DT](#)
 - Class to solve the linear conservation law equation in 3-D by a MUSCL Finite Volume scheme on tetrahedra.*
- class [Muscl](#)

- Parent class for hyperbolic solvers with Muscl scheme.*

 - class [Vect< T_ >](#)
To handle general purpose vectors.
 - class [Muscl1D](#)
Class for 1-D hyperbolic solvers with [Muscl](#) scheme.
 - class [Muscl2DT](#)
Class for 2-D hyperbolic solvers with [Muscl](#) scheme.
 - class [Muscl3DT](#)
Class for 3-D hyperbolic solvers with [Muscl](#) scheme using tetrahedra.
 - class [BiotSavart](#)
Class to compute the magnetic induction from the current density using the Biot-Savart formula.
 - class [EC2D1T3](#)
Eddy current problems in 2-D domains using solenoidal approximation.
 - class [EC2D2T3](#)
Eddy current problems in 2-D domains using transversal approximation.
 - class [Equa_Electromagnetics< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for Electromagnetics [Equation](#) classes.
 - class [HelmholtzBT3](#)
Builds finite element arrays for Helmholtz equations in a bounded media using 3-Node triangles.
 - class [Equation< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for all equation classes.
 - class [Equa_Fluid< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for Fluid Dynamics [Equation](#) classes.
 - class [NSP2DQ41](#)
Builds finite element arrays for incompressible Navier-Stokes equations in 2-D domains using Q_1/P_0 element and a penalty formulation for the incompressibility condition.
 - class [TINS2DT3S](#)
Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 2-D domains. Numerical approximation uses stabilized 3-node triangle finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.
 - class [TINS3DT4S](#)
Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 3-↔D domains. Numerical approximation uses stabilized 4-node tetrahedral finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.
 - class [FastMarching2D](#)
To run a Fast Marching Method on 2-D structured uniform grids.
 - class [FMM2D](#)
class for the fast marching 2-D algorithm
 - class [FMM3D](#)
class for the 3-D fast marching algorithm
 - class [FMMSolver](#)
The Fast Marching Method solver.
 - class [Equa_Laplace< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for classes about the Laplace equation.
 - class [Laplace1DL2](#)
To build element equation for a 1-D elliptic equation using the 2-Node line element (P_1).
 - class [Laplace1DL3](#)
To build element equation for the 1-D elliptic equation using the 3-Node line (P_2).

- class [Laplace2DT3](#)
To build element equation for the Laplace equation using the 2-D triangle element (P_1).
- class [Laplace2DT6](#)
To build element equation for the Laplace equation using the 2-D triangle element (P_2).
- class [SteklovPoincare2DBE](#)
Solver of the Steklov Poincare problem in 2-D geometries using piecewise constant boundary elemen.
- class [Equa_Porous< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for Porous Media Finite Element classes.
- class [WaterPorous2D](#)
To solve water flow equations in porous media (1-D)
- class [Bar2DL2](#)
To build element equations for Planar Elastic Bar element with 2 DOF (Degrees of Freedom) per node.
- class [Beam3DL2](#)
To build element equations for 3-D beam equations using 2-node lines.
- class [Elas2DQ4](#)
To build element equations for 2-D linearized elasticity using 4-node quadrilaterals.
- class [Elas2DT3](#)
To build element equations for 2-D linearized elasticity using 3-node triangles.
- class [Elas3DH8](#)
To build element equations for 3-D linearized elasticity using 8-node hexahedra.
- class [Elas3DT4](#)
To build element equations for 3-D linearized elasticity using 4-node tetrahedra.
- class [Equa_Solid< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for Solid Mechanics Finite Element classes.
- class [DC1DL2](#)
Builds finite element arrays for thermal diffusion and convection in 1-D using 2-Node elements.
- class [DC2DT3](#)
Builds finite element arrays for thermal diffusion and convection in 2-D domains using 3-Node triangles.
- class [DC2DT6](#)
Builds finite element arrays for thermal diffusion and convection in 2-D domains using 6-Node triangles.
- class [DC3DAT3](#)
Builds finite element arrays for thermal diffusion and convection in 3-D domains with axisymmetry using 3-Node triangles.
- class [DC3DT4](#)
Builds finite element arrays for thermal diffusion and convection in 3-D domains using 4-Node tetrahedra.
- class [Equa_Therm< T_, NEN_, NEE_, NSN_, NSE_ >](#)
Abstract class for Heat transfer Finite Element classes.
- class [PhaseChange](#)
This class enables defining phase change laws for a given material.
- class [Funct](#)
A simple class to parse real valued functions.
- class [IOField](#)
Enables working with files in the XML Format.
- class [IPF](#)
To read project parameters from a file in [IPF](#) format.
- class [Prescription](#)

To prescribe various types of data by an algebraic expression. Data may consist in boundary conditions, forces, tractions, fluxes, initial condition. All these data types can be defined through an enumerated variable.

- class [Tabulation](#)
To read and manipulate tabulated functions.
- class [BMatrix< T_ >](#)
To handle band matrices.
- class [DMatrix< T_ >](#)
To handle dense matrices.
- class [DSMatrix< T_ >](#)
To handle symmetric dense matrices.
- class [SkMatrix< T_ >](#)
To handle square matrices in skyline storage format.
- class [SkSMatrix< T_ >](#)
To handle symmetric matrices in skyline storage format.
- class [SpMatrix< T_ >](#)
To handle matrices in sparse storage format.
- class [LocalMatrix< T_, NR_, NC_ >](#)
Handles small size matrices like element matrices, with a priori known size.
- class [Matrix< T_ >](#)
Virtual class to handle matrices for all storage formats.
- class [Point< T_ >](#)
Defines a point with arbitrary type coordinates.
- class [Point2D< T_ >](#)
Defines a 2-D point with arbitrary type coordinates.
- class [TrMatrix< T_ >](#)
To handle tridiagonal matrices.
- class [Domain](#)
To store and treat finite element geometric information.
- class [Edge](#)
To describe an edge.
- class [Element](#)
To store and treat finite element geometric information.
- class [Figure](#)
To store and treat a figure (or shape) information.
- class [Rectangle](#)
To store and treat a rectangular figure.
- class [Brick](#)
To store and treat a brick (parallelepiped) figure.
- class [Circle](#)
To store and treat a circular figure.
- class [Sphere](#)
To store and treat a sphere.
- class [Ellipse](#)
To store and treat an ellipsoidal figure.
- class [Triangle](#)
To store and treat a triangle.

- class [Polygon](#)
To store and treat a polygonal figure.
- class [Grid](#)
To manipulate structured grids.
- class [Material](#)
To treat material data. This class enables reading material data in material data files. It also returns these informations by means of its members.
- class [Mesh](#)
To store and manipulate finite element meshes.
- class [MeshAdapt](#)
To adapt mesh in function of given solution.
- class [NodeList](#)
Class to construct a list of nodes having some common properties.
- class [ElementList](#)
Class to construct a list of elements having some common properties.
- class [SideList](#)
Class to construct a list of sides having some common properties.
- class [EdgeList](#)
Class to construct a list of edges having some common properties.
- class [Node](#)
To describe a node.
- class [Partition](#)
To partition a finite element mesh into balanced submeshes.
- class [Side](#)
To store and treat finite element sides (edges in 2-D or faces in 3-D)
- class [OFELIException](#)
To handle exceptions in [OFELI](#).
- class [FEShape](#)
Parent class from which inherit all finite element shape classes.
- class [triangle](#)
Defines a triangle. The reference element is the rectangle triangle with two unit edges.
- class [Hexa8](#)
Defines a three-dimensional 8-node hexahedral finite element using Q_1 -isoparametric interpolation.
- class [Line2](#)
To describe a 2-Node planar line finite element.
- class [Line3](#)
To describe a 3-Node quadratic planar line finite element.
- class [Penta6](#)
Defines a 6-node pentahedral finite element using P_1 interpolation in local coordinates $(s.x, s.y)$ and Q_1 isoparametric interpolation in local coordinates $(s.x, s.z)$ and $(s.y, s.z)$.
- class [Quad4](#)
Defines a 4-node quadrilateral finite element using Q_1 isoparametric interpolation.
- class [Tetra4](#)
Defines a three-dimensional 4-node tetrahedral finite element using P_1 interpolation.
- class [Triang3](#)
Defines a 3-Node (P_1) triangle.
- class [Triang6S](#)

- Defines a 6-Node straight triangular finite element using P_2 interpolation.*

 - class [Prec< T_ >](#)

To set a preconditioner.
- class [EigenProblemSolver](#)

Class to find eigenvalues and corresponding eigenvectors of a given matrix in a generalized eigenproblem, i.e. Find scalars λ and non-null vectors v such that $[K]\{v\} = \lambda[M]\{v\}$ where $[K]$ and $[M]$ are symmetric matrices. The eigenproblem can be originated from a PDE. For this, we will refer to the matrices K and M as Stiffness and Mass matrices respectively.
- class [Integration](#)

Class for numerical integration methods.
- class [Iter< T_ >](#)

Class to drive an iterative process.
- class [LinearSolver< T_ >](#)

Class to solve systems of linear equations by iterative methods.
- class [MyNLAS](#)

Abstract class to define by user specified function.
- class [MyOpt](#)

Abstract class to define by user specified optimization function.
- class [ODESolver](#)

To solve a system of ordinary differential equations.
- class [TimeStepping](#)

To solve time stepping problems, i.e. systems of linear ordinary differential equations of the form $[A2]\{y''\} + [A1]\{y'\} + [A0]\{y\} = \{b\}$.
- class [Gauss](#)

Calculate data for Gauss integration.
- class [Timer](#)

To handle elapsed time counting.

Enumerations

- enum [PDE_Terms](#) {

[CONSISTENT_MASS](#) = 0x00001000,
[LUMPED_MASS](#) = 0x00002000,
[MASS](#) = 0x00002000,
[CAPACITY](#) = 0x00004000,
[CONSISTENT_CAPACITY](#) = 0x00004000,
[LUMPED_CAPACITY](#) = 0x00008000,
[VISCOSITY](#) = 0x00010000,
[STIFFNESS](#) = 0x00020000,
[DIFFUSION](#) = 0x00040000,
[MOBILITY](#) = 0x00040000,
[CONVECTION](#) = 0x00080000,
[DEVIATORIC](#) = 0x00100000,
[DILATATION](#) = 0x00200000,
[ELECTRIC](#) = 0x00400000,
[MAGNETIC](#) = 0x00800000,
[LOAD](#) = 0x01000000,
[HEAT_SOURCE](#) = 0x02000000,
[BOUNDARY_TRACTION](#) = 0x04000000,
[HEAT_FLUX](#) = 0x08000000,
[CONTACT](#) = 0x10000000,
[BUOYANCY](#) = 0x20000000,

LORENTZ_FORCE = 0x40000000 }

- enum Analysis {
 STATIONARY = 0,
 STEADY_STATE = 0,
 TRANSIENT = 1,
 TRANSIENT_ONE_STEP = 2,
 OPTIMIZATION = 3,
 EIGEN = 4 }
- enum TimeScheme {
 NONE = 0,
 FORWARD_EULER = 1,
 BACKWARD_EULER = 2,
 CRANK_NICOLSON = 3,
 HEUN = 4,
 NEWMARK = 5,
 LEAP_FROG = 6,
 ADAMS_BASHFORTH = 7,
 AB2 = 7,
 RUNGE_KUTTA = 8,
 RK4 = 8,
 RK3_TVD = 9,
 BDF2 = 10,
 BUILTIN = 11 }
- enum FEType {
 FE_2D_3N,
 FE_2D_6N,
 FE_2D_4N,
 FE_3D_AXI3N,
 FE_3D_4N,
 FE_3D_8N }
- enum AccessType

Enumerated values for file access type.

- enum MatrixType {
 DENSE = 1,
 SKYLINE = 2,
 SPARSE = 4,
 DIAGONAL = 8,
 TRIDIAGONAL = 16,
 BAND = 32,
 SYMMETRIC = 64,
 UNSYMMETRIC = 128,
 IDENTITY = 256 }
- enum Iteration {
 DIRECT_SOLVER = 0,
 CG_SOLVER = 1,
 CGS_SOLVER = 2,
 BICG_SOLVER = 3,
 BICG_STAB_SOLVER = 4,
 GMRES_SOLVER = 5 }

Choose iterative solver for the linear system.

- enum Preconditioner {

```

IDENT_PREC = 0,
DIAG_PREC = 1,
DILU_PREC = 2,
ILU_PREC = 3,
SSOR_PREC = 4 }

```

Choose preconditioner for the linear system.

- enum `BCType` {
`PERIODIC_A` = 9999,
`PERIODIC_B` = -9999,
`CONTACT_BC` = 9998,
`CONTACT_M` = 9997,
`CONTACT_S` = -9997,
`SLIP` = 9996 }
- enum `IntegrationScheme` {
`LEFT_RECTANGLE` = 0,
`RIGHT_RECTANGLE` = 1,
`MID_RECTANGLE` = 2,
`TRAPEZOIDAL` = 3,
`SIMPSON` = 4,
`GAUSS_LEGENDRE` = 5 }

Functions

- `T_ * A ()`
Return element matrix.
- `T_ * b ()`
Return element right-hand side.
- `T_ * Prev ()`
Return element previous vector.
- `IOField ()`
Default constructor.
- `IOField (const string &file, AccessType access, bool compact=true)`
Constructor using file name.
- `IOField (const string &mesh.file, const string &file, Mesh &ms, AccessType access, bool compact=true)`
Constructor using file name, mesh file and mesh.
- `IOField (const string &file, Mesh &ms, AccessType access, bool compact=true)`
Constructor using file name and mesh.
- `IOField (const string &file, AccessType access, const string &name)`
Constructor using file name and field name.
- `~IOField ()`
Destructor.
- `void setMeshFile (const string &file)`
Set mesh file.
- `void open ()`
Open file.
- `void open (const string &file, AccessType access)`
Open file.
- `void close ()`

- Close file.*
- `void put (Mesh &ms)`
Store mesh in file.
- `void put (const Vect< real_t > &v)`
Store Vect instance v in file.
- `real_t get (Vect< real_t > &v)`
Get Vect v instance from file.
- `int get (Vect< real_t > &v, const string &name)`
Get Vect v instance from file if the field has the given name.
- `int get (DMatrix< real_t > &A, const string &name)`
Get DMatrix A instance from file if the field has the given name.
- `int get (DSMatrix< real_t > &A, const string &name)`
Get DSMatrix A instance from file if the field has the given name.
- `int get (Vect< real_t > &v, real_t t)`
Get Vect v instance from file corresponding to a specific time value.
- `void saveGMSH (string output_file, string mesh_file)`
Save field vectors in a file using GMSH format.
- `Tabulation ()`
Default constructor.
- `Tabulation (string file)`
Constructor using file name.
- `~Tabulation ()`
Destructor.
- `void setFile (string file)`
Set file name.
- `real_t getValue (string funct, real_t v)`
Return the calculated value of the function.
- `real_t getDerivative (string funct, real_t v)`
Return the derivative of the function at a given point.
- `real_t getValue (string funct, real_t v1, real_t v2)`
Return the calculated value of the function.
- `real_t getValue (string funct, real_t v1, real_t v2, real_t v3)`
Return the calculated value of the function.
- `Point< double > CrossProduct (const Point< double > &lp, const Point< double > &rp)`
Return Cross product of two vectors lp and rp
- `SpMatrix ()`
Default constructor.
- `SpMatrix (size_t nr, size_t nc)`
Constructor that initializes current instance as a dense matrix.
- `SpMatrix (size_t size, int is_diagonal=false)`
Constructor that initializes current instance as a dense matrix.
- `SpMatrix (Mesh &mesh, size_t dof=0, int is_diagonal=false)`
Constructor using a Mesh instance.
- `SpMatrix (const Vect< RC > &I, int opt=1)`
Constructor for a square matrix using non zero row and column indices.
- `SpMatrix (const Vect< RC > &I, const Vect< T_ > &a, int opt=1)`

- Constructor for a square matrix using non zero row and column indices.*

 - **SpMatrix** (size_t nr, size_t nc, const vector< size_t > &row_ptr, const vector< size_t > &col_ind)
- Constructor for a rectangle matrix.*

 - **SpMatrix** (size_t nr, size_t nc, const vector< size_t > &row_ptr, const vector< size_t > &col_ind, const vector< T_ > &a)
- Constructor for a rectangle matrix.*

 - **SpMatrix** (const vector< size_t > &row_ptr, const vector< size_t > &col_ind)
- Constructor for a rectangle matrix.*

 - **SpMatrix** (const vector< size_t > &row_ptr, const vector< size_t > &col_ind, const vector< T_ > &a)
- Constructor for a rectangle matrix.*

 - **SpMatrix** (const SpMatrix &m)
- Copy constructor.*

 - **~SpMatrix** ()
- Destructor.*

 - void **Identity** ()
- Define matrix as identity.*

 - void **Dense** ()
- Define matrix as a dense one.*

 - void **Diagonal** ()
- Define matrix as a diagonal one.*

 - void **Diagonal** (const T_ &a)
- Define matrix as a diagonal one with diagonal entries equal to a*

 - void **Laplace1D** (size_t n, real_t h)
- Sets the matrix as the one for the Laplace equation in 1-D.*

 - void **Laplace2D** (size_t nx, size_t ny)
- Sets the matrix as the one for the Laplace equation in 2-D.*

 - void **setMesh** (Mesh &mesh, size_t dof=0)
- Determine mesh graph and initialize matrix.*

 - void **setOneDOF** ()
- Activate 1-DOF per node option.*

 - void **setSides** ()
- Activate Sides option.*

 - void **setDiag** ()
- Store diagonal entries in a separate internal vector.*

 - void **DiagPrescribe** (Mesh &mesh, Vect< T_ > &b, const Vect< T_ > &u)
- Impose by a diagonal method an essential boundary condition.*

 - void **DiagPrescribe** (Vect< T_ > &b, const Vect< T_ > &u)
- Impose by a diagonal method an essential boundary condition using the **Mesh** instance provided by the constructor.*

 - void **setSize** (size_t size)
- Set size of matrix (case where it's a square matrix).*

 - void **setSize** (size_t nr, size_t nc)
- Set size (number of rows) of matrix.*

 - void **setGraph** (const Vect< RC > &I, int opt=1)
- Set graph of matrix by giving a vector of its nonzero entries.*

- `Vect< T_ > getRow (size_t i) const`
Get i -th row vector.
- `Vect< T_ > getColumn (size_t j) const`
Get j -th column vector.
- `T_ & operator() (size_t i, size_t j)`
Operator () (Non constant version)
- `T_ operator() (size_t i, size_t j) const`
Operator () (Constant version)
- `T_ operator() (size_t i) const`
Operator () with one argument (Constant version)
- `T_ operator[] (size_t i) const`
Operator [] (Constant version).
- `Vect< T_ > operator* (const Vect< T_ > &x) const`
*Operator * to multiply matrix by a vector.*
- `SpMatrix< T_ > & operator*= (const T_ &a)`
*Operator *= to premultiply matrix by a constant.*
- `void getMesh (Mesh &mesh)`
Get mesh instance whose reference will be stored in current instance of `SpMatrix`.
- `void Mult (const Vect< T_ > &x, Vect< T_ > &y) const`
Multiply matrix by vector and save in another one.
- `void MultAdd (const Vect< T_ > &x, Vect< T_ > &y) const`
Multiply matrix by vector x and add to y .
- `void MultAdd (T_ a, const Vect< T_ > &x, Vect< T_ > &y) const`
*Multiply matrix by vector $a*x$ and add to y .*
- `void TMult (const Vect< T_ > &x, Vect< T_ > &y) const`
Multiply transpose of matrix by vector x and save in y .
- `void Axy (T_ a, const SpMatrix< T_ > &m)`
Add to matrix the product of a matrix by a scalar.
- `void Axy (T_ a, const Matrix< T_ > *m)`
Add to matrix the product of a matrix by a scalar.
- `void set (size_t i, size_t j, const T_ &val)`
Assign a value to an entry of the matrix.
- `void add (size_t i, size_t j, const T_ &val)`
Add a value to an entry of the matrix.
- `void operator= (const T_ &x)`
Operator =.
- `size_t getColInd (size_t i) const`
Return storage information.
- `size_t getRowPtr (size_t i) const`
Return Row pointer at position i .
- `int solve (const Vect< T_ > &b, Vect< T_ > &x, bool fact=false)`
Solve the linear system of equations.
- `void setSolver (Iteration solver=CG_SOLVER, Preconditioner prec=DIAG_PREC, int max←
it=1000, real_t toler=1.e-8)`
Choose solver and preconditioner for an iterative procedure.
- `void clear ()`
brief Set all matrix entries to zero

- `T_ * get ()` const
Return C-Array.
- `T_ get (size_t i, size_t j)` const
Return entry (i, j) of matrix if this one is stored, 0 otherwise.
- `TrMatrix ()`
Default constructor.
- `TrMatrix (size_t size)`
Constructor for a tridiagonal matrix with `size` rows.
- `TrMatrix (const TrMatrix &m)`
Copy Constructor.
- `~TrMatrix ()`
Destructor.
- `void Identity ()`
Define matrix as identity matrix.
- `void Diagonal ()`
Define matrix as a diagonal one.
- `void Diagonal (const T_ &a)`
Define matrix as a diagonal one and assign value `a` to all diagonal entries.
- `void Laplace1D (real_t h)`
Define matrix as the one of 3-point finite difference discretization of the second derivative.
- `void setSize (size_t size)`
Set size (number of rows) of matrix.
- `void MultAdd (const Vect< T_ > &x, Vect< T_ > &y)` const
Multiply matrix by vector `x` and add result to `y`.
- `void MultAdd (T_ a, const Vect< T_ > &x, Vect< T_ > &y)` const
*Multiply matrix by vector `a*x` and add result to `y`.*
- `void Mult (const Vect< T_ > &x, Vect< T_ > &y)` const
Multiply matrix by vector `x` and save result in `y`.
- `void TMult (const Vect< T_ > &x, Vect< T_ > &y)` const
Multiply transpose of matrix by vector `x` and save result in `y`.
- `void Axy (T_ a, const TrMatrix< T_ > &m)`
Add to matrix the product of a matrix by a scalar.
- `void Axy (T_ a, const Matrix< T_ > *m)`
Add to matrix the product of a matrix by a scalar.
- `void set (size_t i, size_t j, const T_ &val)`
Assign constant `val` to an entry (i, j) of the matrix.
- `void add (size_t i, size_t j, const T_ &val)`
Add constant `val` value to an entry (i, j) of the matrix.
- `T_ operator\(\) (size_t i, size_t j)` const
Operator `()` (Constant version).
- `T_ & operator\(\) (size_t i, size_t j)`
Operator `()` (Non constant version).
- `TrMatrix< T_ > & operator= (const TrMatrix< T_ > &m)`
Operator `=`.
- `TrMatrix< T_ > & operator= (const T_ &x)`
Operator `=` Assign matrix to identity times `x`.

- `TrMatrix< T_ > & operator*= (const T_ &x)`
Operator *=.
- `int solve (Vect< T_ > &b, bool fact=true)`
Solve a linear system with current matrix (forward and back substitution).
- `int solve (const Vect< T_ > &b, Vect< T_ > &x, bool fact=false)`
Solve a linear system with current matrix (forward and back substitution).
- `T_ * get () const`
Return C-Array.
- `T_ get (size_t i, size_t j) const`
Return entry (i, j) of matrix.
- `Grid ()`
Construct a default grid with 10 intervals in each direction.
- `Grid (real_t xm, real_t xM, size_t npx)`
Construct a 1-D structured grid given its extremal coordinates and number of intervals.
- `Grid (real_t xm, real_t xM, real_t ym, real_t yM, size_t npx, size_t npy)`
Construct a 2-D structured grid given its extremal coordinates and number of intervals.
- `Grid (Point< real_t > m, Point< real_t > M, size_t npx, size_t npy)`
Construct a 2-D structured grid given its extremal coordinates and number of intervals.
- `Grid (real_t xm, real_t xM, real_t ym, real_t yM, real_t zm, real_t zM, size_t npx, size_t npy, size_t npz)`
Construct a 3-D structured grid given its extremal coordinates and number of intervals.
- `Grid (Point< real_t > m, Point< real_t > M, size_t npx, size_t npy, size_t npz)`
Construct a 3-D structured grid given its extremal coordinates and number of intervals.
- `void setXMin (const Point< real_t > &x)`
Set min. coordinates of the domain.
- `void setXMax (const Point< real_t > &x)`
- `void setDomain (real_t xmin, real_t xmax)`
Set Dimensions of the domain: 1-D case.
- `void setDomain (real_t xmin, real_t xmax, real_t ymin, real_t ymax)`
Set Dimensions of the domain: 2-D case.
- `void setDomain (real_t xmin, real_t xmax, real_t ymin, real_t ymax, real_t zmin, real_t zmax)`
Set Dimensions of the domain: 3-D case.
- `void setDomain (Point< real_t > xmin, Point< real_t > xmax)`
Set Dimensions of the domain: 3-D case.
- `const Point< real_t > & getXMin () const`
Return min. Coordinates of the domain.
- `const Point< real_t > & getXMax () const`
Return max. Coordinates of the domain.
- `void setN (size_t nx, size_t ny=0, size_t nz=0)`
Set number of grid intervals in the x, y and z-directions.
- `size_t getNx () const`
Return number of grid intervals in the x-direction.
- `size_t getNy () const`
Return number of grid intervals in the y-direction.
- `size_t getNz () const`
Return number of grid intervals in the z-direction.
- `real_t getHx () const`

- Return grid size in the x-direction.*

 - `real_t getHy () const`

Return grid size in the y-direction.

 - `real_t getHz () const`

Return grid size in the z-direction.

 - `Point< real_t > getCoord (size_t i) const`

Return coordinates a point with label i in a 1-D grid.

 - `Point< real_t > getCoord (size_t i, size_t j) const`

Return coordinates a point with label (i, j) in a 2-D grid.

 - `Point< real_t > getCoord (size_t i, size_t j, size_t k) const`

Return coordinates a point with label (i, j, k) in a 3-D grid.

 - `real_t getX (size_t i) const`

Return x-coordinate of point with index i

 - `real_t getY (size_t j) const`

Return y-coordinate of point with index j

 - `real_t getZ (size_t k) const`

Return z-coordinate of point with index k

 - `Point2D< real_t > getXY (size_t i, size_t j) const`

Return coordinates of point with indices (i, j)

 - `Point< real_t > getXYZ (size_t i, size_t j, size_t k) const`

Return coordinates of point with indices (i, j, k)

 - `real_t getCenter (size_t i) const`

Return coordinates of center of a 1-D cell with indices $i, i+1$

 - `Point< real_t > getCenter (size_t i, size_t j) const`

Return coordinates of center of a 2-D cell with indices $(i, j), (i+1, j), (i+1, j+1), (i, j+1)$

 - `Point< real_t > getCenter (size_t i, size_t j, size_t k) const`

Return coordinates of center of a 3-D cell with indices $(i, j, k), (i+1, j, k), (i+1, j+1, k), (i, j+1, k), (i, j, k+1), (i+1, j, k+1), (i+1, j+1, k+1), (i, j+1, k+1)$

 - `void setCode (string exp, int code)`

Set a code for some grid points.

 - `void setCode (int side, int code)`

Set a code for grid points on sides.

 - `int getCode (int side) const`

Return code for a side number.

 - `int getCode (size_t i, size_t j) const`

Return code for a grid point.

 - `int getCode (size_t i, size_t j, size_t k) const`

Return code for a grid point.

 - `size_t getDim () const`

Return space dimension.

 - `void Deactivate (size_t i)`

Change state of a cell from active to inactive (1-D grid)

 - `void Deactivate (size_t i, size_t j)`

Change state of a cell from active to inactive (2-D grid)

 - `void Deactivate (size_t i, size_t j, size_t k)`

Change state of a cell from active to inactive (2-D grid)

 - `int isActive (size_t i) const`

- Say if cell is active or not (1-D grid)*
- `int isActive (size_t i, size_t j) const`
- Say if cell is active or not (2-D grid)*
- `int isActive (size_t i, size_t j, size_t k) const`
- Say if cell is active or not (3-D grid)*
- `ostream & operator<< (ostream &s, const Grid &g)`
- Output grid data.*
- `OFELIException (const std::string &s)`
- This form will be used most often in a throw.*
- `OFELIException ()`
- Throw with no error message.*
- `Iter ()`
- Default Constructor.*
- `Iter (int max_it, real_t toler)`
- Constructor with iteration parameters.*
- `bool check (Vect< T_ > &u, const Vect< T_ > &v, int opt=2)`
- Check convergence.*
- `bool check (T_ &u, const T_ &v)`
- Check convergence for a scalar case (one equation)*

5.18.1 Detailed Description

5.18.2 Enumeration Type Documentation

`enum PDE_Terms`

Enumerate variable that selects various terms in partial differential equations

Enumerator

`CONSISTENT_MASS` Consistent mass term
`LUMPED_MASS` Lumped mass term
`MASS` Consistent mass term
`CAPACITY` Consistent capacity term
`CONSISTENT_CAPACITY` Consistent capacity term
`LUMPED_CAPACITY` Lumped capacity term
`VISCOSITY` Viscosity term
`STIFFNESS` Stiffness term
`DIFFUSION` Diffusion term
`MOBILITY` Mobility term
`CONVECTION` Convection term
`DEVIATORIC` Deviatoric term
`DILATATION` Dilatational term
`ELECTRIC` Electric term
`MAGNETIC` Magnetic term
`LOAD` Body load term
`HEAT_SOURCE` Body heat source term

BOUNDARY_TRACTION Boundary traction (pressure) term

HEAT_FLUX Boundary heat flux term

CONTACT Signorini contact

BUOYANCY Buoyancy force term

LORENTZ_FORCE Lorentz force term

enum Analysis

Selects Analysis type

Enumerator

STATIONARY Steady State analysis

STEADY_STATE Steady state analysis

TRANSIENT Transient problem

TRANSIENT_ONE_STEP Transient problem, perform only one time step

OPTIMIZATION Optimization problem

EIGEN Eigenvalue problem

enum TimeScheme

Selects Time integration scheme

Enumerator

NONE No time integration scheme

FORWARD_EULER Forward Euler scheme (Explicit)

BACKWARD_EULER Backward Euler scheme (Implicit)

CRANK_NICOLSON Crank-Nicolson scheme

HEUN Heun scheme

NEWMARK Newmark scheme

LEAP_FROG Leap Frog scheme

ADAMS_BASHFORTH Adams-Bashforth scheme (2nd Order)

AB2 Adams-Bashforth scheme (2nd Order)

RUNGE_KUTTA 4-th Order Runge-Kutta scheme (4th Order)

RK4 4-th Order Runge-Kutta scheme

RK3_TVD 3-rd Order Runge-Kutta TVD scheme

BDF2 Backward Difference Formula (2nd Order)

BUILTIN Builtin scheme, implemented in equation class

enum FEType

Choose Finite [Element](#) Type

Enumerator

FE_2D_3N 2-D elements, 3-Nodes (P1)

FE_2D_6N 2-D elements, 6-Nodes (P2)

FE_2D_4N 2-D elements, 4-Nodes (Q1)

FE_3D_AXI_3N 3-D Axisymmetric elements, 3-Nodes (P1)

FE_3D_4N 3-D elements, 4-Nodes (P1)

FE_3D_8N 3-D elements, 8-Nodes (Q1)

enum MatrixType

Choose matrix storage and type

Enumerator

DENSE Dense storage
SKYLINE Skyline storage
SPARSE Sparse storage
DIAGONAL Diagonal storage
TRIDIAGONAL Tridiagonal storage
BAND Band storage
SYMMETRIC Symmetric matrix
UNSYMMETRIC Unsymmetric matrix
IDENTITY Identity matrix

enum Iteration

Choose iterative solver for the linear system.

Enumerator

DIRECT_SOLVER Direct solver
CG_SOLVER CG Method
CGS_SOLVER CGS Method
BICG_SOLVER BiCG Method
BICG_STAB_SOLVER BiCGStab Method
GMRES_SOLVER GMRes Method

enum Preconditioner

Choose preconditioner for the linear system.

Enumerator

IDENT_PREC Identity (No preconditioning)
DIAG_PREC Diagonal preconditioner
DILU_PREC ILU (Incomplete factorization) preconditioner
ILU_PREC DILU (Diagonal Incomplete factorization) preconditioner
SSOR_PREC SSOR preconditioner

enum BCType

To select special boundary conditions.

Enumerator

PERIODIC_A Periodic Boundary condition (first side)
PERIODIC_B Periodic Boundary condition (second side)
CONTACT_BC Contact Boundary conditions
CONTACT_M Contact Boundary condition, set as master side
CONTACT_S Contact Boundary condition, set as slave side
SLIP Slip Boundary condition

enum IntegrationScheme

Choose numerical integration scheme

Enumerator

LEFT_RECTANGLE Left rectangle integration formula
RIGHT_RECTANGLE Right rectangle integration formula
MID_RECTANGLE Midpoint (central) rectangle formula
TRAPEZOIDAL Trapezoidal rule
SIMPSON Simpson formula
GAUSS_LEGENDRE Gauss-Legendre quadrature formulae

5.18.3 Function Documentation

T_* OFELI::A ()

Return element matrix.

Matrix is returned as a C-array

T_* OFELI::b ()

Return element right-hand side.

Right-hand side is returned as a C-array

T_* OFELI::Prev ()

Return element previous vector.

This is the vector given in time dependent constructor. It is returned as a C-array.

IOField (const string & file, AccessType access, bool compact = true)

Constructor using file name.

Parameters

in	<i>file</i>	File name.
in	<i>access</i>	Access code. This number is to be chosen among two enumerated values: <ul style="list-style-type: none"> • IOField::IN to read the file • IOField::OUT to write on it
in	<i>compact</i>	Flag to choose a compact storage or not [Default: true]

IOField (const string & mesh_file, const string & file, Mesh & ms, AccessType access, bool compact = true)

Constructor using file name, mesh file and mesh.

Parameters

in	<i>mesh_file</i>	File containing mesh
in	<i>file</i>	File that contains field stored or to store
in	<i>ms</i>	Mesh instance
in	<i>access</i>	Access code. This number is to be chosen among two enumerated values: <ul style="list-style-type: none"> • <code>IOField::IN</code> to read the file • <code>IOField::OUT</code> to write on it
in	<i>compact</i>	Flag to choose a compact storage or not [Default: <code>true</code>]

IOField (const string & file, Mesh & ms, AccessType access, bool compact = true)

Constructor using file name and mesh.

Parameters

in	<i>file</i>	File that contains field stored or to store
in	<i>ms</i>	Mesh instance
in	<i>access</i>	Access code. This number is to be chosen among two enumerated values: <ul style="list-style-type: none"> • <code>IOField::IN</code> to read the file • <code>IOField::OUT</code> to write on it
in	<i>compact</i>	Flag to choose a compact storage or not [Default: <code>true</code>]

IOField (const string & file, AccessType access, const string & name)

Constructor using file name and field name.

Parameters

in	<i>file</i>	File that contains field stored or to store
in	<i>access</i>	Access code. This number is to be chosen among two enumerated values: <ul style="list-style-type: none"> • <code>IOField::IN</code> to read the file • <code>IOField::OUT</code> to write on it
in	<i>name</i>	Seek a specific field with given <i>name</i>

void setMeshFile (const string & file)

Set mesh file.

Parameters

in	<i>file</i>	Mesh file
----	-------------	---------------------------

void open ()

Open file.

Case where file name has been previously given (in the constructor).

void open (const string &*file*, AccessType *access*)

Open file.

Parameters

in	<i>file</i>	File name.
in	<i>access</i>	Access code. This number is to be chosen among two enumerated values: <ul style="list-style-type: none"> IOField::IN to read the file IOField::OUT to write on it

void put (const Vect< real.t > & v)

Store Vect instance v in file.

Parameters

in	<i>v</i>	Vect instance to store
----	----------	------------------------

real.t get (Vect< real.t > & v)

Get Vect v instance from file.

First time step is read from the XML file.

int get (Vect< real.t > & v, const string & name)

Get Vect v instance from file if the field has the given name.

First time step is read from the XML file.

Parameters

in,out	<i>v</i>	Vect instance
in	<i>name</i>	Name to seek in the XML file

int get (DMatrix< real.t > & A, const string & name)

Get DMatrix A instance from file if the field has the given name.

First time step is read from the XML file.

Parameters

in,out	<i>A</i>	DMatrix instance
in	<i>name</i>	Name to seek in the XML file

int get (DSMatrix< real.t > & A, const string & name)

Get DSMatrix A instance from file if the field has the given name.

First time step is read from the XML file.

Parameters

in,out	<i>A</i>	DSMatrix instance
in	<i>name</i>	Name to seek in the XML file

int get (Vect< real.t > & v, real.t t)

Get Vect v instance from file corresponding to a specific time value.

The sought vector corresponding to the time value is read from the XML file.

Parameters

<code>in,out</code>	<code>v</code>	Vector instance
<code>in</code>	<code>t</code>	Time value

void saveGMSH (string *output_file*, string *mesh_file*)

Save field vectors in a file using **GMSH** format.

This member function enables avoiding the use of `cfield`. It must be used once all field vectors have been stored in output file. It closes this file and copies its contents to a **GMSH** file.

Parameters

<code>in</code>	<code>output_file</code>	Output file name where to store using GMSH format
<code>in</code>	<code>mesh_file</code>	File containing mesh data

void setFile (string *file*)

Set file name.

This function is to be used when the default constructor is invoked.

real.t getValue (string *funct*, real.t *v*)

Return the calculated value of the function.

Case of a function of one variable

Parameters

<code>in</code>	<code>funct</code>	Name of the function to be evaluated, as read from input file
<code>in</code>	<code>v</code>	Value of the variable

Returns

Computed value of the function

real.t getDerivative (string *funct*, real.t *v*)

Return the derivative of the function at a given point.

Case of a function of one variable

Parameters

<code>in</code>	<code>funct</code>	Name of the function to be evaluated, as read from input file
<code>in</code>	<code>v</code>	Value of the variable

Returns

Derivative value

real.t getValue (string *funct*, real.t *v1*, real.t *v2*)

Return the calculated value of the function.

Case of a function of two variables

Parameters

<code>in</code>	<code>func</code>	Name of the function to be evaluated, as read from input file
<code>in</code>	<code>v1</code>	Value of the first variable
<code>in</code>	<code>v2</code>	Value of the second variable

Returns

Computed value of the function

real.t getValue (string *func*, real.t *v1*, real.t *v2*, real.t *v3*)

Return the calculated value of the function.

Case of a function of three variables

Parameters

<code>in</code>	<code>func</code>	Name of the funct to be evaluated, as read from input file
<code>in</code>	<code>v1</code>	Value of the first variable
<code>in</code>	<code>v2</code>	Value of the second variable
<code>in</code>	<code>v3</code>	Value of the third variable

Returns

Computed value of the function

SpMatrix ()

Default constructor.

Initialize a zero-dimension matrix

SpMatrix (size.t *nr*, size.t *nc*)

Constructor that initializes current instance as a dense matrix.

Normally, for a dense matrix this is not the right class.

Parameters

<code>in</code>	<code>nr</code>	Number of matrix rows.
<code>in</code>	<code>nc</code>	Number of matrix columns.

SpMatrix (size.t *size*, int *is_diagonal* = *false*)

Constructor that initializes current instance as a dense matrix.

Normally, for a dense matrix this is not the right class.

Parameters

<code>in</code>	<code>size</code>	Number of matrix rows (and columns).
<code>in</code>	<code>is_diagonal</code>	Boolean argument to say is the matrix is actually a diagonal matrix or not.

SpMatrix (Mesh & *mesh*, size.t *dof* = 0, int *is_diagonal* = *false*)

Constructor using a [Mesh](#) instance.

Parameters

in	<i>mesh</i>	Mesh instance from which matrix graph is extracted.
in	<i>dof</i>	Option parameter, with default value 0. dof=1 means that only one degree of freedom for each node (or element or side) is taken to determine matrix structure. The value dof=0 means that matrix structure is determined using all DOFs.
in	<i>is_diagonal</i>	Boolean argument to say is the matrix is actually a diagonal matrix or not.

SpMatrix (const Vect< RC > & I, int opt = 1)

Constructor for a square matrix using non zero row and column indices.

Parameters

in	<i>I</i>	Vector containing pairs of row and column indices
in	<i>opt</i>	Flag indicating if vectors I is cleaned and ordered (opt=1) or not (opt=0). In the latter case, this vector can have the same contents more than once and are not necessarily ordered

SpMatrix (const Vect< RC > & I, const Vect< T_ > & a, int opt = 1)

Constructor for a square matrix using non zero row and column indices.

Parameters

in	<i>I</i>	Vector containing pairs of row and column indices
in	<i>a</i>	Vector containing matrix entries in the same order than the one given by I
in	<i>opt</i>	Flag indicating if vector I is cleaned and ordered (opt=1: default) or not (opt=0). In the latter case, this vector can have the same contents more than once and are not necessarily ordered

SpMatrix (size_t nr, size_t nc, const vector< size_t > & row_ptr, const vector< size_t > & col_ind)

Constructor for a rectangle matrix.

Parameters

in	<i>nr</i>	Number of rows
in	<i>nc</i>	Number of columns
in	<i>row_ptr</i>	Vector of row pointers (See the above description of this class).
in	<i>col_ind</i>	Vector of column indices (See the above description of this class).

SpMatrix (size_t nr, size_t nc, const vector< size_t > & row_ptr, const vector< size_t > & col_ind, const vector< T_ > & a)

Constructor for a rectangle matrix.

Parameters

<code>in</code>	<code>nr</code>	Number of rows
<code>in</code>	<code>nc</code>	Number of columns
<code>in</code>	<code>row_ptr</code>	Vector of row pointers (See the above description of this class).
<code>in</code>	<code>col_ind</code>	Vector of column indices (See the above description of this class).
<code>in</code>	<code>a</code>	vector instance containing matrix entries stored columnwise

SpMatrix (const vector< size_t > & row_ptr, const vector< size_t > & col_ind)

Constructor for a rectangle matrix.

Parameters

<code>in</code>	<code>row_ptr</code>	Vector of row pointers (See the above description of this class).
<code>in</code>	<code>col_ind</code>	Vector of column indices (See the above description of this class).

SpMatrix (const vector< size_t > & row_ptr, const vector< size_t > & col_ind, const vector< T_ > & a)

Constructor for a rectangle matrix.

Parameters

<code>in</code>	<code>row_ptr</code>	Vector of row pointers (See the above description of this class).
<code>in</code>	<code>col_ind</code>	Vector of column indices (See the above description of this class).
<code>in</code>	<code>a</code>	vector instance that contain matrix entries stored row by row. Number of rows is extracted from vector row_ptr.

void Laplace1D (size_t n, real_t h)

Sets the matrix as the one for the Laplace equation in 1-D.

The matrix is initialized as the one resulting from P_1 finite element discretization of the classical elliptic operator $-u'' = f$ with homogeneous Dirichlet boundary conditions

Remarks

This function is available for real valued matrices only.

Parameters

<code>in</code>	<code>n</code>	Size of matrix (Number of rows)
<code>in</code>	<code>h</code>	Mesh size (assumed constant)

void Laplace2D (size_t nx, size_t ny)

Sets the matrix as the one for the Laplace equation in 2-D.

The matrix is initialized as the one resulting from P_1 finite element discretization of the classical elliptic operator $-\Delta u = f$ with homogeneous Dirichlet boundary conditions

Remarks

This function is available for real valued matrices only.

Parameters

in	<i>nx</i>	Number of unknowns in the x-direction
in	<i>ny</i>	Number of unknowns in the y-direction

Remarks

The number of rows is equal to $nx \times ny$

void setMesh (Mesh & mesh, size_t dof = 0)

Determine mesh graph and initialize matrix.

This member function is called by constructor with the same arguments

Parameters

in	<i>mesh</i>	Mesh instance for which matrix graph is determined.
in	<i>dof</i>	Option parameter, with default value 0. dof=1 means that only one degree of freedom for each node (or element or side) is taken to determine matrix structure. The value dof=0 means that matrix structure is determined using all DOFs.

void DiagPrescribe (Mesh & mesh, Vect< T_ > & b, const Vect< T_ > & u)

Impose by a diagonal method an essential boundary condition.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. The penalty parameter is defined by default equal to 1.e20. It can be modified by member function **setPenal(..)**.

Parameters

in	<i>mesh</i>	Mesh instance from which information is extracted.
in,out	<i>b</i>	Vect instance that contains right-hand side.
in	<i>u</i>	Vect instance that contains imposed values at DOFs where they are to be imposed.

void DiagPrescribe (Vect< T_ > & b, const Vect< T_ > & u)

Impose by a diagonal method an essential boundary condition using the [Mesh](#) instance provided by the constructor.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. The penalty parameter is defined by default equal to 1.e20. It can be modified by member function **setPenal(..)**.

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side.
in	<i>u</i>	Vect instance that contains imposed values at DOFs where they are to be imposed.

void setSize (size_t size)

Set size of matrix (case where it's a square matrix).

Parameters

in	<i>size</i>	Number of rows and columns.
-----------	-------------	-----------------------------

void setSize (size_t *nr*, size_t *nc*)

Set size (number of rows) of matrix.

Parameters

in	<i>nr</i>	Number of rows
in	<i>nc</i>	Number of columns

void setGraph (const Vect< RC > &*I*, int *opt* = 1)

Set graph of matrix by giving a vector of its nonzero entries.

Parameters

in	<i>I</i>	Vector containing pairs of row and column indices
in	<i>opt</i>	Flag indicating if vector <i>I</i> is cleaned and ordered (<i>opt</i> =1: default) or not (<i>opt</i> =0). In the latter case, this vector can have the same contents more than once and are not necessarily ordered

T_& operator() (size_t *i*, size_t *j*) [virtual]

Operator () (Non constant version)

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implements [Matrix< T_ >](#).

T_ operator() (size_t *i*, size_t *j*) const [virtual]

Operator () (Constant version)

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implements [Matrix< T_ >](#).

T_ operator() (size_t *i*) const

Operator () with one argument (Constant version)

Returns *i*-th position in the array storing matrix entries. The first entry is at location 1. Entries are stored row by row.

T_ operator[] (size_t *i*) const

Operator [] (Constant version).

Returns *i*-th position in the array storing matrix entries. The first entry is at location 0. Entries are stored row by row.

Vect<T_> operator* (const Vect< T_ > & x) const

Operator * to multiply matrix by a vector.

Parameters

in	x	Vect instance to multiply by
----	-----	--

Returns

Vector product of matrix by x

SpMatrix<T_>& operator*= (const T_ & a)

Operator *= to premultiply matrix by a constant.

Parameters

in	a	Constant to multiply matrix by
----	-----	--------------------------------

Returns

Resulting matrix

void Mult (const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply matrix by vector and save in another one.

Parameters

in	x	Vector to multiply by matrix
out	y	Vector that contains on output the result.

Implements [Matrix< T_ >](#).

void MultAdd (const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply matrix by vector x and add to y .

Parameters

in	x	Vector to multiply by matrix
out	y	Vector to add to the result. y contains on output the result.

Implements [Matrix< T_ >](#).

void MultAdd (T_ a, const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply matrix by vector $a*x$ and add to y .

Parameters

in	a	Constant to multiply by matrix
in	x	Vector to multiply by matrix
out	y	Vector to add to the result. y contains on output the result.

Implements [Matrix< T_ >](#).

void TMult (const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply transpose of matrix by vector x and save in y .

Parameters

in	x	Vector to multiply by matrix
out	y	Vector that contains on output the result.

Implements [Matrix< T_ >](#).

void Axy (T_ a , const SpMatrix< T_ > & m)

Add to matrix the product of a matrix by a scalar.

Parameters

in	a	Scalar to premultiply
in	m	Matrix by which a is multiplied. The result is added to current instance

void Axy (T_ a , const Matrix< T_ > * m) [virtual]

Add to matrix the product of a matrix by a scalar.

Parameters

in	a	Scalar to premultiply
in	m	Pointer to Matrix by which a is multiplied. The result is added to current instance

Implements [Matrix< T_ >](#).

void set (size_t i , size_t j , const T_ & val) [virtual]

Assign a value to an entry of the matrix.

Parameters

in	i	Row index
in	j	Column index
in	val	Value to assign to $a(i, j)$

Implements [Matrix< T_ >](#).

void add (size_t i , size_t j , const T_ & val) [virtual]

Add a value to an entry of the matrix.

Parameters

in	i	Row index
in	j	Column index
in	val	Constant value to add to $a(i, j)$

Implements [Matrix< T_ >](#).

void operator= (const T_ & x)

Operator =.

Assign constant value x to all matrix entries.

size_t getColInd (size_t i) const [virtual]

Return storage information.

Returns

Column index of the i -th stored element in matrix

Reimplemented from [Matrix< T_ >](#).

int solve (const Vect< T_ > & b , Vect< T_ > & x , bool $fact = false$) [virtual]

Solve the linear system of equations.

The default parameters are:

- CG_SOLVER for solver
- DIAG_PREC for preconditioner
- Max. Number of iterations is 1000
- Tolerance is $1.e-8$

To change these values, call function setSolver before this function

Parameters

in	b	Vector that contains right-hand side
out	x	Vector that contains the obtained solution
in	$fact$	Unused argument

Returns

Number of actual performed iterations

Implements [Matrix< T_ >](#).

void setSolver (Iteration $solver = CG_SOLVER$, Preconditioner $prec = DIAG_PREC$, int $max_it = 1000$, real_t $toler = 1.e-8$)

Choose solver and preconditioner for an iterative procedure.

Parameters

in	<i>solver</i>	Option to choose iterative solver in an enumerated variable <ul style="list-style-type: none"> • CG_SOLVER: Conjugate Gradient [default] • CGS_SOLVER: Squared conjugate gradient • BICG_SOLVER: Biconjugate gradient • BICG_STAB_SOLVER: Biconjugate gradient stabilized • GMRES_SOLVER: Generalized Minimal Residual Default value is CG_SOLVER
in	<i>prec</i>	Option to choose preconditioner in an enumerated variable <ul style="list-style-type: none"> • IDENT_PREC: Identity preconditioner (no preconditioning) • DIAG_PREC: Diagonal preconditioner [default] • SSOR_PREC: SSOR (Symmetric Successive Over Relaxation) preconditioner • DILU_PREC: ILU (Diagonal Incomplete factorization) preconditioner • ILU_PREC: ILU (Incomplete factorization) preconditioner Default value is DIAG_PREC
in	<i>max_it</i>	Maximum number of allowed iterations. Default value is 1000.
in	<i>toler</i>	Tolerance for convergence. Default value is 1.e-8

T_* get () const

Return C-Array.

Non zero terms of matrix is stored row by row.

T_ get (size_t i, size_t j) const [virtual]

Return entry (i, j) of matrix if this one is stored, 0 otherwise.

Parameters

in	<i>i</i>	Row index (Starting from 1)
in	<i>j</i>	Column index (Starting from 1)

Implements [Matrix< T_ >](#).**TrMatrix ()**

Default constructor.

Initialize a zero dimension tridiagonal matrix

void Laplace1D (real_t h)

Define matrix as the one of 3-point finite difference discretization of the second derivative.

Parameters

in	<i>h</i>	mesh size
-----------	----------	-----------

void setSize (size_t size)

Set size (number of rows) of matrix.

Parameters

in	<i>size</i>	Number of rows and columns.
-----------	-------------	-----------------------------

void Axy (T_ a, const TrMatrix< T_ > & m)

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which a is multiplied. The result is added to current instance

void Axy (T_ a, const Matrix< T_ > * m) [virtual]

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which a is multiplied. The result is added to current instance

Implements [Matrix< T_ >](#).

T_ operator() (size_t i, size_t j) const [virtual]

Operator () (Constant version).

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implements [Matrix< T_ >](#).

T_& operator() (size_t i, size_t j) [virtual]

Operator () (Non constant version).

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implements [Matrix< T_ >](#).

TrMatrix< T_ > & operator= (const TrMatrix< T_ > & m)

Operator =.

Copy matrix m to current matrix instance.

TrMatrix<T_>& operator*= (const T_ & x)

Operator *.=.

Premultiply matrix entries by constant value x.

int solve (Vect< T_ > & b, bool fact = true) [virtual]

Solve a linear system with current matrix (forward and back substitution).

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side on input and solution on output.
in	<i>fact</i>	Unused argument

Returns

- 0 if solution was normally performed,
- n if the n-th pivot is null.

Warning: Matrix is modified after this function.

Implements [Matrix< T_ >](#).

int solve (const Vect< T_ > & b, Vect< T_ > & x, bool fact = false) [virtual]

Solve a linear system with current matrix (forward and back substitution).

Parameters

in	<i>b</i>	Vect instance that contains right-hand side.
out	<i>x</i>	Vect instance that contains solution.
in	<i>fact</i>	Unused argument

Returns

- 0 if solution was normally performed,
- n if the n-th pivot is null.

Warning: Matrix is modified after this function.

Implements [Matrix< T_ >](#).

Grid (real_t xm, real_t xM, size_t npx)

Construct a 1-D structured grid given its extremal coordinates and number of intervals.

Parameters

in	<i>xm</i>	Minimal value for x
in	<i>xM</i>	Maximal value for x
in	<i>npx</i>	Number of grid intervals in the x-direction

Grid (real_t xm, real_t xM, real_t ym, real_t yM, size_t npx, size_t npy)

Construct a 2-D structured grid given its extremal coordinates and number of intervals.

Parameters

in	<i>xm</i>	Minimal value for x
in	<i>xM</i>	Maximal value for x
in	<i>ym</i>	Minimal value for y
in	<i>yM</i>	Maximal value for y
in	<i>npx</i>	Number of grid intervals in the x-direction
in	<i>npy</i>	Number of grid intervals in the y-direction

Grid (Point< real.t > *m*, Point< real.t > *M*, size.t *npx*, size.t *npy*)

Construct a 2-D structured grid given its extremal coordinates and number of intervals.

Parameters

in	<i>m</i>	Minimal coordinate value
in	<i>M</i>	Maximal coordinate value
in	<i>npx</i>	Number of grid intervals in the x-direction
in	<i>npy</i>	Number of grid intervals in the y-direction

Grid (real.t *xm*, real.t *xM*, real.t *ym*, real.t *yM*, real.t *zm*, real.t *zM*, size.t *npx*, size.t *npy*, size.t *npz*)

Construct a 3-D structured grid given its extremal coordinates and number of intervals.

Parameters

in	<i>xm</i>	Minimal value for x
in	<i>xM</i>	Maximal value for x
in	<i>ym</i>	Minimal value for y
in	<i>yM</i>	Maximal value for y
in	<i>zm</i>	Minimal value for z
in	<i>zM</i>	Maximal value for z
in	<i>npx</i>	Number of grid intervals in the x-direction
in	<i>npy</i>	Number of grid intervals in the y-direction
in	<i>npz</i>	Number of grid intervals in the z-direction

Grid (Point< real.t > *m*, Point< real.t > *M*, size.t *npx*, size.t *npy*, size.t *npz*)

Construct a 3-D structured grid given its extremal coordinates and number of intervals.

Parameters

in	<i>m</i>	Minimal coordinate value
in	<i>M</i>	Maximal coordinate value
in	<i>npx</i>	Number of grid intervals in the x-direction
in	<i>npy</i>	Number of grid intervals in the y-direction
in	<i>npz</i>	Number of grid intervals in the z-direction

void setXMin (const Point< real.t > &*x*)

Set min. coordinates of the domain.

Parameters

in	<i>x</i>	Minimal values of coordinates
-----------	----------	-------------------------------

void setXMax (const Point< real_t > & x)

Set max. coordinates of the domain.

Parameters

in	<i>x</i>	Maximal values of coordinates
-----------	----------	-------------------------------

void setDomain (real_t xmin, real_t xmax)

Set Dimensions of the domain: 1-D case.

Parameters

in	<i>xmin</i>	Minimal value of x-coordinate
in	<i>xmax</i>	Maximal value of x-coordinate

void setDomain (real_t xmin, real_t xmax, real_t ymin, real_t ymax)

Set Dimensions of the domain: 2-D case.

Parameters

in	<i>xmin</i>	Minimal value of x-coordinate
in	<i>xmax</i>	Maximal value of x-coordinate
in	<i>ymin</i>	Minimal value of y-coordinate
in	<i>ymax</i>	Maximal value of y-coordinate

void setDomain (real_t xmin, real_t xmax, real_t ymin, real_t ymax, real_t zmin, real_t zmax)

Set Dimensions of the domain: 3-D case.

Parameters

in	<i>xmin</i>	Minimal value of x-coordinate
in	<i>xmax</i>	Maximal value of x-coordinate
in	<i>ymin</i>	Minimal value of y-coordinate
in	<i>ymax</i>	Maximal value of y-coordinate
in	<i>zmin</i>	Minimal value of z-coordinate
in	<i>zmax</i>	Maximal value of z-coordinate

void setDomain (Point< real_t > xmin, Point< real_t > xmax)

Set Dimensions of the domain: 3-D case.

Parameters

in	<i>xmin</i>	Minimal coordinate value
in	<i>xmax</i>	Maximal coordinate value

void setN (size_t *nx*, size_t *ny* = 0, size_t *nz* = 0)

Set number of grid intervals in the x, y and z-directions.

Number of points is the number of intervals plus one in each direction

Parameters

<code>in</code>	<code>nx</code>	Number of grid intervals in the x-direction
<code>in</code>	<code>ny</code>	Number of grid intervals in the y-direction (Default=0: 1-D grid)
<code>in</code>	<code>nz</code>	Number of grid intervals in the z-direction (Default=0: 1-D or 2-D grid)

Remarks

: The size of the grid (`xmin` and `xmax`) must have been defined before.

size_t getNy () const

Return number of grid intervals in the y-direction.

`ny=0` for 1-D domains (segments)

size_t getNz () const

Return number of grid intervals in the z-direction.

`nz=0` for 1-D (segments) and 2-D domains (rectangles)

void setCode (string exp, int code)

Set a code for some grid points.

Parameters

<code>in</code>	<code>exp</code>	Regular expression that determines the set of grid points on which the code is applied.
<code>in</code>	<code>code</code>	Code to assign.

void setCode (int side, int code)

Set a code for grid points on sides.

Parameters

<code>in</code>	<code>side</code>	Side for which code is assigned. Possible values are: <code>MIN_X</code> , <code>MAX_X</code> , <code>MIN_Y</code> , <code>MAX_Y</code> , <code>MIN_Z</code> , <code>MAX_Z</code>
<code>in</code>	<code>code</code>	Code to assign.

int getCode (int side) const

Return code for a side number.

Parameters

<code>in</code>	<code>side</code>	Side for which code is returned. Possible values are: <code>MIN_X</code> , <code>MAX_X</code> , <code>MIN_Y</code> , <code>MAX_Y</code> , <code>MIN_Z</code> , <code>MAX_Z</code>
-----------------	-------------------	---

int getCode (size_t i, size_t j) const

Return code for a grid point.

Parameters

<code>in</code>	<code>i</code>	i-th index for node for which code is to be returned.
<code>in</code>	<code>j</code>	j-th index for node for which code is to be returned.

int getCode (size_t *i*, size_t *j*, size_t *k*) const

Return code for a grid point.

Parameters

<code>in</code>	<code>i</code>	i-th index for node for which code is to be returned.
<code>in</code>	<code>j</code>	j-th index for node for which code is to be returned.
<code>in</code>	<code>k</code>	k-th index for node for which code is to be returned.

void Deactivate (size_t *i*)

Change state of a cell from active to inactive (1-D grid)

Parameters

<code>in</code>	<code>i</code>	grid cell to remove
-----------------	----------------	---------------------

void Deactivate (size_t *i*, size_t *j*)

Change state of a cell from active to inactive (2-D grid)

Parameters

<code>in</code>	<code>i</code>	i-th index for grid cell to remove. If this value is 0, all cells (*,j) are deactivated
<code>in</code>	<code>j</code>	j-th index for grid cell to remove If this value is 0, all cells (i,*) are deactivated

Remarks

if i and j have value 0 all grid cells are deactivated !!

void Deactivate (size_t *i*, size_t *j*, size_t *k*)

Change state of a cell from active to inactive (2-D grid)

Parameters

<code>in</code>	<code>i</code>	i-th index for grid cell to remove. If this value is 0, all cells (*,j,k) are deactivated
<code>in</code>	<code>j</code>	j-th index for grid cell to remove If this value is 0, all cells (i,*,k) are deactivated
<code>in</code>	<code>k</code>	k-th index for grid cell to remove If this value is 0, all cells (i,j,*) are deactivated

int isActive (size_t *i*) const

Say if cell is active or not (1-D grid)

Parameters

<code>in</code>	<code>i</code>	Index of cell
-----------------	----------------	---------------

Returns

1 if cell is active, 0 if not

int isActive (size_t *i*, size_t *j*) const

Say if cell is active or not (2-D grid)

Parameters

<code>in</code>	<code>i</code>	i-th index of cell
<code>in</code>	<code>j</code>	j-th index of cell

Returns

1 if cell is active, 0 if not

int isActive (size_t *i*, size_t *j*, size_t *k*) const

Say if cell is active or not (3-D grid)

Parameters

<code>in</code>	<code>i</code>	i-th index of cell
<code>in</code>	<code>j</code>	j-th index of cell
<code>in</code>	<code>k</code>	k-th index of cell

Returns

1 if cell is active, 0 if not

Iter ()

Default Constructor.

This constructor set default values: the maximal number of iterations is set to 100 and the tolerance to $1.e-8$

Iter (int *max_it*, real_t *toler*)

Constructor with iteration parameters.

Parameters

<code>in</code>	<code>max_it</code>	Maximum number of iterations
<code>in</code>	<code>toler</code>	Tolerance value for convergence

bool check (Vect< T_ > & *u*, const Vect< T_ > & *v*, int *opt* = 2)

Check convergence.

Parameters

<code>in,out</code>	u	Solution vector at previous iteration
<code>in</code>	v	Solution vector at current iteration
<code>in</code>	opt	Vector norm for convergence checking 1: 1-norm, 2: 2-norm, 0: Max. norm [Default: 2]

Returns

true if convergence criterion is satisfied, false if not

After checking, this function copied v into u .

bool check (T_ & u , const T_ & v)

Check convergence for a scalar case (one equation)

Parameters

<code>in,out</code>	u	Solution at previous iteration
<code>in</code>	v	Solution at current iteration

Returns

true if convergence criterion is satisfied, false if not

After checking, this function copied v into u .

Chapter 6

Namespace Documentation

6.1 OFELI Namespace Reference

A namespace to group all library classes, functions, ...

Classes

- class [AbsEqua](#)
Mother abstract class to describe equation.
- class [Bar2DL2](#)
To build element equations for Planar Elastic Bar element with 2 DOF (Degrees of Freedom) per node.
- class [Beam3DL2](#)
To build element equations for 3-D beam equations using 2-node lines.
- class [BiotSavart](#)
Class to compute the magnetic induction from the current density using the Biot-Savart formula.
- class [BMatrix](#)
To handle band matrices.
- class [Brick](#)
To store and treat a brick (parallelepiped) figure.
- class [Circle](#)
To store and treat a circular figure.
- class [DC1DL2](#)
Builds finite element arrays for thermal diffusion and convection in 1-D using 2-Node elements.
- class [DC2DT3](#)
Builds finite element arrays for thermal diffusion and convection in 2-D domains using 3-Node triangles.
- class [DC2DT6](#)
Builds finite element arrays for thermal diffusion and convection in 2-D domains using 6-Node triangles.
- class [DC3DAT3](#)
Builds finite element arrays for thermal diffusion and convection in 3-D domains with axisymmetry using 3-Node triangles.
- class [DC3DT4](#)
Builds finite element arrays for thermal diffusion and convection in 3-D domains using 4-Node tetrahedra.
- class [DG](#)
Enables preliminary operations and utilities for the Discontinuous Galerkin method.
- class [DMatrix](#)

- To handle dense matrices.*
- class [Domain](#)
 - To store and treat finite element geometric information.*
- class [DSMatrix](#)
 - To handle symmetric dense matrices.*
- class [EC2D1T3](#)
 - Eddy current problems in 2-D domains using solenoidal approximation.*
- class [EC2D2T3](#)
 - Eddy current problems in 2-D domains using transversal approximation.*
- class [Edge](#)
 - To describe an edge.*
- class [EdgeList](#)
 - Class to construct a list of edges having some common properties.*
- class [EigenProblemSolver](#)
 - Class to find eigenvalues and corresponding eigenvectors of a given matrix in a generalized eigenproblem, i.e. Find scalars λ and non-null vectors v such that $[K]\{v\} = \lambda[M]\{v\}$ where $[K]$ and $[M]$ are symmetric matrices. The eigenproblem can be originated from a PDE. For this, we will refer to the matrices K and M as Stiffness and Mass matrices respectively.*
- class [Elas2DQ4](#)
 - To build element equations for 2-D linearized elasticity using 4-node quadrilaterals.*
- class [Elas2DT3](#)
 - To build element equations for 2-D linearized elasticity using 3-node triangles.*
- class [Elas3DH8](#)
 - To build element equations for 3-D linearized elasticity using 8-node hexahedra.*
- class [Elas3DT4](#)
 - To build element equations for 3-D linearized elasticity using 4-node tetrahedra.*
- class [Element](#)
 - To store and treat finite element geometric information.*
- class [ElementList](#)
 - Class to construct a list of elements having some common properties.*
- class [Ellipse](#)
 - To store and treat an ellipsoidal figure.*
- class [Equa_Electromagnetics](#)
 - Abstract class for Electromagnetics [Equation](#) classes.*
- class [Equa_Fluid](#)
 - Abstract class for Fluid Dynamics [Equation](#) classes.*
- class [Equa_Laplace](#)
 - Abstract class for classes about the Laplace equation.*
- class [Equa_Porous](#)
 - Abstract class for Porous Media Finite Element classes.*
- class [Equa_Solid](#)
 - Abstract class for Solid Mechanics Finite Element classes.*
- class [Equa_Therm](#)
 - Abstract class for Heat transfer Finite Element classes.*
- class [Equation](#)
 - Abstract class for all equation classes.*
- class [Estimator](#)

- To calculate an a posteriori estimator of the solution.*

 - class [FastMarching2D](#)
- To run a Fast Marching Method on 2-D structured uniform grids.*

 - class [FEShape](#)
- Parent class from which inherit all finite element shape classes.*

 - class [Figure](#)
- To store and treat a figure (or shape) information.*

 - class [FMM2D](#)
- class for the fast marching 2-D algorithm*

 - class [FMM3D](#)
- class for the 3-D fast marching algorithm*

 - class [FMMSolver](#)
- The Fast Marching Method solver.*

 - class [Funct](#)
- A simple class to parse real valued functions.*

 - class [Gauss](#)
- Calculate data for Gauss integration.*

 - class [Grid](#)
- To manipulate structured grids.*

 - class [HelmholtzBT3](#)
- Builds finite element arrays for Helmholtz equations in a bounded media using 3-Node triangles.*

 - class [Hexa8](#)
- Defines a three-dimensional 8-node hexahedral finite element using Q1-isoparametric interpolation.*

 - class [ICPG1D](#)
- Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 1-D.*

 - class [ICPG2DT](#)
- Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 2-D.*

 - class [ICPG3DT](#)
- Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 3-D.*

 - class [Integration](#)
- Class for numerical integration methods.*

 - class [IOField](#)
- Enables working with files in the XML Format.*

 - class [IPF](#)
- To read project parameters from a file in [IPF](#) format.*

 - class [Iter](#)
- Class to drive an iterative process.*

 - class [Laplace1DL2](#)
- To build element equation for a 1-D elliptic equation using the 2-Node line element (P_1).*

 - class [Laplace1DL3](#)
- To build element equation for the 1-D elliptic equation using the 3-Node line (P_2).*

 - class [Laplace2DT3](#)
- To build element equation for the Laplace equation using the 2-D triangle element (P_1).*

 - class [Laplace2DT6](#)
- To build element equation for the Laplace equation using the 2-D triangle element (P_2).*

 - class [LaplaceDG2DP1](#)

- To build and solve the linear system for the Poisson problem using the [DG](#) P_1 2-D triangle element.

 - class [LCL1D](#)
- Class to solve the linear conservation law (Hyperbolic equation) in 1-D by a MUSCL Finite Volume scheme.

 - class [LCL2DT](#)
- Class to solve the linear hyperbolic equation in 2-D by a MUSCL Finite Volume scheme on triangles.

 - class [LCL3DT](#)
- Class to solve the linear conservation law equation in 3-D by a MUSCL Finite Volume scheme on tetrahedra.

 - class [Line2](#)
- To describe a 2-Node planar line finite element.

 - class [Line3](#)
- To describe a 3-Node quadratic planar line finite element.

 - class [LinearSolver](#)
- Class to solve systems of linear equations by iterative methods.

 - class [LocalMatrix](#)
- Handles small size matrices like element matrices, with a priori known size.

 - class [LocalVect](#)
- Handles small size vectors like element vectors.

 - class [LPSolver](#)
- To solve a linear programming problem.

 - class [Material](#)
- To treat material data. This class enables reading material data in material data files. It also returns these informations by means of its members.

 - class [Matrix](#)
- Virtual class to handle matrices for all storage formats.

 - class [Mesh](#)
- To store and manipulate finite element meshes.

 - class [MeshAdapt](#)
- To adapt mesh in function of given solution.

 - class [Muscl](#)
- Parent class for hyperbolic solvers with Muscl scheme.

 - class [Muscl1D](#)
- Class for 1-D hyperbolic solvers with [Muscl](#) scheme.

 - class [Muscl2DT](#)
- Class for 2-D hyperbolic solvers with [Muscl](#) scheme.

 - class [Muscl3DT](#)
- Class for 3-D hyperbolic solvers with [Muscl](#) scheme using tetrahedra.

 - class [MyNLAS](#)
- Abstract class to define by user specified function.

 - class [MyOpt](#)
- Abstract class to define by user specified optimization function.

 - class [NLASSolver](#)
- To solve a system of nonlinear algebraic equations of the form $f(u) = 0$.

 - class [Node](#)
- To describe a node.

 - class [NodeList](#)
- Class to construct a list of nodes having some common properties.

 - class [NSP2DQ41](#)

Builds finite element arrays for incompressible Navier-Stokes equations in 2-D domains using Q_1/P_0 element and a penalty formulation for the incompressibility condition.

- class [ODESolver](#)
To solve a system of ordinary differential equations.
- class [OFELIException](#)
To handle exceptions in [OFELI](#).
- class [OptSolver](#)
To solve an optimization problem with bound constraints.
- class [Partition](#)
To partition a finite element mesh into balanced submeshes.
- class [Penta6](#)
Defines a 6-node pentahedral finite element using P_1 interpolation in local coordinates $(s.x, s.y)$ and Q_1 isoparametric interpolation in local coordinates $(s.x, s.z)$ and $(s.y, s.z)$.
- class [PhaseChange](#)
This class enables defining phase change laws for a given material.
- class [Point](#)
Defines a point with arbitrary type coordinates.
- class [Point2D](#)
Defines a 2-D point with arbitrary type coordinates.
- class [Polygon](#)
To store and treat a polygonal figure.
- class [Prec](#)
To set a preconditioner.
- class [Prescription](#)
To prescribe various types of data by an algebraic expression. Data may consist in boundary conditions, forces, tractions, fluxes, initial condition. All these data types can be defined through an enumerated variable.
- class [Quad4](#)
Defines a 4-node quadrilateral finite element using Q_1 isoparametric interpolation.
- class [Reconstruction](#)
To perform various reconstruction operations.
- class [Rectangle](#)
To store and treat a rectangular figure.
- class [Side](#)
To store and treat finite element sides (edges in 2-D or faces in 3-D)
- class [SideList](#)
Class to construct a list of sides having some common properties.
- class [SkMatrix](#)
To handle square matrices in skyline storage format.
- class [SkSMatrix](#)
To handle symmetric matrices in skyline storage format.
- class [Sphere](#)
To store and treat a sphere.
- class [SpMatrix](#)
To handle matrices in sparse storage format.
- class [SteklovPoincare2DBE](#)
Solver of the Steklov Poincare problem in 2-D geometries using piecewise constant boundary elemen.

- class [Tabulation](#)

To read and manipulate tabulated functions.

- class [Tetra4](#)

Defines a three-dimensional 4-node tetrahedral finite element using P_1 interpolation.

- class [Timer](#)

To handle elapsed time counting.

- class [TimeStepping](#)

To solve time stepping problems, i.e. systems of linear ordinary differential equations of the form $[A2]\{y''\} + [A1]\{y'\} + [A0]\{y\} = \{b\}$.

- class [TINS2DT3S](#)

Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 2-D domains. Numerical approximation uses stabilized 3-node triangle finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.

- class [TINS3DT4S](#)

Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 3-D domains. Numerical approximation uses stabilized 4-node tetrahedral finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.

- class [Triang3](#)

Defines a 3-Node (P_1) triangle.

- class [Triang6S](#)

Defines a 6-Node straight triangular finite element using P_2 interpolation.

- class [Triangle](#)

To store and treat a triangle.

- class [triangle](#)

Defines a triangle. The reference element is the rectangle triangle with two unit edges.

- class [TrMatrix](#)

To handle tridiagonal matrices.

- class [Vect](#)

To handle general purpose vectors.

- class [WaterPorous2D](#)

To solve water flow equations in porous media (1-D)

Enumerations

- `enum PDE_Terms {`
`CONSISTENT_MASS = 0x00001000,`
`LUMPED_MASS = 0x00002000,`
`MASS = 0x00002000,`
`CAPACITY = 0x00004000,`
`CONSISTENT_CAPACITY = 0x00004000,`
`LUMPED_CAPACITY = 0x00008000,`
`VISCOSITY = 0x00010000,`
`STIFFNESS = 0x00020000,`
`DIFFUSION = 0x00040000,`
`MOBILITY = 0x00040000,`
`CONVECTION = 0x00080000,`
`DEVIATORIC = 0x00100000,`
`DILATATION = 0x00200000,`
`ELECTRIC = 0x00400000,`
`MAGNETIC = 0x00800000,`
`LOAD = 0x01000000,`
`HEAT_SOURCE = 0x02000000,`
`BOUNDARY_TRACTION = 0x04000000,`
`HEAT_FLUX = 0x08000000,`
`CONTACT = 0x10000000,`
`BUOYANCY = 0x20000000,`
`LORENTZ_FORCE = 0x40000000 }`
- `enum Analysis {`
`STATIONARY = 0,`
`STEADY_STATE = 0,`
`TRANSIENT = 1,`
`TRANSIENT_ONE_STEP = 2,`
`OPTIMIZATION = 3,`
`EIGEN = 4 }`
- `enum TimeScheme {`
`NONE = 0,`
`FORWARD_EULER = 1,`
`BACKWARD_EULER = 2,`
`CRANK_NICOLSON = 3,`
`HEUN = 4,`
`NEWMARK = 5,`
`LEAP_FROG = 6,`
`ADAMS_BASHFORTH = 7,`
`AB2 = 7,`
`RUNGE_KUTTA = 8,`
`RK4 = 8,`
`RK3_TVD = 9,`
`BDF2 = 10,`
`BUILTIN = 11 }`
- `enum FEType {`
`FE_2D_3N,`
`FE_2D_6N,`
`FE_2D_4N,`
`FE_3D_AXI3N,`
`FE_3D_4N,`
`FE_3D_8N }`

- enum `MatrixType` {
`DENSE` = 1,
`SKYLINE` = 2,
`SPARSE` = 4,
`DIAGONAL` = 8,
`TRIDIAGONAL` = 16,
`BAND` = 32,
`SYMMETRIC` = 64,
`UNSYMMETRIC` = 128,
`IDENTITY` = 256 }
- enum `Iteration` {
`DIRECT_SOLVER` = 0,
`CG_SOLVER` = 1,
`CGS_SOLVER` = 2,
`BICG_SOLVER` = 3,
`BICG_STAB_SOLVER` = 4,
`GMRES_SOLVER` = 5 }
- Choose iterative solver for the linear system.*
- enum `Preconditioner` {
`IDENT_PREC` = 0,
`DIAG_PREC` = 1,
`DILU_PREC` = 2,
`ILU_PREC` = 3,
`SSOR_PREC` = 4 }
- Choose preconditioner for the linear system.*
- enum `NormType` {
`NORM1`,
`WNORM1`,
`NORM2`,
`WNORM2`,
`NORM.MAX` }
- enum `BCType` {
`PERIODIC_A` = 9999,
`PERIODIC_B` = -9999,
`CONTACT_BC` = 9998,
`CONTACT_M` = 9997,
`CONTACT_S` = -9997,
`SLIP` = 9996 }
- enum `IntegrationScheme` {
`LEFT_RECTANGLE` = 0,
`RIGHT_RECTANGLE` = 1,
`MID_RECTANGLE` = 2,
`TRAPEZOIDAL` = 3,
`SIMPSON` = 4,
`GAUSS_LEGENDRE` = 5 }

Functions

- `ostream & operator<<` (`ostream &s`, `const Muscl3DT &m`)
Output mesh data as calculated in class `Muscl3DT`.
- `T_ * A ()`
Return element matrix.

- `T_ * b ()`
Return element right-hand side.
- `T_ * Prev ()`
Return element previous vector.
- `ostream & operator<< (ostream &s, const complex.t &x)`
Output a complex number.
- `ostream & operator<< (ostream &s, const std::string &c)`
Output a string.
- `template<class T_ >`
`ostream & operator<< (ostream &s, const vector< T_ > &v)`
Output a vector instance.
- `template<class T_ >`
`ostream & operator<< (ostream &s, const std::list< T_ > &l)`
Output a vector instance.
- `template<class T_ >`
`ostream & operator<< (ostream &s, const std::pair< T_, T_ > &a)`
Output a pair instance.
- `void saveField (Vect< real.t > &v, string output_file, int opt)`
Save a vector to an output file in a given file format.
- `void saveField (const Vect< real.t > &v, const Mesh &mesh, string output_file, int opt)`
Save a vector to an output file in a given file format.
- `void saveField (Vect< real.t > &v, const Grid &g, string output_file, int opt)`
Save a vector to an output file in a given file format, for a structured grid data.
- `void saveGnuplot (string input_file, string output_file, string mesh_file, int f=1)`
*Save a vector to an input **Gnuplot** file.*
- `void saveGnuplot (Mesh &mesh, string input_file, string output_file, int f=1)`
*Save a vector to an input **Gnuplot** file.*
- `void saveTecplot (string input_file, string output_file, string mesh_file, int f=1)`
*Save a vector to an output file to an input **Tecplot** file.*
- `void saveTecplot (Mesh &mesh, string input_file, string output_file, int f=1)`
*Save a vector to an output file to an input **Tecplot** file.*
- `void saveVTK (string input_file, string output_file, string mesh_file, int f=1)`
*Save a vector to an output **VTK** file.*
- `void saveVTK (Mesh &mesh, string input_file, string output_file, int f=1)`
*Save a vector to an output **VTK** file.*
- `void saveGmsh (string input_file, string output_file, string mesh_file, int f=1)`
*Save a vector to an output **Gmsh** file.*
- `void saveGmsh (Mesh &mesh, string input_file, string output_file, int f=1)`
*Save a vector to an output **Gmsh** file.*
- `ostream & operator<< (ostream &s, const Tabulation &t)`
Output Tabulated function data.
- `template<class T_ , size_t N_ , class E_ >`
`void element.assembly (const E_ &e, const LocalVect< T_ , N_ > &be, Vect< T_ > &b)`
Assemble local vector into global vector.
- `template<class T_ , size_t N_ , class E_ >`
`void element.assembly (const E_ &e, const LocalMatrix< T_ , N_ , N_ > &ae, Vect< T_ > &b)`
Assemble diagonal local vector into global vector.

- `template<class T_, size_t N_, class E_>`
`void element_assembly (const E_ &e, const LocalMatrix< T_, N_, N_ > &ae, Matrix< T_ > *A)`
Assemble local matrix into global matrix.
- `template<class T_, size_t N_, class E_>`
`void element_assembly (const E_ &e, const LocalMatrix< T_, N_, N_ > &ae, SkMatrix< T_ > &A)`
Assemble local matrix into global skyline matrix.
- `template<class T_, size_t N_, class E_>`
`void element_assembly (const E_ &e, const LocalMatrix< T_, N_, N_ > &ae, SkSMatrix< T_ > &A)`
Assemble local matrix into global symmetric skyline matrix.
- `template<class T_, size_t N_, class E_>`
`void element_assembly (const E_ &e, const LocalMatrix< T_, N_, N_ > &ae, SpMatrix< T_ > &A)`
Assemble local matrix into global sparse matrix.
- `template<class T_, size_t N_>`
`void side_assembly (const Element &e, const LocalMatrix< T_, N_, N_ > &ae, SpMatrix< T_ > &A)`
Side assembly of local matrix into global matrix (as instance of class SpMatrix).
- `template<class T_, size_t N_>`
`void side_assembly (const Element &e, const LocalMatrix< T_, N_, N_ > &ae, SkSMatrix< T_ > &A)`
Side assembly of local matrix into global matrix (as instance of class SkSMatrix).
- `template<class T_, size_t N_>`
`void side_assembly (const Element &e, const LocalMatrix< T_, N_, N_ > &ae, SkMatrix< T_ > &A)`
Side assembly of local matrix into global matrix (as instance of class SkMatrix).
- `template<class T_, size_t N_>`
`void side_assembly (const Element &e, const LocalVect< T_, N_ > &be, Vect< T_ > &b)`
Side assembly of local vector into global vector.
- `template<class T_>`
`Vect< T_ > operator* (const BMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_>`
`BMatrix< T_ > operator* (T_ a, const BMatrix< T_ > &A)`
*Operator * (Premultiplication of matrix by constant)*
- `template<class T_>`
`ostream & operator<< (ostream &s, const BMatrix< T_ > &a)`
Output matrix in output stream.
- `template<class T_>`
`Vect< T_ > operator* (const DMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*
- `template<class T_>`
`ostream & operator<< (ostream &s, const DMatrix< T_ > &a)`
Output matrix in output stream.
- `template<class T_>`
`Vect< T_ > operator* (const DSMatrix< T_ > &A, const Vect< T_ > &b)`
*Operator * (Multiply vector by matrix and return resulting vector.*

- `template<class T_>`
`ostream & operator<< (ostream &s, const DSMatrix< T_ > &a)`
Output matrix in output stream.
- `template<class T_, size_t NR_, size_t NC_>`
`LocalMatrix< T_, NR_, NC_ > operator* (T_ a, const LocalMatrix< T_, NR_, NC_ > &x)`
*Operator * (Multiply matrix x by scalar a)*
- `template<class T_, size_t NR_, size_t NC_>`
`LocalVect< T_, NR_ > operator* (const LocalMatrix< T_, NR_, NC_ > &A, const LocalVect< T_, NC_ > &x)`
*Operator * (Multiply matrix A by vector x)*
- `template<class T_, size_t NR_, size_t NC_>`
`LocalMatrix< T_, NR_, NC_ > operator/ (T_ a, const LocalMatrix< T_, NR_, NC_ > &x)`
Operator / (Divide matrix x by scalar a)
- `template<class T_, size_t NR_, size_t NC_>`
`LocalMatrix< T_, NR_, NC_ > operator+ (const LocalMatrix< T_, NR_, NC_ > &x, const LocalMatrix< T_, NR_, NC_ > &y)`
Operator + (Add matrix x to y)
- `template<class T_, size_t NR_, size_t NC_>`
`LocalMatrix< T_, NR_, NC_ > operator- (const LocalMatrix< T_, NR_, NC_ > &x, const LocalMatrix< T_, NR_, NC_ > &y)`
Operator - (Subtract matrix y from x)
- `template<class T_, size_t NR_, size_t NC_>`
`ostream & operator<< (ostream &s, const LocalMatrix< T_, NR_, NC_ > &A)`
Output vector in output stream.
- `template<class T_, size_t N_>`
`LocalVect< T_, N_ > operator+ (const LocalVect< T_, N_ > &x, const LocalVect< T_, N_ > &y)`
Operator + (Add two vectors)
- `template<class T_, size_t N_>`
`LocalVect< T_, N_ > operator- (const LocalVect< T_, N_ > &x, const LocalVect< T_, N_ > &y)`
Operator - (Subtract two vectors)
- `template<class T_, size_t N_>`
`LocalVect< T_, N_ > operator* (T_ a, const LocalVect< T_, N_ > &x)`
*Operator * (Premultiplication of vector by constant)*
- `template<class T_, size_t N_>`
`LocalVect< T_, N_ > operator/ (T_ a, const LocalVect< T_, N_ > &x)`
Operator / (Division of vector by constant)
- `template<class T_, size_t N_>`
`real_t Dot (const LocalVect< T_, N_ > &a, const LocalVect< T_, N_ > &b)`
Calculate dot product of 2 vectors (instances of class [LocalVect](#))
- `template<class T_, size_t N_>`
`void Scale (T_ a, const LocalVect< T_, N_ > &x, LocalVect< T_, N_ > &y)`
Multiply vector x by constant a and store result in y .
- `template<class T_, size_t N_>`
`void Scale (T_ a, LocalVect< T_, N_ > &x)`
Multiply vector x by constant a and store result in x .
- `template<class T_, size_t N_>`
`void Axy (T_ a, const LocalVect< T_, N_ > &x, LocalVect< T_, N_ > &y)`

- Add $a*x$ to vector y .*

 - `template<class T_, size_t N_>`
`void Copy (const LocalVect< T_, N_ > &x, LocalVect< T_, N_ > &y)`
Copy vector x into vector y .
 - `template<class T_, size_t N_>`
`ostream & operator<< (ostream &s, const LocalVect< T_, N_ > &v)`
Output vector in output stream.
 - `template<class T_>`
`bool operator== (const Point< T_ > &a, const Point< T_ > &b)`
Operator ==
 - `template<class T_>`
`Point< T_ > operator+ (const Point< T_ > &a, const Point< T_ > &b)`
Operator +
 - `template<class T_>`
`Point< T_ > operator+ (const Point< T_ > &a, const T_ &x)`
Operator +
 - `template<class T_>`
`Point< T_ > operator- (const Point< T_ > &a)`
Unary Operator -
 - `template<class T_>`
`Point< T_ > operator- (const Point< T_ > &a, const Point< T_ > &b)`
Operator -
 - `template<class T_>`
`Point< T_ > operator- (const Point< T_ > &a, const T_ &x)`
Operator -
 - `template<class T_>`
`Point< T_ > operator* (const T_ &a, const Point< T_ > &b)`
*Operator **
 - `template<class T_>`
`Point< T_ > operator* (const int &a, const Point< T_ > &b)`
*Operator *.*
 - `template<class T_>`
`Point< T_ > operator* (const Point< T_ > &b, const T_ &a)`
Operator /
 - `template<class T_>`
`Point< T_ > operator* (const Point< T_ > &b, const int &a)`
*Operator **
 - `template<class T_>`
`T_ operator* (const Point< T_ > &a, const Point< T_ > &b)`
*Operator **
 - `template<class T_>`
`Point< T_ > operator/ (const Point< T_ > &b, const T_ &a)`
Operator /
 - `Point< double > CrossProduct (const Point< double > &lp, const Point< double > &rp)`
Return Cross product of two vectors lp and rp
 - `bool areClose (const Point< double > &a, const Point< double > &b, double toler=OFELI.TOLERANCE)`
Return `true` if both instances of class `Point<double>` are distant with less then `toler`
 - `double SqrDistance (const Point< double > &a, const Point< double > &b)`

- Return squared euclidean distance between points `a` and `b`*

 - double `Distance` (const `Point`< double > &`a`, const `Point`< double > &`b`)
- Return euclidean distance between points `a` and `b`*

 - bool `operator<` (const `Point`< size_t > &`a`, const `Point`< size_t > &`b`)

Comparison operator. Returns true if all components of first vector are lower than those of second one.
- template<class T_ >
std::ostream & `operator<<` (std::ostream &`s`, const `Point`< T_ > &`a`)

Output point coordinates.
- template<class T_ >
bool `operator==` (const `Point2D`< T_ > &`a`, const `Point2D`< T_ > &`b`)

Operator ==.
- template<class T_ >
`Point2D`< T_ > `operator+` (const `Point2D`< T_ > &`a`, const `Point2D`< T_ > &`b`)

Operator +.
- template<class T_ >
`Point2D`< T_ > `operator+` (const `Point2D`< T_ > &`a`, const T_ &`x`)

Operator +.
- template<class T_ >
`Point2D`< T_ > `operator-` (const `Point2D`< T_ > &`a`)

Unary Operator -
- template<class T_ >
`Point2D`< T_ > `operator-` (const `Point2D`< T_ > &`a`, const `Point2D`< T_ > &`b`)

Operator -
- template<class T_ >
`Point2D`< T_ > `operator-` (const `Point2D`< T_ > &`a`, const T_ &`x`)

Operator -
- template<class T_ >
`Point2D`< T_ > `operator*` (const T_ &`a`, const `Point2D`< T_ > &`b`)

*Operator *.*
- template<class T_ >
`Point2D`< T_ > `operator*` (const int &`a`, const `Point2D`< T_ > &`b`)
- template<class T_ >
`Point2D`< T_ > `operator*` (const `Point2D`< T_ > &`b`, const T_ &`a`)

Operator /
- template<class T_ >
`Point2D`< T_ > `operator*` (const `Point2D`< T_ > &`b`, const int &`a`)

*Operator **
- template<class T_ >
T_ `operator*` (const `Point2D`< T_ > &`b`, const `Point2D`< T_ > &`a`)

*Operator *.*
- template<class T_ >
`Point2D`< T_ > `operator/` (const `Point2D`< T_ > &`b`, const T_ &`a`)

Operator /
- bool `areClose` (const `Point2D`< real_t > &`a`, const `Point2D`< real_t > &`b`, real_t `toler`=`OFE←LI.TOLERANCE`)

Return true if both instances of class `Point2D`<real_t> are distant with less then toler [Default: `OFE←LI.EPSMCH`].
- real_t `SqrDistance` (const `Point2D`< real_t > &`a`, const `Point2D`< real_t > &`b`)

Return squared euclidean distance between points `a` and `b`

- `real_t Distance` (const `Point2D`< `real_t` > &a, const `Point2D`< `real_t` > &b)
Return euclidean distance between points a and b
- template<class T_ >
`std::ostream & operator<<` (std::ostream &s, const `Point2D`< T_ > &a)
Output point coordinates.
- template<class T_ >
`Vect`< T_ > `operator*` (const `SkMatrix`< T_ > &A, const `Vect`< T_ > &b)
*Operator * (Multiply vector by matrix and return resulting vector.*
- template<class T_ >
`ostream & operator<<` (ostream &s, const `SkMatrix`< T_ > &a)
Output matrix in output stream.
- template<class T_ >
`Vect`< T_ > `operator*` (const `SkSMatrix`< T_ > &A, const `Vect`< T_ > &b)
*Operator * (Multiply vector by matrix and return resulting vector.*
- template<class T_ >
`ostream & operator<<` (ostream &s, const `SkSMatrix`< T_ > &a)
Output matrix in output stream.
- template<class T_ >
`Vect`< T_ > `operator*` (const `SpMatrix`< T_ > &A, const `Vect`< T_ > &b)
*Operator * (Multiply vector by matrix and return resulting vector.*
- template<class T_ >
`ostream & operator<<` (ostream &s, const `SpMatrix`< T_ > &A)
Output matrix in output stream.
- template<class T_ >
`Vect`< T_ > `operator*` (const `TrMatrix`< T_ > &A, const `Vect`< T_ > &b)
*Operator * (Multiply vector by matrix and return resulting vector.*
- template<class T_ >
`TrMatrix`< T_ > `operator*` (T_ a, const `TrMatrix`< T_ > &A)
*Operator * (Premultiplication of matrix by constant)*
- template<class T_ >
`ostream & operator<<` (ostream &s, const `TrMatrix`< T_ > &A)
Output matrix in output stream.
- template<class T_ >
`Vect`< T_ > `operator+` (const `Vect`< T_ > &x, const `Vect`< T_ > &y)
Operator + (Addition of two instances of class Vect)
- template<class T_ >
`Vect`< T_ > `operator-` (const `Vect`< T_ > &x, const `Vect`< T_ > &y)
Operator - (Difference between two vectors of class Vect)
- template<class T_ >
`Vect`< T_ > `operator*` (const T_ &a, const `Vect`< T_ > &x)
*Operator * (Premultiplication of vector by constant)*
- template<class T_ >
`Vect`< T_ > `operator*` (const `Vect`< T_ > &x, const T_ &a)
*Operator * (Postmultiplication of vector by constant)*
- template<class T_ >
`Vect`< T_ > `operator/` (const `Vect`< T_ > &x, const T_ &a)
Operator / (Divide vector entries by constant)
- template<class T_ >
`T_ Dot` (const `Vect`< T_ > &x, const `Vect`< T_ > &y)

- Calculate dot product of two vectors.*

 - `real_t Discrepancy (Vect< real_t > &x, const Vect< real_t > &y, int n, int type=1)`

Return discrepancy between 2 vectors x and y
- `real_t Discrepancy (Vect< complex_t > &x, const Vect< complex_t > &y, int n, int type=1)`

Return discrepancy between 2 vectors x and y
- `void Modulus (const Vect< complex_t > &x, Vect< real_t > &y)`

Calculate modulus of complex vector.
- `void Real (const Vect< complex_t > &x, Vect< real_t > &y)`

Calculate real part of complex vector.
- `void Imag (const Vect< complex_t > &x, Vect< real_t > &y)`

Calculate imaginary part of complex vector.
- `template<class T_ >`
`istream & operator>> (istream &s, Vect< T_ > &v)`
- `template<class T_ >`
`ostream & operator<< (ostream &s, const Vect< T_ > &v)`

Output vector in output stream.
- `ostream & operator<< (ostream &s, const Edge &ed)`

Output edge data.
- `ostream & operator<< (ostream &s, const Element &el)`

Output element data.
- `Figure operator&& (const Figure &f1, const Figure &f2)`

*Function to define a *Figure* instance as the intersection of two *Figure* instances.*
- `Figure operator|| (const Figure &f1, const Figure &f2)`

*Function to define a *Figure* instance as the union of two *Figure* instances.*
- `Figure operator- (const Figure &f1, const Figure &f2)`

*Function to define a *Figure* instance as the set subtraction of two *Figure* instances.*
- `void getMesh (string file, ExternalFileFormat form, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a mesh file stored in an external file format.*
- `void getBamg (string file, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a mesh file stored in *Bamg* format.*
- `void getEasymesh (string file, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a mesh file stored in *Easymesh* format.*
- `void getGambit (string file, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a mesh file stored in *Gambit* neutral format.*
- `void getGmsh (string file, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a mesh file stored in *Gmsh* format.*
- `void getMatlab (string file, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a Matlab mesh data.*
- `void getNetgen (string file, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a mesh file stored in *Netgen* format.*
- `void getTetgen (string file, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a mesh file stored in *Tetgen* format.*
- `void getTriangle (string file, Mesh &mesh, size_t nb_dof=1)`

*Construct an instance of class *Mesh* from a mesh file stored in *Triangle* format.*
- `ostream & operator<< (ostream &s, const Grid &g)`

Output grid data.
- `ostream & operator<< (ostream &s, const Material &m)`

Output material data.

- `ostream & operator<< (ostream &s, const Mesh &ms)`

Output mesh data.

- `ostream & operator<< (ostream &s, const MeshAdapt &a)`

Output MeshAdapt class data.

- `ostream & operator<< (ostream &s, const NodeList &nl)`

Output NodeList instance.

- `ostream & operator<< (ostream &s, const ElementList &el)`

Output ElementList instance.

- `ostream & operator<< (ostream &s, const SideList &sl)`

Output SideList instance.

- `ostream & operator<< (ostream &s, const EdgeList &el)`

Output EdgeList instance.

- `size_t Label (const Node &nd)`

Return label of a given node.

- `size_t Label (const Element &el)`

Return label of a given element.

- `size_t Label (const Side &sd)`

Return label of a given side.

- `size_t Label (const Edge &ed)`

Return label of a given edge.

- `size_t NodeLabel (const Element &el, size_t n)`

Return global label of node local label in element.

- `size_t NodeLabel (const Side &sd, size_t n)`

Return global label of node local label in side.

- `Point< real_t > Coord (const Node &nd)`

Return coordinates of a given node.

- `int Code (const Node &nd, size_t i=1)`

Return code of a given (degree of freedom of) node.

- `int Code (const Element &el)`

Return code of a given element.

- `int Code (const Side &sd, size_t i=1)`

Return code of a given (degree of freedom of) side.

- `bool operator== (const Element &el1, const Element &el2)`

Check equality between 2 elements.

- `bool operator== (const Side &sd1, const Side &sd2)`

Check equality between 2 sides.

- `void DeformMesh (Mesh &mesh, const Vect< real_t > &u, real_t rate=0.2)`

Calculate deformed mesh using a displacement field.

- `void MeshToMesh (Mesh &m1, Mesh &m2, const Vect< real_t > &u1, Vect< real_t > &u2, size_t nx, size_t ny=0, size_t nz=0, size_t dof=1)`

Function to redefine a vector defined on a mesh to a new mesh.

- `void MeshToMesh (const Vect< real_t > &u1, Vect< real_t > &u2, size_t nx, size_t ny=0, size_t nz=0, size_t dof=1)`

Function to redefine a vector defined on a mesh to a new mesh.

- `void MeshToMesh (Mesh &m1, Mesh &m2, const Vect< real_t > &u1, Vect< real_t > &u2, const Point< real_t > &xmin, const Point< real_t > &xmax, size_t nx, size_t ny, size_t nz, size_t dof=1)`
Function to redefine a vector defined on a mesh to a new mesh.
- `real_t getMaxSize (const Mesh &m)`
Return maximal size of element edges for given mesh.
- `real_t getMinSize (const Mesh &m)`
Return minimal size of element edges for given mesh.
- `real_t getMinElementMeasure (const Mesh &m)`
Return minimal measure (length, area or volume) of elements of given mesh.
- `real_t getMaxElementMeasure (const Mesh &m)`
Return maximal measure (length, area or volume) of elements of given mesh.
- `real_t getMinSideMeasure (const Mesh &m)`
Return minimal measure (length or area) of sides of given mesh.
- `real_t getMaxSideMeasure (const Mesh &m)`
Return maximal measure (length or area) of sides of given mesh.
- `real_t getMeanElementMeasure (const Mesh &m)`
Return average measure (length, area or volume) of elements of given mesh.
- `real_t getMeanSideMeasure (const Mesh &m)`
Return average measure (length or area) of sides of given mesh.
- `void setNodeCodes (Mesh &m, const string &exp, int code, size_t dof=1)`
Assign a given code to all nodes satisfying a boolean expression using node coordinates.
- `void setBoundaryNodeCodes (Mesh &m, const string &exp, int code, size_t dof=1)`
Assign a given code to all nodes on boundary that satisfy a boolean expression using node coordinates.
- `int NodeInElement (const Node *nd, const Element *el)`
Say if a given node belongs to a given element.
- `int NodeInSide (const Node *nd, const Side *sd)`
Say if a given node belongs to a given side.
- `int SideInElement (const Side *sd, const Element *el)`
Say if a given side belongs to a given element.
- `ostream & operator<< (ostream &s, const Node &nd)`
Output node data.
- `void saveMesh (const string &file, const Mesh &mesh, ExternalFileFormat form)`
This function saves mesh data a file for a given external format.
- `void saveGmsh (const string &file, const Mesh &mesh)`
This function outputs a Mesh instance in a file in Gmsh format.
- `void saveGnuplot (const string &file, const Mesh &mesh)`
This function outputs a Mesh instance in a file in Gnuplot format.
- `void saveMatlab (const string &file, const Mesh &mesh)`
This function outputs a Mesh instance in a file in Matlab format.
- `void saveTecplot (const string &file, const Mesh &mesh)`
This function outputs a Mesh instance in a file in Tecplot format.
- `void saveVTK (const string &file, const Mesh &mesh)`
This function outputs a Mesh instance in a file in VTK format.
- `void saveBamg (const string &file, Mesh &mesh)`
This function outputs a Mesh instance in a file in Bamg format.
- `ostream & operator<< (ostream &s, const Side &sd)`

Output side data.

- ostream & **operator<<** (ostream &s, const **Estimator** &r)

Output estimator vector in output stream.

- template<class T_ >
int **BiCG** (const **SpMatrix**< T_ > &A, const **Prec**< T_ > &P, const **Vect**< T_ > &b, **Vect**< T_ > &x, int max_it, **real_t** &toler)

Biconjugate gradient solver function.

- template<class T_ >
int **BiCG** (const **SpMatrix**< T_ > &A, int prec, const **Vect**< T_ > &b, **Vect**< T_ > &x, int max_it, **real_t** toler)

Biconjugate gradient solver function.

- template<class T_ >
int **BiCGStab** (const **SpMatrix**< T_ > &A, const **Prec**< T_ > &P, const **Vect**< T_ > &b, **Vect**< T_ > &x, int max_it, **real_t** toler)

Biconjugate gradient stabilized solver function.

- template<class T_ >
int **BiCGStab** (const **SpMatrix**< T_ > &A, int prec, const **Vect**< T_ > &b, **Vect**< T_ > &x, int max_it, **real_t** toler)

Biconjugate gradient stabilized solver function.

- void **BSpline** (size_t n, size_t t, **Vect**< **Point**< **real_t** > > &control, **Vect**< **Point**< **real_t** > > &output, size_t num_output)

Function to perform a B-spline interpolation.

- template<class T_ >
int **CG** (const **SpMatrix**< T_ > &A, const **Prec**< T_ > &P, const **Vect**< T_ > &b, **Vect**< T_ > &x, int max_it, **real_t** toler)

Conjugate gradient solver function.

- template<class T_ >
int **CG** (const **SpMatrix**< T_ > &A, int prec, const **Vect**< T_ > &b, **Vect**< T_ > &x, int max_it, **real_t** toler)

Conjugate gradient solver function.

- template<class T_ >
int **CGS** (const **SpMatrix**< T_ > &A, const **Prec**< T_ > &P, const **Vect**< T_ > &b, **Vect**< T_ > &x, int max_it, **real_t** toler)

Conjugate Gradient Squared solver function.

- template<class T_ >
int **CGS** (const **SpMatrix**< T_ > &A, int prec, const **Vect**< T_ > &b, **Vect**< T_ > &x, int max_it, **real_t** toler)

Conjugate Gradient Squared solver function.

- ostream & **operator<<** (ostream &s, const **EigenProblemSolver** &es)

Output eigenproblem information.

- template<class T_ >
int **GMRes** (const **SpMatrix**< T_ > &A, const **Prec**< T_ > &P, const **Vect**< T_ > &b, **Vect**< T_ > &x, size_t m, int max_it, **real_t** toler)

GMRes solver function.

- template<class T_ >
int **GMRes** (const **SpMatrix**< T_ > &A, int prec, const **Vect**< T_ > &b, **Vect**< T_ > &x, size_t m, int max_it, **real_t** toler)

GMRes solver function.

- `template<class T_>`
`int GS (const SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x, real_t omega, int max_it, real_t toler)`
Gauss-Seidel solver function.
- `template<class T_>`
`int Jacobi (const SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x, real_t omega, int max_it, real_t toler)`
Jacobi solver function.
- `ostream & operator<< (ostream &s, const LPSolver &os)`
Output solver information.
- `ostream & operator<< (ostream &s, const NLASSolver &nl)`
Output nonlinear system information.
- `ostream & operator<< (ostream &s, const ODESolver &de)`
Output differential system information.
- `ostream & operator<< (ostream &s, const OptSolver &os)`
Output differential system information.
- `template<class T_ , class M_ >`
`int Richardson (const M_ &A, const Vect< T_ > &b, Vect< T_ > &x, real_t omega, int max_it, real_t toler, int verbose)`
Richardson solver function.
- `template<class T_>`
`void Schur (SkMatrix< T_ > &A, SpMatrix< T_ > &U, SpMatrix< T_ > &L, SpMatrix< T_ > &D, Vect< T_ > &b, Vect< T_ > &c)`
Solve a linear system of equations with a 2x2-block matrix.
- `template<class T_ , class M_ >`
`int SSOR (const M_ &A, const Vect< T_ > &b, Vect< T_ > &x, int max_it, real_t toler)`
SSOR solver function.
- `ostream & operator<< (ostream &s, TimeStepping &ts)`
Output differential system information.
- `void banner (const string &prog=" ")`
Outputs a banner as header of any developed program.
- `template<class T_>`
`void QuickSort (std::vector< T_ > &a, int begin, int end)`
Function to sort a vector.
- `template<class T_>`
`void qksort (std::vector< T_ > &a, int begin, int end)`
Function to sort a vector.
- `template<class T_ , class C_ >`
`void qksort (std::vector< T_ > &a, int begin, int end, C_ compare)`
Function to sort a vector according to a key function.
- `int Sgn (real_t a)`
Return sign of a: -1 or 1.
- `real_t Abs2 (complex_t a)`
Return square of modulus of complex number a
- `real_t Abs2 (real_t a)`
Return square of real number a
- `real_t Abs (real_t a)`
Return absolute value of a

- `real_t Abs (complex_t a)`
Return modulus of complex number a
- `real_t Abs (const Point< real_t > &p)`
Return Norm of vector a
- `real_t Conjg (real_t a)`
Return complex conjugate of real number a
- `complex_t Conjg (complex_t a)`
Return complex conjugate of complex number a
- `real_t Max (real_t a, real_t b, real_t c)`
Return maximum value of real numbers a , b and c
- `int Max (int a, int b, int c)`
Return maximum value of integer numbers a , b and c
- `real_t Min (real_t a, real_t b, real_t c)`
Return minimum value of real numbers a , b and c
- `int Min (int a, int b, int c)`
Return minimum value of integer numbers a , b and c
- `real_t Max (real_t a, real_t b, real_t c, real_t d)`
Return maximum value of integer numbers a , b , c and d
- `int Max (int a, int b, int c, int d)`
Return maximum value of integer numbers a , b , c and d
- `real_t Min (real_t a, real_t b, real_t c, real_t d)`
Return minimum value of real numbers a , b , c and d
- `int Min (int a, int b, int c, int d)`
Return minimum value of integer numbers a , b , c and d
- `real_t Arg (complex_t x)`
Return argument of complex number x
- `complex_t Log (complex_t x)`
Return principal determination of logarithm of complex number x
- `template<class T_>`
`T_ Sqr (T_ x)`
Return square of value x
- `template<class T_>`
`void Scale (T_ a, const vector< T_ > &x, vector< T_ > &y)`
Mutiply vector x by a and save result in vector y
- `template<class T_>`
`void Scale (T_ a, const Vect< T_ > &x, Vect< T_ > &y)`
Mutiply vector x by a and save result in vector y
- `template<class T_>`
`void Scale (T_ a, vector< T_ > &x)`
Mutiply vector x by a
- `template<class T_>`
`void Xpy (size_t n, T_ *x, T_ *y)`
Add array x to y
- `template<class T_>`
`void Xpy (const vector< T_ > &x, vector< T_ > &y)`
Add vector x to y
- `template<class T_>`
`void Axy (size_t n, T_ a, T_ *x, T_ *y)`

- Multiply array x by a and add result to y*

 - `template<class T_ >`
`void Axy (T_ a, const vector< T_ > &x, vector< T_ > &y)`
- Multiply vector x by a and add result to y*

 - `template<class T_ >`
`void Axy (T_ a, const Vect< T_ > &x, Vect< T_ > &y)`
- Multiply vector x by a and add result to y*

 - `template<class T_ >`
`void Copy (size_t n, T_ *x, T_ *y)`
- Copy array x to y n is the arrays size.*

 - `real_t Error2 (const vector< real_t > &x, const vector< real_t > &y)`
- Return absolute L2 error between vectors x and y*

 - `real_t RError2 (const vector< real_t > &x, const vector< real_t > &y)`
- Return absolute L^2 error between vectors x and y*

 - `real_t ErrorMax (const vector< real_t > &x, const vector< real_t > &y)`
- Return absolute Max. error between vectors x and y*

 - `real_t RErrorMax (const vector< real_t > &x, const vector< real_t > &y)`
- Return relative Max. error between vectors x and y*

 - `template<class T_ >`
`T_ Dot (size_t n, T_ *x, T_ *y)`
- Return dot product of arrays x and y*

 - `real_t Dot (const vector< real_t > &x, const vector< real_t > &y)`
- Return dot product of vectors x and y .*

 - `real_t operator* (const vector< real_t > &x, const vector< real_t > &y)`
- Operator * (Dot product of 2 vector instances)*

 - `template<class T_ >`
`T_ Dot (const Point< T_ > &x, const Point< T_ > &y)`
- Return dot product of x and y*

 - `real_t exprep (real_t x)`
- Compute the exponential function with avoiding over and underflows.*

 - `template<class T_ >`
`void Assign (vector< T_ > &v, const T_ &a)`
- Assign the value a to all entries of a vector v*

 - `template<class T_ >`
`void clear (vector< T_ > &v)`
- Assign 0 to all entries of a vector.*

 - `template<class T_ >`
`void clear (Vect< T_ > &v)`
- Assign 0 to all entries of a vector.*

 - `real_t Nrm2 (size_t n, real_t *x)`
- Return 2-norm of array x*

 - `real_t Nrm2 (const vector< real_t > &x)`
- Return 2-norm of vector x*

 - `template<class T_ >`
`real_t Nrm2 (const Point< T_ > &a)`
- Return 2-norm of a*

 - `bool Equal (real_t x, real_t y, real_t toler=OFELI.EPSMCH)`
- Function to return true if numbers x and y are close up to a given tolerance $toler$*

- char [itoc](#) (int i)
Function to convert an integer to a character.
- template<class T_>
T_ [stringTo](#) (const std::string &s)
Function to convert a string to a template type parameter.

Variables

- [Node](#) * [theNode](#)
A pointer to [Node](#).
- [Element](#) * [theElement](#)
A pointer to [Element](#).
- [Side](#) * [theSide](#)
A pointer to [Side](#).
- [Edge](#) * [theEdge](#)
A pointer to [Edge](#).
- int [Verbosity](#)
Verbosity parameter.
- int [theStep](#)
Time step counter.
- int [theIteration](#)
Iteration counter.
- int [NbTimeSteps](#)
Number of time steps.
- int [MaxNbIterations](#)
Maximal number of iterations.
- [real.t](#) [theTimeStep](#)
Time step label.
- [real.t](#) [theTime](#)
Time value.
- [real.t](#) [theFinalTime](#)
Final time value.
- [real.t](#) [theTolerance](#)
Tolerance value for convergence.
- [real.t](#) [theDiscrepancy](#)
Value of discrepancy for an iterative procedure Its default value is 1. 0.
- bool [Converged](#)
Boolean variable to say if an iterative procedure has converged.
- bool [InitPetsc](#)

6.1.1 Detailed Description

A namespace to group all library classes, functions, ...

Namespace [OFELI](#) groups all OFELI library classes, functions and global variables.

6.1.2 Enumeration Type Documentation

enum NormType

Choose type of vector norm to compute

Enumerator

NORM1 1-norm

WNORM1 Weighted 1-norm (Discrete L1-Norm)

NORM2 2-norm

WNORM2 Weighted 2-norm (Discrete L2-Norm)

NORM_MAX Max-norm (Infinity norm)


Chapter 7

Class Documentation

7.1 AbsEqua< T_ > Class Template Reference

Mother abstract class to describe equation.

Inheritance diagram for AbsEqua< T_ >:



Public Member Functions

- [AbsEqua](#) ()
Default constructor.
- virtual [~AbsEqua](#) ()
Destructor.
- void [setMesh](#) ([Mesh](#) &m)
Define mesh and renumber DOFs after removing imposed ones.
- [Mesh](#) & [getMesh](#) () const
Return reference to [Mesh](#) instance.
- [LinearSolver](#)< T_ > & [getLinearSolver](#) ()
Return reference to linear solver instance.
- [Matrix](#)< T_ > * [getMatrix](#) () const
Return pointer to matrix.
- void [setSolver](#) ([Iteration](#) ls, [Preconditioner](#) pc=IDENT_PREC)
Choose solver for the linear system.
- void [setLinearSolver](#) ([Iteration](#) ls, [Preconditioner](#) pc=IDENT_PREC)
Choose solver for the linear system.
- void [setMatrixType](#) (int t)
Choose type of matrix.
- int [solveLinearSystem](#) ([Matrix](#)< T_ > *A, [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Solve the linear system with given matrix and right-hand side.
- int [solveLinearSystem](#) ([Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Solve the linear system with given right-hand side.

7.1.1 Detailed Description

template<class T_>class OFELI::AbsEqua< T_ >

Mother abstract class to describe equation.

Template Parameters

<T_>	Data type (real_t, float, complex<real_t>, ...)
------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.1.2 Member Function Documentation

Mesh& getMesh () constReturn reference to [Mesh](#) instance.

Returns

Reference to [Mesh](#) instance**void setSolver (Iteration *ls*, Preconditioner *pc* = IDENT_PREC)**

Choose solver for the linear system.

Parameters

<i>in</i>	<i>ls</i>	<p>Solver of the linear system. To choose among the enumerated values: DIRECT_SOLVER, CG_SOLVER, GMRES_SOLVER</p> <ul style="list-style-type: none"> • DIRECT_SOLVER, Use a facorization solver [default] • CG_SOLVER, Conjugate Gradient iterative solver • CGS_SOLVER, Squared Conjugate Gradient iterative solver • BICG_SOLVER, BiConjugate Gradient iterative solver • BICG_STAB_SOLVER, BiConjugate Gradient Stabilized iterative solver • GMRES_SOLVER, GMRES iterative solver • QMR_SOLVER, QMR iterative solver
-----------	-----------	---

<i>in</i>	<i>pc</i>	<p>Preconditioner to associate to the iterative solver. If the direct solver was chosen for the first argument this argument is not used. Otherwise choose among the enumerated values:</p> <ul style="list-style-type: none"> • IDENT_PREC, Identity preconditioner (no preconditioning [default]) • DIAG_PREC, Diagonal preconditioner • ILU_PREC, Incomplete LU factorization preconditioner
-----------	-----------	--

void setLinearSolver (Iteration *ls*, Preconditioner *pc* = IDENT_PREC)

Choose solver for the linear system.

Parameters

<i>in</i>	<i>ls</i>	<p>Solver of the linear system. To choose among the enumerated values: DIRECT_SOLVER, CG_SOLVER, GMRES_SOLVER</p> <ul style="list-style-type: none"> • DIRECT_SOLVER, Use a facorization solver [default] • CG_SOLVER, Conjugate Gradient iterative solver • CGS_SOLVER, Squared Conjugate Gradient iterative solver • BICG_SOLVER, BiConjugate Gradient iterative solver • BICG_STAB_SOLVER, BiConjugate Gradient Stabilized iterative solver • GMRES_SOLVER, GMRES iterative solver • QMR_SOLVER, QMR iterative solver
-----------	-----------	---

in	<i>pc</i>	Preconditioner to associate to the iterative solver. If the direct solver was chosen for the first argument this argument is not used. Otherwise choose among the enumerated values: <ul style="list-style-type: none"> • IDENT.PREC, Identity preconditioner (no preconditioning [default]) • DIAG.PREC, Diagonal preconditioner • ILU.PREC, Incomplete LU factorization preconditioner
-----------	-----------	---

void setMatrixType (int *t*)

Choose type of matrix.

Parameters

in	<i>t</i>	Type of the used matrix. To choose among the enumerated values: SKYLINE, SPARSE, DIAGONAL TRIDIAGONAL, SYMMETRIC, U↔NSYMMETRIC, IDENTITY
-----------	----------	--

int solveLinearSystem (Matrix< T_ > * *A*, Vect< T_ > & *b*, Vect< T_ > & *x*)

Solve the linear system with given matrix and right-hand side.

Parameters

in	<i>A</i>	Pointer to matrix of the system
in	<i>b</i>	Vector containing right-hand side
in,out	<i>x</i>	Vector containing initial guess of solution on input, actual solution on output

int solveLinearSystem (Vect< T_ > & *b*, Vect< T_ > & *x*)

Solve the linear system with given right-hand side.


Parameters

in	<i>b</i>	Vector containing right-hand side
in,out	<i>x</i>	Vector containing initial guess of solution on input, actual solution on output

7.2 Bar2DL2 Class Reference

To build element equations for Planar Elastic Bar element with 2 DOF (Degrees of Freedom) per node.

Inheritance diagram for Bar2DL2:



Public Member Functions

- **Bar2DL2** ()
Default Constructor.
- **Bar2DL2** (**Mesh** &ms)
*Constructor using a **Mesh** instance.*
- **Bar2DL2** (**Mesh** &ms, **Vect**< **real_t** > &u)
*Constructor using a **Mesh** instance and a solution vector instance.*
- **~Bar2DL2** ()
Destructor.
- void **setSection** (**real_t** A)
Define bar section.
- void **LMass** (**real_t** coef=1)
*Add lumped mass matrix to element matrix after multiplying it by coefficient **coef***
- void **Mass** (**real_t** coef=1)
*Add consistent mass matrix to element matrix after multiplying it by coefficient **coef***
- void **Stiffness** (**real_t** coef=1.)
Add element stiffness to left hand side.
- **real_t** **Stress** () const
Return stresses in bar.
- void **getStresses** (**Vect**< **real_t** > &cs)
Return stresses in the truss structure (elementwise)
- void **build** ()
Build the linear system of equations.

Additional Inherited Members

7.2.1 Detailed Description

To build element equations for Planar Elastic Bar element with 2 DOF (Degrees of Freedom) per node.

This class implements a planar (two-dimensional) elastic bar using 2-node lines. Note that members calculating element arrays have as an argument a **real** **coef** that is multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.2.2 Constructor & Destructor Documentation

Bar2DL2 ()

Default Constructor.

Constructs an empty equation.

Bar2DL2 (Mesh & *ms*)

Constructor using a [Mesh](#) instance.

Parameters

<code>in</code>	<code>ms</code>	Reference Mesh instance
-----------------	-----------------	---

Bar2DL2 (Mesh & *ms*, Vect< real_t > & *u*)

Constructor using a [Mesh](#) instance and a solution vector instance.

Parameters

<code>in</code>	<code>ms</code>	Reference Mesh instance
<code>in, out</code>	<code>u</code>	Reference to solution vector

7.2.3 Member Function Documentation

void LMass (real_t *coef* = 1) [virtual]

Add lumped mass matrix to element matrix after multiplying it by coefficient *coef*

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by added term [Default: 1].
-----------------	-------------------	---

Reimplemented from [Equa.Solid< real_t, 2, 4, 1, 2 >](#).

void Mass (real_t *coef* = 1) [virtual]

Add consistent mass matrix to element matrix after multiplying it by coefficient *coef*

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by added term [Default: 1].
-----------------	-------------------	---

Reimplemented from [Equa.Solid< real_t, 2, 4, 1, 2 >](#).

void Stiffness (real_t *coef* = 1.) [virtual]

Add element stiffness to left hand side.

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by added term [Default: 1].
-----------------	-------------------	---

Reimplemented from [Equa.Solid< real_t, 2, 4, 1, 2 >](#).

void getStresses (Vect< real_t > & *s*)

Return stresses in the truss structure (elementwise)

Parameters

<code>in</code>	<code>s</code>	Vect instance containing axial stresses in elements
-----------------	----------------	---

void build ()

Build the linear system of equations.


Before using this function, one must have properly selected appropriate options for:

- The choice of a steady state or transient analysis
- In the case of transient analysis, the choice of a time integration scheme and a lumped or consistent mass matrix
- The choice of desired linear system solver

7.3 Beam3DL2 Class Reference

To build element equations for 3-D beam equations using 2-node lines.

Inheritance diagram for Beam3DL2:



Public Member Functions

- [Beam3DL2 \(\)](#)
Default Constructor.
- [Beam3DL2 \(Mesh &ms, real_t A, real_t I1, real_t I2\)](#)
Constructor using mesh and constant beam properties.
- [Beam3DL2 \(Mesh &ms\)](#)
Constructor using a [Mesh](#) instance.
- [Beam3DL2 \(Mesh &ms, Vect< real_t > &u\)](#)
Constructor using a [Mesh](#) instance and solution vector.
- [~Beam3DL2 \(\)](#)
Destructor.
- [void set \(real_t A, real_t I1, real_t I2\)](#)
Set constant beam properties.
- [void set \(const Vect< real_t > &A, const Vect< real_t > &I1, const Vect< real_t > &I2\)](#)
Set nonconstant beam properties.
- [void getDisp \(Vect< real_t > &d\)](#)
Get vector of displacements at nodes.
- [void LMass \(real_t coef=1.\)](#)
Add element lumped Mass contribution to element matrix after multiplication by coef
- [void Mass \(real_t coef=1.\)](#)
Add element consistent Mass contribution to RHS after multiplication by coef (not implemented)
- [void Stiffness \(real_t coef=1.\)](#)
Add element stiffness to element matrix.
- [void Load \(const Vect< real_t > &f\)](#)
Add contributions for loads.
- [void setBending \(\)](#)
Set bending contribution to stiffness.
- [void setAxial \(\)](#)
Set axial contribution to stiffness.
- [void setShear \(\)](#)
Set shear contribution to stiffness.

- void [setTorsion](#) ()
Set torsion contribution to stiffness.
- void [setNoBending](#) ()
Set no bending contribution.
- void [setNoAxial](#) ()
Set no axial contribution.
- void [setNoShear](#) ()
Set no shear contribution.
- void [setNoTorsion](#) ()
Set no torsion contribution.
- void [setReducedIntegration](#) ()
Set reduced integration.
- void [AxialForce](#) (Vect< [real_t](#) > &f)
Return axial force in element.
- void [ShearForce](#) (Vect< [real_t](#) > &sh)
Return shear force in element.
- void [BendingMoment](#) (Vect< [real_t](#) > &m)
Return bending moment in element.
- void [TwistingMoment](#) (Vect< [real_t](#) > &m)
Return twisting moments.
- void [build](#) ()
Build the linear system of equations.
- void [buildEigen](#) (SkSMatrix< [real_t](#) > &K, Vect< [real_t](#) > &M)
Build global stiffness and mass matrices for the eigen system.

Additional Inherited Members

7.3.1 Detailed Description

To build element equations for 3-D beam equations using 2-node lines.

This class enables building finite element arrays for 3-D beam elements using 6 degrees of freedom per node and 2-Node line elements.

7.3.2 Constructor & Destructor Documentation

Beam3DL2 (Mesh & *ms*, [real_t](#) *A*, [real_t](#) *I1*, [real_t](#) *I2*)

Constructor using mesh and constant beam properties.

Parameters

in	<i>ms</i>	Mesh instance
in	<i>A</i>	Section area of the beam
in	<i>I1</i>	first (x) momentum of inertia
in	<i>I2</i>	second (y) momentum of inertia

Beam3DL2 (Mesh & *ms*)

Constructor using a [Mesh](#) instance.

Parameters

in	<i>ms</i>	Reference to Mesh instance
----	-----------	--

Beam3DL2 (Mesh & *ms*, Vect< real.t > & *u*)

Constructor using a [Mesh](#) instance and solution vector.

Parameters

in	<i>ms</i>	Reference to Mesh instance
in,out	<i>u</i>	Solution vector

7.3.3 Member Function Documentation

void set (real.t *A*, real.t *I1*, real.t *I2*)

Set constant beam properties.

Parameters

in	<i>A</i>	Section area of the beam
in	<i>I1</i>	first (x) momentum of inertia
in	<i>I2</i>	second (y) momentum of inertia

void set (const Vect< real.t > & *A*, const Vect< real.t > & *I1*, const Vect< real.t > & *I2*)

Set nonconstant beam properties.

Parameters

in	<i>A</i>	Vector containing section areas of the beam (for each element)
in	<i>I1</i>	Vector containing first (x) momentum of inertia (for each element)
in	<i>I2</i>	Vector containing second (y) momentum of inertia (for each element)

void getDisp (Vect< real.t > & *d*)

Get vector of displacements at nodes.

Parameters

out	<i>d</i>	Vector containing three components for each node that are x, y and z displacements.
-----	----------	---

void AxialForce (Vect< real.t > & *f*)

Return axial force in element.

Parameters

out	<i>f</i>	Vector containing axial force in each element. This vector is resized in the function
-----	----------	---

void ShearForce (Vect< real.t > & *sh*)

Return shear force in element.

Parameters

out	sh	Vector containing shear forces (2 components) in each element. This vector is resized in the function
-----	----	---

void BendingMoment (Vect< real.t > & m)

Return bending moment in element.

Parameters

out	m	Vector containing bending moments (2 components) in each element. This vector is resized in the function
-----	---	--

void TwistingMoment (Vect< real.t > & m)

Return twisting moments.

Parameters

out	m	Vector containing twisting moment in each element. This vector is resized in the function
-----	---	---

void buildEigen (SkSMatrix< real.t > & K, Vect< real.t > & M)

Build global stiffness and mass matrices for the eigen system.

Case where the mass matrix is lumped

Parameters

in	K	Stiffness matrix
in	M	Vector containing diagonal mass matrix

7.4 BiotSavart Class Reference

Class to compute the magnetic induction from the current density using the Biot-Savart formula.

Public Member Functions

- [BiotSavart \(\)](#)
Default constructor.
- [BiotSavart \(Mesh &ms\)](#)
Constructor using mesh data.
- [BiotSavart \(Mesh &ms, const Vect< real.t > &J, Vect< real.t > &B, int code=0\)](#)
Constructor using mesh and vector of real current density.
- [BiotSavart \(Mesh &ms, const Vect< complex.t > &J, Vect< complex.t > &B, int code=0\)](#)
Constructor using mesh and vector of complex current density.
- [~BiotSavart \(\)](#)
Destructor.
- void [setCurrentDensity](#) (const Vect< real.t > &J)
Set (real) current density given at elements.
- void [setCurrentDensity](#) (const Vect< complex.t > &J)
Set (real) current density given at elements.

- void `setMagneticInduction` (`Vect< real.t > &B`)
Transmit (real) magnetic induction vector given at nodes.
- void `setMagneticInduction` (`Vect< complex.t > &B`)
Transmit (complex) magnetic induction vector given at nodes.
- void `selectCode` (int code)
Choose code of faces or edges at which current density is given.
- void `setPermeability` (real.t mu)
Set the magnetic permeability coefficient.
- void `setBoundary` ()
Choose to compute the magnetic induction at boundary nodes only.
- `Point< real.t > getB3` (`Point< real.t > x`)
Compute the real magnetic induction at a given point using the volume Biot-Savart formula.
- `Point< real.t > getB2` (`Point< real.t > x`)
Compute the real magnetic induction at a given point using the surface Biot-Savart formula.
- `Point< real.t > getB1` (`Point< real.t > x`)
Compute the real magnetic induction at a given point using the line Biot-Savart formula.
- `Point< complex.t > getBC3` (`Point< real.t > x`)
Compute the complex magnetic induction at a given point using the volume Biot-Savart formula.
- `Point< complex.t > getBC2` (`Point< real.t > x`)
Compute the complex magnetic induction at a given point using the surface Biot-Savart formula.
- `Point< complex.t > getBC1` (`Point< real.t > x`)
Compute the complex magnetic induction at a given point using the line Biot-Savart formula.
- int `run` ()
Run the calculation by the Biot-Savart formula.

7.4.1 Detailed Description

Class to compute the magnetic induction from the current density using the Biot-Savart formula.

Given a current density vector given at elements, a collection of sides of edges (piecewise constant), this class enables computing the magnetic induction vector (continuous and piecewise linear) using the Ampere equation. This magnetic induction is obtained by using the Biot-Savart formula which can be either a volume, surface or line formula depending on the nature of the current density vector.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.4.2 Constructor & Destructor Documentation

BiotSavart (`Mesh & ms`)

Constructor using mesh data.

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
-----------------	-----------------	-------------------------------

BiotSavart (Mesh & *ms*, const Vect< real.t > & *J*, Vect< real.t > & *B*, int *code* = 0)

Constructor using mesh and vector of real current density.

The current density is assumed piecewise constant

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
<code>in</code>	<code>J</code>	Sidewise vector of current density (<i>J</i> is a real valued vector), in the case of a surface supported current
<code>in</code>	<code>B</code>	Nodewise vector that contains, once the member function run is used, the magnetic induction
<code>in</code>	<code>code</code>	Only sides with given <i>code</i> support current [Default: 0]

BiotSavart (Mesh & *ms*, const Vect< complex.t > & *J*, Vect< complex.t > & *B*, int *code* = 0)

Constructor using mesh and vector of complex current density.

The current density is assumed piecewise constant

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
<code>in</code>	<code>J</code>	Sidewise vector of current density (<i>J</i> is a complex valued vector), in the case of a surface supported current
<code>in</code>	<code>B</code>	Nodewise vector that contains, once the member function run is used, the magnetic induction
<code>in</code>	<code>code</code>	Only sides with given <i>code</i> support current [Default: 0]

7.4.3 Member Function Documentation

void setCurrentDensity (const Vect< real.t > & *J*)

Set (real) current density given at elements.

The current density is assumed piecewise constant and real valued. This function can be used in the case of the volume Biot-Savart formula.

Parameters

<code>in</code>	<code>J</code>	Current density vector (Vect instance) and real entries
-----------------	----------------	--

void setCurrentDensity (const Vect< complex.t > & *J*)

Set (real) current density given at elements.

The current density is assumed piecewise constant and complex valued. This function can be used in the case of the volume Biot-Savart formula.

Parameters

<code>in</code>	<code>J</code>	Current density vector (Vect instance) of complex entries
-----------------	----------------	--

void setMagneticInduction (Vect< real.t > & *B*)

Transmit (real) magnetic induction vector given at nodes.

Parameters

out	B	Magnetic induction vector (Vect instance) and real entries
-----	-----	---

void setMagneticInduction (Vect< complex.t > & B)

Transmit (complex) magnetic induction vector given at nodes.

Parameters

out	B	Magnetic induction vector (Vect instance) and complex entries
-----	-----	--

void setPermeability (real.t μ)

Set the magnetic permeability coefficient.

Parameters

in	μ	Magnetic permeability
----	-------	-----------------------

void setBoundary ()

Choose to compute the magnetic induction at boundary nodes only.

By default the magnetic induction is computed (using the function `run`) at all mesh nodes

Note

This function has no effect for surface of line Biot-Savart formula

Point<real.t> getB3 (Point< real.t > x)

Compute the real magnetic induction at a given point using the volume Biot-Savart formula.

This function computes a real valued magnetic induction for a real valued current density field

Parameters

in	x	Coordinates of point at which the magnetic induction is computed
----	-----	--

Returns

Value of the magnetic induction at x

Point<real.t> getB2 (Point< real.t > x)

Compute the real magnetic induction at a given point using the surface Biot-Savart formula.

This function computes a real valued magnetic induction for a real valued current density field

Parameters

in	x	Coordinates of point at which the magnetic induction is computed
----	-----	--

Returns

Value of the magnetic induction at x

Point<real_t> getB1 (Point< real_t > x)

Compute the real magnetic induction at a given point using the line Biot-Savart formula.

This function computes a real valued magnetic induction for a real valued current density field

Parameters

in	x	Coordinates of point at which the magnetic induction is computed
----	-----	--

Returns

Value of the magnetic induction at x

Point<complex_t> getBC3 (Point< real_t > x)

Compute the complex magnetic induction at a given point using the volume Biot-Savart formula.

This function computes a complex valued magnetic induction for a complex valued current density field

Parameters

in	x	Coordinates of point at which the magnetic induction is computed
----	-----	--

Returns

Value of the magnetic induction at x

Point<complex_t> getBC2 (Point< real_t > x)

Compute the complex magnetic induction at a given point using the surface Biot-Savart formula.

This function computes a complex valued magnetic induction for a complex valued current density field

Parameters

in	x	Coordinates of point at which the magnetic induction is computed
----	-----	--

Returns

Value of the magnetic induction at x

Point<complex_t> getBC1 (Point< real_t > x)

Compute the complex magnetic induction at a given point using the line Biot-Savart formula.

This function computes a complex valued magnetic induction for a complex valued current density field

Parameters

in	x	Coordinates of point at which the magnetic induction is computed
----	-----	--

Returns

Value of the magnetic induction at x

int run ()


Run the calculation by the Biot-Savart formula.

This function computes the magnetic induction, which is stored in the vector B given in the constructor

7.5 BMatrix< T_ > Class Template Reference

To handle band matrices.

Inheritance diagram for BMatrix< T_ >:



Public Member Functions

- **BMatrix** ()
Default constructor.
- **BMatrix** (size_t size, int ld, int ud)
Constructor that for a band matrix with given size and bandwidth.
- **BMatrix** (const BMatrix &m)
Copy Constructor.
- **~BMatrix** ()
Destructor.
- void **setSize** (size_t size, int ld, int ud)
Set size (number of rows) and storage of matrix.
- void **MultAdd** (const Vect< T_ > &x, Vect< T_ > &y) const
Multiply matrix by vector x and add result to y
- void **MultAdd** (T_ a, const Vect< T_ > &x, Vect< T_ > &y) const
*Multiply matrix by vector a*x and add result to y*
- void **Mult** (const Vect< T_ > &x, Vect< T_ > &y) const
Multiply matrix by vector x and save result in y
- void **TMult** (const Vect< T_ > &x, Vect< T_ > &y) const
Multiply transpose of matrix by vector x and save result in y
- void **Axpy** (T_ a, const BMatrix< T_ > &x)
Add to matrix the product of a matrix by a scalar.
- void **Axpy** (T_ a, const Matrix< T_ > *x)
Add to matrix the product of a matrix by a scalar.
- void **set** (size_t i, size_t j, const T_ &val)
Add constant val to an entry (i, j) of the matrix.
- void **add** (size_t i, size_t j, const T_ &val)
Add constant val value to an entry (i, j) of the matrix.
- T_ **operator()** (size_t i, size_t j) const
Operator () (Constant version).
- T_ & **operator()** (size_t i, size_t j)

- *Operator () (Non constant version).*
- **BMatrix**< T_ > & **operator=** (const **BMatrix**< T_ > &m)
- *Operator =.*
- **BMatrix**< T_ > & **operator=** (const T_ &x)
- *Operator = Assign matrix to identity times x.*
- **BMatrix**< T_ > & **operator*=** (const T_ &x)
- *Operator *.=.*
- **BMatrix**< T_ > & **operator+=** (const T_ &x)
- *Operator +=.*
- int **setLU** ()
- *Factorize the matrix (LU factorization)*
- int **solve** (**Vect**< T_ > &b, bool fact=false)
- *Solve linear system.*
- int **solve** (const **Vect**< T_ > &b, **Vect**< T_ > &x, bool fact=false)
- *Solve linear system.*
- T_ * **get** () const
- *Return C-Array.*
- T_ **get** (size_t i, size_t j) const
- *Return entry (i, j) of matrix.*

7.5.1 Detailed Description

template<class T_>class OFELI::BMatrix< T_ >

To handle band matrices.

This class enables storing and manipulating band matrices. The matrix can have different numbers of lower and upper co-diagonals

Template Parameters

T_	Data type (double, float, complex<double>, ...)
-----------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.5.2 Constructor & Destructor Documentation

BMatrix ()

Default constructor.

Initialize a zero dimension band matrix

BMatrix (size_t size, int ld, int ud)

Constructor that for a band matrix with given size and bandwidth.

Assign 0 to all matrix entries.

Parameters

in	<i>size</i>	Number of rows and columns
in	<i>ld</i>	Number of lower co-diagonals (must be > 0)
in	<i>ud</i>	Number of upper co-diagonals (must be > 0)

7.5.3 Member Function Documentation

void setSize (size_t size, int ld, int ud)

Set size (number of rows) and storage of matrix.

Parameters

in	<i>size</i>	Number of rows and columns
in	<i>ld</i>	Number of lower co-diagonals (must be > 0)
in	<i>ud</i>	Number of upper co-diagonals (must be > 0)

void Axy (T_ a, const BMatrix< T_ > & x)

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>x</i>	Matrix by which a is multiplied. The result is added to current instance

void Axy (T_ a, const Matrix< T_ > * x) [virtual]

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>x</i>	Matrix by which a is multiplied. The result is added to current instance

Implements [Matrix< T_ >](#).

T_ operator() (size_t i, size_t j) const [virtual]

Operator () (Constant version).

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implements [Matrix< T_ >](#).

T_& operator() (size_t i, size_t j) [virtual]

Operator () (Non constant version).

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implements [Matrix< T_ >](#).

BMatrix<T_>& operator= (const BMatrix< T_ > & m)

Operator =.

Copy matrix m to current matrix instance.

BMatrix<T_>& operator*= (const T_ & x)

Operator *.

Premultiply matrix entries by constant value x

BMatrix<T_>& operator+= (const T_ & x)

Operator +.

Add constant x to matrix entries.

int setLU ()

Factorize the matrix (LU factorization)

LU factorization of the matrix is realized. Note that since this is an in place factorization, the contents of the matrix are modified.

Returns

- 0 if factorization was normally performed,
- n if the n-th pivot is null.

Remarks

A flag in this class indicates after factorization that this one has been realized, so that, if the member function solve is called after this no further factorization is done.

int solve (Vect< T_ > & b, bool fact = false) [virtual]

Solve linear system.

The linear system having the current instance as a matrix is solved by using the LU decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents if a factorization is performed. Naturally, if the matrix has been modified after using this function, the user has to refactorize it using the function setLU. This is because the class has no non-expensive way to detect if the matrix has been modified. The function setLU realizes the factorization step only.

Parameters

in, out	<i>b</i>	Vect instance that contains right-hand side on input and solution on output.
in	<i>fact</i>	Unused argument

Returns

- 0 if solution was normally performed,
- n if the n-th pivot is null.

Implements [Matrix< T_ >](#).

```
int solve ( const Vect< T_ > &b, Vect< T_ > &x, bool fact = false ) [virtual]
```

Solve linear system.

The linear system having the current instance as a matrix is solved by using the LU decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents is a factorization is performed. Naturally, if the the matrix has been modified after using this function, the user has to refactorize it using the function setLU. This is because the class has no non-expensive way to detect if the matrix has been modified. The function setLU realizes the factorization step only.

Parameters

in	<i>b</i>	Vect instance that contains right-hand side.
out	<i>x</i>	Vect instance that contains solution
in	<i>fact</i>	Unused argument

Returns


- 0 if solution was normally performed,
- n if the n-th pivot is null.

Implements [Matrix< T_ >](#).

7.6 Brick Class Reference

To store and treat a brick (parallelepiped) figure.

Inheritance diagram for Brick:



Public Member Functions

- [Brick](#) ()
Default constructor.
- [Brick](#) (const [Point](#)< [real.t](#) > &bbm, const [Point](#)< [real.t](#) > &bbM, int code=1)
Constructor.
- void [setBoundingBox](#) (const [Point](#)< [real.t](#) > &bbm, const [Point](#)< [real.t](#) > &bbM)
Assign bounding box of the brick.
- [Point](#)< [real.t](#) > [getBoundingBox1](#) () const
Return first point of bounding box (xmin,ymin,zmin)
- [Point](#)< [real.t](#) > [getBoundingBox2](#) () const
Return second point of bounding box (xmax,ymax,zmax)
- [real.t](#) [getSignedDistance](#) (const [Point](#)< [real.t](#) > &p) const
Return signed distance of a given point from the current brick.
- [Brick](#) & [operator+=](#) ([Point](#)< [real.t](#) > a)
Operator +=.
- [Brick](#) & [operator+=](#) ([real.t](#) a)
*Operator *+=.*

7.6.1 Detailed Description

To store and treat a brick (parallelepiped) figure.

7.6.2 Constructor & Destructor Documentation

Brick (const Point< real_t > & *bbm*, const Point< real_t > & *bbM*, int *code* = 1)

Constructor.

Parameters

in	<i>bbm</i>	first point (xmin,ymin,zmin)
in	<i>bbM</i>	second point (xmax,ymax,zmax)
in	<i>code</i>	Code to assign to rectangle

7.6.3 Member Function Documentation

void setBoundingBox (const Point< real_t > & *bbm*, const Point< real_t > & *bbM*)

Assign bounding box of the brick.

Parameters

in	<i>bbm</i>	first point (xmin,ymin,zmin)
in	<i>bbM</i>	second point (xmax,ymax,zmax)

real_t getSignedDistance (const Point< real_t > & *p*) const [virtual]

Return signed distance of a given point from the current brick.

The computed distance is negative if *p* lies in the brick, negative if it is outside, and 0 on its boundary

Parameters

in	<i>p</i>	Point<double> instance
----	----------	------------------------

Reimplemented from [Figure](#).

Brick& operator+=(Point< real_t > *a*)

Operator +=.

Translate brick by a vector *a*

Brick& operator+=(real_t *a*)


Operator *+=.

Scale brick by a factor *a*

7.7 Circle Class Reference

To store and treat a circular figure.

Inheritance diagram for Circle:



Public Member Functions

- **Circle** ()
Default constructor.
- **Circle** (const **Point**< **real_t** > &c, **real_t** r, int code=1)
Constructor.
- void **setRadius** (**real_t** r)
Assign radius of circle.
- **real_t** **getRadius** () const
Return radius of circle.
- void **setCenter** (const **Point**< **real_t** > &c)
Assign coordinates of center of circle.
- **Point**< **real_t** > **getCenter** () const
Return coordinates of center of circle.
- **real_t** **getSignedDistance** (const **Point**< **real_t** > &p) const
Return signed distance of a given point from the current circle.
- **Circle** & **operator+=** (**Point**< **real_t** > a)
Operator +=.
- **Circle** & **operator+=** (**real_t** a)
*Operator *+=.*

7.7.1 Detailed Description

To store and treat a circular figure.

7.7.2 Constructor & Destructor Documentation

Circle (const **Point**< **real_t** > & c, **real_t** r, int code = 1)

Constructor.

Parameters

in	<i>c</i>	Coordinates of center of circle
in	<i>r</i>	Radius
in	<i>code</i>	Code to assign to the generated domain [Default: 1]

7.7.3 Member Function Documentation

real_t **getSignedDistance** (const **Point**< **real_t** > & p) const [virtual]

Return signed distance of a given point from the current circle.

The computed distance is negative if p lies in the disk, positive if it is outside, and 0 on the circle

Parameters

in	<i>p</i>	Point<double> instance
----	----------	------------------------

Reimplemented from [Figure](#).

Circle& operator+= (Point< real_t > a)

Operator +=.

Translate circle by a vector a

Circle& operator+= (real_t a)


Operator *.

Scale circle by a factor a

7.8 DC1DL2 Class Reference

Builds finite element arrays for thermal diffusion and convection in 1-D using 2-Node elements.

Inheritance diagram for DC1DL2:



Public Member Functions

- [DC1DL2](#) ()
Default Constructor.
- [DC1DL2](#) (Mesh &ms)
- [DC1DL2](#) (Mesh &ms, Vect< real_t > &u)
- [~DC1DL2](#) ()
Destructor.
- void [LCapacity](#) (real_t coef=1)
Add lumped capacity matrix to element matrix after multiplying it by coefficient coef
- void [Capacity](#) (real_t coef=1)
Add Consistent capacity matrix to element matrix after multiplying it by coefficient coef.
- void [Diffusion](#) (real_t coef=1)
Add diffusion matrix to element matrix after multiplying it by coefficient coef
- void [Convection](#) (const real_t &v, real_t coef=1)
Add convection matrix to element matrix after multiplying it by coefficient coef
- void [Convection](#) (const Vect< real_t > &v, real_t coef=1)
Add convection matrix to element matrix after multiplying it by coefficient coef
- void [Convection](#) (real_t coef=1)

Add convection matrix to element matrix after multiplying it by coefficient `coef`

- void `BodyRHS` (const `Vect< real_t > &f`)

Add body right-hand side term to right hand side.

- `real_t Flux` () const

Return (constant) heat flux in element.

- void `setInput` (EqDataType opt, `Vect< real_t > &u`)

Set equation input data.

Additional Inherited Members

7.8.1 Detailed Description

Builds finite element arrays for thermal diffusion and convection in 1-D using 2-Node elements.

Note that members calculating element arrays have as an argument a real `coef` that will be multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.8.2 Constructor & Destructor Documentation

DC1DL2 ()

Default Constructor.

Constructs an empty equation.

DC1DL2 (Mesh & *ms*)

Constructor using mesh instance

Parameters

<code>in</code>	<code>ms</code>	<code>Mesh</code> instance
-----------------	-----------------	----------------------------

DC1DL2 (Mesh & *ms*, Vect< real_t > & *u*)

Constructor using mesh instance and solution vector

Parameters

<code>in</code>	<code>ms</code>	<code>Mesh</code> instance
<code>in,out</code>	<code>u</code>	<code>Vect</code> instance containing solution vector

7.8.3 Member Function Documentation

void LCapacity (real_t *coef* = 1) [virtual]

Add lumped capacity matrix to element matrix after multiplying it by coefficient `coef`

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by added term [default: 1]
-----------------	-------------------	--

Reimplemented from `Equa.Therm< real_t, 2, 2, 1, 1 >`.

void Capacity (real_t *coef* = 1) [virtual]

Add Consistent capacity matrix to element matrix after multiplying it by coefficient `coef`.

Parameters

in	<i>coef</i>	Coefficient to multiply by added term [default: 1]
-----------	-------------	--

Reimplemented from [Equa.Therm< real.t, 2, 2, 1, 1 >](#).

void Diffusion (real.t coef = 1) [virtual]

Add diffusion matrix to element matrix after multiplying it by coefficient *coef*

Parameters

in	<i>coef</i>	Coefficient to multiply by added term [default: 1]
-----------	-------------	--

Reimplemented from [Equa.Therm< real.t, 2, 2, 1, 1 >](#).

void Convection (const real.t & v, real.t coef = 1)

Add convection matrix to element matrix after multiplying it by coefficient *coef*

Parameters

in	<i>v</i>	Constant velocity vector
in	<i>coef</i>	Coefficient to multiply by added term [default: 1]

void Convection (const Vect< real.t > & v, real.t coef = 1)

Add convection matrix to element matrix after multiplying it by coefficient *coef*

Case where velocity field is given by a vector *v*

Parameters

in	<i>v</i>	Velocity vector
in	<i>coef</i>	Coefficient to multiply by added term [default: 1]

void Convection (real.t coef = 1) [virtual]

Add convection matrix to element matrix after multiplying it by coefficient *coef*

Case where velocity field has been previously defined

Parameters

in	<i>coef</i>	Coefficient to multiply by added term [default: 1]
-----------	-------------	--

Reimplemented from [Equa.Therm< real.t, 2, 2, 1, 1 >](#).

void BodyRHS (const Vect< real.t > & f) [virtual]

Add body right-hand side term to right hand side.

Parameters

in	<i>f</i>	Vector containing source at nodes.
-----------	----------	------------------------------------

Reimplemented from [Equa.Therm< real.t, 2, 2, 1, 1 >](#).

void setInput (EqDataType opt, Vect< real.t > & u)

Set equation input data.


Parameters

in	opt	Parameter that selects data type for input. This parameter is to be chosen in the enumerated variable EqDataType <ul style="list-style-type: none"> INITIAL_FIELD: Initial temperature BOUNDARY_CONDITION_DATA: Boundary condition (Dirichlet) SOURCE_DATA: Heat source FLUX_DATA: Heat flux (Neumann boundary condition) VELOCITY: Velocity vector (for the convection term)
in	u	Vector containing input data

7.9 DC2DT3 Class Reference

Builds finite element arrays for thermal diffusion and convection in 2-D domains using 3-Node triangles.

Inheritance diagram for DC2DT3:



Public Member Functions

- [DC2DT3](#) ()
Default Constructor. Constructs an empty equation.
- [DC2DT3](#) ([Mesh](#) &ms)
Constructor using [Mesh](#) data.
- [DC2DT3](#) ([Mesh](#) &ms, [Vect](#)< [real.t](#) > &u)
Constructor using [Mesh](#) and initial condition.
- [~DC2DT3](#) ()
Destructor.
- void [LCapacity](#) ([real.t](#) coef=1)
*Add lumped capacity matrix to element matrix after multiplying it by coefficient *coef**
- void [Capacity](#) ([real.t](#) coef=1)
*Add Consistent capacity matrix to element matrix after multiplying it by coefficient *coef**
- void [Diffusion](#) ([real.t](#) coef=1)
*Add diffusion matrix to element matrix after multiplying it by coefficient *coef**
- void [Diffusion](#) (const [LocalMatrix](#)< [real.t](#), 2, 2 > &diff, [real.t](#) coef=1)

- Add diffusion matrix to element matrix after multiplying it by coefficient `coef`*
 - void `Convection` (const `Point`< `real_t` > &`v`, `real_t` `coef`=1)
- Add convection matrix to element matrix after multiplying it by coefficient `coef`*
 - void `Convection` (const `Vect`< `real_t` > &`v`, `real_t` `coef`=1)
- Add convection matrix to element matrix after multiplying it by coefficient `coef`*
 - void `Convection` (`real_t` `coef`=1)
- Add convection matrix to element matrix after multiplying it by coefficient `coef`*
 - void `LinearExchange` (`real_t` `coef`, `real_t` `T`)
- Add an edge linear exchange term to left and right-hand sides.*
 - void `BodyRHS` (const `Vect`< `real_t` > &`f`)
- Add body right-hand side term to right hand side.*
 - void `BodyRHS` (`real_t` `f`)
- Add body right-hand side term to right hand side.*
 - void `BoundaryRHS` (`real_t` `flux`)
- Add boundary right-hand side flux to right hand side.*
 - void `BoundaryRHS` (const `Vect`< `real_t` > &`f`)
- Add boundary right-hand side term to right hand side after multiplying it by coefficient `coef`*
 - void `Periodic` (`real_t` `coef`=1.e20)
- Add contribution of periodic boundary condition (by a penalty technique).*
 - `Point`< `real_t` > & `Flux` () const
- Return (constant) heat flux in element.*
 - void `Grad` (`Vect`< `Point`< `real_t` > > &`g`)
- Compute gradient of solution.*
 - `Point`< `real_t` > & `Grad` (const `Vect`< `real_t` > &`u`) const
- Return gradient of a vector in element.*
 - void `setInput` (`EqDataType` `opt`, `Vect`< `real_t` > &`u`)
- Set equation input data.*
 - void `JouleHeating` (const `Vect`< `real_t` > &`sigma`, const `Vect`< `real_t` > &`psi`)
- Set Joule heating term as source.*

Additional Inherited Members

7.9.1 Detailed Description

Builds finite element arrays for thermal diffusion and convection in 2-D domains using 3-Node triangles.

Note that members calculating element arrays have as an argument a `real coef` that will be multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.9.2 Constructor & Destructor Documentation

`DC2DT3 (Mesh & ms)`

Constructor using `Mesh` data.

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
-----------------	-----------------	-------------------------------

DC2DT3 ([Mesh](#) & *ms*, [Vect](#)< `real_t` > & *u*)

Constructor using [Mesh](#) and initial condition.

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
<code>in</code>	<code>u</code>	Vect instance containing initial solution

7.9.3 Member Function Documentation

void LCapacity (`real_t coef = 1`) [virtual]

Add lumped capacity matrix to element matrix after multiplying it by coefficient `coef`

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by added term [Default: 1].
-----------------	-------------------	---

Reimplemented from [Equa_Therm](#)< `real_t`, 3, 3, 2, 2 >.

void Capacity (`real_t coef = 1`) [virtual]

Add Consistent capacity matrix to element matrix after multiplying it by coefficient `coef`

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by added term [Default: 1]
-----------------	-------------------	--

Reimplemented from [Equa_Therm](#)< `real_t`, 3, 3, 2, 2 >.

void Diffusion (`real_t coef = 1`) [virtual]

Add diffusion matrix to element matrix after multiplying it by coefficient `coef`

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by added term [Default: 1]
-----------------	-------------------	--

Reimplemented from [Equa_Therm](#)< `real_t`, 3, 3, 2, 2 >.

void Diffusion (`const LocalMatrix`< `real_t`, 2, 2 > & *diff*, `real_t coef = 1`)

Add diffusion matrix to element matrix after multiplying it by coefficient `coef`

Case where the diffusivity matrix is given as an argument.

Parameters

<code>in</code>	<code>diff</code>	Diffusion matrix (class LocalMatrix).
<code>in</code>	<code>coef</code>	Coefficient to multiply by added term [Default: 1]

void Convection (`const Point`< `real_t` > & *v*, `real_t coef = 1`)

Add convection matrix to element matrix after multiplying it by coefficient `coef`

Parameters

in	v	Constant velocity vector
in	$coef$	Coefficient to multiply by added term [Default: 1]

void Convection (const Vect< real.t > &v, real.t coef = 1)

Add convection matrix to element matrix after multiplying it by coefficient $coef$

Case where velocity field is given by a vector v

Parameters

in	v	Velocity vector
in	$coef$	Coefficient to multiply by added term (Default: 1)

void Convection (real.t coef = 1) [virtual]

Add convection matrix to element matrix after multiplying it by coefficient $coef$

Case where velocity field has been previously defined

Parameters

in	$coef$	Coefficient to multiply by added term [Default: 1]
----	--------	--

Reimplemented from [Equa.Therm< real.t, 3, 3, 2, 2 >](#).

void LinearExchange (real.t coef, real.t T)

Add an edge linear exchange term to left and right-hand sides.

Parameters

in	$coef$	Coefficient of exchange
in	T	External value for exchange

Remarks

This assumes a constant value of T

void BodyRHS (const Vect< real.t > &f) [virtual]

Add body right-hand side term to right hand side.

Parameters

in	f	Vector containing source at nodes.
----	-----	------------------------------------

Reimplemented from [Equa.Therm< real.t, 3, 3, 2, 2 >](#).

void BodyRHS (real.t f)

Add body right-hand side term to right hand side.

Case where the body right-hand side is piecewise constant.

Parameters

in	<i>f</i>	Value of thermal source (Constant in element).
-----------	-----------------	--

void BoundaryRHS (real_t *flux*)

Add boundary right-hand side flux to right hand side.

Parameters

in	<i>flux</i>	Vector containing source at side nodes.
-----------	--------------------	---

void BoundaryRHS (const Vect< real_t > &*f*) [virtual]

Add boundary right-hand side term to right hand side after multiplying it by coefficient *coef*

Parameters

in	<i>f</i>	Vector containing source at nodes
-----------	-----------------	-----------------------------------

Reimplemented from [Equa_Therm< real_t, 3, 3, 2, 2 >](#).

void Periodic (real_t *coef* = 1.e20)

Add contribution of periodic boundary condition (by a penalty technique).

Boundary nodes where periodic boundary conditions are to be imposed must have codes equal to PERIODIC_A on one side and PERIODIC_B on the opposite side.

Parameters

in	<i>coef</i>	Value of penalty parameter [Default: 1.e20]
-----------	--------------------	---

void Grad (Vect< Point< real_t > > &*g*)

Compute gradient of solution.

Parameters

in	<i>g</i>	Elementwise vector containing gradient of solution.
-----------	-----------------	---

Point<real_t>& Grad (const Vect< real_t > &*u*) const

Return gradient of a vector in element.

Parameters

in	<i>u</i>	Global vector for which gradient is computed. Vector <i>u</i> has as size the total number of nodes
-----------	-----------------	---

void setInput (EqDataType *opt*, Vect< real_t > &*u*)

Set equation input data.

Parameters

in	opt	Parameter to select type of input (enumerated values) <ul style="list-style-type: none"> INITIAL_FIELD: Initial temperature BOUNDARY_CONDITION_DATA: Boundary condition (Dirichlet) SOURCE_DATA: Heat source FLUX_DATA: Heat flux (Neumann boundary condition) VELOCITY_FIELD: Velocity vector (for the convection term)
in	u	Vector containing input data

void JouleHeating (const Vect< real_t > & sigma, const Vect< real_t > & psi)

Set Joule heating term as source.


Parameters

in	sigma	Vect instance containing electric conductivity (elementwise)
in	psi	Vect instance containing electric potential (elementwise)

7.10 DC2DT6 Class Reference

Builds finite element arrays for thermal diffusion and convection in 2-D domains using 6-Node triangles.

Inheritance diagram for DC2DT6:



Public Member Functions

- [DC2DT6 \(\)](#)
Default Constructor.
- [DC2DT6 \(Mesh &ms\)](#)
Constructor using Mesh data.
- [DC2DT6 \(Mesh &ms, Vect< real_t > &u\)](#)
Constructor using Mesh data and solution vector.
- [~DC2DT6 \(\)](#)
Destructor.
- void [LCapacity \(real_t coef=1\)](#)

- *Add lumped capacity matrix to element matrix after multiplying it by coefficient `coef`.*
 • void [Capacity](#) ([real_t](#) coef=1)
- *Add Consistent capacity matrix to element matrix after multiplying it by coefficient `coef`.*
 • void [Diffusion](#) ([real_t](#) coef=1)
- *Add diffusion matrix to element matrix after multiplying it by coefficient `coef`*
 • void [Convection](#) ([real_t](#) coef=1)
- *Add convection matrix to left-hand side after multiplying it by coefficient `coef`*
 • void [Convection](#) ([Point](#)< [real_t](#) > &[v](#), [real_t](#) coef=1)
- *Add convection matrix to left hand side after multiplying it by coefficient `coef`*
 • void [Convection](#) (const [Vect](#)< [real_t](#) > &[v](#), [real_t](#) coef=1)
- *Add convection matrix to left-hand side after multiplying it by coefficient `coef`*
 • void [BodyRHS](#) (const [Vect](#)< [real_t](#) > &[f](#))
- *Add body right-hand side term to right hand side.*
 • void [BoundaryRHS](#) (const [Vect](#)< [real_t](#) > &[f](#))
- *Add boundary right-hand side term to right hand side after multiplying it by coefficient `coef`*

Additional Inherited Members

7.10.1 Detailed Description

Builds finite element arrays for thermal diffusion and convection in 2-D domains using 6-Node triangles.

Note that members calculating element arrays have as an argument a real `coef` that will be multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.10.2 Constructor & Destructor Documentation

DC2DT6 ()

Default Constructor.

Constructs an empty equation.

DC2DT6 ([Mesh](#) & *ms*)

Constructor using [Mesh](#) data.

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
-----------------	-----------------	-------------------------------

DC2DT6 ([Mesh](#) & *ms*, [Vect](#)< [real_t](#) > &*u*)

Constructor using [Mesh](#) data and solution vector.

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
<code>in,out</code>	<code>u</code>	Vect instance containing solution vector

7.10.3 Member Function Documentation

void [LCapacity](#) ([real_t](#) *coef* = 1) [virtual]

Add lumped capacity matrix to element matrix after multiplying it by coefficient `coef`.

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term (default value = 1).
-----------	-------------	--

Reimplemented from [Equa.Therm< real.t, 6, 6, 3, 3 >](#).

void Capacity (real.t coef = 1) [virtual]

Add Consistent capacity matrix to element matrix after multiplying it by coefficient *coef*.

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term (default value = 1).
-----------	-------------	--

Reimplemented from [Equa.Therm< real.t, 6, 6, 3, 3 >](#).

void Diffusion (real.t coef = 1) [virtual]

Add diffusion matrix to element matrix after multiplying it by coefficient *coef*

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Therm< real.t, 6, 6, 3, 3 >](#).

void Convection (real.t coef = 1) [virtual]

Add convection matrix to left-hand side after multiplying it by coefficient *coef*

Case where velocity field has been previously defined

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Therm< real.t, 6, 6, 3, 3 >](#).

void Convection (Point< real.t > &v, real.t coef = 1)

Add convection matrix to left hand side after multiplying it by coefficient *coef*

Parameters

<i>in</i>	<i>v</i>	Constant velocity vector.
<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].

void Convection (const Vect< real.t > &v, real.t coef = 1)

Add convection matrix to left-hand side after multiplying it by coefficient *coef*

Case where velocity field is given by a vector *v*

Parameters

<i>in</i>	<i>v</i>	Velocity vector.
<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].

void BodyRHS (const Vect< real.t > &f) [virtual]

Add body right-hand side term to right hand side.

Parameters

in	<i>f</i>	Local vector (of size 6) containing source at nodes
----	----------	---

Reimplemented from [Equa_Therm< real_t, 6, 6, 3, 3 >](#).

void BoundaryRHS (const Vect< real_t > &*f*) [virtual]

Add boundary right-hand side term to right hand side after multiplying it by coefficient *coef*

Parameters


in	<i>f</i>	Vector containing source at nodes
----	----------	-----------------------------------

Reimplemented from [Equa_Therm< real_t, 6, 6, 3, 3 >](#).

7.11 DC3DAT3 Class Reference

Builds finite element arrays for thermal diffusion and convection in 3-D domains with axisymmetry using 3-Node triangles.

Inheritance diagram for DC3DAT3:



Public Member Functions

- [DC3DAT3 \(\)](#)
Default Constructor.
- [DC3DAT3 \(Mesh &ms\)](#)
Constructor using Mesh data.
- [DC3DAT3 \(Mesh &ms, Vect< real_t > &u\)](#)
Constructor using Mesh data and solution vector.
- [~DC3DAT3 \(\)](#)
Destructor.
- **void LCapacity (real_t coef=1)**
Add lumped capacity matrix to element matrix after multiplying it by coefficient coef.
- **void Capacity (real_t coef=1)**
Add Consistent capacity matrix to element matrix after multiplying it by coefficient coef
- **void Diffusion (real_t coef=1)**
Add diffusion matrix to left-hand side after multiplying it by coefficient coef
- **void Diffusion (const LocalMatrix< real_t, 2, 2 > &diff, real_t coef=1)**
Add diffusion matrix to left-hand side after multiplying it by coefficient coef
- **void BodyRHS (const Vect< real_t > &f)**
Add body right-hand side term to right hand side.

- void [BoundaryRHS](#) ([real.t](#) flux)
Add boundary right-hand side term to right hand side.
- void [BoundaryRHS](#) (const [Vect](#)< [real.t](#) > &f)
*Add boundary right-hand side term to right hand side after multiplying it by coefficient *coef**
- [Point](#)< [real.t](#) > & [Grad](#) (const [Vect](#)< [real.t](#) > &u)
Return gradient of a vector in element.

Additional Inherited Members

7.11.1 Detailed Description

Builds finite element arrays for thermal diffusion and convection in 3-D domains with axisymmetry using 3-Node triangles.

Note that members calculating element arrays have as an argument a real *coef* that will be multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.11.2 Constructor & Destructor Documentation

DC3DAT3 ()

Default Constructor.

Constructs an empty equation.

DC3DAT3 ([Mesh](#) & *ms*)

Constructor using [Mesh](#) data.

Parameters

<i>in</i>	<i>ms</i>	Mesh instance
-----------	-----------	-------------------------------

DC3DAT3 ([Mesh](#) & *ms*, [Vect](#)< [real.t](#) > & *u*)

Constructor using [Mesh](#) data and solution vector.

Parameters

<i>in</i>	<i>ms</i>	Mesh instance
<i>in,out</i>	<i>u</i>	Vect instance containing solution vector

7.11.3 Member Function Documentation

void [LCapacity](#) ([real.t](#) *coef* = 1) [virtual]

Add lumped capacity matrix to element matrix after multiplying it by coefficient *coef*.

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa_Therm](#)< [real.t](#), 3, 3, 2, 2 >.

void [Capacity](#) ([real.t](#) *coef* = 1) [virtual]

Add Consistent capacity matrix to element matrix after multiplying it by coefficient *coef*

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Therm< real.t, 3, 3, 2, 2 >](#).

void Diffusion (real.t coef = 1) [virtual]

Add diffusion matrix to left-hand side after multiplying it by coefficient *coef*

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Therm< real.t, 3, 3, 2, 2 >](#).

void Diffusion (const LocalMatrix< real.t, 2, 2 > &diff, real.t coef = 1)

Add diffusion matrix to left-hand side after multiplying it by coefficient *coef*

Case where the diffusivity matrix is given as an argument

Parameters

<i>in</i>	<i>diff</i>	Instance of class DMatrix containing diffusivity matrix
<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1]

void BodyRHS (const Vect< real.t > &f) [virtual]

Add body right-hand side term to right hand side.

Parameters

<i>in</i>	<i>f</i>	Local vector (of size 3) containing source at odes.
-----------	----------	---

Reimplemented from [Equa.Therm< real.t, 3, 3, 2, 2 >](#).

void BoundaryRHS (real.t flux)

Add boundary right-hand side term to right hand side.

Parameters

<i>in</i>	<i>flux</i>	Value of flux to impose on the side
-----------	-------------	-------------------------------------

void BoundaryRHS (const Vect< real.t > &f) [virtual]

Add boundary right-hand side term to right hand side after multiplying it by coefficient *coef*

Parameters

<i>in</i>	<i>f</i>	Vector containing source at nodes
-----------	----------	-----------------------------------

Reimplemented from [Equa.Therm< real.t, 3, 3, 2, 2 >](#).

Point<real.t>& Grad (const Vect< real.t > &u)

Return gradient of a vector in element.


Parameters

<i>in</i>	<i>u</i>	Vector for which gradient is computed.
-----------	----------	--

7.12 DC3DT4 Class Reference

Builds finite element arrays for thermal diffusion and convection in 3-D domains using 4-Node tetrahedra.

Inheritance diagram for DC3DT4:



Public Member Functions

- **DC3DT4** ()
Default Constructor.
- **DC3DT4** (Mesh &ms)
*Constructor using *Mesh* data.*
- **DC3DT4** (Mesh &ms, Vect< real_t > &u)
*Constructor using *Mesh* and initial condition.*
- **~DC3DT4** ()
Destructor.
- void **LCapacity** (real_t coef=1)
*Add lumped capacity matrix to element matrix after multiplying it by coefficient *coef**
- void **Capacity** (real_t coef=1)
*Add consistent capacity matrix to element matrix after multiplying it by coefficient *coef**
- void **Diffusion** (real_t coef=1)
*Add diffusion matrix to element matrix after multiplying it by coefficient *coef*.*
- void **Diffusion** (const DMatrix< real_t > &diff, real_t coef=1)
*Add diffusion matrix to element matrix after multiplying it by coefficient *coef**
- void **Convection** (real_t coef=1)
*Add convection matrix to element matrix after multiplying it by coefficient *coef**
- void **Convection** (const Point< real_t > &v, real_t coef=1)
*Add convection matrix to element matrix after multiplying it by coefficient *coef**
- void **Convection** (const Vect< Point< real_t > > &v, real_t coef=1)
*Add convection matrix to element matrix after multiplying it by coefficient *coef**
- void **BodyRHS** (const Vect< real_t > &f)
Add body right-hand side term to right hand side.
- void **BoundaryRHS** (const Vect< real_t > &f)
*Add boundary right-hand side term to right hand side after multiplying it by coefficient *coef**
- void **BoundaryRHS** (real_t flux)
Add boundary right-hand side flux to right hand side.
- **Point< real_t > Flux** () const

Return (constant) heat flux in element.

- void **Grad** (**Vect**< **Point**< **real.t** > > &g)

Compute gradient of solution.

- void **Periodic** (**real.t** coef=1.e20)

Add contribution of periodic boundary condition (by a penalty technique).

Additional Inherited Members

7.12.1 Detailed Description

Builds finite element arrays for thermal diffusion and convection in 3-D domains using 4-Node tetrahedra.

Note that members calculating element arrays have as an argument a real coef that will be multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.12.2 Constructor & Destructor Documentation

DC3DT4 ()

Default Constructor.

Constructs an empty equation.

DC3DT4 (**Mesh** & *ms*)

Constructor using **Mesh** data.

Parameters

in	<i>ms</i>	Mesh instance
-----------	-----------	----------------------

DC3DT4 (**Mesh** & *ms*, **Vect**< **real.t** > & *u*)

Constructor using **Mesh** and initial condition.

Parameters

in	<i>ms</i>	Mesh instance
in	<i>u</i>	Vect instance containing initial solution

7.12.3 Member Function Documentation

void **LCapacity** (**real.t** *coef* = 1) [virtual]

Add lumped capacity matrix to element matrix after multiplying it by coefficient coef

Parameters

in	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from **Equa.Therm**< **real.t**, 4, 4, 3, 3 >.

void **Capacity** (**real.t** *coef* = 1) [virtual]

Add consistent capacity matrix to element matrix after multiplying it by coefficient coef

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Therm< real.t, 4, 4, 3, 3 >](#).

void Diffusion (real.t coef = 1) [virtual]

Add diffusion matrix to element matrix after multiplying it by coefficient *coef*.

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term (default value = 1).
-----------	-------------	--

Reimplemented from [Equa.Therm< real.t, 4, 4, 3, 3 >](#).

void Diffusion (const DMatrix< real.t > & diff, real.t coef = 1)

Add diffusion matrix to element matrix after multiplying it by coefficient *coef*

Case where the diffusivity matrix is given as an argument.

Parameters

<i>in</i>	<i>diff</i>	Diffusion matrix (class DMatrix).
<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].

void Convection (real.t coef = 1) [virtual]

Add convection matrix to element matrix after multiplying it by coefficient *coef*

Case where velocity field has been previously defined

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Therm< real.t, 4, 4, 3, 3 >](#).

void Convection (const Point< real.t > & v, real.t coef = 1)

Add convection matrix to element matrix after multiplying it by coefficient *coef*

Parameters

<i>in</i>	<i>v</i>	Constant velocity vector
<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].

void Convection (const Vect< Point< real.t > > & v, real.t coef = 1)

Add convection matrix to element matrix after multiplying it by coefficient *coef*

Case where velocity field is given by a vector *v*.

Parameters

<i>in</i>	<i>v</i>	Velocity vector.
<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].

void BodyRHS (const Vect< real.t > & f) [virtual]

Add body right-hand side term to right hand side.

Parameters

<i>in</i>	<i>f</i>	Vector containing source at nodes.
-----------	----------	------------------------------------

Reimplemented from [Equa.Therm< real_t, 4, 4, 3, 3 >](#).

void BoundaryRHS (const Vect< real_t > &*f*) [virtual]

Add boundary right-hand side term to right hand side after multiplying it by coefficient *coef*

Case where body source is given by a vector

Parameters

<i>in</i>	<i>f</i>	Vector containing source at nodes.
-----------	----------	------------------------------------

Reimplemented from [Equa.Therm< real_t, 4, 4, 3, 3 >](#).

void BoundaryRHS (real_t *flux*)

Add boundary right-hand side flux to right hand side.

Parameters

<i>in</i>	<i>flux</i>	Vector containing source at side nodes.
-----------	-------------	---

void Grad (Vect< Point< real_t > > &*g*)

Compute gradient of solution.

Parameters

<i>in</i>	<i>g</i>	Elementwise vector containing gradient of solution.
-----------	----------	---

void Periodic (real_t *coef* = 1 . e20)

Add contribution of periodic boundary condition (by a penalty technique).

Boundary nodes where periodic boundary conditions are to be imposed must have codes equal to PERIODIC.A on one side and PERIODIC.B on the opposite side.


Parameters

<i>in</i>	<i>coef</i>	Value of penalty parameter [Default: 1 . e20].
-----------	-------------	--

7.13 DG Class Reference

Enables preliminary operations and utilities for the Discontinuous Galerkin method.

Inheritance diagram for DG:



Public Member Functions

- [DG](#) ([Mesh](#) &ms, size_t degree=1)
Constructor with mesh and degree of the method.
- [~DG](#) ()
Destructor.
- int [setGraph](#) ()
Set matrix graph.

7.13.1 Detailed Description

Enables preliminary operations and utilities for the Discontinuous Galerkin method.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.13.2 Constructor & Destructor Documentation

DG ([Mesh](#) & *ms*, size_t *degree* = 1)

Constructor with mesh and degree of the method.


Parameters

in	<i>ms</i>	Mesh instance
in	<i>degree</i>	Polynomial degree of the DG method [Default: 1]

7.14 DMatrix< T_ > Class Template Reference

To handle dense matrices.

Inheritance diagram for DMatrix< T_ >:



Public Member Functions

- [DMatrix](#) ()
Default constructor.
- [DMatrix](#) (size_t nr)
*Constructor for a matrix with **nr** rows and **nr** columns.*
- [DMatrix](#) (size_t nr, size_t nc)
*Constructor for a matrix with **nr** rows and **nc** columns.*
- [DMatrix](#) ([Vect](#)< T_ > &v)

- Constructor that uses a [Vect](#) instance. The class uses the memory space occupied by this vector.

 - [DMatrix](#) (const [DMatrix](#)< T_ > &m)

Copy Constructor.
- [DMatrix](#) ([Mesh](#) &mesh, size_t dof=0, int is_diagonal=false)

Constructor using mesh to initialize structure of matrix.
- [~DMatrix](#) ()

Destructor.
- void [setDiag](#) ()

Store diagonal entries in a separate internal vector.
- void [setDiag](#) (const T_ &a)

Set matrix as diagonal and assign its diagonal entries as a constant.
- void [setDiag](#) (const vector< T_ > &d)

Set matrix as diagonal and assign its diagonal entries.
- void [setSize](#) (size_t size)

Set size (number of rows) of matrix.
- void [setSize](#) (size_t nr, size_t nc)

Set size (number of rows and columns) of matrix.
- void [getColumn](#) (size_t j, [Vect](#)< T_ > &v) const

Get j-th column vector.
- [Vect](#)< T_ > [getColumn](#) (size_t j) const

Get j-th column vector.
- void [getRow](#) (size_t i, [Vect](#)< T_ > &v) const

Get i-th row vector.
- [Vect](#)< T_ > [getRow](#) (size_t i) const

Get i-th row vector.
- void [set](#) (size_t i, size_t j, const T_ &val)

Assign a constant value to an entry of the matrix.
- void [reset](#) ()

Set matrix to 0 and reset factorization parameter.
- void [setRow](#) (size_t i, const [Vect](#)< T_ > &v)

Copy a given vector to a prescribed row in the matrix.
- void [setColumn](#) (size_t j, const [Vect](#)< T_ > &v)

Copy a given vector to a prescribed column in the matrix.
- void [MultAdd](#) (T_ a, const [Vect](#)< T_ > &x, [Vect](#)< T_ > &y) const

Multiply matrix by vector $a*x$ and add result to y .
- void [MultAdd](#) (const [Vect](#)< T_ > &x, [Vect](#)< T_ > &y) const

Multiply matrix by vector x and add result to y .
- void [Mult](#) (const [Vect](#)< T_ > &x, [Vect](#)< T_ > &y) const

Multiply matrix by vector x and save result in y .
- void [TMult](#) (const [Vect](#)< T_ > &x, [Vect](#)< T_ > &y) const

Multiply transpose of matrix by vector x and add result in y .
- void [add](#) (size_t i, size_t j, const T_ &val)

Add constant val to entry (i, j) of the matrix.
- void [Axy](#) (T_ a, const [DMatrix](#)< T_ > &m)

Add to matrix the product of a matrix by a scalar.
- void [Axy](#) (T_ a, const [Matrix](#)< T_ > *m)

- Add to matrix the product of a matrix by a scalar.*

 - `int setQR ()`
Construct a QR factorization of the matrix.
 - `int setTransQR ()`
Construct a QR factorization of the transpose of the matrix.
 - `int solveQR (const Vect< T_ > &b, Vect< T_ > &x)`
Solve a linear system by QR decomposition.
 - `int solveTransQR (const Vect< T_ > &b, Vect< T_ > &x)`
Solve a transpose linear system by QR decomposition.
 - `T_ operator() (size_t i, size_t j) const`
Operator () (Constant version). Return $a(i, j)$
 - `T_ & operator() (size_t i, size_t j)`
Operator () (Non constant version). Return $a(i, j)$
 - `int setLU ()`
Factorize the matrix (LU factorization)
 - `int setTransLU ()`
Factorize the transpose of the matrix (LU factorization)
 - `int solve (Vect< T_ > &b, bool fact=true)`
Solve linear system.
 - `int solveTrans (Vect< T_ > &b, bool fact=true)`
Solve the transpose linear system.
 - `int solve (const Vect< T_ > &b, Vect< T_ > &x, bool fact=true)`
Solve linear system.
 - `int solveTrans (const Vect< T_ > &b, Vect< T_ > &x, bool fact=true)`
Solve the transpose linear system.
 - `DMatrix & operator= (DMatrix< T_ > &m)`
Operator =
 - `DMatrix & operator+= (const DMatrix< T_ > &m)`
Operator +=.
 - `DMatrix & operator-= (const DMatrix< T_ > &m)`
Operator -=.
 - `DMatrix & operator= (const T_ &x)`
Operator =
 - `DMatrix & operator*= (const T_ &x)`
*Operator *=*
 - `DMatrix & operator+= (const T_ &x)`
Operator +=
 - `DMatrix & operator-= (const T_ &x)`
Operator -=
 - `T_ * getArray () const`
Return matrix as C-Array.
 - `T_ get (size_t i, size_t j) const`
Return entry (i, j) of matrix.

7.14.1 Detailed Description

template<class T_>class OFELI::DMatrix< T_ >

To handle dense matrices.

This class enables storing and manipulating general dense matrices. Matrices can be square or rectangle ones.

Template Parameters

<i>T_</i>	Data type (double, float, complex<double>, ...)
-----------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.14.2 Constructor & Destructor Documentation

DMatrix ()

Default constructor.

Initializes a zero-dimension matrix.

DMatrix (size_t nr)

Constructor for a matrix with nr rows and nr columns.

Matrix entries are set to 0.

DMatrix (size_t nr, size_t nc)

Constructor for a matrix with nr rows and nc columns.

[Matrix](#) entries are set to 0.**DMatrix (Vect< T_ > & v)**Constructor that uses a [Vect](#) instance. The class uses the memory space occupied by this vector.

Parameters

<i>in</i>	<i>v</i>	Vector to copy
-----------	----------	----------------

DMatrix (const DMatrix< T_ > & m)

Copy Constructor.

Parameters

<i>in</i>	<i>m</i>	Matrix to copy
-----------	----------	----------------

DMatrix (Mesh & mesh, size_t dof = 0, int is_diagonal = false)

Constructor using mesh to initialize structure of matrix.

Parameters

<i>in</i>	<i>mesh</i>	Mesh instance for which matrix graph is determined.
<i>in</i>	<i>dof</i>	Option parameter, with default value 0. dof=1 means that only one degree of freedom for each node (or element or side) is taken to determine matrix structure. The value dof=0 means that matrix structure is determined using all DOFs.
<i>in</i>	<i>is_diagonal</i>	Boolean argument to say is the matrix is actually a diagonal matrix or not.

7.14.3 Member Function Documentation

void setDiag (const T_ & *a*)

Set matrix as diagonal and assign its diagonal entries as a constant.

Parameters

in	<i>a</i>	Value to assign to all diagonal entries
-----------	----------	---

void setDiag (const vector< T_ > & d)

Set matrix as diagonal and assign its diagonal entries.

Parameters

in	<i>d</i>	Vector entries to assign to matrix diagonal entries
-----------	----------	---

void setSize (size_t size)

Set size (number of rows) of matrix.

Parameters

in	<i>size</i>	Number of rows and columns.
-----------	-------------	-----------------------------

void setSize (size_t nr, size_t nc)

Set size (number of rows and columns) of matrix.

Parameters

in	<i>nr</i>	Number of rows.
in	<i>nc</i>	Number of columns.

void getColumn (size_t j, Vect< T_ > & v) const

Get j-th column vector.

Parameters

in	<i>j</i>	Index of column to extract
out	<i>v</i>	Reference to Vect instance where the column is stored

Remarks

Vector v does not need to be sized before. It is resized in the function

Vect<T_> getColumn (size_t j) const

Get j-th column vector.

Parameters

in	<i>j</i>	Index of column to extract
-----------	----------	----------------------------

Returns

[Vect](#) instance where the column is stored

Remarks

Vector v does not need to be sized before. It is resized in the function

void getRow (size_t i, Vect< T_ > & v) const

Get i-th row vector.

Parameters

in	<i>i</i>	Index of row to extract
out	<i>v</i>	Reference to Vect instance where the row is stored

Remarks

Vector *v* does not need to be sized before. It is resized in the function

Vect<T_> getRow (size_t *i*) const

Get *i*-th row vector.

Parameters

in	<i>i</i>	Index of row to extract
----	----------	-------------------------

Returns

[Vect](#) instance where the row is stored

Remarks

Vector *v* does not need to be sized before. It is resized in the function

void set (size_t *i*, size_t *j*, const T_ & *val*) [virtual]

Assign a constant value to an entry of the matrix.

Parameters

in	<i>i</i>	row index of matrix
in	<i>j</i>	column index of matrix
in	<i>val</i>	Value to assign to <i>a</i> (<i>i</i> , <i>j</i>).

Implements [Matrix< T_ >](#).

void reset () [virtual]

Set matrix to 0 and reset factorization parameter.

Warning

This function must be used if after a factorization, the matrix has modified

Reimplemented from [Matrix< T_ >](#).

void setRow (size_t *i*, const Vect< T_ > & *v*)

Copy a given vector to a prescribed row in the matrix.

Parameters

in	<i>i</i>	row index to be assigned
in	<i>v</i>	Vect instance to copy

void setColumn (size_t *j*, const Vect< T_ > & *v*)

Copy a given vector to a prescribed column in the matrix.

Parameters

in	<i>j</i>	column index to be assigned
in	<i>v</i>	Vect instance to copy

void MultAdd (T_ *a*, const Vect< T_ > & *x*, Vect< T_ > & *y*) const [virtual]

Multiply matrix by vector *a***x* and add result to *y*.

Parameters

in	<i>a</i>	constant to multiply by
in	<i>x</i>	Vector to multiply by <i>a</i>
in,out	<i>y</i>	on input, vector to add to. On output, result.

Implements [Matrix< T_ >](#).

void MultAdd (const Vect< T_ > & *x*, Vect< T_ > & *y*) const [virtual]

Multiply matrix by vector *x* and add result to *y*.

Parameters

in	<i>x</i>	Vector to add to <i>y</i>
in,out	<i>y</i>	on input, vector to add to. On output, result.

Implements [Matrix< T_ >](#).

void Mult (const Vect< T_ > & *x*, Vect< T_ > & *y*) const [virtual]

Multiply matrix by vector *x* and save result in *y*.

Parameters

in	<i>x</i>	Vector to add to <i>y</i>
out	<i>y</i>	Result.

Implements [Matrix< T_ >](#).

void TMult (const Vect< T_ > & *x*, Vect< T_ > & *y*) const [virtual]

Multiply transpose of matrix by vector *x* and add result in *y*.

Parameters

in	<i>x</i>	Vector to add to <i>y</i>
in,out	<i>y</i>	on input, vector to add to. On output, result.

Implements [Matrix< T_ >](#).

void add (size_t *i*, size_t *j*, const T_ & *val*) [virtual]

Add constant *val* to entry (*i*,*j*) of the matrix.

Parameters

in	<i>i</i>	row index
in	<i>j</i>	column index
in	<i>val</i>	Constant to add

Implements [Matrix< T_ >](#).

void Apy (T_ *a*, const DMatrix< T_ > & *m*)

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which <i>a</i> is multiplied. The result is added to current instance

void Apxy (T_ *a*, const Matrix< T_ > * *m*) [virtual]

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which <i>a</i> is multiplied. The result is added to current instance

Implements [Matrix< T_ >](#).

int setQR ()

Construct a QR factorization of the matrix.

This function constructs the QR decomposition using the Householder method. The upper triangular matrix R is returned in the upper triangle of the current matrix, except for the diagonal elements of R which are stored in an internal vector. The orthogonal matrix Q is represented as a product of $n-1$ Householder matrices $Q_1 \dots Q_{n-1}$, where $Q_j = 1 - u_j u_j / c_j$. The i -th component of u_j is zero for $i = 1, \dots, j-1$ while the nonzero components are returned in $a[i][j]$ for $i = j, \dots, n$.

Returns

0 if the decomposition was successful, k is the k -th row is singular

Remarks

The matrix can be square or rectangle

int setTransQR ()

Construct a QR factorization of the transpose of the matrix.

This function constructs the QR decomposition using the Householder method. The upper triangular matrix R is returned in the upper triangle of the current matrix, except for the diagonal elements of R which are stored in an internal vector. The orthogonal matrix Q is represented as a product of $n-1$ Householder matrices $Q_1 \dots Q_{n-1}$, where $Q_j = 1 - u_j u_j / c_j$. The i -th component of u_j is zero for $i = 1, \dots, j-1$ while the nonzero components are returned in $a[i][j]$ for $i = j, \dots, n$.

Returns

0 if the decomposition was successful, k is the k -th row is singular

Remarks

The matrix can be square or rectangle

int solveQR (const Vect< T_ > & *b*, Vect< T_ > & *x*)

Solve a linear system by QR decomposition.

This function constructs the QR decomposition, if this was not already done by using the member function QR and solves the linear system

Parameters

in	b	Right-hand side vector
out	x	Solution vector. Must have been sized before using this function.

Returns

The same value as returned by the function QR

int solveTransQR (const Vect< T_ > & b , Vect< T_ > & x)

Solve a transpose linear system by QR decomposition.

This function constructs the QR decomposition, if this was not already done by using the member function QR and solves the linear system

Parameters

in	b	Right-hand side vector
out	x	Solution vector. Must have been sized before using this function.

Returns

The same value as returned by the function QR

T_ operator() (size_t i , size_t j) const [virtual]

Operator () (Constant version). Return $a(i, j)$

Parameters

in	i	row index
in	j	column index

Implements [Matrix< T_ >](#).

T_& operator() (size_t i , size_t j) [virtual]

Operator () (Non constant version). Return $a(i, j)$

Parameters

in	i	row index
in	j	column index

Implements [Matrix< T_ >](#).

int setLU ()

Factorize the matrix (LU factorization)

LU factorization of the matrix is realized. Note that since this is an in place factorization, the contents of the matrix are modified.

Returns

- 0 if factorization was normally performed,
- n if the n -th pivot is null.

Remarks

A flag in this class indicates after factorization that this one has been realized, so that, if the member function solve is called after this no further factorization is done.

int setTransLU ()

Factorize the transpose of the matrix (LU factorization)

LU factorization of the transpose of the matrix is realized. Note that since this is an in place factorization, the contents of the matrix are modified.

Returns

- 0 if factorization was normally performed,
- n if the n-th pivot is null.

Remarks

A flag in this class indicates after factorization that this one has been realized, so that, if the member function solve is called after this no further factorization is done.

int solve (Vect< T_ > & b, bool fact = true) [virtual]

Solve linear system.

The linear system having the current instance as a matrix is solved by using the LU decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents is a factorization is performed. Naturally, if the the matrix has been modified after using this function, the user has to refactorize it using the function setLU. This is because the class has no non-expensive way to detect if the matrix has been modified. The function setLU realizes the factorization step only.

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side on input and solution on output.
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- n if the n-th pivot is null.

Implements [Matrix< T_ >](#).

int solveTrans (Vect< T_ > & b, bool fact = true)

Solve the transpose linear system.

The linear system having the current instance as a transpose matrix is solved by using the LU decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents is a factorization is performed. Naturally, if the the matrix has been modified after using this function, the user has to refactorize it using the function setLU. This is because the class has no non-expensive way to detect if the matrix has been modified. The function setLU realizes the factorization step only.

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side on input and solution on output.
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- *n* if the *n*-th pivot is null.

int solve (const Vect< T_ > & *b*, Vect< T_ > & *x*, bool *fact* = *true*) [virtual]

Solve linear system.

The linear system having the current instance as a matrix is solved by using the LU decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents if a factorization is performed. Naturally, if the matrix has been modified after using this function, the user has to refactorize it using the function `setLU`. This is because the class has no non-expensive way to detect if the matrix has been modified. The function `setLU` realizes the factorization step only.

Parameters

in	<i>b</i>	Vect instance that contains right-hand side.
out	<i>x</i>	Vect instance that contains solution
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- *n* if the *n*-th pivot is null.

Implements [Matrix< T_ >](#).

int solveTrans (const Vect< T_ > & *b*, Vect< T_ > & *x*, bool *fact* = *true*)

Solve the transpose linear system.

The linear system having the current instance as a transpose matrix is solved by using the LU decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents if a factorization is performed. Naturally, if the matrix has been modified after using this function, the user has to refactorize it using the function `setLU`. This is because the class has no non-expensive way to detect if the matrix has been modified. The function `setLU` realizes the factorization step only.

Parameters

in	<i>b</i>	Vect instance that contains right-hand side.
out	<i>x</i>	Vect instance that contains solution
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- *n* if the *n*-th pivot is null.

DMatrix& operator= (DMatrix< T_ > & m)

Operator =

Copy matrix *m* to current matrix instance.

DMatrix& operator+= (const DMatrix< T_ > & m)

Operator +=.

Add matrix *m* to current matrix instance.

DMatrix& operator-= (const DMatrix< T_ > & m)

Operator -=.

Subtract matrix *m* from current matrix instance.

DMatrix& operator= (const T_ & x)

Operator =

Assign matrix to identity times *x*

DMatrix& operator*= (const T_ & x)

Operator *=

Premultiply matrix entries by constant value *x*.

DMatrix& operator+= (const T_ & x)

Operator +=

Add constant value *x* to matrix entries

DMatrix& operator-= (const T_ & x)

Operator -=

Subtract constant value *x* from matrix entries.

T_* getArray () const

Return matrix as C-Array.

Matrix is stored row by row.

7.15 Domain Class Reference

To store and treat finite element geometric information.

Public Member Functions

- [Domain](#) ()
Constructor of a null domain.
- [Domain](#) (const string &file)
Constructor with an input file.
- [~Domain](#) ()
Destructor.
- void [setFile](#) (string file)

- Set file containing [Domain](#) data.
 - void [setDim](#) (size_t d)
 - Set space dimension.
 - size_t [getDim](#) () const
 - Return space dimension.
 - void [setNbDOF](#) (size_t n)
 - Set number of degrees of freedom.
 - size_t [getNbDOF](#) () const
 - Return number of degrees of freedom.
 - size_t [getNbVertices](#) () const
 - Return number of vertices.
 - size_t [getNbLines](#) () const
 - Return number of lines.
 - size_t [getNbContours](#) () const
 - Return number of contours.
 - size_t [getNbHoles](#) () const
 - Return number of holes.
 - size_t [getNbSubDomains](#) () const
 - Return number of sub-domains.
 - int [get](#) ()
 - Read domain data interactively.
 - void [get](#) (const string &file)
 - Read domain data from a data file.
 - [Mesh](#) & [getMesh](#) () const
 - Return reference to generated [Mesh](#) instance.
 - void [genGeo](#) (string file)
 - Generate geometry file.
 - void [genMesh](#) ()
 - Generate 2-D mesh.
 - void [genMesh](#) (const string &file)
 - Generate 2-D mesh and save in file ([OFELI](#) format)
 - void [genMesh](#) (string geo_file, string bamg_file, string mesh_file)
 - Generate 2-D mesh and save geo, bamg and mesh file ([OFELI](#) format)
 - void [generateMesh](#) ()
 - Generate 2-D mesh using the BAMG mesh generator.
 - [Domain](#) & operator*= (real_t a)
 - Operator *=
 - void [insertVertex](#) (real_t x, real_t y, real_t h, int code)
 - Insert a vertex.
 - void [insertVertex](#) (real_t x, real_t y, real_t z, real_t h, int code)
 - Insert a vertex (3-D case)
 - void [insertLine](#) (size_t n1, size_t n2, int c)
 - Insert a straight line.
 - void [insertLine](#) (size_t n1, size_t n2, int dc, int nc)
 - Insert a straight line.
 - void [insertCircle](#) (size_t n1, size_t n2, size_t n3, int c)

- Insert a circular arc.*
- void `insertCircle` (size_t n1, size_t n2, size_t n3, int dc, int nc)
- Insert a circular arc.*
- void `insertRequiredVertex` (size_t v)
- Insert a required (imposed) vertex.*
- void `insertRequiredEdge` (size_t e)
- Insert a required (imposed) edge (or line)*
- void `insertSubDomain` (size_t n, int code)
- Insert subdomain.*
- void `insertSubDomain` (size_t ln, int orient, int code)
- Insert subdomain.*
- void `setNbDOF` (int nb_dof)
- Set Number of degrees of freedom per node.*
- `Point< real.t > getMinCoord` () const
- Return minimum coordinates of vertices.*
- `Point< real.t > getMaxCoord` () const
- Return maximum coordinates of vertices.*
- `real.t getMinh` () const
- Return minimal value of mesh size.*
- void `setOutputFile` (string file)
- Define output mesh file.*

7.15.1 Detailed Description

To store and treat finite element geometric information.

This class is essentially useful to construct data for mesh generators.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.15.2 Constructor & Destructor Documentation

Domain ()

Constructor of a null domain.

This constructor assigns maximal values of parameters.

Domain (const string & file)

Constructor with an input file.

Parameters

in	<i>file</i>	Input file in the XML format defining the domain
-----------	-------------	--

7.15.3 Member Function Documentation

void get (const string & *file*)

Read domain data from a data file.

Parameters

in	<i>file</i>	Input file in Domain XML format
-----------	-------------	---

void genMesh (const string & *file*)

Generate 2-D mesh and save in file ([OFELI](#) format)

Parameters

in	<i>file</i>	File where the generated mesh is saved
-----------	-------------	--

void genMesh (string *geo_file*, string *bamg_file*, string *mesh_file*)

Generate 2-D mesh and save geo, bamg and mesh file ([OFELI](#) format)

Parameters

in	<i>geo_file</i>	Geo file
in	<i>bamg_file</i>	Bamg file
in	<i>mesh_file</i>	File where the generated mesh is saved

Domain& operator*= (real_t *a*)

Operator *=

Rescale domain coordinates by multiplying by a factor

Parameters

in	<i>a</i>	Value to multiply by
-----------	----------	----------------------

void insertVertex (real_t *x*, real_t *y*, real_t *h*, int *code*)

Insert a vertex.

Parameters

in	<i>x</i>	x-coordinate of vertex
in	<i>y</i>	y-coordinate of vertex
in	<i>h</i>	mesh size around vertex
in	<i>code</i>	code of coordinate

void insertVertex (real_t *x*, real_t *y*, real_t *z*, real_t *h*, int *code*)

Insert a vertex (3-D case)

Parameters

in	x	x-coordinate of vertex
in	y	y-coordinate of vertex
in	z	z-coordinate of vertex
in	h	mesh size around vertex
in	$code$	code of coordinate

void insertLine (size_t $n1$, size_t $n2$, int c)

Insert a straight line.

Parameters

in	$n1$	Label of the first vertex of line
in	$n2$	Label of the second vertex of line
in	c	Code to associate to created nodes (Dirichlet) or sides (Neumann) if < 0

void insertLine (size_t $n1$, size_t $n2$, int dc , int nc)

Insert a straight line.

Parameters

in	$n1$	Label of the first vertex of line
in	$n2$	Label of the second vertex of line
in	dc	Code to associate to created nodes (Dirichlet)
in	nc	Code to associate to created sides (Neumann)

void insertCircle (size_t $n1$, size_t $n2$, size_t $n3$, int c)

Insert a circluar arc.

Parameters

in	$n1$	Label of vertex defining the first end of the arc
in	$n2$	Label of vertex defining the second end of the arc
in	$n3$	Label of vertex defining the center of the arc
in	c	Code to associate to created nodes (Dirichlet) or sides (Neumann) if < 0

void insertCircle (size_t $n1$, size_t $n2$, size_t $n3$, int dc , int nc)

Insert a circluar arc.

Parameters

in	$n1$	Label of vertex defining the first end of the arc
in	$n2$	Label of vertex defining the second end of the arc
in	$n3$	Label of vertex defining the center of the arc
in	dc	Code to associate to created nodes (Dirichlet)

in	<i>nc</i>	Code to associate to created sides (Neumann)
-----------	-----------	--

void insertRequiredVertex (size_t *v*)

Insert a required (imposed) vertex.

Parameters

in	<i>v</i>	Label of vertex
-----------	----------	-----------------

void insertRequiredEdge (size_t *e*)

Insert a required (imposed) edge (or line)

Parameters

in	<i>e</i>	Label of line
-----------	----------	---------------

void insertSubDomain (size_t *n*, int *code*)

Insert subdomain.

Parameters

in	<i>n</i>	
in	<i>code</i>	

void insertSubDomain (size_t *ln*, int *orient*, int *code*)

Insert subdomain.

Parameters

in	<i>ln</i>	Line label
in	<i>orient</i>	Orientation (1 or -1)
in	<i>code</i>	Subdomain code or reference

void setOutputFile (string *file*)

Define output mesh file.


Parameters

in	<i>file</i>	String defining output mesh file
-----------	-------------	----------------------------------

7.16 DSMatrix< T_ > Class Template Reference

To handle symmetric dense matrices.

Inheritance diagram for DSMatrix< T_ >:



Public Member Functions

- `DSMatrix ()`
Default constructor.
- `DSMatrix (size_t dim)`
Constructor that for a symmetric matrix with given number of rows.
- `DSMatrix (const DSMatrix< T_ > &m)`
Copy Constructor.
- `DSMatrix (Mesh &mesh, size_t dof=0, int is_diagonal=false)`
Constructor using mesh to initialize matrix.
- `~DSMatrix ()`
Destructor.
- `void setDiag ()`
Store diagonal entries in a separate internal vector.
- `void setSize (size_t dim)`
Set size (number of rows) of matrix.
- `void set (size_t i, size_t j, const T_ &val)`
Assign constant to entry (i, j) of the matrix.
- `void getColumn (size_t j, Vect< T_ > &v) const`
Get j-th column vector.
- `Vect< T_ > getColumn (size_t j) const`
Get j-th column vector.
- `void getRow (size_t i, Vect< T_ > &v) const`
Get i-th row vector.
- `Vect< T_ > getRow (size_t i) const`
Get i-th row vector.
- `void setRow (size_t i, const Vect< T_ > &v)`
Copy a given vector to a prescribed row in the matrix.
- `void setColumn (size_t j, const Vect< T_ > &v)`
Copy a given vector to a prescribed column in the matrix.
- `void setDiag (const T_ &a)`
Set matrix as diagonal and assign its diagonal entries as a constant.
- `void setDiag (const vector< T_ > &d)`
Set matrix as diagonal and assign its diagonal entries.
- `void add (size_t i, size_t j, const T_ &val)`
Add constant to an entry of the matrix.
- `T_ operator() (size_t i, size_t j) const`
Operator () (Constant version).
- `T_ & operator() (size_t i, size_t j)`
Operator () (Non constant version).
- `DSMatrix< T_ > & operator= (const DSMatrix< T_ > &m)`
Operator = Copy matrix m to current matrix instance.
- `DSMatrix< T_ > & operator= (const T_ &x)`
Operator = Assign matrix to identity times x.
- `DSMatrix & operator+= (const T_ &x)`
Operator +=.
- `DSMatrix & operator-= (const T_ &x)`

- Operator `--`.
- int `setLDLt ()`
Factorize matrix (LDL^T)
- void `MultAdd (const Vect< T_ > &x, Vect< T_ > &y) const`
Multiply matrix by vector $a*x$ and add result to y .
- void `MultAdd (T_ a, const Vect< T_ > &x, Vect< T_ > &y) const`
Multiply matrix by vector $a*x$ and add to y .
- void `Mult (const Vect< T_ > &x, Vect< T_ > &y) const`
Multiply matrix by vector x and save result in y .
- void `TMult (const Vect< T_ > &x, Vect< T_ > &y) const`
Multiply transpose of matrix by vector x and add result in y .
- void `Axpy (T_ a, const DSMatrix< T_ > &m)`
Add to matrix the product of a matrix by a scalar.
- void `Axpy (T_ a, const Matrix< T_ > *m)`
Add to matrix the product of a matrix by a scalar.
- int `solve (Vect< T_ > &b, bool fact=true)`
Solve linear system.
- int `solve (const Vect< T_ > &b, Vect< T_ > &x, bool fact=true)`
Solve linear system.
- T_ * `getArray () const`
Return matrix as C-Array. *Matrix* is stored row by row. Only lower triangle is stored.
- T_ `get (size_t i, size_t j) const`
Return entry (i, j) of matrix.

7.16.1 Detailed Description

template<class T_>class OFELI::DSMatrix< T_ >

To handle symmetric dense matrices.

This class enables storing and manipulating symmetric dense matrices.

Template Parameters

<code>T_</code>	Data type (double, float, complex<double>, ...)
-----------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.16.2 Constructor & Destructor Documentation

DSMatrix (size_t dim)

Constructor that for a symmetric matrix with given number of rows.

Parameters

in	<i>dim</i>	Number of rows
-----------	------------	----------------

DSMatrix (const DSMatrix< T_ > & m)

Copy Constructor.

Parameters

in	<i>m</i>	DSMatrix instance to copy
-----------	----------	---

DSMatrix (Mesh & mesh, size_t dof = 0, int is_diagonal = false)

Constructor using mesh to initialize matrix.

Parameters

in	<i>mesh</i>	Mesh instance for which matrix graph is determined.
in	<i>dof</i>	Option parameter, with default value 0. dof=1 means that only one degree of freedom for each node (or element or side) is taken to determine matrix structure. The value dof=0 means that matrix structure is determined using all DOFs.
in	<i>is_diagonal</i>	Boolean argument to say is the matrix is actually a diagonal matrix or not.

7.16.3 Member Function Documentation

void setSize (size_t dim)

Set size (number of rows) of matrix.

Parameters

in	<i>dim</i>	Number of rows and columns.
-----------	------------	-----------------------------

void set (size_t i, size_t j, const T_ & val) [virtual]

Assign constant to entry (i,j) of the matrix.

Parameters

in	<i>i</i>	row index
in	<i>j</i>	column index
in	<i>val</i>	value to assign to a(i,j)

Implements [Matrix< T_ >](#).

void getColumn (size_t j, Vect< T_ > & v) const

Get j-th column vector.

Parameters

in	<i>j</i>	Index of column to extract
-----------	----------	----------------------------

out	<i>v</i>	Reference to Vect instance where the column is stored
-----	----------	---

Remarks

Vector *v* does not need to be sized before. It is resized in the function

Vect<T_> getColumn (size_t *j*) const

Get *j*-th column vector.

Parameters

in	<i>j</i>	Index of column to extract
----	----------	----------------------------

Returns

[Vect](#) instance where the column is stored

Remarks

Vector *v* does not need to be sized before. It is resized in the function

void getRow (size_t *i*, Vect< T_ > & *v*) const

Get *i*-th row vector.

Parameters

in	<i>i</i>	Index of row to extract
out	<i>v</i>	Reference to Vect instance where the row is stored

Remarks

Vector *v* does not need to be sized before. It is resized in the function

Vect<T_> getRow (size_t *i*) const

Get *i*-th row vector.

Parameters

in	<i>i</i>	Index of row to extract
----	----------	-------------------------

Returns

[Vect](#) instance where the row is stored

Remarks

Vector *v* does not need to be sized before. It is resized in the function

void setRow (size_t *i*, const Vect< T_ > & *v*)

Copy a given vector to a prescribed row in the matrix.

Parameters

in	<i>i</i>	row index to be assigned
in	<i>v</i>	Vect instance to copy

void setColumn (size_t *j*, const Vect< T_ > & *v*)

Copy a given vector to a prescribed column in the matrix.

Parameters

in	<i>j</i>	column index to be assigned
in	<i>v</i>	Vect instance to copy

void setDiag (const T_ & *a*)

Set matrix as diagonal and assign its diagonal entries as a constant.

Parameters

in	<i>a</i>	Value to assign to all diagonal entries
----	----------	---

void setDiag (const vector< T_ > & *d*)

Set matrix as diagonal and assign its diagonal entries.

Parameters

in	<i>d</i>	Vector entries to assign to matrix diagonal entries
----	----------	---

void add (size_t *i*, size_t *j*, const T_ & *val*) [virtual]

Add constant to an entry of the matrix.

Parameters

in	<i>i</i>	row index
in	<i>j</i>	column index
in	<i>val</i>	value to add to a(<i>i</i> , <i>j</i>)

Implements [Matrix< T_ >](#).

T_ operator() (size_t *i*, size_t *j*) const [virtual]

Operator () (Constant version).

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implements [Matrix< T_ >](#).

T_& operator() (size_t *i*, size_t *j*) [virtual]

Operator () (Non constant version).

Parameters

in	i	Row index
in	j	Column index

Warning

To modify a value of an entry of the matrix it is safer not to modify both lower and upper triangles. Otherwise, wrong values will be assigned. If not sure, use the member functions `set` or `add`.

Implements [Matrix< T_ >](#).

DSMatrix& operator+=(const T_ & x)

Operator +=.

Add constant value x to all matrix entries.

DSMatrix& operator-=(const T_ & x)

Operator -=.

Subtract constant value x from to all matrix entries.

int setLDLt ()

Factorize matrix (LDL^T)

Returns

- 0, if factorization was normally performed,
- n , if the n -th pivot is null.

void MultAdd (T_ a, const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply matrix by vector $a*x$ and add to y .

Parameters

in	a	Constant to multiply by matrix
in	x	Vector to multiply by matrix
in,out	y	Vector to add to the result. y contains on output the result.

Implements [Matrix< T_ >](#).

void TMult (const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply transpose of matrix by vector x and add result in y .

Parameters

in	x	Vector to add to y
in,out	y	on input, vector to add to. On output, result.

Implements [Matrix< T_ >](#).

void Axy (T_ a, const DSMatrix< T_ > & m)

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which <i>a</i> is multiplied. The result is added to current instance

void Axy (T_ *a*, const Matrix< T_ > * *m*) [virtual]

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which <i>a</i> is multiplied. The result is added to current instance

Implements [Matrix< T_ >](#).

int solve (Vect< T_ > & *b*, bool *fact* = *true*) [virtual]

Solve linear system.

The matrix is factorized using the LDLt (Crout) decomposition. If this one is already factorized, no further factorization is performed. If the matrix has been modified the user has to refactorize it using the function `setLDLt`.

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side on input and solution on output.
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- *n* if the *n*-th pivot is null.

Implements [Matrix< T_ >](#).

int solve (const Vect< T_ > & *b*, Vect< T_ > & *x*, bool *fact* = *true*) [virtual]

Solve linear system.

The matrix is factorized using the LDLt (Crout) decomposition. If this one is already factorized, no further factorization is performed. If the matrix has been modified the user has to refactorize it using the function `setLDLt`.

Parameters

in	<i>b</i>	Vect instance that contains right-hand side.
out	<i>x</i>	Vect instance that contains solution
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns


- 0 if solution was normally performed,
- *n* if the *n*-th pivot is null.

Implements [Matrix< T_ >](#).

7.17 EC2D1T3 Class Reference

Eddy current problems in 2-D domains using solenoidal approximation.

Inheritance diagram for EC2D1T3:



Public Member Functions

- [EC2D1T3](#) ()
Default constructor.
- [EC2D1T3](#) ([Mesh](#) &ms)
Constructor using mesh.
- [EC2D1T3](#) ([Mesh](#) &ms, [Vect](#)< [complex_t](#) > &u)
Constructor using mesh and solution vector.
- [~EC2D1T3](#) ()
Destructor.
- void [setData](#) ([real_t](#) omega, [real_t](#) volt)
Define data for equation.
- void [build](#) ()
Build the linear system of equations.
- void [Magnetic](#) ([real_t](#) coef=1.)
Add magnetic contribution to matrix.
- void [Electric](#) ([real_t](#) coef=1.)
Add electric contribution to matrix.
- [real_t](#) [Joule](#) ()
Compute Joule density in element.
- [complex_t](#) [IntegMF](#) ()
Add element integral contribution.
- [complex_t](#) [IntegND](#) (const [Vect](#)< [complex_t](#) > &h)
Compute integral of normal derivative on edge.
- [real_t](#) [VacuumArea](#) ()
Add contribution to vacuum area calculation.

Additional Inherited Members

7.17.1 Detailed Description

Eddy current problems in 2-D domains using solenoidal approximation.

Builds finite element arrays for time harmonic eddy current problems in 2-D domains with solenoidal configurations (Magnetic field has only one nonzero component). Magnetic field is

constant in the vacuum, and then zero in the outer vacuum.

Uses 3-Node triangles.

The unknown is the time-harmonic magnetic induction (complex valued).

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.17.2 Constructor & Destructor Documentation

EC2D1T3 (Mesh & *ms*)

Constructor using mesh.

Parameters

in	<i>ms</i>	Mesh instance
----	-----------	-------------------------------

EC2D1T3 (Mesh & *ms*, Vect< complex_t > & *u*)

Constructor using mesh and solution vector.

Parameters

in	<i>ms</i>	Mesh instance
in,out	<i>u</i>	Reference to solution vector instance

7.17.3 Member Function Documentation

void setData (real_t *omega*, real_t *volt*)

Define data for equation.

Parameters

in	<i>omega</i>	Angular frequency
in	<i>volt</i>	Voltage

void build ()

Build the linear system of equations.

Before using this function, one must have properly selected appropriate options for:

- The choice of a steady state or transient analysis. By default, the analysis is stationary
- In the case of transient analysis, the choice of a time integration scheme and a lumped or consistent capacity matrix. If transient analysis is chosen, the lumped capacity matrix option is chosen by default, and the implicit Euler scheme is used by default for time integration.

void Magnetic (real_t *coef* = 1.)

Add magnetic contribution to matrix.

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by [Default: 1]
-----------------	-------------------	---

void Electric (`real_t coef = 1.`)

Add electric contribution to matrix.

Parameters

<code>in</code>	<code>coef</code>	Coefficient to multiply by [Default: 1]
-----------------	-------------------	---

complex_t IntegND (`const Vect< complex_t > & h`)

Compute integral of normal derivative on edge.

Parameters

<code>in</code>	<code>h</code>	Vect instance containing magnetic field at nodes
-----------------	----------------	--


Note

This member function is to be called within each element, it detects boundary sides as the ones with nonzero code

7.18 EC2D2T3 Class Reference

Eddy current problems in 2-D domains using transversal approximation.

Inheritance diagram for EC2D2T3:



Public Member Functions

- [EC2D2T3](#) ()
Default Constructor.
- [EC2D2T3](#) ([Mesh](#) &ms)
Constructor using mesh.
- [EC2D2T3](#) ([Mesh](#) &ms, [Vect](#)< `real_t` > &u)
Constructor using mesh and solution vector.
- [EC2D2T3](#) (`const` [Side](#) *sd1, `const` [Side](#) *sd2)
Constructor using two side data.
- [~EC2D2T3](#) ()
Destructor.

- void [RHS](#) ([real_t](#) coef=1.)
Compute Contribution to Right-Hand [Side](#).
- void [FEBlock](#) ()
Compute Finite [Element](#) Diagonal Block.
- void [BEBlocks](#) (size_t n1, size_t n2, [SpMatrix](#)< [real_t](#) > &L, [SpMatrix](#)< [real_t](#) > &U, [SpMatrix](#)< [real_t](#) > &D)
Compute boundary element blocks.
- [complex_t](#) [Constant](#) (const [Vect](#)< [real_t](#) > &u, [complex_t](#) &I)
Compute constant to multiply by potential.
- [real_t](#) [MagneticPressure](#) (const [Vect](#)< [real_t](#) > &u)
Compute magnetic pressure in element.

Additional Inherited Members

7.18.1 Detailed Description

Eddy current problems in 2-D domains using transversal approximation.

Builds finite element arrays for time harmonic eddy current problems in 2-D domains with transversal configurations (Magnetic field has two nonzero components). Uses 3-Node triangles.

The unknown is the time-harmonic scalar potential (complex valued).

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.18.2 Constructor & Destructor Documentation

EC2D2T3 ([Mesh](#) & *ms*)

Constructor using mesh.

Parameters

in	<i>ms</i>	Mesh instance
--------------------	-----------	-------------------------------

EC2D2T3 ([Mesh](#) & *ms*, [Vect](#)< [real_t](#) > & *u*)

Constructor using mesh and solution vector.

Parameters

in	<i>ms</i>	Mesh instance
in,out	<i>u</i>	Vect instance containing solution

7.19 Edge Class Reference

To describe an edge.

Public Member Functions

- [Edge](#) ()
Default Constructor.
- [Edge](#) (size_t label)
Constructor with label.
- [Edge](#) (const [Edge](#) &ed)
Copy constructor.
- [~Edge](#) ()
Destructor.
- void [Add](#) ([Node](#) *node)
Insert a node at end of list of nodes of edge.
- void [setLabel](#) (size_t i)
Assign label of edge.
- void [setFirstDOF](#) (size_t n)
Define First DOF.
- void [setNbDOF](#) (size_t nb_dof)
Define number of DOF of edge.
- void [DOF](#) (size_t i, size_t dof)
Define label of DOF.
- void [setDOF](#) (size_t &first_dof, size_t nb_dof)
Define number of DOF.
- void [setCode](#) (size_t dof, int code)
Assign code `code` to DOF number `dof`.
- void [AddNeighbor](#) ([Side](#) *sd)
Add side pointed by `sd` to list of edge sides.
- size_t [getLabel](#) () const
Return label of edge.
- size_t [n](#) () const
Return label of edge.
- size_t [getNbEq](#) () const
Return number of edge equations.
- size_t [getNbDOF](#) () const
Return number of DOF.
- int [getCode](#) (size_t dof=1) const
Return code for a given DOF of node.
- size_t [getDOF](#) (size_t i) const
*Return label of *i*-th DOF.*
- size_t [getFirstDOF](#) () const
Return number of first dof of node.
- [Node](#) * [getPtrNode](#) (size_t i) const
List of element nodes.
- [Node](#) * [operator\(\)](#) (size_t i) const
Operator ().
- size_t [getNodeLabel](#) (size_t i) const
Return node label.
- [Side](#) * [getNeighborSide](#) (size_t i) const

- *Return pointer to neighbor i -th side.*
• `int isOnBoundary () const`
Say if current edge is a boundary edge or not.
- `void setOnBoundary ()`
Say that the edge is on the boundary.
- `Node * operator() (size_t i)`
Operator ().

7.19.1 Detailed Description

To describe an edge.

Defines an edge of a 3-D finite element mesh. The edges are given in particular by a list of nodes. Each node can be accessed by the member function `getPtrNode`.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.19.2 Constructor & Destructor Documentation

`Edge ()`

Default Constructor.

Initializes data to zero

`Edge (size_t label)`

Constructor with label.

Define an edge by giving its `label`

7.19.3 Member Function Documentation

`void DOF (size_t i, size_t dof)`

Define label of DOF.

Parameters

<code>in</code>	<code>i</code>	DOF index
<code>in</code>	<code>dof</code>	Its label

`void setDOF (size_t &first_dof, size_t nb_dof)`

Define number of DOF.

Parameters

<code>in, out</code>	<code>first_dof</code>	Label of the first DOF in input that is actualized
----------------------	------------------------	--

<code>in</code>	<code>nb_dof</code>	Number of DOF
-----------------	---------------------	---------------

void setCode (size_t dof, int code)

Assign code code to DOF number dof.

Parameters

<code>in</code>	<code>dof</code>	index of dof for assignment.
<code>in</code>	<code>code</code>	Value of code to assign.

int getCode (size_t dof = 1) const

Return code for a given DOF of node.

Default value is 1

Node* operator() (size_t i) const

Operator ().

Return pointer to node of local label i.

size_t getNodeLabel (size_t i) const

Return node label.

Parameters

<code>in</code>	<code>i</code>	Local label of node for which global label is returned
-----------------	----------------	--

int isOnBoundary () const

Say if current edge is a boundary edge or not.

Note this information is available only if boundary edges were determined. See class [Mesh](#)

Node* operator() (size_t i)

Operator ().

Returns pointer to node of local label i

7.20 EdgeList Class Reference

Class to construct a list of edges having some common properties.

Public Member Functions

- [EdgeList](#) ([Mesh](#) &ms)
Constructor using a [Mesh](#) instance.
- [~EdgeList](#) ()
Destructor.
- void [selectCode](#) (int code, int dof=1)
Select edges having a given code for a given degree of freedom.
- void [unselectCode](#) (int code, int dof=1)

Unselect edges having a given code for a given degree of freedom.

- `size_t getNbEdges () const`
Return number of selected edges.
- `void top ()`
Reset list of edges at its top position (Non constant version)
- `void top () const`
Reset list of edges at its top position (Constant version)
- `Edge * get ()`
Return pointer to current edge and move to next one (Non constant version)
- `Edge * get () const`
Return pointer to current edge and move to next one (Constant version)

7.20.1 Detailed Description

Class to construct a list of edges having some common properties.

This class enables choosing multiple selection criteria by using function `select...`. However, the intersection of these properties must be empty.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.20.2 Member Function Documentation

`void selectCode (int code, int dof = 1)`

Select edges having a given code for a given degree of freedom.

Parameters

<code>in</code>	<code>code</code>	Code that edges share
<code>in</code>	<code>dof</code>	Degree of Freedom label [Default: 1]

`void unselectCode (int code, int dof = 1)`

Unselect edges having a given code for a given degree of freedom.

Parameters

<code>in</code>	<code>code</code>	Code of edges to exclude
<code>in</code>	<code>dof</code>	Degree of Freedom label [Default: 1]

7.21 EigenProblemSolver Class Reference

Class to find eigenvalues and corresponding eigenvectors of a given matrix in a generalized eigenproblem, *i.e.* Find scalars l and non-null vectors v such that $[K]\{v\} = l[M]\{v\}$ where $[K]$ and $[M]$ are symmetric matrices. The eigenproblem can be originated from a PDE. For this, we will refer to the matrices K and M as *Stiffness* and *Mass* matrices respectively.

Public Member Functions

- [EigenProblemSolver](#) ()
Default constructor.
- [EigenProblemSolver](#) (DSMatrix< [real_t](#) > &K, int n=0)
Constructor for a dense symmetric matrix that computes the eigenvalues.
- [EigenProblemSolver](#) (SkSMMatrix< [real_t](#) > &K, SkSMMatrix< [real_t](#) > &M, int n=0)
Constructor for Symmetric Skyline Matrices.
- [EigenProblemSolver](#) (SkSMMatrix< [real_t](#) > &K, Vect< [real_t](#) > &M, int n=0)
Constructor for Symmetric Skyline Matrices.
- [EigenProblemSolver](#) (DSMatrix< [real_t](#) > &A, Vect< [real_t](#) > &ev, int n=0)
Constructor for a dense matrix that compute the eigenvalues.
- [EigenProblemSolver](#) (AbsEqua< [real_t](#) > &eq, bool lumped=true)
Constructor using partial differential equation.
- [~EigenProblemSolver](#) ()
Destructor.
- void [setMatrix](#) (SkSMMatrix< [real_t](#) > &K, SkSMMatrix< [real_t](#) > &M)
Set matrix instances (Symmetric matrices).
- void [setMatrix](#) (SkSMMatrix< [real_t](#) > &K, Vect< [real_t](#) > &M)
Set matrix instances (Symmetric matrices).
- void [setMatrix](#) (DSMatrix< [real_t](#) > &K)
Set matrix instance (Symmetric matrix).
- void [setPDE](#) (AbsEqua< [real_t](#) > &eq, bool lumped=true)
Define partial differential equation to solve.
- int [run](#) (int nb=0)
Run the eigenproblem solver.
- void [Assembly](#) (const [Element](#) &el, [real_t](#) *eK, [real_t](#) *eM)
Assemble element arrays into global matrices.
- void [SAssembly](#) (const [Side](#) &sd, [real_t](#) *sK)
Assemble side arrays into global matrix and right-hand side.
- int [runSubSpace](#) (size_t nb_eigv, size_t ss_dim=0)
Run the subspace iteration solver.
- void [setSubspaceDimension](#) (int dim)
Define the subspace dimension.
- void [setMaxIter](#) (int max_it)
set maximal number of iterations.
- void [setTolerance](#) ([real_t](#) eps)
set tolerance value
- int [checkSturm](#) (int &nb_found, int &nb_lost)
Check how many eigenvalues have been found using Sturm sequence method.
- int [getNbIter](#) () const
Return actual number of performed iterations.
- [real_t](#) [getEigenValue](#) (int n) const
Return the n-th eigenvalue.
- void [getEigenVector](#) (int n, Vect< [real_t](#) > &v) const
Return the n-th eigenvector.

7.21.1 Detailed Description

Class to find eigenvalues and corresponding eigenvectors of a given matrix in a generalized eigenproblem, *i.e.* Find scalars λ and non-null vectors v such that $[K]\{v\} = \lambda[M]\{v\}$ where $[K]$ and $[M]$ are symmetric matrices. The eigenproblem can be originated from a PDE. For this, we will refer to the matrices K and M as *Stiffness* and *Mass* matrices respectively.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.21.2 Constructor & Destructor Documentation

EigenProblemSolver (DSMatrix< real.t > & K, int $n = 0$)

Constructor for a dense symmetric matrix that computes the eigenvalues.

This constructor solves in place the eigenvalues problem and stores them in a vector (No need to use the function runSubSpace). The eigenvectors can be obtained by calling the member function getEigenVector.

Parameters

in	K	Matrix for which eigenmodes are sought.
in	n	Number of eigenvalues to extract. By default all eigenvalues are computed.

EigenProblemSolver (SkSMatrix< real.t > & K, SkSMatrix< real.t > & M, int $n = 0$)

Constructor for Symmetric Skyline Matrices.

Parameters

in	K	"Stiffness" matrix
in	M	"Mass" matrix
in	n	Number of eigenvalues to extract. By default all eigenvalues are computed.

Note

The generalized eigenvalue problem is defined by $Kx = \lambda Mx$, where K and M are referred to as stiffness and mass matrix.

EigenProblemSolver (SkSMatrix< real.t > & K, Vect< real.t > & M, int $n = 0$)

Constructor for Symmetric Skyline Matrices.

Parameters

in	K	"Stiffness" matrix
----	-----	--------------------

in	M	Diagonal "Mass" matrix stored as a Vect instance
in	n	Number of eigenvalues to extract. By default all eigenvalues are computed.

Note

The generalized eigenvalue problem is defined by $Kx = \lambda Mx$, where K and M are referred to as stiffness and mass matrix.

EigenProblemSolver (DSMatrix< real.t > & A, Vect< real.t > & ev, int n = 0)

Constructor for a dense matrix that compute the eigenvalues.

This constructor solves in place the eigenvalues problem and stores them in a vector (No need to use the function runSubSpace). The eigenvectors can be obtained by calling the member function getEigenVector.

Parameters

in	A	Matrix for which eigenmodes are sought.
in	ev	Vector containing all computed eigenvalues sorted increasingly.
in	n	Number of eigenvalues to extract. By default all eigenvalues are computed.

Remarks

The vector ev does not need to be sized before.

EigenProblemSolver (AbsEqua< real.t > & eq, bool lumped = true)

Constructor using partial differential equation.

The used equation class must have been constructed using the [Mesh](#) instance

Parameters

in	eq	Reference to equation instance
in	$lumped$	Mass matrix is lumped (<i>true</i>) or not (<i>false</i>) [Default: true]

7.21.3 Member Function Documentation

void setMatrix (SkSMatrix< real.t > & K, SkSMatrix< real.t > & M)

Set matrix instances (Symmetric matrices).

This function is to be used when the default constructor is applied. Case where the mass matrix is consistent.

Parameters

in	K	Stiffness matrix instance
in	M	Mass matrix instance

void setMatrix (SkSMatrix< real.t > & K, Vect< real.t > & M)

Set matrix instances (Symmetric matrices).

This function is to be used when the default constructor is applied. Case where the mass matrix is (lumped) diagonal and stored in a vector.

Parameters

in	K	Stiffness matrix instance
in	M	Mass matrix instance where diagonal terms are stored as a vector.

void setMatrix (DSMatrix< real_t > & K)

Set matrix instance (Symmetric matrix).

This function is to be used when the default constructor is applied. Case of a standard (not generalized) eigen problem is to be solved

Parameters

in	K	Stiffness matrix instance
----	-----	---------------------------

void setPDE (AbsEqua< real_t > & eq, bool lumped = true)

Define partial differential equation to solve.

The used equation class must have been constructed using the [Mesh](#) instance

Parameters

in	eq	Reference to equation instance
in	$lumped$	Mass matrix is lumped (<i>true</i>) or not (<i>false</i>) [Default: true]

int run (int nb = 0)

Run the eigenproblem solver.

Parameters

in	nb	Number of eigenvalues to be computed. By default, all eigenvalues are computed.
----	------	---

void Assembly (const Element & el, real_t * eK, real_t * eM)

Assemble element arrays into global matrices.

This member function is to be called from finite element equation classes

Parameters

in	el	Reference to Element class
in	eK	Pointer to element stiffness (or assimilated) matrix
in	eM	Pointer to element mass (or assimilated) matrix

void SAssembly (const Side & sd, real_t * sK)

Assemble side arrays into global matrix and right-hand side.

This member function is to be called from finite element equation classes

Parameters

in	sd	Reference to Side class
----	------	---

in	sK	Pointer to side stiffness
-----------	-----------	---------------------------

int runSubSpace (size.t *nb_eigv*, size.t *ss_dim* = 0)

Run the subspace iteration solver.

This function runs the Bathe subspace iteration method.

Parameters

in	<i>nb_eigv</i>	Number of eigenvalues to be extracted
in	<i>ss_dim</i>	Subspace dimension. Must be at least equal to the number eigenvalues to seek. [Default: <i>nb_eigv</i>]

Returns

1: Normal execution. Convergence has been achieved. 2: Convergence for eigenvalues has not been attained.

void setSubspaceDimension (int *dim*)

Define the subspace dimension.

Parameters

in	<i>dim</i>	Subspace dimension. Must be larger or equal to the number of wanted eigenvalues. By default this value will be set to the number of wanted eigenvalues
-----------	-------------------	--

void setTolerance (real.t *eps*)

set tolerance value

Parameters

in	<i>eps</i>	Convergence tolerance for eigenvalues [Default: 1.e-8]
-----------	-------------------	--

int checkSturm (int & *nb_found*, int & *nb_lost*)

Check how many eigenvalues have been found using Sturm sequence method.

Parameters

out	<i>nb_found</i>	number of eigenvalues actually found
out	<i>nb_lost</i>	number of eigenvalues missing

Returns

- 0, Successful completion of subroutine.
- 1, No convergent eigenvalues found.

void getEigenVector (int *n*, Vect< real.t > & *v*) const

Return the n-th eigenvector.


Parameters

in	n	Label of eigenvector (They are stored in ascending order of eigenvalues)
in,out	v	Vect instance where the eigenvector is stored.

7.22 Elas2DQ4 Class Reference

To build element equations for 2-D linearized elasticity using 4-node quadrilaterals.

Inheritance diagram for Elas2DQ4:



Public Member Functions

- [Elas2DQ4](#) ()
Default Constructor.
- [Elas2DQ4](#) ([Mesh](#) &ms)
Constructor using [Mesh](#) instance.
- [Elas2DQ4](#) ([Mesh](#) &ms, [Vect](#)< [real.t](#) > &u)
Constructor using [Mesh](#) instance and solution vector.
- [~Elas2DQ4](#) ()
Destructor.
- void [PlaneStrain](#) ()
Set plane strain hypothesis.
- void [PlaneStrain](#) ([real.t](#) E, [real.t](#) nu)
Set plane strain hypothesis by giving values of Young's modulus and Poisson ratio.
- void [PlaneStress](#) ()
Set plane stress hypothesis.
- void [PlaneStress](#) ([real.t](#) E, [real.t](#) nu)
Set plane stress hypothesis by giving values of Young's modulus and Poisson ratio.
- void [LMass](#) ([real.t](#) coef=1.)
Add element lumped mass contribution to element matrix after multiplication by coef [Default: 1].
- void [Mass](#) ([real.t](#) coef=1.)
Add element consistent mass contribution to matrix and right-hand side after multiplication by coef [Default: 1].
- void [Deviator](#) ([real.t](#) coef=1.)
Add element deviatoric matrix to element matrix after multiplication by coef [Default: 1].
- void [Dilatation](#) ([real.t](#) coef=1.)

- Add element dilatational contribution to element matrix after multiplication by `coef` [Default: 1].*

 - void **BodyRHS** (const **Vect**< **real_t** > &f)

Add body right-hand side term to right hand side.
- void **BodyRHS** ()

Add body right-hand side term to right hand side.
- void **BoundaryRHS** (const **Vect**< **real_t** > &f)

Add boundary right-hand side term to right hand side.
- void **BoundaryRHS** ()

Add boundary right-hand side term to right hand side.
- void **Strain** (**Vect**< **real_t** > &eps)

Calculate strains at element barycenters.
- void **Stress** (**Vect**< **real_t** > &st, **Vect**< **real_t** > &vm)

Calculate principal stresses and Von-Mises stress at element barycenter.
- void **Stress** (**Vect**< **real_t** > &sigma, **Vect**< **real_t** > &s, **Vect**< **real_t** > &st)

Calculate principal stresses and Von-Mises stress at element barycenter.

Additional Inherited Members

7.22.1 Detailed Description

To build element equations for 2-D linearized elasticity using 4-node quadrilaterals.

This class enables building finite element arrays for linearized isotropic elasticity problem in 2-D domains using 4-Node quadrilaterals.

Unilateral contact is handled using a penalty function. Note that members calculating element arrays have as an argument a real `coef` that is multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.22.2 Constructor & Destructor Documentation

Elas2DQ4 ()

Default Constructor.

Constructs an empty equation.

Elas2DQ4 (**Mesh** & *ms*)

Constructor using **Mesh** instance.

Parameters

in	<i>ms</i>	Reference to Mesh instance
-----------	-----------	-----------------------------------

Elas2DQ4 (**Mesh** & *ms*, **Vect**< **real_t** > & *u*)

Constructor using **Mesh** instance and solution vector.

Parameters

in	<i>ms</i>	Reference to Mesh instance
-----------	-----------	-----------------------------------

in,out	u	Solution vector
--------	-----	-----------------

7.22.3 Member Function Documentation

void PlaneStrain (real.t E , real.t ν)

Set plane strain hypothesis by giving values of Young's modulus and Poisson ratio.

Parameters

in	E	Young's modulus
in	ν	Poisson ratio

void PlaneStress (real.t E , real.t ν)

Set plane stress hypothesis by giving values of Young's modulus and Poisson ratio.

Parameters

in	E	Young's modulus
in	ν	Poisson ratio

void BodyRHS (const Vect< real.t > & f)

Add body right-hand side term to right hand side.

Parameters

in	f	Vector containing source at nodes (DOF by DOF).
----	-----	---

void BoundaryRHS (const Vect< real.t > & f)

Add boundary right-hand side term to right hand side.

Parameters

in	f	Vector containing source at nodes (DOF by DOF).
----	-----	---

void Strain (Vect< real.t > & ϵ)

Calculate strains at element barycenters.

Parameters

out	ϵ	Vector containing strains in elements
-----	------------	---------------------------------------

Remarks

The instance of [Elas2DQ4](#) must have been constructed using the constructor with [Mesh](#) instance and solution vector

void Stress (Vect< real.t > & st , Vect< real.t > & vm)

Calculate principal stresses and Von-Mises stress at element barycenter.

Parameters

out	<i>st</i>	Vector containing principal stresses in elements
out	<i>vm</i>	Vector containing Von-Mises stresses in elements

Remarks

The instance of [Elas2DQ4](#) must have been constructed using the constructor with [Mesh](#) instance and solution vector

void Stress (Vect< real_t > & *sigma*, Vect< real_t > & *s*, Vect< real_t > & *st*)

Calculate principal stresses and Von-Mises stress at element barycenter.

Parameters

out	<i>sigma</i>	Vector containing principal stresses in elements
out	<i>s</i>	Vector containing principal stresses in elements
out	<i>st</i>	Value of Von-Mises stress in elements


Remarks

The instance of [Elas2DQ4](#) must have been constructed using the constructor with [Mesh](#) instance and solution vector

7.23 Elas2DT3 Class Reference

To build element equations for 2-D linearized elasticity using 3-node triangles.

Inheritance diagram for Elas2DT3:



Public Member Functions

- [Elas2DT3](#) ()
Default Constructor.
- [Elas2DT3](#) ([Mesh](#) &ms)
Constructor using [Mesh](#) data.
- [Elas2DT3](#) ([Mesh](#) &ms, Vect< [real_t](#) > &u)
Constructor using [Mesh](#) data and solution vector.
- [~Elas2DT3](#) ()
Destructor.
- void [Media](#) ([real_t](#) E, [real_t](#) nu, [real_t](#) rho)
Set media properties.

- void **PlaneStrain** ()
Set plane strain hypothesis.
- void **PlaneStrain** (real_t E, real_t nu)
Set plane strain hypothesis by giving values of Young's modulus E and Poisson ratio nu
- void **PlaneStress** ()
Set plane stress hypothesis.
- void **PlaneStress** (real_t E, real_t nu)
Set plane stress hypothesis by giving values of Young's modulus E and Poisson ratio nu
- void **LMass** (real_t coef=1.)
Add element lumped mass contribution to element matrix after multiplication by coef
- void **Mass** (real_t coef=1.)
Add element consistent mass contribution to element matrix after multiplication by coef
- void **Deviator** (real_t coef=1.)
Add element deviatoric matrix to element matrix after multiplication by coef
- void **Dilatation** (real_t coef=1.)
Add element dilatational contribution to element matrix after multiplication by coef
- void **BodyRHS** (const Vect< real_t > &f)
Add body right-hand side term to right hand side.
- void **BodyRHS** ()
Add body right-hand side term to right hand side.
- void **BoundaryRHS** (const Vect< real_t > &f)
Add boundary right-hand side term to right hand side.
- void **BoundaryRHS** ()
Add boundary right-hand side term to right hand side.
- int **Contact** (real_t coef=1.e07)
Penalty Signorini contact side contribution to matrix and right-hand side.
- void **Reaction** (Vect< real_t > &r)
Calculate reactions.
- void **ContactPressure** (const Vect< real_t > &f, real_t penal, Point< real_t > &p)
Calculate contact pressure.
- void **Strain** (Vect< real_t > &eps)
Calculate strains in element.
- void **Stress** (Vect< real_t > &s, Vect< real_t > &vm)
Calculate principal stresses and Von-Mises stress in element.
- void **Periodic** (real_t coef=1.e20)
Add contribution of periodic boundary condition (by a penalty technique).

Additional Inherited Members

7.23.1 Detailed Description

To build element equations for 2-D linearized elasticity using 3-node triangles.

This class enables building finite element arrays for linearized isotropic elasticity problem in 2-D domains using 3-Node triangles.

Unilateral contact is handled using a penalty function. Note that members calculating element arrays have as an argument a real coef that is multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.23.2 Constructor & Destructor Documentation

Elas2DT3 ()

Default Constructor.

Constructs an empty equation.

Elas2DT3 (Mesh & *ms*)

Constructor using [Mesh](#) data.

Parameters

<i>in</i>	<i>ms</i>	Mesh instance
-----------	-----------	-------------------------------

Elas2DT3 (Mesh & *ms*, Vect< real.t > & *u*)

Constructor using [Mesh](#) data and solution vector.

Parameters

<i>in</i>	<i>ms</i>	Mesh instance
<i>in,out</i>	<i>u</i>	Reference to solution vector

7.23.3 Member Function Documentation

void Media (real.t *E*, real.t *nu*, real.t *rho*)

Set media properties.

Useful to override material properties deduced from mesh file.

void LMass (real.t *coef* = 1.) [virtual]

Add element lumped mass contribution to element matrix after multiplication by *coef*

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Solid< real.t, 3, 6, 2, 4 >](#).

void Mass (real.t *coef* = 1.) [virtual]

Add element consistent mass contribution to element matrix after multiplication by *coef*

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Solid< real.t, 3, 6, 2, 4 >](#).

void Deviator (real.t *coef* = 1.) [virtual]

Add element deviatoric matrix to element matrix after multiplication by *coef*

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Solid< real.t, 3, 6, 2, 4 >](#).

void Dilatation (real.t *coef* = 1.) [virtual]

Add element dilatational contribution to element matrix after multiplication by *coef*

Parameters

<i>in</i>	<i>coef</i>	Coefficient to multiply by added term [Default: 1].
-----------	-------------	---

Reimplemented from [Equa.Solid< real_t, 3, 6, 2, 4 >](#).

void BodyRHS (const Vect< real_t > &f)

Add body right-hand side term to right hand side.

Parameters

<i>in</i>	<i>f</i>	Vector containing source at nodes (DOF by DOF)
-----------	----------	--

void BoundaryRHS (const Vect< real_t > &f)

Add boundary right-hand side term to right hand side.

Parameters

<i>in</i>	<i>f</i>	Vect instance that contains constant traction to impose to side.
-----------	----------	--

int Contact (real_t coef = 1.e07)

Penalty Signorini contact side contribution to matrix and right-hand side.

Parameters

<i>in</i>	<i>coef</i>	Penalty value by which the added term is multiplied [Default: 1.e07]
-----------	-------------	--

Returns

= 0 if no contact is achieved on this side, 1 otherwise

void Reaction (Vect< real_t > &r)

Calculate reactions.

This function can be invoked in postprocessing

Parameters

<i>in</i>	<i>r</i>	Reaction on the side
-----------	----------	----------------------

void ContactPressure (const Vect< real_t > &f, real_t penal, Point< real_t > &p)

Calculate contact pressure.

This function can be invoked in postprocessing

Parameters

<i>in</i>	<i>f</i>	
<i>in</i>	<i>penal</i>	Penalty parameter that was used to impose contact condition
<i>out</i>	<i>p</i>	Contact pressure

void Strain (Vect< real_t > &eps)

Calculate strains in element.

This function can be invoked in postprocessing.

Parameters

out	<i>eps</i>	vector of strains in elements
-----	------------	-------------------------------

void Stress (Vect< real_t > & s, Vect< real_t > & vm)

Calculate principal stresses and Von-Mises stress in element.

Parameters

out	<i>s</i>	vector of principal stresses in elements
out	<i>vm</i>	Von-Mises stresses in elements This function can be invoked in postprocessing.

void Periodic (real_t coef = 1.e20)

Add contribution of periodic boundary condition (by a penalty technique).

Boundary nodes where periodic boundary conditions are to be imposed must have codes equal to PERIODIC_A on one side and PERIODIC_B on the opposite side.


Parameters

in	<i>coef</i>	Value of penalty parameter [Default: 1.e20]
----	-------------	---

7.24 Elas3DH8 Class Reference

To build element equations for 3-D linearized elasticity using 8-node hexahedra.

Inheritance diagram for Elas3DH8:



Public Member Functions

- [Elas3DH8 \(\)](#)
Default Constructor.
- [Elas3DH8 \(Mesh &ms\)](#)
Constructor using [Mesh](#) instance.
- [~Elas3DH8 \(\)](#)
Destructor.
- void [LMass \(real_t coef=1.\)](#)
Add element lumped mass contribution to element matrix after multiplication by coef.
- void [Mass \(real_t coef=1.\)](#)
Add element lumped mass contribution to element matrix and right-hand side after multiplication by coef.

- void **Deviator** ([real_t](#) coef=1.)
Add element deviatoric matrix to element matrix after multiplication by coef.
- void **Dilatation** ([real_t](#) coef=1.)
Add element dilatational contribution to element matrix after multiplication by coef.
- void **BoundaryRHS** (const [Vect](#)< [real_t](#) > &f)
Add boundary right-hand side term to right hand side.
- void **BoundaryRHS** ()
Add boundary right-hand side term to right hand side.
- void **BodyRHS** (const [Vect](#)< [real_t](#) > &f)
Add body right-hand side term to right hand side.
- void **BodyRHS** ()
Add body right-hand side term to right hand side.

Additional Inherited Members

7.24.1 Detailed Description

To build element equations for 3-D linearized elasticity using 8-node hexahedra.

This class enables building finite element arrays for linearized isotropic elasticity problem in 3-D domains using 8-Node hexahedra.

Note that members calculating element arrays have as an argument a double `coef` that is multiplied by the contribution of the current element. This makes possible testing different algorithms.

7.24.2 Constructor & Destructor Documentation

Elas3DH8 ()

Default Constructor.

Constructs an empty equation.

Elas3DH8 ([Mesh](#) & *ms*)

Constructor using [Mesh](#) instance.

Parameters

<code>in</code>	<code>ms</code>	Reference to Mesh instance
-----------------	-----------------	--

7.24.3 Member Function Documentation

void BoundaryRHS (const [Vect](#)< [real_t](#) > &*f*)

Add boundary right-hand side term to right hand side.

Parameters

<code>in</code>	<code>f</code>	Vector containing traction (boundary force) at sides
-----------------	----------------	--

void BodyRHS (const [Vect](#)< [real_t](#) > &*f*)

Add body right-hand side term to right hand side.


Parameters

<code>in</code>	<code>f</code>	Vector containing source at nodes (DOF by DOF).
-----------------	----------------	---

7.25 Elas3DT4 Class Reference

To build element equations for 3-D linearized elasticity using 4-node tetrahedra.

Inheritance diagram for Elas3DT4:



Public Member Functions

- [Elas3DT4](#) ()
Default Constructor.
- [Elas3DT4](#) ([Mesh](#) &ms)
Constructor using a [Mesh](#) instance.
- [Elas3DT4](#) ([Mesh](#) &ms, [Vect](#)< [real_t](#) > &u)
Constructor using a [Mesh](#) instance and solution vector.
- [~Elas3DT4](#) ()
Destructor.
- void [Media](#) ([real_t](#) E, [real_t](#) nu, [real_t](#) rho)
Set Media properties.
- void [LMass](#) ([real_t](#) coef=1)
Add element lumped mass contribution to element matrix after multiplication by coef.
- void [Deviator](#) ([real_t](#) coef=1.)
Add element deviatoric matrix to element matrix after multiplication by coef.
- void [Dilatation](#) ([real_t](#) coef=1.)
Add element dilatational contribution to left-hand side after multiplication by coef.
- void [BodyRHS](#) (const [Vect](#)< [real_t](#) > &f)
Add body right-hand side term to right hand side.
- void [BodyRHS](#) ()
Add body right-hand side term to right hand side.
- void [BoundaryRHS](#) (const [Vect](#)< [real_t](#) > &f)
Add boundary right-hand side term to right hand side.
- void [BoundaryRHS](#) ()
Add boundary right-hand side term to right hand side.

Additional Inherited Members

7.25.1 Detailed Description

To build element equations for 3-D linearized elasticity using 4-node tetrahedra.

This class enables building finite element arrays for linearized isotropic elasticity problem in 3-D domains using 4-Node tetrahedra.

7.25.2 Constructor & Destructor Documentation

Elas3DT4 (Mesh & *ms*)

Constructor using a [Mesh](#) instance.

Parameters

<i>in</i>	<i>ms</i>	Reference to Mesh instance
-----------	-----------	--

Elas3DT4 (Mesh & *ms*, Vect< real.t > & *u*)

Constructor using a [Mesh](#) instance and solution vector.

Parameters

<i>in</i>	<i>ms</i>	Reference to Mesh instance
<i>in, out</i>	<i>u</i>	Reference to solution vector

7.25.3 Member Function Documentation

void Media (real.t *E*, real.t *nu*, real.t *rho*)

Set Media properties.

Parameters

<i>in</i>	<i>E</i>	Young's modulus
<i>in</i>	<i>nu</i>	Poisson ratio
<i>in</i>	<i>rho</i>	Density

void BodyRHS (const Vect< real.t > & *f*)

Add body right-hand side term to right hand side.

Parameters

<i>in</i>	<i>f</i>	Vect instance containing source at nodes (DOF by DOF).
-----------	----------	--

void BoundaryRHS (const Vect< real.t > & *f*)

Add boundary right-hand side term to right hand side.

Parameters

<i>in</i>	<i>f</i>	Vect instance that contains constant traction to impose to side.
-----------	----------	--

7.26 Element Class Reference

To store and treat finite element geometric information.

Public Member Functions

- [Element](#) ()
Default constructor.
- [Element](#) (size_t label, const string &shape)
Constructor initializing label, shape of element.
- [Element](#) (size_t label, int shape)
Constructor initializing label, shape of element.
- [Element](#) (size_t label, const string &shape, int c)
Constructor initializing label, shape and code of element.
- [Element](#) (size_t label, int shape, int c)
Constructor initializing label, shape and code of element.
- [Element](#) (const [Element](#) &el)
Copy constructor.
- [~Element](#) ()
Destructor.
- void [setLabel](#) (size_t i)
Define label of element.
- void [setCode](#) (int c)
Define code of element.
- void [Add](#) ([Node](#) *node)
Insert a node at end of list of nodes of element.
- void [Add](#) ([Node](#) *node, int n)
Insert a node and set its local node number.
- void [Replace](#) (size_t label, [Node](#) *node)
Replace a node at a given local label.
- void [Replace](#) (size_t label, [Side](#) *side)
Replace a side at a given local label.
- void [Add](#) ([Side](#) *sd)
Assign Side to Element.
- void [Add](#) ([Side](#) *sd, int k)
Assign Side to Element with assigned local label.
- void [Add](#) ([Element](#) *el)
Add a neighbor element.
- void [set](#) ([Element](#) *el, int n)
Add a neighbor element and set its label.
- void [setDOF](#) (size_t i, size_t dof)
Define label of DOF.
- void [setCode](#) (size_t dof, int code)
Assign code to a DOF.
- void [setNode](#) (size_t i, [Node](#) *node)
Assign a node given by its pointer as the i-th node of element.
- void [setNbDOF](#) (size_t i)

- Set number of degrees of freedom of element.*

 - void **setFirstDOF** (size_t i)
- Set label of first DOF in element.*

 - int **getShape** () const
- Return element shape.*

 - size_t **getLabel** () const
- Return label of element.*

 - size_t **n** () const
- Return label of element.*

 - int **getCode** () const
- Return code of element.*

 - size_t **getNbNodes** () const
- Return number of element nodes.*

 - size_t **getNbVertices** () const
- Return number of element vertices.*

 - size_t **getNbSides** () const
- Return number of element sides (Constant version)*

 - size_t **getNbEq** () const
- Return number of element equations.*

 - size_t **getNbDOF** () const
- return element nb of DOF*

 - size_t **getDOF** (size_t i=1) const
- Return element DOF label.*

 - size_t **getFirstDOF** () const
- Return element first DOF label.*

 - size_t **getNodeLabel** (size_t n) const
- Return global label of node of local label i.*

 - size_t **getSideLabel** (size_t n) const
- Return global label of side of local label i.*

 - **Node** * **getPtrNode** (size_t i) const
- Return pointer to node of label i (Local labelling).*

 - **Node** * **operator()** (size_t i) const
- Operator ().*

 - **Side** * **getPtrSide** (size_t i) const
- Return pointer to side of label i (Local labelling).*

 - int **Contains** (const **Node** *nd) const
- Say if element contains given node.*

 - int **Contains** (const **Node** &nd) const
- Say if element contains given node.*

 - int **Contains** (const **Side** *sd) const
- Say if element contains given side.*

 - int **Contains** (const **Side** &sd) const
- Say if element contains given side.*

 - **Element** * **getNeighborElement** (size_t i) const
- Return pointer to element Neighboring element.*

 - size_t **getNbNeigElements** () const

- Return number of neighboring elements.*
 - `real_t getMeasure () const`
- Return measure of element.*
 - `Point< real_t > getCenter () const`
- Return coordinates of center of element.*
 - `Point< real_t > getUnitNormal (size_t i) const`
- Return outward unit normal to i-th side of element.*
 - `bool isOnBoundary () const`
- Say if current element is a boundary element or not.*
 - `Node * operator() (size_t i)`
- Operator ().*
 - `int setSide (size_t n, size_t *nd)`
- Initialize information on element sides.*
 - `bool isActive () const`
- Return true or false whether element is active or not.*
 - `int getLevel () const`
- Return element level `Element` level decreases when element is refined (starting from 0). If the level is 0, then the element has no father.*
 - `void setChild (Element *el)`
- Assign element as child of current one and assign current element as father This function is principally used when refining is invoked (e.g. for mesh adaption)*
 - `Element * getChild (size_t i) const`
- Return pointer to i-th child element Return null pointer is no childs.*
 - `size_t getNbChilds () const`
- Return number of children of element.*
 - `Element * getParent () const`
- Return pointer to parent element Return null if no parent.*
 - `size_t IsIn (const Node *nd)`
- Check if a given node belongs to current element.*

7.26.1 Detailed Description

To store and treat finite element geometric information.

Class `Element` enables defining an element of a finite element mesh. The element is given in particular by its shape and a list of nodes. Each node can be accessed by the member function `getPtrNode`. Moreover, class `Mesh` can generate for each element its list of sides. The string that defines the element shape must be chosen according to the following list :

Remarks

Once a `Mesh` instance is constructed, one has access for each `Element` of the mesh to pointers to element sides provided the member function `getAllSides` of `Mesh` has been invoked. With this, an element can be tested to see if it is on the boundary, i.e. if it has at least one side on the boundary

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.26.2 Constructor & Destructor Documentation

Element (`size_t label`, `const string & shape`)

Constructor initializing label, shape of element.

Parameters

<code>in</code>	<i>label</i>	Label to assign to element.
<code>in</code>	<i>shape</i>	Shape of element (See class description).

Element (`size_t label`, `int shape`)

Constructor initializing label, shape of element.

Parameters

<code>in</code>	<i>label</i>	Label to assign to element.
<code>in</code>	<i>shape</i>	Shape of element (See enum <code>ElementShape</code> in Mesh)

Element (`size_t label`, `const string & shape`, `int c`)

Constructor initializing label, shape and code of element.

Parameters

<code>in</code>	<i>label</i>	Label to assign to element.
<code>in</code>	<i>shape</i>	Shape of element (See class description).
<code>in</code>	<i>c</i>	Code to assign to element (useful for media properties).

Element (`size_t label`, `int shape`, `int c`)

Constructor initializing label, shape and code of element.

Parameters

<code>in</code>	<i>label</i>	Label to assign to element.
<code>in</code>	<i>shape</i>	Shape of element (See enum <code>ElementShape</code> in Mesh).
<code>in</code>	<i>c</i>	Code to assign to element (useful for media properties).

7.26.3 Member Function Documentation

void setLabel (`size_t i`)

Define label of element.

Parameters

<code>in</code>	<i>i</i>	Label to assign to element
-----------------	----------	----------------------------

void setCode (`int c`)

Define code of element.

Parameters

<code>in</code>	<i>c</i>	Code to assign to element.
-----------------	----------	----------------------------

void Add (`Node * node`)

Insert a node at end of list of nodes of element.

Parameters

in	<i>node</i>	Pointer to Node instance.
-----------	-------------	---

void Add (Node * *node*, int *n*)

Insert a node and set its local node number.

Parameters

	<i>node</i>	[in] Pointer to Node instance
in	<i>n</i>	Element node number to assign

void Replace (size_t *label*, Node * *node*)

Replace a node at a given local label.

Parameters

in	<i>label</i>	Node to replace.
in	<i>node</i>	Pointer to Node instance to copy to current instance.

void Replace (size_t *label*, Side * *side*)

Replace a side at a given local label.

Parameters

in	<i>label</i>	Side to replace.
in	<i>side</i>	Pointer to Side instance to copy to current instance.

void Add (Side * *sd*)

Assign [Side](#) to [Element](#).

Parameters

in	<i>sd</i>	Pointer to Side instance.
-----------	-----------	---

void Add (Side * *sd*, int *k*)

Assign [Side](#) to [Element](#) with assigned local label.

Parameters

in	<i>sd</i>	Pointer to Side instance.
in	<i>k</i>	Local label.

void Add (Element * *el*)

Add a neighbor element.

Parameters

in	<i>el</i>	Pointer to Element instance
-----------	-----------	---

void set (Element * *el*, int *n*)

Add a neighbor element and set its label.

Parameters

in	<i>el</i>	Pointer to Element instance
in	<i>n</i>	Neighbor element number to assign

void setDOF (size.t *i*, size.t *dof*)

Define label of DOF.

Parameters

in	<i>i</i>	Index of DOF.
in	<i>dof</i>	Label of DOF to assign.

void setCode (size.t *dof*, int *code*)

Assign code to a DOF.

Parameters

in	<i>dof</i>	Index of dof for assignment.
in	<i>code</i>	Code to assign.

Node* operator() (size.t *i*) const

Operator ().

Return pointer to node of local label *i*.

int Contains (const Node * *nd*) const

Say if element contains given node.

This function tests if the element contains a node with the same pointer at the sought one

Parameters

in	<i>nd</i>	Pointer to Node instance
-----------	-----------	--

Returns

Local node label in element. If 0, the element does not contain this node

int Contains (const Node & *nd*) const

Say if element contains given node.

This function tests if the element contains a node with the same label at the sought one

Parameters

in	<i>nd</i>	Reference to Node instance
-----------	-----------	--

Returns

Local node label in element. If 0, the element does not contain this node

int Contains (const Side * *sd*) const

Say if element contains given side.

This function tests if the element contains a side with the same pointer at the sought one

Parameters

in	<i>sd</i>	Pointer to Side instance
-----------	-----------	--

Returns

Local side label in element. If 0, the element does not contain this side

int Contains (const Side & sd) const

Say if element contains given side.

This function tests if the element contains a side with the same label as the sought one

Parameters

in	<i>sd</i>	Reference to Side instance
-----------	-----------	--

Returns

Local side label in element. If 0, the element does not contain this side

Element* getNeighborElement (size_t i) const

Return pointer to element Neighboring element.

Parameters

in	<i>i</i>	Index of element to look for.
-----------	----------	-------------------------------

Note

This method returns valid information only if the [Mesh](#) member function [Mesh::getElement↵NeighborElements\(\)](#) has been called before.

size_t getNbNeigElements () const

Return number of neighboring elements.

Note

This method returns valid information only if the [Mesh](#) member function [Mesh::getElement↵NeighborElements\(\)](#) has been called before.

real_t getMeasure () const

Return measure of element.

This member function returns length, area or volume of element. In case of quadrilaterals and hexahedrals it returns determinant of Jacobian of mapping between reference and actual element

Point<real_t> getUnitNormal (size_t i) const

Return outward unit normal to i-th side of element.

Sides are ordered [node_1,node_2], [node_2,node_3], ...

bool isOnBoundary () const

Say if current element is a boundary element or not.

Note

this information is available only if boundary elements were determined i.e. if member function [Mesh::getBoundarySides](#) or [Mesh::getAllSides](#) has been invoked before.

Node* operator() (size_t i)

Operator ().

Return pointer to node of local label i.

int setSide (size_t n, size_t * nd)

Initialize information on element sides.

This function is to be used to initialize loops over sides.

Parameters

in	n	Label of side.
in	nd	Array of pointers to nodes of the side (nd[0] , nd[1] , ... point to first, second nodes, ...

void setChild (Element * el)

Assign element as child of current one and assign current element as father This function is principally used when refining is invoked (e.g. for mesh adaption)

Parameters

in	el	Pointer to element to assign
----	----	------------------------------

size_t IsIn (const Node * nd)

Check if a given node belongs to current element.

Parameters

in	nd	Pointer to node to locate
----	----	---------------------------

Returns

local label of node if this one is found, 0 otherwise

7.27 ElementList Class Reference

Class to construct a list of elements having some common properties.

Public Member Functions

- [ElementList](#) ([Mesh](#) &ms)
Constructor using a [Mesh](#) instance.
- [~ElementList](#) ()
Destructor.

- void `selectCode` (int code)
Select elements having a given code.
- void `unselectCode` (int code)
Unselect elements having a given code.
- void `selectLevel` (int level)
Select elements having a given level.
- size_t `getNbElements` () const
Return number of selected elements.
- void `top` ()
Reset list of elements at its top position (Non constant version)
- void `top` () const
Reset list of elements at its top position (Constant version)
- `Element *` `get` ()
Return pointer to current element and move to next one (Non constant version)
- `Element *` `get` () const
Return pointer to current element and move to next one (Constant version)

7.27.1 Detailed Description

Class to construct a list of elements having some common properties.

This class enables choosing multiple selection criteria by using function `select...`. However, the intersection of these properties must be empty.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.27.2 Member Function Documentation

void `unselectCode` (int *code*)

Unselect elements having a given code.

Parameters

in	<i>code</i>	Code of elements to exclude
----	-------------	-----------------------------

void `selectLevel` (int *level*)

Select elements having a given level.

Parameters


in	<i>level</i>	Level of elements to select
----	--------------	-----------------------------

Elements having a given level (for mesh adaption) are selected in a list

7.28 Ellipse Class Reference

To store and treat an ellipsoidal figure.

Inheritance diagram for Ellipse:



Public Member Functions

- `Ellipse ()`
Default constructor.
- `Ellipse (Point< real.t > c, real.t a, real.t b, int code=1)`
Constructor with given ellipse data.
- `real.t getSignedDistance (const Point< real.t > &p) const`
Return signed distance of a given point from the current ellipse.
- `Ellipse & operator+= (Point< real.t > a)`
Operator +=
- `Ellipse & operator*= (real.t a)`
*Operator *=*

7.28.1 Detailed Description

To store and treat an ellipsoidal figure.

7.28.2 Constructor & Destructor Documentation

Ellipse ()

Default constructor.

Constructs an ellipse with semimajor axis = 1, and semiminor axis = 1

Ellipse (Point< real.t > c, real.t a, real.t b, int code = 1)

Constructor with given ellipse data.

Parameters

in	<i>c</i>	Coordinates of center
in	<i>a</i>	Semimajor axis
in	<i>b</i>	Semiminor axis
in	<i>code</i>	Code to assign to the generated figure [Default: 1]

7.28.3 Member Function Documentation

`real.t getSignedDistance (const Point< real.t > &p) const` [virtual]

Return signed distance of a given point from the current ellipse.

The computed distance is negative if p lies in the ellipse, positive if it is outside, and 0 on its boundary

Parameters

in	<i>p</i>	Point<double> instance
----	----------	------------------------

Reimplemented from [Figure](#).

Ellipse& operator+= (Point< real_t > a)

Operator +=

Translate ellipse by a vector a

Parameters

in	<i>a</i>	Vector defining the translation
----	----------	---------------------------------

Ellipse& operator+= (real_t a)

Operator *=

Scale ellipse by a factor a


Parameters

in	<i>a</i>	Scaling value
----	----------	---------------

7.29 Equa_Electromagnetics< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference

Abstract class for Electromagnetics [Equation](#) classes.

Inheritance diagram for Equa_Electromagnetics< T_, NEN_, NEE_, NSN_, NSE_ >:



Protected Member Functions

- void [MagneticPermeability](#) (const [real_t](#) &mu)
Set (constant) magnetic permeability.
- void [MagneticPermeability](#) (const string &exp)
Set magnetic permeability given by an algebraic expression.
- void [ElectricConductivity](#) (const [real_t](#) &sigma)
Set (constant) electric conductivity.
- void [ElectricConductivity](#) (const string &exp)
set electric conductivity given by an algebraic expression
- void [setMaterial](#) ()
Set material properties.

Additional Inherited Members

7.29.1 Detailed Description

`template<class T_, size_t NEN_, size_t NEE_, size_t NSN_, size_t NSE_>class OFELI::Equa_↵
Electromagnetics< T_, NEN_, NEE_, NSN_, NSE_ >`

Abstract class for Electromagnetics [Equation](#) classes.

Template Parameters

<T_>	data type (double, float, ...)
<NEN_>	Number of element nodes
<NEE_>	Number of element equations
<NSN_>	Number of side nodes
<NSE_>	Number of side equations

Author

Rachid Touzani


Copyright

GNU Lesser Public License

7.30 Equa_Fluid< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference

Abstract class for Fluid Dynamics [Equation](#) classes.

Inheritance diagram for Equa_Fluid< T_, NEN_, NEE_, NSN_, NSE_ >:



Public Member Functions

- [Equa_Fluid](#) ()
Default constructor.
- virtual [~Equa_Fluid](#) ()
Destructor.
- void [Reynolds](#) (const [real.t](#) &Re)
Set Reynolds number.
- void [Viscosity](#) (const [real.t](#) &visc)
Set (constant) Viscosity.
- void [Viscosity](#) (const string &exp)
Set viscosity given by an algebraic expression.
- void [Density](#) (const [real.t](#) &dens)
Set (constant) Viscosity.
- void [Density](#) (const string &exp)
Set Density given by an algebraic expression.
- void [ThermalExpansion](#) (const [real.t](#) *e)
Set (constant) thermal expansion coefficient.
- void [ThermalExpansion](#) (const string &exp)

Set thermal expansion coefficient given by an algebraic expression.

- void [setMaterial](#) ()
Set material properties.

7.30.1 Detailed Description

```
template<class T_, size_t NEN_, size_t NEE_, size_t NSN_, size_t NSE_>class OFELI::Equa_↵
Fluid< T_, NEN_, NEE_, NSN_, NSE_ >
```

Abstract class for Fluid Dynamics [Equation](#) classes.

Template Parameters

<T_>	data type (double, float, ...)
<NEN_>	Number of element nodes
<NEE_>	Number of element equations
<NSN_>	Number of side nodes
<NSE_>	Number of side equations

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.30.2 Constructor & Destructor Documentation

[Equa_Fluid](#) ()


Default constructor.

Constructs an empty equation.

7.31 Equa_Laplace< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference

Abstract class for classes about the Laplace equation.

Inheritance diagram for [Equa_Laplace](#)< T_, NEN_, NEE_, NSN_, NSE_ >:



Public Member Functions

- [Equa_Laplace](#) ()
Default constructor.
- virtual [~Equa_Laplace](#) ()

Destructor.

- virtual void [LHS](#) ()
Add finite element matrix to left-hand side.
- virtual void [BodyRHS](#) (const [Vect](#)< [real.t](#) > &f)
Add body source term to right-hand side.
- virtual void [BoundaryRHS](#) (const [Vect](#)< [real.t](#) > &h)
Add boundary source term to right-hand side.
- void [build](#) ()
Build global matrix and right-hand side.
- virtual void [buildEigen](#) (int opt=0)
Build matrices for an eigenvalue problem.
- void [build](#) ([EigenProblemSolver](#) &e)
Build the linear system for an eigenvalue problem.

7.31.1 Detailed Description

template<class [T_](#), size_t [NEN_](#), size_t [NEE_](#), size_t [NSN_](#), size_t [NSE_](#)>**class** [OFELI::Equa_](#)↔
Laplace< [T_](#), [NEN_](#), [NEE_](#), [NSN_](#), [NSE_](#) >

Abstract class for classes about the Laplace equation.

Template Parameters

T_	Data type (real.t, float, complex<real.t>, ...)
NEN_	Number of element nodes
NEE_	Number of element equations
NSN_	Number of side nodes
NSE_	Number of side equations

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.31.2 Constructor & Destructor Documentation

Equa.Laplace ()

Default constructor.

Constructs an empty equation.

7.31.3 Member Function Documentation

virtual void [BodyRHS](#) (const [Vect](#)< [real.t](#) > &*f*) [virtual]

Add body source term to right-hand side.

7.32. EQUA_POROUS< T_, NEN_, NEE_, NSN_, NSE_ > CLASS TEMPLATE REFERENCE

Parameters

in	f	Vector containing the source given function at mesh nodes
----	-----	---

Reimplemented in [Laplace2DT3](#), [Laplace1DL2](#), [Laplace1DL3](#), and [Laplace2DT6](#).

virtual void BoundaryRHS (const Vect< real_t > & h) [virtual]

Add boundary source term to right-hand side.

Parameters

in	h	Vector containing the source given function at mesh nodes
----	-----	---

Reimplemented in [Laplace2DT3](#), [Laplace1DL2](#), [Laplace1DL3](#), and [Laplace2DT6](#).

void build ()

Build global matrix and right-hand side.

The problem matrix and right-hand side are the ones used in the constructor. They are updated in this member function.

void build (EigenProblemSolver & e)

Build the linear system for an eigenvalue problem.


Parameters

in	e	Reference to used EigenProblemSolver instance
----	-----	---

7.32 Equa_Porous< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference

Abstract class for Porous Media Finite Element classes.

Inheritance diagram for Equa_Porous< T_, NEN_, NEE_, NSN_, NSE_ >:



Public Member Functions

- [Equa_Porous](#) ()
Default constructor.
- virtual [~Equa_Porous](#) ()
Destructor.
- virtual void [Mobility](#) ()
Add mobility term to the 0-th order element matrix.
- virtual void [Mass](#) ()
Add porosity term to the 1-st order element matrix.

- virtual void **BodyRHS** (const **Vect**< **real.t** > &bf)
Add source right-hand side term to right-hand side.
- virtual void **BoundaryRHS** (const **Vect**< **real.t** > &sf)
Add boundary right-hand side term to right-hand side.
- void **build** ()
Build the linear system of equations.
- void **build** (**TimeStepping** &s)
Build the linear system of equations.
- void **build** (**EigenProblemSolver** &e)
Build the linear system for an eigenvalue problem.
- int **run** ()
Run the equation.
- void **Mu** (const string &exp)
Set viscosity given by an algebraic expression.

Protected Member Functions

- void **setMaterial** ()
Set material properties.

7.32.1 Detailed Description

template<class **T_**, size_t **NEN_**, size_t **NEE_**, size_t **NSN_**, size_t **NSE_**>**class OFELI::Equa**↵
Porous< **T_**, **NEN_**, **NEE_**, **NSN_**, **NSE_** >

Abstract class for Porous Media Finite Element classes.
Template Parameters

< T_ >	data type (real.t, float, ...)
< NEN_ >	Number of element nodes
< NEE_ >	Number of element equations
< NSN_ >	Number of side nodes
< NSE_ >	Number of side equations

7.32.2 Constructor & Destructor Documentation

Equa.Porous ()

Default constructor.

Constructs an empty equation.

7.32.3 Member Function Documentation

virtual void BodyRHS (const **Vect**< **real.t** > &**bf**) [virtual]

Add source right-hand side term to right-hand side.

Parameters

in	bf	Vector containing source at nodes.
-----------	-----------	------------------------------------

Reimplemented in [WaterPorous2D](#).

virtual void BoundaryRHS (const **Vect**< **real.t** > &**sf**) [virtual]

Add boundary right-hand side term to right-hand side.

7.33. EQUA_SOLID< T_, NEN_, NEE_, NSN_, NSE_ > CLASS TEMPLATE REFERENCE

Parameters

in	<i>sf</i>	Vector containing source at nodes.
-----------	-----------	------------------------------------

Reimplemented in [WaterPorous2D](#).

void build ()

Build the linear system of equations.

Before using this function, one must have properly selected appropriate options for:

- The choice of a steady state or transient analysis. By default, the analysis is stationary
- In the case of transient analysis, the choice of a time integration scheme and a lumped or consistent capacity matrix. If transient analysis is chosen, the lumped capacity matrix option is chosen by default, and the implicit Euler scheme is used by default for time integration.

void build (TimeStepping & s)

Build the linear system of equations.

Before using this function, one must have properly selected appropriate options for:

- The choice of a steady state or transient analysis. By default, the analysis is stationary
- In the case of transient analysis, the choice of a time integration scheme. If transient analysis is chosen, the implicit Euler scheme is used by default for time integration.

Parameters

in	<i>s</i>	Reference to used TimeStepping instance
-----------	----------	---

void build (EigenProblemSolver & e)

Build the linear system for an eigenvalue problem.

Parameters

in	<i>e</i>	Reference to used EigenProblemSolver instance
-----------	----------	---

int run ()

Run the equation.


If the analysis (see function setAnalysis) is STEADY_STATE, then the function solves the stationary equation.

If the analysis is TRANSIENT, then the function performs time stepping until the final time is reached.

7.33 Equa_Solid< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference

Abstract class for Solid Mechanics Finite Element classes.

Inheritance diagram for Equa_Solid< T_, NEN_, NEE_, NSN_, NSE_ >:



Public Member Functions

- [Equa.Solid](#) ()
Default constructor.
- virtual [~Equa.Solid](#) ()
Destructor.
- virtual void [LMass](#) (real.t coef=1)
Add lumped mass contribution to left-hand side.
- virtual void [Mass](#) (real.t coef=1)
Add consistent mass contribution to left-hand side.
- virtual void [Deviator](#) (real.t coef=1)
Add deviator matrix to left-hand side taking into account time integration scheme, after multiplication by coef [Default: 1].
- virtual void [Dilatation](#) (real.t coef=1)
Add dilatation matrix to left-hand side taking into account time integration scheme, after multiplication by coef [Default: 1].
- virtual void [Stiffness](#) (real.t coef=1)
Add stiffness matrix to left-hand side taking into account time integration scheme, after multiplication by coef [Default: 1].
- void [setInput](#) (EqDataType opt, [Vect](#)< real.t > &u)
Set specific input data to solid mechanics.

Protected Member Functions

- void [Young](#) (const real.t &E)
Set (constant) Young modulus.
- void [Poisson](#) (const real.t &nu)
Set (constant) Poisson ratio.
- void [Density](#) (const real.t &rho)
Set (constant) density.
- void [Young](#) (const string &exp)
Set Young modulus given by an algebraic expression.
- void [Poisson](#) (const string &exp)
Set Poisson ratio given by an algebraic expression.
- void [Density](#) (const string &exp)
Set density given by an algebraic expression.
- void [setMaterial](#) ()
Set material properties.

7.33.1 Detailed Description

```
template<class T_, size_t NEN_, size_t NEE_, size_t NSN_, size_t NSE_>class OFELI::Equa_↔
Solid< T_, NEN_, NEE_, NSN_, NSE_ >
```

Abstract class for Solid Mechanics Finite Element classes.

Template Parameters

<T_>	data type (double, float, ...)
<NEN_>	Number of element nodes
<NEE_>	Number of element equations
<NSN_>	Number of side nodes
<NSE_>	Number of side equations

7.33.2 Constructor & Destructor Documentation

Equa_Solid ()

Default constructor.

Constructs an empty equation.

7.33.3 Member Function Documentation

virtual void LMass (real_t coef = 1) [virtual]

Add lumped mass contribution to left-hand side.

Parameters

in	coef	coefficient to multiply by the matrix before adding [Default: 1]
----	------	--

Reimplemented in [Beam3DL2](#), [Elas2DT3](#), [Elas2DQ4](#), [Elas3DT4](#), [Bar2DL2](#), and [Elas3DH8](#).

virtual void Mass (real_t coef = 1) [virtual]

Add consistent mass contribution to left-hand side.

Parameters


in	coef	coefficient to multiply by the matrix before adding [Default: 1]
----	------	--

Reimplemented in [Beam3DL2](#), [Elas2DT3](#), [Elas2DQ4](#), [Bar2DL2](#), and [Elas3DH8](#).

7.34 Equa_Therm< T_, NEN_, NEE_, NSN_, NSE_ > Class Template Reference

Abstract class for Heat transfer Finite Element classes.

Inheritance diagram for Equa_Therm< T_, NEN_, NEE_, NSN_, NSE_ >:



Public Member Functions

- [Equa_Therm](#) ()
Default constructor.
- virtual [~Equa_Therm](#) ()

Destructor.

- virtual void [setStab](#) ()
Set stabilized formulation.
- virtual void [LCapacity](#) (real.t coef=1)
Add lumped capacity contribution to element matrix.
- virtual void [Capacity](#) (real.t coef=1)
Add consistent capacity contribution to left-hand side.
- virtual void [Diffusion](#) (real.t coef=1.)
Add diffusion term to element matrix.
- virtual void [Convection](#) (real.t coef=1.)
Add convection term to element matrix.
- virtual void [BodyRHS](#) (const [Vect](#)< real.t > &f)
Add body right-hand side term to right-hand side.
- virtual void [BoundaryRHS](#) (const [Vect](#)< real.t > &f)
Add boundary right-hand side term to right-hand side.
- void [build](#) ()
Build the linear system of equations.
- void [build](#) ([TimeStepping](#) &s)
Build the linear system of equations.
- void [build](#) ([EigenProblemSolver](#) &e)
Build the linear system for an eigenvalue problem.
- void [setRho](#) (const real.t &rho)
Set Density (constant)
- void [setCp](#) (const real.t &cp)
Set Specific heat (constant)
- void [setConductivity](#) (const real.t &diff)
Set (constant) thermal conductivity.

Protected Member Functions

- void [setMaterial](#) ()
Set material properties.

7.34.1 Detailed Description

```
template<class T_, size_t NEN_, size_t NEE_, size_t NSN_, size_t NSE_>class OFELI::Equa_↵
Therm< T_, NEN_, NEE_, NSN_, NSE_ >
```

Abstract class for Heat transfer Finite Element classes.
Template Parameters

<T_>	data type (real.t, float, ...)
<NEN>	Number of element nodes
<NEE_>	Number of element equations
<NSN_>	Number of side nodes
<NSE_>	Number of side equations

7.3.4.2 Constructor & Destructor Documentation

Equa_Therm ()

Default constructor.

Constructs an empty equation.

7.3.4.3 Member Function Documentation

virtual void setStab () [virtual]

Set stabilized formulation.

Stabilized variational formulations are to be used when the Péclet number is large.
By default, no stabilization is used.

virtual void LCapacity (real_t coef = 1) [virtual]

Add lumped capacity contribution to element matrix.

Parameters

in	coef	coefficient to multiply by the matrix before adding [Default: 1]
----	------	--

Reimplemented in [DC2DT3](#), [DC1DL2](#), [DC3DT4](#), [DC3DAT3](#), and [DC2DT6](#).

virtual void Capacity (real_t coef = 1) [virtual]

Add consistent capacity contribution to left-hand side.

Parameters

in	coef	coefficient to multiply by the matrix before adding [Default: 1]
----	------	--

Reimplemented in [DC2DT3](#), [DC1DL2](#), [DC3DT4](#), [DC3DAT3](#), and [DC2DT6](#).

virtual void BodyRHS (const Vect< real_t > &f) [virtual]

Add body right-hand side term to right-hand side.

Parameters

in	f	Vector containing source at nodes.
----	---	------------------------------------

Reimplemented in [DC2DT3](#), [DC3DT4](#), [DC1DL2](#), [DC2DT6](#), and [DC3DAT3](#).

virtual void BoundaryRHS (const Vect< real_t > &f) [virtual]

Add boundary right-hand side term to right-hand side.

Parameters

in	f	Vector containing source at nodes.
----	---	------------------------------------

Reimplemented in [DC2DT3](#), [DC3DT4](#), [DC2DT6](#), and [DC3DAT3](#).

void build ()

Build the linear system of equations.

Before using this function, one must have properly selected appropriate options for:

- The choice of a steady state or transient analysis. By default, the analysis is stationary

7.35. EQUATION< T₋, NEN₋, NEE₋, NSN₋, NSE₋ > CLASS TEMPLATE REFERENCE

- In the case of transient analysis, the choice of a time integration scheme and a lumped or consistent capacity matrix. If transient analysis is chosen, the lumped capacity matrix option is chosen by default, and the implicit Euler scheme is used by default for time integration.

void build (TimeStepping & s)

Build the linear system of equations.

Before using this function, one must have properly selected appropriate options for:

- The choice of a steady state or transient analysis. By default, the analysis is stationary
- In the case of transient analysis, the choice of a time integration scheme and a lumped or consistent capacity matrix. If transient analysis is chosen, the lumped capacity matrix option is chosen by default, and the implicit Euler scheme is used by default for time integration.

Parameters

in	s	Reference to used TimeStepping instance
----	---	---

void build (EigenProblemSolver & e)

Build the linear system for an eigenvalue problem.


Parameters

in	e	Reference to used EigenProblemSolver instance
----	---	---

7.35 Equation< T₋, NEN₋, NEE₋, NSN₋, NSE₋ > Class Template Reference

Abstract class for all equation classes.

Inheritance diagram for Equation< T₋, NEN₋, NEE₋, NSN₋, NSE₋ >:



Public Member Functions

- [Equation](#) ()
Constructor with mesh instance.
- [Equation](#) (Mesh &mesh)
Constructor with mesh instance and solution vector.
- [Equation](#) (Mesh &mesh, Vect< T₋ > &u, real_t &init_time, real_t &final_time, real_t &time←_step)
Constructor with mesh instance, matrix and right-hand side.
- virtual ~[Equation](#) ()
Destructor.
- void [updateBC](#) (const [Element](#) &el, const Vect< T₋ > &bc)

- Update Right-Hand side by taking into account essential boundary conditions.*

 - void **DiagBC** (DOFSupport dof_type=NODE_DOF, int dof=0)

Update element matrix to impose bc by diagonalization technique.
- void **LocalNodeVector** (Vect< T_ > &b)

Localize Element Vector from a Vect instance.
- void **ElementNodeVector** (const Vect< T_ > &b, LocalVect< T_, NEE_ > &be)

Localize Element Vector from a Vect instance.
- void **SideNodeVector** (const Vect< T_ > &b, LocalVect< T_, NSE_ > &bs)

Localize Side Vector from a Vect instance.
- void **SideSideVector** (const Vect< T_ > &b, T_ *bs)

Localize Side Vector from a Vect instance.
- void **ElementNodeVectorSingleDOF** (const Vect< T_ > &b, LocalVect< T_, NEN_ > &be)

Localize Element Vector from a Vect instance.
- void **ElementNodeVector** (const Vect< T_ > &b, LocalVect< T_, NEN_ > &be, int dof)

Localize Element Vector from a Vect instance.
- void **ElementSideVector** (const Vect< T_ > &b, LocalVect< T_, NSE_ > &be)

Localize Element Vector from a Vect instance.
- void **ElementVector** (const Vect< T_ > &b, DOFSupport dof_type=NODE_DOF, int flag=0)

Localize Element Vector.
- void **SideVector** (const Vect< T_ > &b, T_ *sb)

Localize Side Vector.
- void **ElementNodeCoordinates** ()

Localize coordinates of element nodes.
- void **SideNodeCoordinates** ()

Localize coordinates of side nodes.
- void **ElementAssembly** (Matrix< T_ > *A)

Assemble element matrix into global one.
- void **ElementAssembly** (BMatrix< T_ > &A)

Assemble element matrix into global one.
- void **ElementAssembly** (SkSMatrix< T_ > &A)

Assemble element matrix into global one.
- void **ElementAssembly** (SkMatrix< T_ > &A)

Assemble element matrix into global one.
- void **ElementAssembly** (SpMatrix< T_ > &A)

Assemble element matrix into global one.
- void **ElementAssembly** (TrMatrix< T_ > &A)

Assemble element matrix into global one.
- void **DGElementAssembly** (Matrix< T_ > *A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.
- void **DGElementAssembly** (SkSMatrix< T_ > &A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.
- void **DGElementAssembly** (SkMatrix< T_ > &A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.
- void **DGElementAssembly** (SpMatrix< T_ > &A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.
- void **DGElementAssembly** (TrMatrix< T_ > &A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.

Assemble element matrix into global one for the Discontinuous Galerkin approximation.

- void [SideAssembly](#) ([Matrix](#)< T_ > *A)

Assemble side (edge or face) matrix into global one.

- void [SideAssembly](#) ([SkSMatrix](#)< T_ > &A)

Assemble side (edge or face) matrix into global one.

- void [SideAssembly](#) ([SkMatrix](#)< T_ > &A)

Assemble side (edge or face) matrix into global one.

- void [SideAssembly](#) ([SpMatrix](#)< T_ > &A)

Assemble side (edge or face) matrix into global one.

- void [ElementAssembly](#) ([Vect](#)< T_ > &v)

Assemble element vector into global one.

- void [SideAssembly](#) ([Vect](#)< T_ > &v)

Assemble side (edge or face) vector into global one.

- void [AxbAssembly](#) (const [Element](#) &el, const [Vect](#)< T_ > &x, [Vect](#)< T_ > &b)

Assemble product of element matrix by element vector into global vector.

- void [AxbAssembly](#) (const [Side](#) &sd, const [Vect](#)< T_ > &x, [Vect](#)< T_ > &b)

Assemble product of side matrix by side vector into global vector.

- size_t [getNbNodes](#) () const

Return number of element nodes.

- size_t [getNbEq](#) () const

Return number of element equations.

- [real_t](#) [setMaterialProperty](#) (const string &exp, const string &prop)

Define a material property by an algebraic expression.

7.35.1 Detailed Description

```
template<class T_, size_t NEN_, size_t NEE_, size_t NSN_, size_t NSE_>class OFELI::Equation<
T_, NEN_, NEE_, NSN_, NSE_ >
```

Abstract class for all equation classes.

Template Arguments:

- T_ : data type (real.t, float, ...)
- NEN_ : Number of element nodes
- NEE_ : Number of element equations
- NSN_ : Number of side nodes
- NSE_ : Number of side equations

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.35.2 Constructor & Destructor Documentation

Equation ()

Default constructor. Constructs an "empty" equation

Equation (Mesh & *mesh*)

Constructor with mesh instance.

7.35. EQUATION< T_, NEN_, NEE_, NSN_, NSE_ > ~~CLASS TEMPLATE DOCUMENTATION~~ ~~CLASS REFERENCE~~

Parameters

in	mesh	Mesh instance
----	------	-------------------------------

Equation (Mesh & mesh, Vect< T_ > & u)

Constructor with mesh instance and solution vector.

Parameters

in	mesh	Mesh instance
in	u	Vect instance containing solution.

Equation (Mesh & mesh, Vect< T_ > & u, real.t & init_time, real.t & final_time, real.t & time_step)

Constructor with mesh instance, matrix and right-hand side.

Parameters

in	mesh	Mesh instance
in	u	Vect instance containing Right-hand side.
in	init_time	Initial Time value
in	final_time	Final Time value
in	time_step	Time step value

7.35.3 Member Function Documentation

void updateBC (const Element & el, const Vect< T_ > & bc)

Update Right-Hand side by taking into account essential boundary conditions.

Parameters

in	el	Reference to current element instance
in	bc	Vector that contains imposed values at all DOFs

void DiagBC (DOFSupport dof_type = NODE_DOF, int dof = 0)

Update element matrix to impose bc by diagonalization technique.

Parameters

in	dof_type	DOF type option. To choose among the enumerated values: <ul style="list-style-type: none"> NODE_DOF, DOFs are supported by nodes [Default] ELEMENT_DOF, DOFs are supported by elements SIDE_DOF, DOFs are supported by sides
in	dof	DOF setting: <ul style="list-style-type: none"> = 0, All DOFs are taken into account [Default] != 0, Only DOF No. dof is handled in the system

void LocalNodeVector (Vect< T_ > & b)

Localize [Element](#) Vector from a [Vect](#) instance.

7.35. EQUATION< T_, NEN_, NEE_, NSN_, NSE_ > ~~CLASS TEMPLATE SPECIALIZATION~~

Parameters

in	<i>b</i>	Reference to global vector to be localized. The resulting local vector can be accessed by attribute ePrev. This member function is to be used if a constructor with Element was invoked.
----	----------	--

void ElementNodeVector (const Vect< T_ > & *b*, LocalVect< T_, NEE_ > & *be*)

Localize [Element](#) Vector from a [Vect](#) instance.

Parameters

in	<i>b</i>	Global vector to be localized.
out	<i>be</i>	Local vector, the length of which is the total number of element equations.

Remarks

All degrees of freedom are transferred to the local vector

void SideNodeVector (const Vect< T_ > & *b*, LocalVect< T_, NSE_ > & *bs*)

Localize [Side](#) Vector from a [Vect](#) instance.

Parameters

in	<i>b</i>	Global vector to be localized.
out	<i>bs</i>	Local vector, the length of which is the total number of side equations.

Remarks

All degrees of freedom are transferred to the local vector

void SideSideVector (const Vect< T_ > & *b*, T_ * *bs*)

Localize [Side](#) Vector from a [Vect](#) instance.

Parameters

in	<i>b</i>	Global vector to be localized.
out	<i>bs</i>	Local constant value of vector at given side.

Remarks

All degrees of freedom are transferred to the local vector

void ElementNodeVectorSingleDOF (const Vect< T_ > & *b*, LocalVect< T_, NEN_ > & *be*)

Localize [Element](#) Vector from a [Vect](#) instance.

Parameters

in	<i>b</i>	Global vector to be localized.
out	<i>be</i>	Local vector, the length of which is the total number of element equations.

Remarks

Vector *b* is assumed to contain only one degree of freedom by node.

void ElementNodeVector (const Vect< T_ > & *b*, LocalVect< T_, NEN_ > & *be*, int *dof*)

Localize [Element](#) Vector from a [Vect](#) instance.

7.35. EQUATION< T_, NEN_, NEE_, NSN_, NSE_ > ~~CLASS TEMPLATE~~ ~~DECLARATION~~ ~~DEFINITION~~

Parameters

in	<i>b</i>	Global vector to be localized.
out	<i>be</i>	Local vector, the length of which is the total number of element equations.
in	<i>dof</i>	Degree of freedom to transfer to the local vector

Remarks

Only the dega dof is transferred to the local vector

void ElementSideVector (const Vect< T_ > & b, LocalVect< T_, NSE_ > & be)

Localize [Element](#) Vector from a [Vect](#) instance.

Parameters

in	<i>b</i>	Global vector to be localized.
out	<i>be</i>	Local vector, the length of which is

void ElementVector (const Vect< T_ > & b, DOFSupport *dof_type* = NODE_DOF, int *flag* = 0)

Localize [Element](#) Vector.

Parameters

in	<i>b</i>	Global vector to be localized
in	<i>dof_type</i>	DOF type option. To choose among the enumerated values: <ul style="list-style-type: none"> • NODE_DOF, DOFs are supported by nodes [Default] • ELEMENT_DOF, DOFs are supported by elements • SIDE_DOF, DOFs are supported by sides
in	<i>flag</i>	Option to set: <ul style="list-style-type: none"> • = 0, All DOFs are taken into account [Default] • != 0, Only DOF number dof is handled in the system The resulting local vector can be accessed by attribute ePrev.

Remarks

This member function is to be used if a constructor with [Element](#) was invoked. It uses the [Element](#) pointer `_theElement`

void SideVector (const Vect< T_ > & b, T_ * sb)

Localize [Side](#) Vector.

Parameters

in	<i>b</i>	Global vector to be localized <ul style="list-style-type: none"> • <code>NODE_DOF</code>, DOFs are supported by nodes [default] • <code>ELEMENT_DOF</code>, DOFs are supported by elements • <code>SIDE_DOF</code>, DOFs are supported by sides • <code>BOUNDARY_SIDE_DOF</code>, DOFs are supported by boundary sides
out	<i>sb</i>	Array in which local vector is stored The resulting local vector can be accessed by attribute <code>ePrev</code> .

Remarks

This member function is to be used if a constructor with [Side](#) was invoked. It uses the [Side](#) pointer `_theSide`

void ElementNodeCoordinates ()

Localize coordinates of element nodes.

Coordinates are stored in array `_x[0]` , `_x[1]` , ... which are instances of class [Point<real.t>](#)

Remarks

This member function uses the [Side](#) pointer `_theSide`

void SideNodeCoordinates ()

Localize coordinates of side nodes.

Coordinates are stored in array `_x[0]` , `_x[1]` , ... which are instances of class [Point<real.t>](#)

Remarks

This member function uses the [Element](#) pointer `_theElement`

void ElementAssembly ([Matrix< T_ > * A](#))

Assemble element matrix into global one.

Parameters

<i>A</i>	Pointer to global matrix (abstract class: can be any of classes SkSMatrix , SkMatrix , SpMatrix)
----------	---

Warning

The element pointer is given by the global variable `theElement`

void ElementAssembly ([BMatrix< T_ > & A](#))

Assemble element matrix into global one.

7.35. EQUATION< T_, NEN_, NEE_, NSN_, NSE_ > ~~CLASS TEMPLATE SPECIALIZATION~~

Parameters

A	Global matrix stored as a BMatrix instance
-----	--

Warning

The element pointer is given by the global variable theElement

void ElementAssembly (SkSMatrix< T_ > & A)

Assemble element matrix into global one.

Parameters

A	Global matrix stored as an SkSMatrix instance
-----	---

Warning

The element pointer is given by the global variable theElement

void ElementAssembly (SkMatrix< T_ > & A)

Assemble element matrix into global one.

Parameters

in	A	Global matrix stored as an SkMatrix instance
----	-----	--

Warning

The element pointer is given by the global variable theElement

void ElementAssembly (SpMatrix< T_ > & A)

Assemble element matrix into global one.

Parameters

in	A	Global matrix stored as an SpMatrix instance
----	-----	--

Warning

The element pointer is given by the global variable theElement

void ElementAssembly (TrMatrix< T_ > & A)

Assemble element matrix into global one.

Parameters

in	A	Global matrix stored as an TrMatrix instance
----	-----	--

Warning

The element pointer is given by the global variable theElement

void DGElementAssembly (Matrix< T_ > * A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.

Parameters

A	Pointer to global matrix (abstract class: can be any of classes SkSMatrix , SkMatrix , SpMatrix)
-----	---

Warning

The element pointer is given by the global variable `theElement`

void DGElementAssembly (SkSMatrix< T_ > & A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.

Parameters

A	Global matrix stored as an SkSMatrix instance
-----	---

Warning

The element pointer is given by the global variable `theElement`

void DGElementAssembly (SkMatrix< T_ > & A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.

Parameters

<code>in</code>	A	Global matrix stored as an SkMatrix instance
-----------------	-----	--

Warning

The element pointer is given by the global variable `theElement`

void DGElementAssembly (SpMatrix< T_ > & A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.

Parameters

<code>in</code>	A	Global matrix stored as an SpMatrix instance
-----------------	-----	--

Warning

The element pointer is given by the global variable `theElement`

void DGElementAssembly (TrMatrix< T_ > & A)

Assemble element matrix into global one for the Discontinuous Galerkin approximation.

Parameters

<code>in</code>	A	Global matrix stored as an TrMatrix instance
-----------------	-----	--

Warning

The element pointer is given by the global variable `theElement`

void SideAssembly (Matrix< T_ > * A)

Assemble side (edge or face) matrix into global one.

7.35. EQUATION< T_, NEN_, NEE_, NSN_, NSE_ > ~~CLASS TEMPLATE~~ ~~DECLARATION~~ ~~IMPLEMENTATION~~

Parameters

A	Pointer to global matrix (abstract class: can be any of classes SkSMatrix , SkMatrix , SpMatrix)
-----	---

Warning

The side pointer is given by the global variable theSide

void SideAssembly (SkSMatrix< T_ > & A)

Assemble side (edge or face) matrix into global one.

Parameters

in	A	Global matrix stored as an SkSMatrix instance
----	-----	---

Warning

The side pointer is given by the global variable theSide

void SideAssembly (SkMatrix< T_ > & A)

Assemble side (edge or face) matrix into global one.

Parameters

in	A	Global matrix stored as an SkMatrix instance
----	-----	--

Warning

The side pointer is given by the global variable theSide

void SideAssembly (SpMatrix< T_ > & A)

Assemble side (edge or face) matrix into global one.

Parameters

in	A	Global matrix stored as an SpMatrix instance
----	-----	--

Warning

The side pointer is given by the global variable theSide

void ElementAssembly (Vect< T_ > & v)

Assemble element vector into global one.

Parameters

in	v	Global vector (Vect instance)
----	-----	--

Warning

The element pointer is given by the global variable theElement

void SideAssembly (Vect< T_ > & v)

Assemble side (edge or face) vector into global one.

Parameters

in	v	Global vector (Vect instance)
----	-----	--

Warning

The side pointer is given by the global variable `theSide`

void AxbAssembly (const Element & *el*, const Vect< T_ > & *x*, Vect< T_ > & *b*)

Assemble product of element matrix by element vector into global vector.

Parameters

in	<i>el</i>	Reference to Element instance
in	<i>x</i>	Global vector to multiply by (Vect instance)
out	<i>b</i>	Global vector to add (Vect instance)

void AxbAssembly (const Side & *sd*, const Vect< T_ > & *x*, Vect< T_ > & *b*)

Assemble product of side matrix by side vector into global vector.

Parameters

in	<i>sd</i>	Reference to Side instance
in	<i>x</i>	Global vector to multiply by (Vect instance)
out	<i>b</i>	Global vector (Vect instance)

real.t setMaterialProperty (const string & *exp*, const string & *prop*)

Define a material property by an algebraic expression.

Parameters

in	<i>exp</i>	Algebraic expression
in	<i>prop</i>	Property name

Returns

Return value in expression evaluation:

- =0, Normal evaluation
- !=0, An error message is displayed

7.36 Estimator Class Reference

To calculate an a posteriori estimator of the solution.

Public Types

- enum [EstimatorType](#) {
[ESTIM_ZZ](#) = 0,
[ESTIM_ND_JUMP](#) = 1 }

Public Member Functions

- [Estimator](#) ()
Default Constructor.
- [Estimator](#) ([Mesh](#) &m)
Constructor using finite element mesh.
- [~Estimator](#) ()
Destructor.
- void [setType](#) ([EstimatorType](#) t=[ESTIM_ZZ](#))
Select type of a posteriori estimator.
- void [setSolution](#) (const [Vect](#)< [real_t](#) > &u)
Provide solution vector in order to determine error index.
- void [getElementWiseIndex](#) ([Vect](#)< [real_t](#) > &e)
Get vector containing elementwise error index.
- void [getNodeWiseIndex](#) ([Vect](#)< [real_t](#) > &e)
Get vector containing nodewise error index.
- void [getSideWiseIndex](#) ([Vect](#)< [real_t](#) > &e)
Get vector containing sidewise error index.
- [real_t](#) [getAverage](#) () const
Return averaged error.
- [Mesh](#) & [getMesh](#) () const
Return a reference to the finite element mesh.

7.36.1 Detailed Description

To calculate an a posteriori estimator of the solution.

This class enables calculating an estimator of a solution in order to evaluate reliability. Estimation uses the so-called Zienkiewicz-Zhu estimator.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.36.2 Member Enumeration Documentation

enum [EstimatorType](#)

Enumerate variable that selects an error estimator for mesh adaptation purposes

Enumerator

[ESTIM_ZZ](#) Zhu-Zienckiewicz elementwise estimator

[ESTIM_ND_JUMP](#) Normal derivative jump sidewise estimator

7.36.3 Constructor & Destructor Documentation

[Estimator](#) ([Mesh](#) & *m*)

Constructor using finite element mesh.

Parameters

in	<i>m</i>	Mesh instance
----	----------	-------------------------------

7.36.4 Member Function Documentation

void setType (EstimatorType *t* = ESTIM_ZZ)

Select type of a posteriori estimator.

Parameters

in	<i>t</i>	Type of estimator. It has to be chosen among the enumerated values: <ul style="list-style-type: none"> • ESTIM_ZZ: The Zhu-Zienckiewicz estimator (Default value) • ESTIM_ND_JUMP: An estimator based on the jump of normal derivatives of the solution across mesh sides
----	----------	---

void setSolution (const Vect< real_t > & *u*)

Provide solution vector in order to determine error index.

Parameters

in	<i>u</i>	Vector containing solution at mesh nodes
----	----------	--

void getElementWiseIndex (Vect< real_t > & *e*)

Get vector containing elementwise error index.

Parameters

in,out	<i>e</i>	Vector that contains once the member function setError is invoked a posteriori estimator at each element
--------	----------	--

void getNodeWiseIndex (Vect< real_t > & *e*)

Get vector containing nodewise error index.

Parameters

in,out	<i>e</i>	Vector that contains once the member function setError is invoked a posteriori estimator at each node
--------	----------	---

void getSideWiseIndex (Vect< real_t > & *e*)

Get vector containing sidewise error index.

Parameters

in,out	<i>e</i>	Vector that contains once the member function setError is invoked a posteriori estimator at each side
--------	----------	---

7.37 FastMarching2D Class Reference

To run a Fast Marching Method on 2-D structured uniform grids.

Public Member Functions

- [FastMarching2D](#) ()
Default constructor.
- [FastMarching2D](#) (const [Grid](#) &g, [Vect](#)< [real_t](#) > &ls)
Constructor using grid and level set function.
- [FastMarching2D](#) (const [Grid](#) &g, [Vect](#)< [real_t](#) > &ls, [Vect](#)< [real_t](#) > &F)
Constructor using grid, level set function and velocity to extend.
- [~FastMarching2D](#) ()
Destructor.
- void [execute](#) ()
Execute Fast Marching Procedure.
- void [Check](#) ()
Check distance function.

7.37.1 Detailed Description

To run a Fast Marching Method on 2-D structured uniform grids.

This class enables running a Fast Marching procedure to calculate the signed distance function and extend a given front speed.

Author

M. Sylla, B. Meden

Copyright

GNU Lesser Public License

7.37.2 Constructor & Destructor Documentation

[FastMarching2D](#) (const [Grid](#) &g, [Vect](#)< [real_t](#) > &ls)

Constructor using grid and level set function.

Parameters

in	<i>g</i>	Instance of class Grid
in	<i>ls</i>	Vector containing the level set function at grid nodes. The values are 0 on the interface (from which the distance is computed), positive on one side and negative on the other side. They must contain the signed distance on the nodes surrounding the interface but can take any value on other nodes, provided they have the right sign.

[FastMarching2D](#) (const [Grid](#) &g, [Vect](#)< [real_t](#) > &ls, [Vect](#)< [real_t](#) > &F)

Constructor using grid, level set function and velocity to extend.

Parameters

in	g	Instance of class Grid
in	ls	Vector containing the level set function at grid nodes. The values are 0 on the interface (from which the distance is computed), positive on one side and negative on the other side. They must contain the signed distance on the nodes surrounding the interface but can take any value on other nodes, provided their sign is right.
in	F	Vector containing the front speed at grid nodes. Only values on nodes surrounding the interface are relevant.

7.37.3 Member Function Documentation

void execute ()


Execute Fast Marching Procedure.

Once this function was called, the vector ls used in the constructor will contain the signed distance function and F will contain the extended speed.

7.38 FEShape Class Reference

Parent class from which inherit all finite element shape classes.

Inheritance diagram for FEShape:



Public Member Functions

- [FEShape](#) ()
Default Constructor.
- [FEShape](#) (const [Element](#) *el)
Constructor for an element.
- [FEShape](#) (const [Side](#) *sd)
Constructor for a side.
- virtual [~FEShape](#) ()
Destructor.
- [real.t Sh](#) (size_t i) const
Return shape function of node i at given point.
- [real.t Sh](#) (size_t i, [Point](#)< [real.t](#) > s) const
Calculate shape function of node i at a given point s .
- [real.t getDet](#) () const
Return determinant of jacobian.
- [Point](#)< [real.t](#) > [getCenter](#) () const

Return coordinates of center of element.

- `Point< real.t > getLocalPoint ()` const

Localize a point in the element.

- `Point< real.t > getLocalPoint (const Point< real.t > &s)` const

Localize a point in the element.

7.38.1 Detailed Description

Parent class from which inherit all finite element shape classes.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.38.2 Constructor & Destructor Documentation

FEShape (const Element * *el*)

Constructor for an element.

Parameters

in	<i>el</i>	Pointer to element
----	-----------	--------------------

FEShape (const Side * *sd*)

Constructor for a side.

Parameters

in	<i>sd</i>	Pointer to side
----	-----------	-----------------

7.38.3 Member Function Documentation

real.t Sh (size_t *i*, Point< real.t > *s*) const

Calculate shape function of node *i* at a given point *s*.

Parameters

in	<i>i</i>	Local node label
in	<i>s</i>	Point in the reference triangle where the shape function is evaluated

real.t getDet () const

Return determinant of jacobian.

If the transformation (Reference element -> Actual element) is not affine, member function **setLocal()** must have been called before in order to calculate relevant quantities.

Point<real_t> getLocalPoint () const

Localize a point in the element.

Return actual coordinates in the reference element. If the transformation (Reference element -> Actual element) is not affine, member function **setLocal()** must have been called before in order to calculate relevant quantities.

Point<real_t> getLocalPoint (const Point< real_t > & s) const


Localize a point in the element.

Return actual coordinates where s are coordinates in the reference element.

7.39 Figure Class Reference

To store and treat a figure (or shape) information.

Inheritance diagram for Figure:



Public Member Functions

- **Figure ()**
Default constructor.
- **Figure (const Figure &f)**
Copy constructor.
- **virtual ~Figure ()**
Destructor.
- **void setCode (int code)**
Choose a code for the domain defined by the figure.
- **virtual real_t getSignedDistance (const Point< real_t > &p) const**
Return signed distance from a given point to current figure.
- **Figure & operator= (const Figure &f)**
Operator =.
- **void getSignedDistance (const Grid &g, Vect< real_t > &d) const**
Calculate signed distance to current figure with respect to grid points.
- **real_t dLine (const Point< real_t > &p, const Point< real_t > &a, const Point< real_t > &b) const**
Compute signed distance from a line.

7.39.1 Detailed Description

To store and treat a figure (or shape) information.

This class is essentially useful to construct data for mesh generators and for distance calculations.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.39.2 Member Function Documentation

virtual real_t getSignedDistance (const Point< real_t > & p) const [virtual]

Return signed distance from a given point to current figure.

Parameters

in	<i>p</i>	Point instance from which distance is computed
----	----------	--

Reimplemented in [Polygon](#), [Triangle](#), [Ellipse](#), [Sphere](#), [Circle](#), [Brick](#), and [Rectangle](#).

void getSignedDistance (const Grid & g, Vect< real_t > & d) const

Calculate signed distance to current figure with respect to grid points.

Parameters

in	<i>g</i>	Grid instance
in	<i>d</i>	Vect instance containing calculated distance from each grid index to Figure

Remarks

Vector d doesn't need to be sized before invoking this function

real_t dLine (const Point< real_t > & p, const Point< real_t > & a, const Point< real_t > & b) const

Compute signed distance from a line.

Parameters

in	<i>p</i>	Point for which distance is computed
in	<i>a</i>	First vertex of line
in	<i>b</i>	Second vertex of line

Returns

Signed distance

7.40 FMM2D Class Reference

class for the fast marching 2-D algorithm

Inherits FMM.

Public Member Functions

- **FMM2D** (const [Grid](#) &g, [Vect](#)< [real_t](#) > &phi, bool HA)
Constructor.
- **FMM2D** (const [Grid](#) &g, [Vect](#)< [real_t](#) > &phi, const [Vect](#)< [real_t](#) > &F, bool HA)
Constructor.
- void **init** ()
Initialize the heap.
- void **run** ()
Execute Fast Marching Procedure.
- void **eval** (IPoint &pt, int sign)
compute the distance from node to interface
- void **ExtendSpeed** ([Vect](#)< [real_t](#) > &F)
Extend the speed function to the whole grid.
- [real_t](#) **check_error** ()
Check error by comparing with the gradient norm.

7.40.1 Detailed Description

class for the fast marching 2-D algorithm

This class manages the 2-D Fast Marching method

Author

M. Sylla, B. Meden

Copyright

GNU Lesser Public License

7.40.2 Constructor & Destructor Documentation

FMM2D (const [Grid](#) &g, [Vect](#)< [real_t](#) > &phi, bool HA)

Constructor.

Constructor using [Grid](#) instance

Parameters

in	<i>g</i>	Instance of class Grid
in	<i>phi</i>	Vector containing the level set function at grid nodes. The values are 0 on the interface (from which the distance is computed), positive on one side and negative on the other side. They must contain the signed distance on the nodes surrounding the interface but can take any value on other nodes, provided they have the right sign.

in	<i>HA</i>	true if the program must be executed with high accuracy, false otherwise
----	-----------	--

FMM2D (const Grid &g, Vect< real.t > &phi, const Vect< real.t > &F, bool HA)

Constructor.

Constructor using [Grid](#) instance

Parameters

in	<i>g</i>	Instance of class Grid
in	<i>phi</i>	Vector containing the level set function at grid nodes. The values are 0 on the interface (from which the distance is computed), positive on one side and negative on the other side. They must contain the signed distance on the nodes surrounding the interface but can take any value on other nodes, provided they have the right sign.
in	<i>F</i>	Right hand-side of the Eikonal equation
in	<i>HA</i>	true if the program must be executed with high accuracy, false otherwise

7.40.3 Member Function Documentation

void eval (IPoint &pt, int sign)

compute the distance from node to interface

Parameters

in	<i>pt</i>	node to treat
in	<i>sign</i>	Node sign

Returns

distance from node pt to interface

void ExtendSpeed (Vect< real.t > &F)

Extend the speed function to the whole grid.

Parameters

in,out	<i>F</i>	Vector containing the speed at interface nodes on input and extended speed to all grid nodes
--------	----------	--

real.t check_error ()

Check error by comparing with the gradient norm.

This function returns discrete L^2 and Max. errors

7.41 FMM3D Class Reference

class for the 3-D fast marching algorithm

Inherits FMM.

Public Member Functions

- **FMM3D** (const [Grid](#) &g, [Vect](#)< [real.t](#) > &phi, bool HA)
Constructor.
- **FMM3D** (const [Grid](#) &g, [Vect](#)< [real.t](#) > &phi, const [Vect](#)< [real.t](#) > &F, bool HA)
Constructor.
- void **init** ()
Initialize heap.
- void **run** ()
Execute Fast Marching Procedure.
- void **eval** (IPoint &pt, int sign)
Compute the distance from node to interface.
- void **ExtendSpeed** ([Vect](#)< [real.t](#) > &F)
Extend the speed function to the whole grid.
- [real.t](#) **check.error** ()
Check error by comparing with the gradient norm.

7.41.1 Detailed Description

class for the 3-D fast marching algorithm

This class manages the 3-D Fast Marching Method

7.41.2 Constructor & Destructor Documentation

FMM3D (const [Grid](#) &g, [Vect](#)< [real.t](#) > &phi, bool HA)

Constructor.

Constructor using [Grid](#) instance

Parameters

in	<i>g</i>	Instance of class Grid
in	<i>phi</i>	Vector containing the level set function at grid nodes. The values are 0 on the interface (from which the distance is computed), positive on one side and negative on the other side. They must contain the signed distance on the nodes surrounding the interface but can take any value on other nodes, provided they have the right sign.
in	<i>HA</i>	true if the program must be executed with high accuracy, false otherwise

Author

M. Sylla, B. Meden

Copyright

GNU Lesser Public License

FMM3D (const [Grid](#) &g, [Vect](#)< [real.t](#) > &phi, const [Vect](#)< [real.t](#) > &F, bool HA)

Constructor.

Constructor using [Grid](#) instance

Parameters

in	g	Instance of class Grid
in	ϕ	Vector containing the level set function at grid nodes. The values are 0 on the interface (from which the distance is computed), positive on one side and negative on the other side. They must contain the signed distance on the nodes surrounding the interface but can take any value on other nodes, provided they have the right sign.
in	F	Vector containing the right-hand side of the Eikonal equation
in	HA	true if the program must be executed with high accuracy, false otherwise

Author

M. Sylla, B. Meden

Copyright

GNU Lesser Public License

7.41.3 Member Function Documentation

void eval (IPoint & pt , int $sign$)

Compute the distance from node to interface.

Parameters

in	pt	Node to treat
in	$sign$	Node's sign

Returns

Distance from node pt to interface

void ExtendSpeed (Vect< real.t > & F)

Extend the speed function to the whole grid.

Parameters

in,out	F	Vector containing the speed at interface nodes on input and extended speed at whole grid nodes
--------	-----	--

real.t check.error ()

Check error by comparing with the gradient norm.

This function prints discrete L^2 and Max. errors

7.42 FMMSolver Class Reference

The Fast Marching Method solver.

Public Member Functions

- `FMMSolver` (const `Grid` &`g`, `Vect`< `real_t` > &`phi`, bool `ha`=false)
Constructor.
- `~FMMSolver` ()
Destructor.
- void `run` ()
Execute the fast marching program.
- void `ExtendSpeed` (`Vect`< `real_t` > &`F`)
Extend speed by Sethian's method.
- `real_t check_error` ()
Return the consistency error of the method.

7.42.1 Detailed Description

The Fast Marching Method solver.

This class enables computing the signed distance function with respect to an interface. It works in 2-D and 3-D on a structured grid. The class is an interface for client. It points to FMM

Author

M. Sylla, B. Meden

Copyright

GNU Lesser Public License

7.42.2 Constructor & Destructor Documentation

`FMMSolver` (const `Grid` &`g`, `Vect`< `real_t` > &`phi`, bool `ha` = *false*)

Constructor.

Parameters

in	<code>g</code>	Instance of class <code>Grid</code> defining the grid on which the distance is computed.
in	<code>phi</code>	Vector containing the level set function at grid nodes. The vector entries are 0 on the interface (from which the distance is computed), positive on one side and negative on the other side. They must contain the signed distance on the nodes surrounding the interface. These values identify by linear interpolation the interface position. The vector entries can take any value on other grid nodes, provided they have the right sign.

in	ha	true if high accuracy FMM is active. The high accuracy version is more accurate but requires more accurate values on the nodes neighbouring the interface.
----	----	--

7.42.3 Member Function Documentation

void ExtendSpeed (Vect< real.t > &F)

Extend speed by Sethian's method.

The method consists in calculating a speed F such that its gradient is orthogonal to the gradient of the level set function

Parameters

in,out	F	Speed function where on input the value of the function is meaningful on the interface. On output F contains the extended speed
--------	---	---

real.t check_error ()

Return the consistency error of the method.

Consistency is measured by computing the discrete value of the norm of the gradient of the signed distance and subtracting the obtained norm from 1. The absolute value of the result is returned.

7.43 Funct Class Reference

A simple class to parse real valued functions.

Public Member Functions

- [Funct](#) ()
Default constructor.
- [Funct](#) (string v)
Constructor for a function of one variable.
- [Funct](#) (string v1, string v2)
Constructor for a function of two variables.
- [Funct](#) (string v1, string v2, string v3)
Constructor for a function of three variables.
- [Funct](#) (string v1, string v2, string v3, string v4)
Constructor for a function of four variables.
- [~Funct](#) ()
Destructor.
- [real.t operator\(\)](#) (real.t x) const
Operator () to evaluate the function with one variable x
- [real.t operator\(\)](#) (real.t x, real.t y) const
Operator () to evaluate the function with two variables x, y
- [real.t operator\(\)](#) (real.t x, real.t y, real.t z) const
Operator () to evaluate the function with three variables x, y, z
- [real.t operator\(\)](#) (real.t x, real.t y, real.t z, real.t t) const
Operator () to evaluate the function with four variables x, y, z
- void [operator=](#) (string e)
Operator =.

7.43.1 Detailed Description

A simple class to parse real valued functions.

Functions must have 1, 2, 3 or at most 4 variables.

Warning

Data in the file must be listed in the following order:

```
for x=x_0,...,x_I
  for y=y_0,...,y_J
    for z=z_0,...,z_K
      read v(x,y,z)
```

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.43.2 Constructor & Destructor Documentation

Funct (string *v*)

Constructor for a function of one variable.

Parameters

<code>in</code>	<code>v</code>	Name of the variable
-----------------	----------------	----------------------

Funct (string *v1*, string *v2*)

Constructor for a function of two variables.

Parameters

<code>in</code>	<code>v1</code>	Name of the first variable
<code>in</code>	<code>v2</code>	Name of the second variable

Funct (string *v1*, string *v2*, string *v3*)

Constructor for a function of three variables.

Parameters

<code>in</code>	<code>v1</code>	Name of the first variable
<code>in</code>	<code>v2</code>	Name of the second variable
<code>in</code>	<code>v3</code>	Name of the third variable

Funct (string *v1*, string *v2*, string *v3*, string *v4*)

Constructor for a function of four variables.

Parameters

in	<i>v1</i>	Name of the first variable
in	<i>v2</i>	Name of the second variable
in	<i>v3</i>	Name of the third variable
in	<i>v4</i>	Name of the fourth variable

7.43.3 Member Function Documentation

void operator= (string *e*)

Operator =.

Define the function by an algebraic expression

Parameters

in	<i>e</i>	Algebraic expression defining the function.
----	----------	---

7.44 Gauss Class Reference

Calculate data for Gauss integration.

Public Member Functions

- [Gauss](#) ()
Default constructor.
- [Gauss](#) (size_t np)
Constructor using number of [Gauss](#) points.
- void [setNbPoints](#) (size_t np)
Set number of integration points.
- void [setTriangle](#) ([LocalVect](#)< [real_t](#), 7 > &*w*, [LocalVect](#)< [Point](#)< [real_t](#) >, 7 > &*x*)
Choose integration on triangle (7-point formula)
- [real_t](#) *x* (size_t i) const
*Return coordinate of *i*-th Gauss-Legendre point.*
- const [Point](#)< [real_t](#) > & *xt* (size_t i) const
Return coordinates of points in the reference triangle.
- [real_t](#) *w* (size_t i) const
*Return weight of *i*-th Gauss-Legendre point.*

7.44.1 Detailed Description

Calculate data for Gauss integration.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.44.2 Constructor & Destructor Documentation

Gauss (size.t *np*)

Constructor using number of [Gauss](#) points.

Parameters

in	<i>np</i>	Number of integration points
----	-----------	------------------------------

7.44.3 Member Function Documentation

void setTriangle (LocalVect< real.t, 7 > &w, LocalVect< Point< real.t >, 7 > &x)

Choose integration on triangle (7-point formula)

If this is not selected, [Gauss](#) integration formula on $[-1, 1]$ is calculated.

Parameters

out	<i>w</i>	Array of weights of integration points
out	<i>x</i>	Array of coordinates of integration points

7.45 Grid Class Reference

To manipulate structured grids.

Public Member Functions

- [Grid](#) ()
Construct a default grid with 10 intervals in each direction.
- [Grid](#) (real.t xm, real.t xM, size.t npx)
Construct a 1-D structured grid given its extremal coordinates and number of intervals.
- [Grid](#) (real.t xm, real.t xM, real.t ym, real.t yM, size.t npx, size.t npy)
Construct a 2-D structured grid given its extremal coordinates and number of intervals.
- [Grid](#) (Point< real.t > m, Point< real.t > M, size.t npx, size.t npy)
Construct a 2-D structured grid given its extremal coordinates and number of intervals.
- [Grid](#) (real.t xm, real.t xM, real.t ym, real.t yM, real.t zm, real.t zM, size.t npx, size.t npy, size.t npz)
Construct a 3-D structured grid given its extremal coordinates and number of intervals.
- [Grid](#) (Point< real.t > m, Point< real.t > M, size.t npx, size.t npy, size.t npz)
Construct a 3-D structured grid given its extremal coordinates and number of intervals.
- void [setXMin](#) (const [Point](#)< real.t > &x)
Set min. coordinates of the domain.
- void [setXMax](#) (const [Point](#)< real.t > &x)
- void [setDomain](#) (real.t xmin, real.t xmax)
Set Dimensions of the domain: 1-D case.
- void [setDomain](#) (real.t xmin, real.t xmax, real.t ymin, real.t ymax)
Set Dimensions of the domain: 2-D case.
- void [setDomain](#) (real.t xmin, real.t xmax, real.t ymin, real.t ymax, real.t zmin, real.t zmax)
Set Dimensions of the domain: 3-D case.
- void [setDomain](#) (Point< real.t > xmin, Point< real.t > xmax)
Set Dimensions of the domain: 3-D case.
- const [Point](#)< real.t > &[getXMin](#) () const
Return min. Coordinates of the domain.
- const [Point](#)< real.t > &[getXMax](#) () const
Return max. Coordinates of the domain.

- `void setN (size_t nx, size_t ny=0, size_t nz=0)`
Set number of grid intervals in the x , y and z -directions.
- `size_t getNx () const`
Return number of grid intervals in the x -direction.
- `size_t getNy () const`
Return number of grid intervals in the y -direction.
- `size_t getNz () const`
Return number of grid intervals in the z -direction.
- `real_t getHx () const`
Return grid size in the x -direction.
- `real_t getHy () const`
Return grid size in the y -direction.
- `real_t getHz () const`
Return grid size in the z -direction.
- `Point< real_t > getCoord (size_t i) const`
Return coordinates a point with label i in a 1-D grid.
- `Point< real_t > getCoord (size_t i, size_t j) const`
Return coordinates a point with label (i, j) in a 2-D grid.
- `Point< real_t > getCoord (size_t i, size_t j, size_t k) const`
Return coordinates a point with label (i, j, k) in a 3-D grid.
- `real_t getX (size_t i) const`
Return x -coordinate of point with index i
- `real_t getY (size_t j) const`
Return y -coordinate of point with index j
- `real_t getZ (size_t k) const`
Return z -coordinate of point with index k
- `Point2D< real_t > getXY (size_t i, size_t j) const`
Return coordinates of point with indices (i, j)
- `Point< real_t > getXYZ (size_t i, size_t j, size_t k) const`
Return coordinates of point with indices (i, j, k)
- `real_t getCenter (size_t i) const`
Return coordinates of center of a 1-D cell with indices $i, i+1$
- `Point< real_t > getCenter (size_t i, size_t j) const`
Return coordinates of center of a 2-D cell with indices $(i, j), (i+1, j), (i+1, j+1), (i, j+1)$
- `Point< real_t > getCenter (size_t i, size_t j, size_t k) const`
Return coordinates of center of a 3-D cell with indices $(i, j, k), (i+1, j, k), (i+1, j+1, k), (i, j+1, k), (i, j, k+1), (i+1, j, k+1), (i+1, j+1, k+1), (i, j+1, k+1)$
- `void setCode (string exp, int code)`
Set a code for some grid points.
- `void setCode (int side, int code)`
Set a code for grid points on sides.
- `int getCode (int side) const`
Return code for a side number.
- `int getCode (size_t i, size_t j) const`
Return code for a grid point.
- `int getCode (size_t i, size_t j, size_t k) const`
Return code for a grid point.

- `size_t getDim () const`
Return space dimension.
- `void Deactivate (size_t i)`
Change state of a cell from active to inactive (1-D grid)
- `void Deactivate (size_t i, size_t j)`
Change state of a cell from active to inactive (2-D grid)
- `void Deactivate (size_t i, size_t j, size_t k)`
Change state of a cell from active to inactive (2-D grid)
- `int isActive (size_t i) const`
Say if cell is active or not (1-D grid)
- `int isActive (size_t i, size_t j) const`
Say if cell is active or not (2-D grid)
- `int isActive (size_t i, size_t j, size_t k) const`
Say if cell is active or not (3-D grid)

7.45.1 Detailed Description

To manipulate structured grids.

Author

Rachid Touzani


Copyright

GNU Lesser Public License

7.46 HelmholtzBT3 Class Reference

Builds finite element arrays for Helmholtz equations in a bounded media using 3-Node triangles.

Inheritance diagram for HelmholtzBT3:



Public Member Functions

- `HelmholtzBT3 ()`
Default Constructor.
- `HelmholtzBT3 (Mesh &ms)`
Constructor using mesh data.
- `HelmholtzBT3 (Mesh &ms, Vect< complex_t > &u)`

Constructor using mesh and solution vector.

- [~HelmholtzBT3](#) ()

Destructor.

- void [build](#) ()

Builds system of equations.

- void [LHS](#) ()

Add element Left-Hand [Side](#).

- void [BodyRHS](#) ([Vect](#)< [complex_t](#) > &f)

Add element Right-Hand [Side](#).

- void [BoundaryRHS](#) ([Vect](#)< [complex_t](#) > &f)

Add side Right-Hand [Side](#).

Additional Inherited Members

7.46.1 Detailed Description

Builds finite element arrays for Helmholtz equations in a bounded media using 3-Node triangles.

Problem being formulated in time harmonics, the solution is complex valued.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.46.2 Constructor & Destructor Documentation

HelmholtzBT3 ([Mesh](#) & *ms*)

Constructor using mesh data.

Parameters

in	<i>ms</i>	Mesh instance
--------------------	-----------	-------------------------------

HelmholtzBT3 ([Mesh](#) & *ms*, [Vect](#)< [complex_t](#) > & *u*)

Constructor using mesh and solution vector.


Parameters

in	<i>ms</i>	Mesh instance
in , out	<i>u</i>	Vect instance containing solution

7.47 Hexa8 Class Reference

Defines a three-dimensional 8-node hexahedral finite element using Q1-isoparametric interpolation.

Inheritance diagram for Hexa8:



Public Member Functions

- **Hexa8** ()
Default Constructor.
- **Hexa8** (const **Element** *el)
*Constructor when data of **Element** el are given.*
- **~Hexa8** ()
Destructor.
- void **setLocal** (const **Point**< **real.t** > &s)
Initialize local point coordinates in element.
- void **atGauss** (int n, std::vector< **Point**< **real.t** > > &dsh, std::vector< **real.t** > &w)
Calculate shape function derivatives and integration weights.
- void **atGauss** (int n, std::vector< **real.t** > &sh, std::vector< **real.t** > &w)
Calculate shape functions and integration weights.
- **real.t** **getMaxEdgeLength** () const
Return maximal edge length.
- **real.t** **getMinEdgeLength** () const
Return minimal edge length.
- **Point**< **real.t** > **Grad** (const **LocalVect**< **real.t**, 8 > &u, const **Point**< **real.t** > &s)
Return gradient of a function defined at element nodes.

7.47.1 Detailed Description

Defines a three-dimensional 8-node hexahedral finite element using Q1-isoparametric interpolation.

The reference element is the cube $[-1, 1] \times [-1, 1] \times [-1, 1]$. The user must take care to the fact that determinant of jacobian and other quantities depend on the point in the reference element where they are calculated. For this, before any utilization of shape functions or jacobian, function **getLocal(s)** must be invoked.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.47.2 Member Function Documentation

void setLocal (const **Point**< **real.t** > & s)

Initialize local point coordinates in element.

Parameters

<code>in</code>	<code>s</code>	Point in the reference element This function computes jacobian, shape functions and their partial derivatives at <code>s</code> . Other member functions only return these values.
-----------------	----------------	--

void atGauss (int *n*, std::vector< Point< real.t > > & *dsh*, std::vector< real.t > & *w*)

Calculate shape function derivatives and integration weights.

Parameters

<code>in</code>	<code>n</code>	Number of Gauss-Legendre integration points in each direction
<code>in</code>	<code>dsh</code>	Vector of shape function derivatives at the Gauss points
<code>in</code>	<code>w</code>	Weights of integration formula at Gauss points

void atGauss (int *n*, std::vector< real.t > & *sh*, std::vector< real.t > & *w*)

Calculate shape functions and integration weights.

Parameters

<code>in</code>	<code>n</code>	Number of Gauss-Legendre integration points in each direction
<code>in</code>	<code>sh</code>	Vector of shape functions at the Gauss points
<code>in</code>	<code>w</code>	Weights of integration formula at Gauss points

Point<real.t> Grad (const LocalVect< real.t, 8 > & *u*, const Point< real.t > & *s*)

Return gradient of a function defined at element nodes.

Parameters

<code>in</code>	<code>u</code>	Vector of values at nodes
<code>in</code>	<code>s</code>	Local coordinates (in $[-1,1] \times [-1,1] \times [-1,1]$) of point where the gradient is evaluated

Returns

Value of gradient


Note

If the derivatives of shape functions were not computed before calling this function (by calling `setLocal`), this function will compute them

7.48 ICPG1D Class Reference

Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 1-D.

Inheritance diagram for ICPG1D:



Public Member Functions

- **ICPG1D** (**Mesh** &ms)
*Constructor using **Mesh** instance.*
- **ICPG1D** (**Mesh** &ms, **Vect**< **real.t** > &r, **Vect**< **real.t** > &v, **Vect**< **real.t** > &p)
Constructor using mesh and initial data.
- **~ICPG1D** ()
Destructor.
- void **setReconstruction** ()
*Set reconstruction from class **Muscl**.*
- **real.t** **runOneTimeStep** ()
Advance one time step.
- void **Forward** (const **Vect**< **real.t** > &flux, **Vect**< **real.t** > &field)
Add flux to field.
- void **setSolver** (**SolverType** solver)
Choose solver type.
- void **setGamma** (**real.t** gamma)
Set value of constant Gamma for gases.
- void **setCv** (**real.t** Cv)
Set value of Cv (specific heat at constant volume)
- void **setCp** (**real.t** Cp)
Set value of Cp (specific heat at constant pressure)
- void **setKappa** (**real.t** Kappa)
Set value of constant Kappa.
- **real.t** **getGamma** () const
Return value of constant Gamma.
- **real.t** **getCv** () const
Return value of Cv (specific heat at constant volume)
- **real.t** **getCp** () const
Return value of Cp (specific heat at constant pressure)
- **real.t** **getKappa** () const
Return value of constant Kappa.
- void **getMomentum** (**Vect**< **real.t** > &m) const
Get vector of momentum at elements.
- void **getInternalEnergy** (**Vect**< **real.t** > &ie) const
Get vector of internal energy at elements.
- void **getTotalEnergy** (**Vect**< **real.t** > &te) const
Get vector of total energy at elements.
- void **getSoundSpeed** (**Vect**< **real.t** > &s) const

- Get vector of sound speed at elements.*
- void `getMach` (`Vect< real.t > &m`) const
- Get vector of elementwise Mach number.*
- void `setInitialCondition_shock_tube` (const `LocalVect< real.t, 3 > &BcG`, const `LocalVect< real.t, 3 > &BcD`, `real.t x0`)
- Initial condition corresponding to the shock tube.*
- void `setInitialCondition` (const `LocalVect< real.t, 3 > &u`)
- A constant initial condition.*
- void `setBC` (const `Side &sd`, `real.t u`)
- Assign a boundary condition as a constant to a given side.*
- void `setBC` (int code, `real.t a`)
- Assign a boundary condition value.*
- void `setBC` (`real.t a`)
- Assign a boundary condition value.*
- void `setBC` (const `Side &sd`, const `LocalVect< real.t, 3 > &u`)
- Assign a Dirichlet boundary condition vector.*
- void `setBC` (int code, const `LocalVect< real.t, 3 > &U`)
- Assign a Dirichlet boundary condition vector.*
- void `setBC` (const `LocalVect< real.t, 3 > &u`)
- Assign a Dirichlet boundary condition vector.*
- void `setInOutflowBC` (const `Side &sd`, const `LocalVect< real.t, 3 > &u`)
- Impose a constant inflow or outflow boundary condition on a given side.*
- void `setInOutflowBC` (int code, const `LocalVect< real.t, 3 > &u`)
- Impose a constant inflow or outflow boundary condition on sides with a given code.*
- void `setInOutflowBC` (const `LocalVect< real.t, 3 > &u`)
- Impose a constant inflow or outflow boundary condition on boundary sides.*

Additional Inherited Members

7.48.1 Detailed Description

Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 1-D.
Solution method is a second-order MUSCL Finite Volume scheme

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.48.2 Constructor & Destructor Documentation

`ICPG1D (Mesh & ms, Vect< real.t > & r, Vect< real.t > & v, Vect< real.t > & p)`

Constructor using mesh and initial data.

Parameters

in	<i>ms</i>	Reference to Mesh instance
in	<i>r</i>	Vector containing initial (elementwise) density
in	<i>v</i>	Vector containing initial (elementwise) velocity
in	<i>p</i>	Vector containing initial (elementwise) pressure

7.48.3 Member Function Documentation

void Forward (const Vect< real_t > & flux, Vect< real_t > & field)

Add flux to field.

If this function is used, the user must call getFlux himself

Parameters

in	<i>flux</i>	Vector containing fluxes at sides (points)
out	<i>field</i>	Vector containing solution vector

void getMomentum (Vect< real_t > & m) const

Get vector of momentum at elements.

Parameters

in,out	<i>m</i>	Vect instance that contains on output element momentum
--------	----------	--

void getInternalEnergy (Vect< real_t > & ie) const

Get vector of internal energy at elements.

Parameters

in,out	<i>ie</i>	Vect instance that contains on output element internal energy
--------	-----------	---

void getTotalEnergy (Vect< real_t > & te) const

Get vector of total energy at elements.

Parameters

in,out	<i>te</i>	Vect instance that contains on output element total energy
--------	-----------	--

void getSoundSpeed (Vect< real_t > & s) const

Get vector of sound speed at elements.

Parameters

in,out	<i>s</i>	Vect instance that contains on output element sound speed
--------	----------	---

void getMach (Vect< real_t > & m) const

Get vector of elementwise Mach number.

Parameters

in,out	<i>m</i>	Vect instance that contains on output element Mach number
--------	----------	---

void setInitialCondition (const LocalVect< real_t, 3 > & u)

A constant initial condition.

Parameters

in	<i>u</i>	LocalVect instance containing density, velocity and pressure
----	----------	--

void setBC (const Side & sd, real_t u)

Assign a boundary condition as a constant to a given side.

Parameters

in	<i>sd</i>	Side to which the value is assigned
in	<i>u</i>	Value to assign

void setBC (int code, real_t a)

Assign a boundary condition value.

Parameters

in	<i>code</i>	Code value to which boundary condition is assigned
in	<i>a</i>	Value to assign to sides that have code code

void setBC (real_t a)

Assign a boundary condition value.

Parameters

in	<i>a</i>	Value to assign to all boundary sides
----	----------	---------------------------------------

void setBC (const Side & sd, const LocalVect< real_t, 3 > & u)

Assign a Dirichlet boundary condition vector.

Parameters

in	<i>sd</i>	Side instance to which the values are assigned
in	<i>u</i>	LocalVect instance that contains values to assign to the side

void setBC (int code, const LocalVect< real_t, 3 > & U)

Assign a Dirichlet boundary condition vector.

Parameters

in	<i>code</i>	Side code for which the values are assigned
----	-------------	---

in	u	LocalVect instance that contains values to assign to sides with code <i>code</i>
----	-----	--

void setBC (const LocalVect< real_t, 3 > & u)

Assign a Dirichlet boundary condition vector.

Parameters

in	u	LocalVect instance that contains values to assign to all boundary sides
----	-----	---

void setInOutflowBC (const Side & sd , const LocalVect< real_t, 3 > & u)

Impose a constant inflow or outflow boundary condition on a given side.

Parameters

in	sd	Instance of Side on which the condition is prescribed
in	u	LocalVect instance that contains values to assign to the side

void setInOutflowBC (int *code*, const LocalVect< real_t, 3 > & u)

Impose a constant inflow or outflow boundary condition on sides with a given code.

Parameters

in	<i>code</i>	Value of code for which the condition is prescribed
in	u	LocalVect instance that contains values to assign to the sides

void setInOutflowBC (const LocalVect< real_t, 3 > & u)

Impose a constant inflow or outflow boundary condition on boundary sides.


Parameters

in	u	LocalVect instance that contains values to assign to the sides
----	-----	--

7.49 ICPG2DT Class Reference

Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 2-D.

Inheritance diagram for ICPG2DT:



Public Member Functions

- [ICPG2DT](#) ([Mesh](#) &ms)
Constructor using mesh instance.
- [ICPG2DT](#) ([Mesh](#) &ms, [Vect](#)< [real_t](#) > &r, [Vect](#)< [real_t](#) > &v, [Vect](#)< [real_t](#) > &p)
Constructor using mesh and initial data.
- [~ICPG2DT](#) ()
Destructor.
- void [setReconstruction](#) ()
Reconstruct.
- [real_t](#) [runOneTimeStep](#) ()
Advance one time step.
- void [Forward](#) (const [Vect](#)< [real_t](#) > &Flux, [Vect](#)< [real_t](#) > &Field)
Add Flux to Field.
- [real_t](#) [getFlux](#) ()
Get flux.
- void [setSolver](#) ([SolverType](#) s)
Choose solver.
- void [setGamma](#) ([real_t](#) gamma)
Set Gamma value.
- void [setCv](#) ([real_t](#) Cv)
Set value of heat capacity at constant volume.
- void [setCp](#) ([real_t](#) Cp)
Set value of heat capacity at constant pressure.
- void [setKappa](#) ([real_t](#) Kappa)
Set Kappa value.
- [real_t](#) [getGamma](#) () const
Return value of Gamma.
- [real_t](#) [getCv](#) () const
Return value of heat capacity at constant volume.
- [real_t](#) [getCp](#) () const
Return value of heat capacity at constant pressure.
- [real_t](#) [getKappa](#) () const
Return value of Kappa.
- [Mesh](#) & [getMesh](#) ()
Return reference to mesh instance.
- void [getMomentum](#) ([Vect](#)< [real_t](#) > &m) const
Calculate elementwise momentum.
- void [getInternalEnergy](#) ([Vect](#)< [real_t](#) > &e) const
Calculate elementwise internal energy.
- void [getTotalEnergy](#) ([Vect](#)< [real_t](#) > &e) const
Return elementwise total energy.
- void [getSoundSpeed](#) ([Vect](#)< [real_t](#) > &s) const
Return elementwise sound speed.
- void [getMach](#) ([Vect](#)< [real_t](#) > &m) const
Return elementwise Mach number.

- void `setInitialConditionShockTube` (const `LocalVect< real_t, 4 >` &BcL, const `LocalVect< real_t, 4 >` &BcR, `real_t` x0)
Set initial condition for the schock tube problem.
- void `setInitialCondition` (const `LocalVect< real_t, 4 >` &u)
Set initial condition.
- void `setBC` (const `Side` &sd, `real_t` a)
Prescribe a constant boundary condition at given side.
- void `setBC` (int code, `real_t` a)
Prescribe a constant boundary condition for a given code.
- void `setBC` (`real_t` u)
Prescribe a constant boundary condition on all boundary sides.
- void `setBC` (const `Side` &sd, const `LocalVect< real_t, 4 >` &u)
Prescribe a constant boundary condition at a given side.
- void `setBC` (int code, const `LocalVect< real_t, 4 >` &u)
Prescribe a constant boundary condition for a given code.
- void `setBC` (const `LocalVect< real_t, 4 >` &u)
Prescribe a constant boundary condition at all boundary sides.
- `real_t` `getR` (size_t i) const
Return density at given element label.
- `real_t` `getV` (size_t i, size_t j) const
- `real_t` `getP` (size_t i) const
Return pressure at given element label.

Additional Inherited Members

7.49.1 Detailed Description

Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 2-D.
Solution method is a second-order MUSCL Finite Volume scheme on triangles

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.49.2 Constructor & Destructor Documentation

`ICPG2DT (Mesh & ms, Vect< real_t > & r, Vect< real_t > & v, Vect< real_t > & p)`

Constructor using mesh and initial data.

Parameters

in	<i>ms</i>	<code>Mesh</code> instance
in	<i>r</i>	Initial density vector (as instance of <code>Vect</code>)

in	v	Initial velocity vector (as instance of Vect)
in	p	Initial pressure vector (as instance of Vect)

7.49.3 Member Function Documentation

void setReconstruction ()

Reconstruct.

exit(3) if reconstruction fails

void Forward (const Vect< real.t > & Flux, Vect< real.t > & Field)

Add Flux to Field.

If this function is used, the function getFlux must be called

void setSolver (SolverType s)

Choose solver.

Parameters

in	s	Index of solver in the enumerated variable SolverType Available values are: ROE_SOLVER, VFROE_SOLVER, LF_SOLVER, RUSANOV_SOLVER, HLL_SOLVER, HLLC_SOLVER, MAX_SOLVER
----	-----	--

void setBC (const Side & sd, real.t a)

Prescribe a constant boundary condition at given side.

Parameters

in	sd	Reference to Side instance
in	a	Value to prescribe

void setBC (int code, real.t a)

Prescribe a constant boundary condition for a given code.

Parameters

in	$code$	Code for which value is imposed
in	a	Value to prescribe

void setBC (real.t u)

Prescribe a constant boundary condition on all boundary sides.

Parameters

in	u	Value to prescribe
----	-----	--------------------

void setBC (const Side & sd, const LocalVect< real.t, 4 > & u)

Prescribe a constant boundary condition at a given side.

Parameters

in	<i>sd</i>	Reference to Side instance
in	<i>u</i>	Vector (instance of class LocalVect) with as components the constant values to prescribe for the four fields (r, vx, vy, p)

void setBC (int *code*, const LocalVect< real_t, 4 > & *u*)

Prescribe a constant boundary condition for a given code.

Parameters

in	<i>code</i>	Code for which value is imposed
in	<i>u</i>	Vector (instance of class LocalVect) with as components the constant values to prescribe for the four fields (r, vx, vy, p)

void setBC (const LocalVect< real_t, 4 > & *u*)

Prescribe a constant boundary condition at all boundary sides.

Parameters

in	<i>u</i>	Vector (instance of class LocalVect) with as components the constant values to prescribe for the four fields (r, vx, vy, p)
----	----------	--

real_t getR (size_t *i*) const

Return density at given element label.

Parameters

in	<i>i</i>	Element label
----	----------	-------------------------------

real_t getV (size_t *i*, size_t *j*) const

Return velocity at given element label

Parameters

in	<i>i</i>	Element label
in	<i>j</i>	component index (1 or 2)

real_t getP (size_t *i*) const

Return pressure at given element label.


Parameters

in	<i>i</i>	Element label
----	----------	-------------------------------

7.50 ICPG3DT Class Reference

Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 3-D.

Inheritance diagram for ICPG3DT:



Public Member Functions

- [ICPG3DT](#) ([Mesh](#) &ms)
Constructor using mesh data.
- [ICPG3DT](#) ([Mesh](#) &ms, [Vect](#)< [real_t](#) > &r, [Vect](#)< [real_t](#) > &v, [Vect](#)< [real_t](#) > &p)
Constructor using mesh and initial data.
- [~ICPG3DT](#) ()
Destructor.
- void [setReconstruction](#) ()
Reconstruct.
- [real_t](#) [runOneTimeStep](#) ()
Advance one time step.
- void [Forward](#) (const [Vect](#)< [real_t](#) > &flux, [Vect](#)< [real_t](#) > &field)
Add flux to field.
- [real_t](#) [getFlux](#) ()
Return flux.
- void [setSolver](#) ([SolverType](#) solver)
Choose solver.
- void [setReferenceLength](#) ([real_t](#) dx)
Assign a reference length.
- void [setTimeStep](#) ([real_t](#) dt)
Assign a time step.
- void [setCFL](#) ([real_t](#) CFL)
Assign CFL value.
- [real_t](#) [getReferenceLength](#) () const
Return reference length.
- [real_t](#) [getTimeStep](#) () const
Return time step.
- [real_t](#) [getCFL](#) () const
Return CFL.
- void [setGamma](#) ([real_t](#) gamma)
Set γ value.
- void [setCv](#) ([real_t](#) Cv)
Set value of C_v (Heat capacity at constant volume)
- void [setCp](#) ([real_t](#) Cp)
Set value of C_p (Heat capacity at constant pressure)
- void [setKappa](#) ([real_t](#) Kappa)
Set Kappa value.
- [real_t](#) [getGamma](#) () const

- Return value of γ .*

 - `real_t getCv () const`
Return value of C_v (Heat capacity at constant volume)
 - `real_t getCp () const`
Return value of C_p (Heat capacity at constant pressure)
 - `real_t getKappa () const`
Return value of κ .
 - `Mesh & getMesh ()`
Return reference to mesh instance.
 - `Mesh * getPtrMesh ()`
Return pointer to mesh.
 - `void getMomentum (Vect< real_t > &m) const`
Calculate elementwise momentum.
 - `void getInternalEnergy (Vect< real_t > &e) const`
Calculate elementwise internal energy.
 - `void getTotalEnergy (Vect< real_t > &e) const`
Return elementwise total energy.
 - `void getSoundSpeed (Vect< real_t > &s) const`
Return elementwise sound speed.
 - `void getMach (Vect< real_t > &m) const`
Return elementwise Mach number.
 - `void setInitialConditionShockTube (const LocalVect< real_t, 5 > &BcG, const LocalVect< real_t, 5 > &BcD, real_t x0)`
Set initial condition for the schock tube problem.
 - `void setInitialCondition (const LocalVect< real_t, 5 > &u)`
Set initial condition.

Additional Inherited Members

7.50.1 Detailed Description

Class to solve the Inviscid compressible fluid flows (Euler equations) for perfect gas in 3-D.
 Solution method is a second-order MUSCL Finite Volume scheme with tetrahedra

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.50.2 Constructor & Destructor Documentation

`ICPG3DT (Mesh & ms)`

Constructor using mesh data.

Parameters

in	<i>ms</i>	Mesh instance
----	-----------	-------------------------------

ICPG3DT ([Mesh](#) & *ms*, Vect< real.t > & *r*, Vect< real.t > & *v*, Vect< real.t > & *p*)

Constructor using mesh and initial data.

Parameters

in	<i>ms</i>	Mesh instance
in	<i>r</i>	Elementwise initial density vector (as instance of Element Vect)
in	<i>v</i>	Elementwise initial velocity vector (as instance of Element Vect)
in	<i>p</i>	Elementwise initial pressure vector (as instance of Element Vect)

7.50.3 Member Function Documentation

void setReconstruction ()

Reconstruct.

exit(3) if reconstruction failed

7.51 Integration Class Reference

Class for numerical integration methods.

Public Member Functions

- [Integration](#) ()
Default constructor.
- [Integration](#) (real.t low, real.t high, function< real.t(real.t)> const &f, [IntegrationScheme](#) s, real.t error)
Constructor.
- [~Integration](#) ()
Destructor.
- void [setFunction](#) (function< real.t(real.t)> const &f)
Define function to integrate numerically.
- void [setScheme](#) ([IntegrationScheme](#) s)
Set time integration scheme.
- void [setTriangle](#) (real.t x1, real.t y1, real.t x2, real.t y2, real.t x3, real.t y3)
Define integration domain as a quadrilateral.
- void [setQuadrilateral](#) (real.t x1, real.t y1, real.t x2, real.t y2, real.t x3, real.t y3, real.t x4, real.t y4)
Define integration domain as a quadrilateral.
- real.t [run](#) ()
Run numerical integration.

7.51.1 Detailed Description

Class for numerical integration methods.

Class NumInt defines and stores numerical integration data

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.51.2 Constructor & Destructor Documentation

Integration (*real.t low*, *real.t high*, *function*< *real.t*(*real.t*)> *const &f*, *IntegrationScheme s*, *real.t error*)

Constructor.

Parameters

<i>in</i>	<i>low</i>	Lower value of integration interval
<i>in</i>	<i>high</i>	Upper value of integration interval
<i>in</i>	<i>f</i>	Function to integrate
<i>in</i>	<i>s</i>	<p>Integration scheme. To choose among enumerated values:</p> <ul style="list-style-type: none"> • LEFT_RECTANGLE: • RIGHT_RECTANGLE: • MID_RECTANGLE: • TRAPEZOIDAL: • SIMPSON: • GAUSS_LEGENDRE:
<i>in</i>	<i>error</i>	

7.51.3 Member Function Documentation

void setFunction (*function*< *real.t*(*real.t*)> *const &f*)

Define function to integrate numerically.

Parameters

<i>in</i>	<i>f</i>	Function to integrate
-----------	----------	-----------------------

void setScheme (*IntegrationScheme s*)

Set time inegration scheme.

Parameters

in	s	Scheme to choose among enumerated values: <ul style="list-style-type: none"> • LEFT_RECTANGLE: • RIGHT_RECTANGLE: • MID_RECTANGLE: • TRAPEZOIDAL: • SIMPSON: • GAUSS_LEGENDRE:
----	---	--

void setTriangle (real_t x1, real_t y1, real_t x2, real_t y2, real_t x3, real_t y3)

Define integration domain as a quadrilateral.

Parameters

in	x1	x-coordinate of first vertex of triangle
in	y1	y-coordinate of first vertex of triangle
in	x2	x-coordinate of second vertex of triangle
in	y2	y-coordinate of second vertex of triangle
in	x3	x-coordinate of third vertex of triangle
in	y3	y-coordinate of third vertex of triangle

void setQuadrilateral (real_t x1, real_t y1, real_t x2, real_t y2, real_t x3, real_t y3, real_t x4, real_t y4)

Define integration domain as a quadrilateral.

Parameters

in	x1	x-coordinate of first vertex of quadrilateral
in	y1	y-coordinate of first vertex of quadrilateral
in	x2	x-coordinate of second vertex of quadrilateral
in	y2	y-coordinate of second vertex of quadrilateral
in	x3	x-coordinate of third vertex of quadrilateral
in	y3	y-coordinate of third vertex of quadrilateral
in	x4	x-coordinate of fourth vertex of quadrilateral
in	y4	y-coordinate of fourth vertex of quadrilateral

real_t run ()

Run numerical integration.

Returns

Computed approximate value of integral

7.52 IOField Class Reference

Enables working with files in the XML Format.

Inherits XMLParser.

Public Types

- enum [AccessType](#)
Enumerated values for file access type.

Public Member Functions

- [IOField](#) ()
Default constructor.
- [IOField](#) (const string &file, [AccessType](#) access, bool compact=true)
Constructor using file name.
- [IOField](#) (const string &mesh_file, const string &file, [Mesh](#) &ms, [AccessType](#) access, bool compact=true)
Constructor using file name, mesh file and mesh.
- [IOField](#) (const string &file, [Mesh](#) &ms, [AccessType](#) access, bool compact=true)
Constructor using file name and mesh.
- [IOField](#) (const string &file, [AccessType](#) access, const string &name)
Constructor using file name and field name.
- [~IOField](#) ()
Destructor.
- void [setMeshFile](#) (const string &file)
Set mesh file.
- void [open](#) ()
Open file.
- void [open](#) (const string &file, [AccessType](#) access)
Open file.
- void [close](#) ()
Close file.
- void [put](#) ([Mesh](#) &ms)
Store mesh in file.
- void [put](#) (const [Vect](#)< [real_t](#) > &v)
Store [Vect](#) instance v in file.
- [real_t](#) [get](#) ([Vect](#)< [real_t](#) > &v)
Get [Vect](#) v instance from file.
- int [get](#) ([Vect](#)< [real_t](#) > &v, const string &name)
Get [Vect](#) v instance from file if the field has the given name.
- int [get](#) ([DMatrix](#)< [real_t](#) > &A, const string &name)
Get [DMatrix](#) A instance from file if the field has the given name.
- int [get](#) ([DSMatrix](#)< [real_t](#) > &A, const string &name)
Get [DSMatrix](#) A instance from file if the field has the given name.
- int [get](#) ([Vect](#)< [real_t](#) > &v, [real_t](#) t)
Get [Vect](#) v instance from file corresponding to a specific time value.
- void [saveGMSH](#) (string output_file, string mesh_file)
Save field vectors in a file using [GMSH](#) format.

7.52.1 Detailed Description

Enables working with files in the XML Format.

This class has methods to store vectors in files and read from files.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.53 IPF Class Reference

To read project parameters from a file in [IPF](#) format.

Public Member Functions

- [IPF](#) ()
Default constructor.
- [IPF](#) (const string &file)
Constructor that gives the data file name.
- [IPF](#) (const string &prog, const string &file)
Constructor that reads parameters in file `file` and prints header information for the calling program `prog`. It reads parameters in [IPF](#) Format from this file.
- [~IPF](#) ()
Destructor.
- [real_t](#) [getDisplay](#) ()
Display acquired parameters.
- [int](#) [getVerbose](#) ()
*Return parameter read using keyword **Verbose**.*
- [int](#) [getOutput](#) () const
*Return parameter read using keyword **Output**.*
- [int](#) [getSave](#) () const
*Return parameter read using keyword **Save**.*
- [int](#) [getPlot](#) () const
*Return parameter read using keyword **Plot**.*
- [int](#) [getBC](#) () const
*Return parameter read using keyword **BC**.*
- [int](#) [getBF](#) () const
*Return parameter read using keyword **BF**.*
- [int](#) [getSF](#) () const
*Return parameter read using keyword **SF**.*
- [int](#) [getInit](#) () const
*Return parameter read using keyword **Init**.*
- [int](#) [getData](#) () const
*Return parameter read using keyword **Data**.*
- [size_t](#) [getNbSteps](#) () const
*Return parameter read using keyword **NbSteps**.*

- `size_t getNbIter ()` const
Return parameter read using keyword *NbIter*.
- `real_t getTimeStep ()` const
Return parameter read using keyword *TimeStep*.
- `real_t getMaxTime ()` const
Return parameter read using keyword *MaxTime*.
- `real_t getTolerance ()` const
Return parameter read using keyword *Tolerance*.
- `int getIntPar (size_t n=1)` const
Return *n*-th parameter read using keyword *IntPar*.
- `string getStringPar (size_t n=1)` const
Return *n*-th parameter read using keyword *StringPar*.
- `real_t getDoublePar (size_t n=1)` const
Return *n*-th parameter read using keyword *DoublePar*.
- `Point< real_t > getPointDoublePar (size_t n=1)` const
Return *n*-th parameter read using keyword *PointDoublePar*.
- `complex_t getComplexPar (size_t n=1)` const
Return *n*-th parameter read using keyword *StringPar*.
- `string getString (const string &label)` const
Return parameter corresponding to a given label, when its value is a string.
- `string getString (const string &label, string def)` const
Return parameter corresponding to a given label, when its value is a string.
- `int getInteger (const string &label)` const
Return parameter corresponding to a given label, when its value is an integer.
- `int getInteger (const string &label, int def)` const
Return parameter corresponding to a given label, when its value is an integer.
- `real_t getDouble (const string &label)` const
Return parameter corresponding to a given label, when its value is a *real_t*.
- `real_t getDouble (const string &label, real_t def)` const
Return parameter corresponding to a given label, when its value is a *real_t*.
- `complex_t getComplex (const string &label)` const
Return parameter corresponding to a given label, when its value is a complex number.
- `complex_t getComplex (const string &label, complex_t def)` const
Return parameter corresponding to a given label, when its value is a complex number.
- `int contains (const string &label)` const
check if the project file contains a given parameter
- `void get (const string &label, Vect< real_t > &a)` const
Read an array of real values, corresponding to a given label.
- `real_t getArraySize (const string &label, size_t j)` const
Return an array entry for a given label.
- `void get (const string &label, int &a)` const
Return integer parameter corresponding to a given label.
- `void get (const string &label, real_t &a)` const
Return real parameter corresponding to a given label.
- `void get (const string &label, complex_t &a)` const
Return complex parameter corresponding to a given label.

- void `get` (const string &label, string &a) const
Return string parameter corresponding to a given label.
- string `getProject` () const
Return parameter read using keyword **Project**.
- string `getDomainFile` () const
Return parameter using keyword **Mesh**.
- string `getMeshFile` (size_t i=1) const
Return *i*-th parameter read using keyword **mesh_file**.
- string `getInitFile` () const
Return parameter read using keyword **InitFile**.
- string `getRestartFile` () const
Return parameter read using keyword **RestartFile**.
- string `getBCFile` () const
Return parameter read using keyword **BCFile**.
- string `getBFFFile` () const
Return parameter read using keyword **BFFFile**.
- string `getSFFFile` () const
Return parameter read using keyword **SFFFile**.
- string `getSaveFile` () const
Return parameter read using keyword **SaveFile**.
- string `getPlotFile` (int i=1) const
Return *i*-th parameter read using keyword **PlotFile**.
- string `getPrescriptionFile` (int i=1) const
Return parameter read using keyword **DataFile**.
- string `getAuxFile` (size_t i=1) const
Return *i*-th parameter read using keyword **Auxfile**.
- string `getDensity` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for density function.
- string `getElectricConductivity` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for electric conductivity.
- string `getElectricPermittivity` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for electric permittivity.
- string `getMagneticPermeability` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for magnetic permeability.
- string `getPoissonRatio` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for Poisson ratio.
- string `getThermalConductivity` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for thermal conductivity.
- string `getRhoCp` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for density * specific heat.
- string `getViscosity` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for viscosity.
- string `getYoungModulus` () const
Return expression (to be parsed, function of *x*, *y*, *z*, *t*) for Young's modulus.

7.53.1 Detailed Description

To read project parameters from a file in [IPF](#) format.

This class can be used to acquire various parameters from a parameter file of [IPF](#) (Input Project File). The declaration of an instance of this class avoids reading data in your main program. The acquired parameters are retrieved through information members of the class. Note that all the parameters have default values

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.53.2 Constructor & Destructor Documentation

IPF (const string & *file*)

Constructor that gives the data file name.

It reads parameters in [IPF](#) Format from this file.

7.53.3 Member Function Documentation

int getOutput () const

Return parameter read using keyword **Output**.

This parameter can be used to control output behavior in a program.

int getSave () const

Return parameter read using keyword **Save**.

This parameter can be used to control result saving in a program (*e.g.* for a restarting purpose).

int getPlot () const

Return parameter read using keyword **Plot**.

This parameter can be used to control result saving for plotting in a program.

int getBC () const

Return parameter read using keyword **BC**.

This parameter can be used to set a boundary condition flag.

int getBF () const

Return parameter read using keyword **BF**.

This parameter can be used to set a body force flag.

int getSF () const

Return parameter read using keyword **SF**.

This parameter can be used to set a surface force flag.

int getInit () const

Return parameter read using keyword **Init**.

This parameter can be used to set an initial data flag.

int getData () const

Return parameter read using keyword **Data**.

This parameter can be used to set a various data flag.

size_t getNbSteps () const

Return parameter read using keyword **NbSteps**.

This parameter can be used to read a number of time steps.

size_t getNbIter () const

Return parameter read using keyword **NbIter**.

This parameter can be used to read a number of iterations.

real_t getTimeStep () const

Return parameter read using keyword **TimeStep**.

This parameter can be used to read a time step value.

real_t getMaxTime () const

Return parameter read using keyword **MaxTime**.

This parameter can be used to read a maximum time value.

real_t getTolerance () const

Return parameter read using keyword **Tolerance**.

This parameter can be used to read a tolerance value to control convergence.

int getIntPar (size_t n = 1) const

Return n -th parameter read using keyword **IntPar**

Here we have at most 20 integer extra parameters that can be used for any purpose. Default value for n is 1

string getStringPar (size_t n = 1) const

Return n -th parameter read using keyword **StringPar**.

Here we have at most 20 integer extra parameters that can be used for any purpose. Default value for n is 1

real_t getDoublePar (size_t n = 1) const

Return n -th parameter read using keyword **DoublePar**.

Here we have at most 20 integer extra parameters that can be used for any purpose. Default value for n is 1

Point<real_t> getPointDoublePar (size_t n = 1) const

Return n-th parameter read using keyword **PointDoublePar**.

Here we have at most 20 integer extra parameters that can be used for any purpose. Default value for n is 1

complex_t getComplexPar (size_t n = 1) const

Return n-th parameter read using keyword **StringPar**.

Here we have at most 20 integer extra parameters that can be used for any purpose. Default value for n is 1

string getString (const string & label) const

Return parameter corresponding to a given label, when its value is a string.

Parameters

in	<i>label</i>	Label that identifies the string (read from input file) If this label is not found an error message is displayed and program stops
-----------	--------------	--

string getString (const string & label, string def) const

Return parameter corresponding to a given label, when its value is a string.

Case where a default value is provided

Parameters

in	<i>label</i>	Label that identifies the string (read from input file)
in	<i>def</i>	Default value: Value to assign if the sought parameter is not found

int getInteger (const string & label) const

Return parameter corresponding to a given label, when its value is an integer.

Parameters

in	<i>label</i>	Label that identifies the integer number (read from input file) If this label is not found an error message is displayed and program stops
-----------	--------------	--

int getInteger (const string & label, int def) const

Return parameter corresponding to a given label, when its value is an integer.

Case where a default value is provided

Parameters

in	<i>label</i>	Label that identifies the integer number (read from input file).
in	<i>def</i>	Default value: Value to assign if the sought parameter is not found

real_t getDouble (const string & label) const

Return parameter corresponding to a given label, when its value is a real_t.

Parameters

in	<i>label</i>	Label that identifies the real number (read from input file). If this label is not found an error message is displayed and program stops.
-----------	--------------	---

real_t getDouble (const string & label, real_t def) const

Return parameter corresponding to a given label, when its value is a real_t.

Case where a default value is provided

Parameters

in	<i>label</i>	Label that identifies the real number (read from input file)
in	<i>def</i>	Default value: Value to assign if the sought parameter is not found

complex_t getComplex (const string & label) const

Return parameter corresponding to a given label, when its value is a complex number.

Parameters

in	<i>label</i>	Label that identifies the complex number (read from input file) If this label is not found an error message is displayed and program stops
-----------	--------------	--

complex_t getComplex (const string & label, complex_t def) const

Return parameter corresponding to a given label, when its value is a complex number.

Case where a default value is provided

Parameters

in	<i>label</i>	Label that identifies the complex number (read from input file)
in	<i>def</i>	Default value: Value to assign if the sought parameter is not found

int contains (const string & label) const

check if the project file contains a given parameter

Parameters

in	<i>label</i>	Label that identifies the label to seek in file
-----------	--------------	---

Returns

0 if the parameter is not found, n if the parameter is found, where n is the parameter index in the parameter list

void get (const string & label, Vect< real_t > & a) const

Read an array of real values, corresponding to a given label.

Parameters

in	<i>label</i>	Label that identifies the array (read from input file).
in	<i>a</i>	Vector that contain the array. The vector is properly resized before filling.

Remarks

If this label is not found an error message is displayed.

real_t getArraySize (const string & *label*, size_t *j*) const

Return an array entry for a given label.

Parameters

in	<i>label</i>	Label that identifies the array (read from input file).
in	<i>j</i>	Index of entry in the array (Starting from 1)

Remarks

If this label is not found an error message is displayed and program stops.

void get (const string & *label*, int & *a*) const

Return integer parameter corresponding to a given label.

Parameters

in	<i>label</i>	Label that identifies the integer number (read from input file).
out	<i>a</i>	Returned value. If this label is not found an error message is displayed and program stops. Note: This member function can be used instead of getInteger

void get (const string & *label*, real_t & *a*) const

Return real parameter corresponding to a given label.

Parameters

in	<i>label</i>	Label that identifies the real (real_t) number (read from input file).
out	<i>a</i>	Returned value. If this label is not found an error message is displayed and program stops. Note: This member function can be used instead of getReal_T

void get (const string & *label*, complex_t & *a*) const

Return complex parameter corresponding to a given label.

Parameters

in	<i>label</i>	Label that identifies the complex number (read from input file).
out	<i>a</i>	Returned value. If this label is not found an error message is displayed and program stops.

void get (const string & *label*, string & *a*) const

Return string parameter corresponding to a given label.

Parameters

in	<i>label</i>	Label that identifies the atring (read from input file).
out	<i>a</i>	Returned value. Note: This member function can be used instead of getString If this label is not found an error message is displayed and program stops. Note: This member function can be used instead of getString

string getProject () const

Return parameter read using keyword **Project**.
This parameter can be used to read a project's name.

string getMeshFile (size_t i = 1) const

Return i-th parameter read using keyword **mesh_file**.
Here we have at most 10 integer extra parameters that can be used for any purpose. Default value for i is 1

string getInitFile () const

Return parameter read using keyword **InitFile**.
This parameter can be used to read an initial data file name.

string getRestartFile () const

Return parameter read using keyword **RestartFile**.
This parameter can be used to read a restart file name.

string getBCFile () const

Return parameter read using keyword **BCFile**.
This parameter can be used to read a boundary condition file name.

string getBFFile () const

Return parameter read using keyword **BFFile**.
This parameter can be used to read a body force file name.

string getSFFile () const

Return parameter read using keyword **SFFile**.
This parameter can be used to read a source force file name.

string getSaveFile () const

Return parameter read using keyword **SaveFile**.
This parameter can be used to read a save file name.

string getPlotFile (int i = 1) const

Return i-th parameter read using keyword **PlotFile**.
Here we have at most 10 integer extra parameters that can be used for plot file names. Default value for i is 1

string getPrescriptionFile (int *i* = 1) const

Return parameter read using keyword **DataFile**.

This parameter can be used to read a [Prescription](#) file.

string getAuxFile (size_t *i* = 1) const

Return *i*-th parameter read using keyword **Auxfile**.

Here we have at most 10 integer extra parameters that can be used for any auxiliary file names.
Default value for *i* is 1

7.54 Iter< T_ > Class Template Reference

Class to drive an iterative process.

Public Member Functions

- [Iter](#) ()
Default Constructor.
- [Iter](#) (int max_it, [real_t](#) toler)
Constructor with iteration parameters.
- [~Iter](#) ()
Destructor.
- void [setMaxIter](#) (int max_it)
Set maximal number of iterations.
- void [setTolerance](#) ([real_t](#) toler)
Set tolerance value for convergence.
- void [setVerbose](#) (int v)
Set verbosity parameter.
- bool [check](#) ([Vect](#)< T_ > &u, const [Vect](#)< T_ > &v, int opt=2)
Check convergence.
- bool [check](#) (T_ &u, const T_ &v)
Check convergence for a scalar case (one equation)

7.54.1 Detailed Description

template<class T_>class OFELI::Iter< T_ >

Class to drive an iterative process.

This template class enables monitoring any iterative process. It simply sets default values for tolerance, maximal number of iterations and enables checking convergence using two successive iterates.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.54.2 Member Function Documentation

void setMaxIter (int *max_it*)

Set maximal number of iterations.

Parameters

in	max_it	Maximal number of iterations [Default: 100]
----	--------	---

void setTolerance (real_t toler)

Set tolerance value for convergence.

Parameters

in	toler	Tolerance value [Default: 1.e-8]
----	-------	----------------------------------

void setVerbose (int v)

Set verbosity parameter.


Parameters

in	v	Verbosity parameter [Default: 0]
----	---	----------------------------------

7.55 Laplace1DL2 Class Reference

To build element equation for a 1-D elliptic equation using the 2-Node line element (P_1).

Inheritance diagram for Laplace1DL2:



Public Member Functions

- [Laplace1DL2 \(\)](#)
Default constructor.
- [Laplace1DL2 \(Mesh &ms, Vect< real_t > &u\)](#)
- [Laplace1DL2 \(Mesh &ms\)](#)
- [~Laplace1DL2 \(\)](#)
Destructor.
- void [LHS \(\)](#)
Add finite element matrix to left hand side.
- void [buildEigen](#) (int opt=0)
Build global stiffness and mass matrices for the eigen system.
- void [BodyRHS](#) (const Vect< real_t > &f)
Add Right-Hand Side Contribution.
- void [BoundaryRHS](#) (const Vect< real_t > &f)
Add Neumann contribution to Right-Hand Side.

- void [setBoundaryCondition](#) ([real.t](#) f, int lr)
Set Dirichlet boundary data.
- void [setTraction](#) ([real.t](#) f, int lr)
Set Traction data.

7.55.1 Detailed Description

To build element equation for a 1-D elliptic equation using the 2-Node line element (P_1).

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.55.2 Constructor & Destructor Documentation

Laplace1DL2 (Mesh & *ms*, Vect< real.t > & *u*)

Constructor using mesh instance and solution vector

Parameters

in	<i>ms</i>	Mesh instance
in,out	<i>u</i>	Vect instance that contains, after execution of run() the solution

Laplace1DL2 (Mesh & *ms*)

Constructor using mesh instance

Parameters

in	<i>ms</i>	Mesh instance
----	-----------	-------------------------------

7.55.3 Member Function Documentation

void buildEigen (int *opt* = 0) [virtual]

Build global stiffness and mass matrices for the eigen system.

Parameters

in	<i>opt</i>	Flag to choose a lumped mass matrix (0) or consistent (1) [Default: 0]
----	------------	---

Reimplemented from [Equa.Laplace< real.t, 2, 2, 1, 1 >](#).

void BodyRHS (const Vect< real.t > & *f*) [virtual]

Add Right-Hand Side Contribution.

Parameters

in	<i>f</i>	Vector containing the source given function at mesh nodes
----	----------	---

Reimplemented from [Equa.Laplace< real.t, 2, 2, 1, 1 >](#).

void BoundaryRHS (const Vect< real.t > & *f*) [virtual]

Add Neumann contribution to Right-Hand Side.

Parameters

<code>in</code>	<code>f</code>	Vector with size the total number of nodes. The first entry stands for the force at the first node (Neumann condition) and the last entry is the force at the last node (Neumann condition)
-----------------	----------------	---

Reimplemented from [Equa.Laplace< real_t, 2, 2, 1, 1 >](#).

void setBoundaryCondition (real_t f, int lr)

Set Dirichlet boundary data.

Parameters

<code>in</code>	<code>f</code>	Value to assign
<code>in</code>	<code>lr</code>	Option to choose location of the value (-1: Left end, 1: Right end)

void setTraction (real_t f, int lr)

Set Traction data.


Parameters

<code>in</code>	<code>f</code>	Value of traction (Neumann boundary condition)
<code>in</code>	<code>lr</code>	Option to choose location of the traction (-1: Left end, 1: Right end)

7.56 Laplace1DL3 Class Reference

To build element equation for the 1-D elliptic equation using the 3-Node line (P_2).

Inheritance diagram for Laplace1DL3:



Public Member Functions

- [Laplace1DL3 \(\)](#)
Default constructor. Initializes an empty equation.
- [Laplace1DL3 \(Mesh &ms\)](#)
Constructor using mesh instance.
- [Laplace1DL3 \(Mesh &ms, Vect< real_t > &u\)](#)
- [~Laplace1DL3 \(\)](#)
Destructor.
- void [LHS \(\)](#)
Compute element matrix.

- void **BodyRHS** (const **Vect**< **real_t** > &f)
Add Right-hand side contribution.
- void **BoundaryRHS** (const **Vect**< **real_t** > &h)
Add Neumann contribution to Right-Hand Side.
- void **setTraction** (**real_t** f, int lr)
Set Traction data.

7.56.1 Detailed Description

To build element equation for the 1-D elliptic equation using the 3-Node line (P_2).

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.56.2 Constructor & Destructor Documentation

Laplace1DL3 (Mesh & *ms*)

Constructor using mesh instance.

Parameters

in	<i>ms</i>	Mesh instance
-----------	------------------	----------------------

Laplace1DL3 (Mesh & *ms*, Vect< **real_t > & *u*)**

Constructor using mesh instance and solution vector

Parameters

in	<i>ms</i>	Mesh instance
in,out	<i>u</i>	Vect instance that contains, after execution of run() the solution

7.56.3 Member Function Documentation

void BodyRHS (const Vect< **real_t > & *f*)** [virtual]

Add Right-hand side contribution.

Parameters

in	<i>f</i>	Vector of right-hand side of the Poisson equation at nodes
-----------	-----------------	--

Reimplemented from **Equa.Laplace< **real_t**, 3, 3, 1, 1 >**.

void BoundaryRHS (const Vect< **real_t > & *h*)** [virtual]

Add Neumann contribution to Right-Hand Side.

Parameters

in	h	Vector with size the total number of nodes. The first entry stands for the force at the first node (Neumann condition) and the last entry is the force at the last node (Neumann condition)
----	-----	---

Reimplemented from [Equa.Laplace< real_t, 3, 3, 1, 1 >](#).

void setTraction (real_t f, int lr)

Set Traction data.


Parameters

in	f	Value of traction (Neumann boundary condition)
in	lr	Option to choose location of the traction (-1: Left end, 1: Right end)

7.57 Laplace2DT3 Class Reference

To build element equation for the Laplace equation using the 2-D triangle element (P_1).

Inheritance diagram for Laplace2DT3:



Public Member Functions

- [Laplace2DT3 \(\)](#)
Default constructor.
- [Laplace2DT3 \(Mesh &ms\)](#)
Constructor with mesh.
- [Laplace2DT3 \(Mesh &ms, Vect< real_t > &u\)](#)
Constructor using mesh and solution vector.
- [Laplace2DT3 \(Mesh &ms, Vect< real_t > &b, Vect< real_t > &Dbc, Vect< real_t > &Nbc, Vect< real_t > &u\)](#)
Constructor that initializes a standard Poisson equation.
- [~Laplace2DT3 \(\)](#)
Destructor.
- void [LHS \(\)](#)
Add finite element matrix to left-hand side.
- void [BodyRHS](#) (const Vect< real_t > &f)
Add body source term to right-hand side.
- void [BoundaryRHS](#) (const Vect< real_t > &h)

Add boundary source term to right-hand side.

- void [buildEigen](#) (int opt=0)
Build global stiffness and mass matrices for the eigen system.
- void [Post](#) (const [Vect](#)< [real.t](#) > &u, [Vect](#)< [Point](#)< [real.t](#) > > &p)
Perform post calculations.

7.57.1 Detailed Description

To build element equation for the Laplace equation using the 2-D triangle element (P_1).

To build element equation for the Laplace equation using the 3-D tetrahedral element (P_1).

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.57.2 Constructor & Destructor Documentation

Laplace2DT3 ([Mesh](#) & *ms*)

Constructor with mesh.
Parameters

in	<i>ms</i>	Mesh instance
--------------------	-----------	-------------------------------

Laplace2DT3 ([Mesh](#) & *ms*, [Vect](#)< [real.t](#) > & *u*)

Constructor using mesh and solution vector.
Parameters

in	<i>ms</i>	Mesh instance
in	<i>u</i>	Problem right-hand side

Laplace2DT3 ([Mesh](#) & *ms*, [Vect](#)< [real.t](#) > & *b*, [Vect](#)< [real.t](#) > & *Dbc*, [Vect](#)< [real.t](#) > & *Nbc*, [Vect](#)< [real.t](#) > & *u*)

Constructor that initializes a standard Poisson equation.

This constructor sets data for the Poisson equation with mixed (Dirichlet and Neumann) boundary conditions.

Parameters

in	<i>ms</i>	Mesh instance
in	<i>b</i>	Vector containing the source term (right-hand side of the equation) at mesh nodes
in	<i>Dbc</i>	Vector containing prescribed values of the solution (Dirichlet boundary condition) at nodes with positive code. Its size is the total number of nodes
in	<i>Nbc</i>	Vector containing prescribed fluxes (Neumann boundary conditions) at sides, its size is the total number of sides
in	<i>u</i>	Vector to contain the finite element solution at nodes once the member function run() is called.

7.57.3 Member Function Documentation

void BodyRHS (const Vect< real.t > &*f*) [virtual]

Add body source term to right-hand side.

Parameters

in	f	Vector containing the source given function at mesh nodes
----	-----	---

Reimplemented from [Equa.Laplace< real_t, 3, 3, 2, 2 >](#).

void BoundaryRHS (const Vect< real_t > &h) [virtual]

Add boundary source term to right-hand side.

Parameters

in	h	Vector containing the source given function at mesh nodes
----	-----	---

Reimplemented from [Equa.Laplace< real_t, 3, 3, 2, 2 >](#).

void buildEigen (int opt = 0) [virtual]

Build global stiffness and mass matrices for the eigen system.

Parameters

in	opt	Flag to choose a lumped mass matrix (0) or consistent (1) [Default: 0]
----	-----	---

Reimplemented from [Equa.Laplace< real_t, 3, 3, 2, 2 >](#).

void Post (const Vect< real_t > &u, Vect< Point< real_t > > &p)

Perform post calculations.


Parameters

in	u	Solution at nodes
out	p	Vector containing gradient at elements

7.58 Laplace2DT6 Class Reference

To build element equation for the Laplace equation using the 2-D triangle element (P₂).

Inheritance diagram for Laplace2DT6:



Public Member Functions

- [Laplace2DT6 \(\)](#)
Default constructor.
- [Laplace2DT6 \(Mesh &ms\)](#)
Constructor with mesh.

- **Laplace2DT6** (**Mesh** &ms, **Vect**< **real.t** > &u)
Constructor using mesh and solution vector.
- **~Laplace2DT6** ()
Destructor.
- void **LHS** ()
Add finite element matrix to left-hand side.
- void **BodyRHS** (const **Vect**< **real.t** > &f)
Add body source term to right-hand side.
- void **BoundaryRHS** (const **Vect**< **real.t** > &h)
Add boundary source term to right-hand side.
- void **buildEigen** (int opt=0)
Build global stiffness and mass matrices for the eigen system.

7.58.1 Detailed Description

To build element equation for the Laplace equation using the 2-D triangle element (P₂).

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.58.2 Constructor & Destructor Documentation

Laplace2DT6 (**Mesh** & ms)

Constructor with mesh.

Parameters

in	ms	Mesh instance
----	----	----------------------

Laplace2DT6 (**Mesh** & ms, **Vect**< **real.t** > & u)

Constructor using mesh and solution vector.

Parameters

in	ms	Mesh instance
in	u	Problem right-hand side

7.58.3 Member Function Documentation

void BodyRHS (const **Vect**< **real.t** > & f) [virtual]

Add body source term to right-hand side.

Parameters

in	f	Vector containing the source given function at mesh nodes
----	---	---

Reimplemented from **Equa.Laplace**< **real.t**, 6, 6, 3, 3 >.

void BoundaryRHS (const **Vect**< **real.t** > & h) [virtual]

Add boundary source term to right-hand side.

Parameters

in	<i>h</i>	Vector containing the source given function at mesh nodes
-----------	----------	---

Reimplemented from [Equa.Laplace< real_t, 6, 6, 3, 3 >](#).

void buildEigen (int *opt* = 0) [virtual]

Build global stiffness and mass matrices for the eigen system.

Parameters


in	<i>opt</i>	Flag to choose a lumped mass matrix (0) or consistent (1) [Default: 0]
-----------	------------	--

Reimplemented from [Equa.Laplace< real_t, 6, 6, 3, 3 >](#).

7.59 LaplaceDG2DP1 Class Reference

To build and solve the linear system for the Poisson problem using the [DG](#) P_1 2-D triangle element.

Inheritance diagram for LaplaceDG2DP1:



Public Member Functions

- [LaplaceDG2DP1](#) ([Mesh](#) &ms, [Vect< real_t >](#) &f, [Vect< real_t >](#) &Dbc, [Vect< real_t >](#) &Nbc, [Vect< real_t >](#) &u)

Constructor with mesh and vector data.

- [~LaplaceDG2DP1](#) ()

Destructor.

- void [set](#) ([real_t](#) sigma, [real_t](#) eps)

Set parameters for the [DG](#) method.

- void [set](#) (const [LocalMatrix< real_t, 2, 2 >](#) &K)

Set diffusivity matrix.

- void [build](#) ()

Build global matrix and right-hand side.

- void [Smooth](#) ([Vect< real_t >](#) &u)

Perform post calculations.

- int [run](#) ()

Build and solve the linear system of equations using an iterative method.

7.59.1 Detailed Description

To build and solve the linear system for the Poisson problem using the [DG](#) P_1 2-D triangle element.

This class build the linear system of equations for a standard elliptic equation using the Discontinuous Galerkin P_1 finite element method.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.59.2 Constructor & Destructor Documentation

LaplaceDG2DP1 ([Mesh](#) & *ms*, [Vect](#)< [real.t](#) > & *f*, [Vect](#)< [real.t](#) > & *Dbc*, [Vect](#)< [real.t](#) > & *Nbc*, [Vect](#)< [real.t](#) > & *u*)

Constructor with mesh and vector data.

Parameters

in	<i>ms</i>	Mesh instance
in	<i>f</i>	Vector containing the right-hand side of the elliptic equation at triangle vertices
in	<i>Dbc</i>	Vector containing prescribed values of the solution (Dirichlet boundary condition) at nodes having a positive code
in	<i>Nbc</i>	Vector containing prescribed values of the flux (Neumann boundary condition) at each side having a positive code
in	<i>u</i>	Vector where the solution is stored once the linear system is solved

7.59.3 Member Function Documentation

void set ([real.t](#) *sigma*, [real.t](#) *eps*)

Set parameters for the [DG](#) method.

Parameters

in	<i>sigma</i>	Penalty parameters to enforce continuity at nodes (Must be positive) [Default: 100]
in	<i>eps</i>	<p>Epsilon value of the DG method to choose among the values:</p> <ul style="list-style-type: none"> • 0 Incomplete Interior Penalty Galerkin method (IIPG) • -1 Symmetric Interior Penalty Galerkin method (SIPG) • 1 Non symmetric interior penalty Galerkin method (NIPG) <p>For a user not familiar with the method, please choose the value of <i>eps</i>=-1 and <i>sigma</i>>100 which leads to a symmetric positive definite matrix [Default: -1]</p>

void set (const LocalMatrix< real_t, 2, 2 > & K)

Set diffusivity matrix.

This function provides the diffusivity matrix as instance of class [LocalMatrix](#). The default diffusivity matrix is the identity matrix

Parameters

in	K	Diffusivity matrix
----	-----	--------------------

void build ()

Build global matrix and right-hand side.

The problem matrix and right-hand side are the ones used in the constructor. They are updated in this member function.

void Smooth (Vect< real.t > &u)

Perform post calculations.

This function gives an averaged solution given at mesh nodes (triangle vertices) by a standard L_2 -projection method.

Parameters

in	u	Solution at nodes
----	-----	-------------------

int run ()

Build and solve the linear system of equations using an iterative method.

The matrix is preconditioned by the diagonal ILU method. The linear system is solved either by the Conjugate Gradient method if the matrix is symmetric positive definite ($\text{eps}=-1$) or the GMRES method if not. The solution is stored in the vector u given in the constructor.


Returns

Number of performed iterations. Note that the maximal number is 1000 and the tolerance is $1.e-8$

7.60 LCL1D Class Reference

Class to solve the linear conservation law (Hyperbolic equation) in 1-D by a MUSCL Finite Volume scheme.

Inheritance diagram for LCL1D:



Public Member Functions

- [LCL1D \(Mesh &m\)](#)
Constructor using mesh instance.
- [LCL1D \(Mesh &m, Vect< real.t > &U\)](#)
Constructor.
- [~LCL1D \(\)](#)

Destructor.

- `Vect< real_t > & getFlux ()`
Return sidewise fluxes.
- `void setInitialCondition (Vect< real_t > &u)`
Assign initial condition by a vector.
- `void setInitialCondition (real_t u)`
Assign a constant initial condition.
- `void setReconstruction ()`
Run MUSCL reconstruction.
- `real_t runOneTimeStep ()`
Run one time step of the linear conservation law.
- `void setBC (real_t u)`
Set Dirichlet boundary condition.
- `void setBC (const Side &sd, real_t u)`
Set Dirichlet boundary condition.
- `void setBC (int code, real_t u)`
Set Dirichlet boundary condition.
- `void setVelocity (Vect< real_t > &v)`
Set convection velocity.
- `void setVelocity (real_t v)`
Set (constant) convection velocity.
- `void setReferenceLength (real_t dx)`
Assign reference length value.
- `real_t getReferenceLength () const`
Return reference length.
- `void Forward (const Vect< real_t > &Flux, Vect< real_t > &Field)`
Computation of the primal variable $n \rightarrow n+1$.

Additional Inherited Members

7.60.1 Detailed Description

Class to solve the linear conservation law (Hyperbolic equation) in 1-D by a MUSCL Finite Volume scheme.

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.60.2 Member Function Documentation

`void setInitialCondition (Vect< real_t > & u)`

Assign initial condition by a vector.

Parameters

in	<i>u</i>	Vector containing initial condition
-----------	----------	-------------------------------------

void setInitialCondition (real_t *u*)

Assign a constant initial condition.

Parameters

in	<i>u</i>	Constant value for the initial condition
-----------	----------	--

real_t runOneTimeStep ()

Run one time step of the linear conservation law.

Returns

Value of the time step

void setBC (real_t *u*)

Set Dirichlet boundary condition.

Assign a constant value *u* to all boundary sides

void setBC (const Side & *sd*, real_t *u*)

Set Dirichlet boundary condition.

Assign a constant value to a side

Parameters

in	<i>sd</i>	Side to which value is prescribed
in	<i>u</i>	Value to prescribe

void setBC (int *code*, real_t *u*)

Set Dirichlet boundary condition.

Assign a constant value sides with a given code

Parameters

in	<i>code</i>	Code of sides to which value is prescribed
in	<i>u</i>	Value to prescribe

void setVelocity (Vect< real_t > & *v*)

Set convection velocity.

Parameters

in	<i>v</i>	Vect instance containing velocity
-----------	----------	---

void Forward (const Vect< real_t > & Flux, Vect< real_t > & Field)


Computation of the primal variable $n \rightarrow n+1$.

Vector **Flux** contains elementwise fluxes issued from the Riemann problem, calculated with, as left element, **getNeighborElement(1)** and right element **getNeighborElement(2)** if **getNeighborElement(2)** doesn't exist, we are on a boundary and we prescribe a symmetry condition

7.61 LCL2DT Class Reference

Class to solve the linear hyperbolic equation in 2-D by a MUSCL Finite Volume scheme on triangles.

Inheritance diagram for LCL2DT:



Public Member Functions

- **LCL2DT (Mesh &m)**
*Constructor using **Mesh** instance.*
- **LCL2DT (Mesh &m, Vect< real_t > &U)**
Constructor using mesh and initial data.
- **~LCL2DT ()**
Destructor.
- **Vect< real_t > & getFlux ()**
Return sidewise flux vector.
- **void setInitialCondition (Vect< real_t > &u)**
Set elementwise initial condition.
- **void setInitialCondition (real_t u)**
Set a constant initial condition.
- **void setReconstruction ()**
*Reconstruct flux using **Muscl** scheme.*
- **real_t runOneTimeStep ()**
Run one time step of the linear conservation law.
- **void setBC (real_t u)**
Set Dirichlet boundary condition.
- **void setBC (const Side &sd, real_t u)**
Set Dirichlet boundary condition.
- **void setBC (int code, real_t u)**
Set Dirichlet boundary condition.
- **void setVelocity (const Vect< real_t > &v)**
Set convection velocity.
- **void setVelocity (const LocalVect< real_t, 2 > &v)**

Set (constant) convection velocity.

- void **Forward** (const **Vect**< **real.t** > &Flux, **Vect**< **real.t** > &Field)

Computation of the primal variable $n \rightarrow n+1$.

Additional Inherited Members

7.61.1 Detailed Description

Class to solve the linear hyperbolic equation in 2-D by a MUSCL Finite Volume scheme on triangles.

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.61.2 Constructor & Destructor Documentation

LCL2DT (**Mesh** & *m*, **Vect**< **real.t** > & *U*)

Constructor using mesh and initial data.

Parameters

in	<i>m</i>	Reference to Mesh instance
in	<i>U</i>	Vector containing initial (elementwise) solution

7.61.3 Member Function Documentation

void setInitialCondition (**Vect**< **real.t** > & *u*)

Set elementwise initial condition.

Parameters

in	<i>u</i>	Vect instance containing initial condition values
----	----------	--

void setInitialCondition (**real.t** *u*)

Set a constant initial condition.

Parameters

in	<i>u</i>	Value of initial condition to assign to all elements
----	----------	--

real.t runOneTimeStep ()

Run one time step of the linear conservation law.

Returns

Value of the time step

void setBC (real_t *u*)

Set Dirichlet boundary condition.

Assign a constant value *u* to all boundary sides

void setBC (const Side & *sd*, real_t *u*)

Set Dirichlet boundary condition.

Assign a constant value to a side

Parameters

in	<i>sd</i>	Side to which value is prescribed
in	<i>u</i>	Value to prescribe

void setBC (int *code*, real_t *u*)

Set Dirichlet boundary condition.

Assign a constant value sides with a given code

Parameters

in	<i>code</i>	Code of sides to which value is prescribed
in	<i>u</i>	Value to prescribe

void setVelocity (const Vect< real_t > & *v*)

Set convection velocity.

Parameters

in	<i>v</i>	Vect instance containing velocity
----	----------	---

void setVelocity (const LocalVect< real_t, 2 > & *v*)

Set (constant) convection velocity.

Parameters

in	<i>v</i>	Vector containing constant velocity to prescribe
----	----------	--

void Forward (const Vect< real_t > & *Flux*, Vect< real_t > & *Field*)


Computation of the primal variable $n \rightarrow n+1$.

Vector *Flux* contains elementwise fluxes issued from the Riemann problem, calculated with, as left element, **getNeighborElement(1)** and right element **getNeighborElement(2)** if **getNeighborElement(2)** doesn't exist, we are on a boundary and we prescribe a symmetry condition

7.62 LCL3DT Class Reference

Class to solve the linear conservation law equation in 3-D by a MUSCL Finite Volume scheme on tetrahedra.

Inheritance diagram for LCL3DT:



Public Member Functions

- **LCL3DT** (**Mesh** &m)
Constructor using mesh.
- **LCL3DT** (**Mesh** &m, **Vect**< **real_t** > &U)
Constructor using mesh and initial field.
- **~LCL3DT** ()
Destructor.
- void **setInitialCondition** (**Vect**< **real_t** > &u)
Set elementwise initial condition.
- void **setInitialCondition** (**real_t** u)
Set a constant initial condition.
- void **setReconstruction** ()
*Reconstruct flux using **Muscl** scheme.*
- **real_t** **runOneTimeStep** ()
Run one time step.
- void **setBC** (**real_t** u)
Set Dirichlet boundary condition. Assign a constant value u to all boundary sides.
- void **setBC** (const **Side** &sd, **real_t** u)
Set Dirichlet boundary condition.
- void **setBC** (int code, **real_t** u)
Set Dirichlet boundary condition.
- void **setVelocity** (const **Vect**< **real_t** > &v)
Set convection velocity.
- void **setVelocity** (const **LocalVect**< **real_t**, 3 > &v)
Set (constant) convection velocity.
- void **setReferenceLength** (**real_t** dx)
Assign reference length value.
- **real_t** **getReferenceLength** () const
Return reference length.
- void **Forward** (const **Vect**< **real_t** > &Flux, **Vect**< **real_t** > &Field)
Computation of the primal variable n->n+1.

Additional Inherited Members

7.62.1 Detailed Description

Class to solve the linear conservation law equation in 3-D by a MUSCL Finite Volume scheme on tetrahedra.

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.62.2 Constructor & Destructor Documentation

LCL3DT (Mesh & *m*, Vect< real_t > & *U*)

Constructor using mesh and initial field.

Parameters

in	<i>m</i>	Reference to Mesh instance
in	<i>U</i>	Vector containing initial (elementwise) solution

7.62.3 Member Function Documentation

void setInitialCondition (Vect< real_t > & *u*)

Set elementwise initial condition.

Parameters

in	<i>u</i>	Vect instance containing initial condition values
----	----------	---

void setInitialCondition (real_t *u*)

Set a constant initial condition.

Parameters

in	<i>u</i>	Value of initial condition to assign to all elements
----	----------	--

void setBC (const Side & *sd*, real_t *u*)

Set Dirichlet boundary condition.

Assign a constant value to a side

Parameters

in	<i>sd</i>	Side to which value is prescribed
in	<i>u</i>	Value to prescribe

void setBC (int *code*, real_t *u*)

Set Dirichlet boundary condition.

Assign a constant value sides with a given code

Parameters

in	<i>code</i>	Code of sides to which value is prescribed
----	-------------	--

in	u	Value to prescribe
----	-----	--------------------

void setVelocity (const Vect< real_t > & v)

Set convection velocity.

Parameters

in	v	Vect instance containing velocity
----	-----	---

void setVelocity (const LocalVect< real_t, 3 > & v)

Set (constant) convection velocity.

Parameters

in	v	Vector containing constant velocity to prescribe
----	-----	--

void Forward (const Vect< real_t > & Flux, Vect< real_t > & Field)


Computation of the primal variable $n \rightarrow n+1$.

Vector Flux contains elementwise fluxes issued from the Riemann problem, calculated with, as left element, `getNeighborElement(1)` and right element `getNeighborElement(2)` if `getNeighborElement(2)` doesn't exist, we are on a boundary and we prescribe a symmetry condition

7.63 Line2 Class Reference

To describe a 2-Node planar line finite element.

Inheritance diagram for Line2:



Public Member Functions

- [Line2](#) ()
Default Constructor.
- [Line2](#) (const [Element](#) *el)
Constructor for an element.
- [Line2](#) (const [Side](#) *side)
Constructor for a side.
- [Line2](#) (const [Edge](#) *edge)
Constructor for an edge.
- [~Line2](#) ()
Destructor.
- [real_t getLength](#) () const
Return element length.

- `Point< real_t > getNormal () const`
Return unit normal vector to line.
- `Point< real_t > getTangent () const`
Return unit tangent vector to line.
- `real_t Sh (size_t i, real_t s) const`
Calculate shape function of a given node at a given point.
- `std::vector< Point< real_t > > DSh () const`
Return partial derivatives of shape functions of element nodes.
- `Point< real_t > getRefCoord (const Point< real_t > &x)`
Return reference coordinates of a point x in element.
- `bool isIn (const Point< real_t > &x)`
Check whether point x is in current line element or not.
- `real_t getInterpolate (const Point< real_t > &x, const LocalVect< real_t, 2 > &v)`
Return interpolated value at a given point.

7.63.1 Detailed Description

To describe a 2-Node planar line finite element.

Defines geometric quantities associated to 2-node linear segment element P_1 in the space. The reference element is the segment $[-1, 1]$. Note that the line length is not checked unless the function check is called.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.63.2 Constructor & Destructor Documentation

Line2 (const Element * *el*)

Constructor for an element.

Parameters

<i>in</i>	<i>el</i>	Pointer to element
-----------	-----------	--------------------

Line2 (const Side * *side*)

Constructor for a side.

Parameters

<i>in</i>	<i>side</i>	Pointer to side
-----------	-------------	-----------------

Line2 (const Edge * *edge*)

Constructor for an edge.

Parameters

in	<i>edge</i>	Pointer to edge
----	-------------	-----------------

7.63.3 Member Function Documentation

real_t Sh (size_t *i*, real_t *s*) const

Calculate shape function of a given node at a given point.

Parameters

in	<i>i</i>	Node number (1 or 2).
in	<i>s</i>	Localization of point in natural coordinates (must be between -1 and 1).

std::vector<Point<real_t> > DSh () const

Return partial derivatives of shape functions of element nodes.

Returns

[LocalVect](#) instance of partial derivatives of shape functions *e.g.* `dsh(i).x`, `dsh(i).y`, are partial derivatives of the *i*-th shape function.

Point<real_t> getRefCoord (const Point< real_t > & *x*)

Return reference coordinates of a point *x* in element.

Only the x-coordinate of the returned value has a meaning

real_t interpolate (const Point< real_t > & *x*, const LocalVect< real_t, 2 > & *v*)

Return interpolated value at a given point.


Parameters

in	<i>x</i>	Point where interpolation is evaluated (in the reference element).
out	<i>v</i>	Computed value.

7.64 Line3 Class Reference

To describe a 3-Node quadratic planar line finite element.

Inheritance diagram for Line3:



Public Member Functions

- [Line3](#) ()
Default Constructor.
- [Line3](#) (const [Element](#) *el)
Constructor for an element.
- [Line3](#) (const [Side](#) *sd)
Constructor for a side.
- [~Line3](#) ()
Destructor.
- void [setLocal](#) ([real_t](#) s)
Initialize local point coordinates in element.
- [LocalVect](#)< [Point](#)< [real_t](#) >, 3 > [DSh](#) () const
Return partial derivatives of shape functions of element nodes.
- [Point](#)< [real_t](#) > [getLocalPoint](#) () const
Return actual coordinates of localized point.

7.64.1 Detailed Description

To describe a 3-Node quadratic planar line finite element.

Defines geometric quantities associated to 3-node quadratic element P_2 in the space. The reference element is the segment $[-1, 1]$. The user must take care to the fact that determinant of jacobian and other quantities depend on the point in the reference element where they are calculated. For this, before any utilization of shape functions or jacobian, function [setLocal\(\)](#) must be invoked.

[Element](#) nodes are ordered as the following: the left one, the central one and the right one.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.64.2 Member Function Documentation

[LocalVect](#)<[Point](#)<[real_t](#)>,3> [DSh](#) () const

Return partial derivatives of shape functions of element nodes.

Returns

[LocalVect](#) instance of partial derivatives of shape functions *e.g.* `dsh(i).x`, `dsh(i).y`, are partial derivatives of the *i*-th shape function.

Note

The local point at which the derivatives are computed must be chosen before by using the member function `setLocal`

7.65 LinearSolver< T_ > Class Template Reference

Class to solve systems of linear equations by iterative methods.

Public Member Functions

- [LinearSolver](#) ()
Default Constructor.
- [LinearSolver](#) (int max_it, [real_t](#) tolerance)
Constructor with iteration parameters.
- [LinearSolver](#) ([SpMatrix](#)< T_ > &A, const [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Constructor using matrix, right-hand side and solution vector.
- [LinearSolver](#) ([SkMatrix](#)< T_ > &A, const [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Constructor using skyline-stored matrix, right-hand side and solution vector.
- [LinearSolver](#) ([TrMatrix](#)< T_ > &A, const [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Constructor using a tridiagonal matrix, right-hand side and solution vector.
- [LinearSolver](#) ([BMatrix](#)< T_ > &A, const [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Constructor using a banded matrix, right-hand side and solution vector.
- [LinearSolver](#) ([DMatrix](#)< T_ > &A, const [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Constructor using a dense matrix, right-hand side and solution vector.
- [LinearSolver](#) ([DSMatrix](#)< T_ > &A, const [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Constructor using a dense symmetric matrix, right-hand side and solution vector.
- [LinearSolver](#) ([SkSMatrix](#)< T_ > &A, const [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Constructor using skyline-stored symmetric matrix, right-hand side and solution vector.
- [LinearSolver](#) ([SkMatrix](#)< T_ > &A, [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Constructor using matrix, right-hand side.
- virtual [~LinearSolver](#) ()
Destructor.
- void [setMaxIter](#) (int m)
Set Maximum number of iterations.
- void [setTolerance](#) ([real_t](#) tol)
Set tolerance value.
- void [setSolution](#) ([Vect](#)< T_ > &x)
Set solution vector.
- void [setRHS](#) ([Vect](#)< T_ > &b)
Set right-hand side vector.
- void [setMatrix](#) ([OFELI::Matrix](#)< T_ > *A)
Set matrix in the case of a pointer to [Matrix](#).
- void [setMatrix](#) ([SpMatrix](#)< T_ > &A)
Set matrix in the case of a pointer to matrix.
- void [setMatrix](#) ([SkMatrix](#)< T_ > &A)
Set matrix in the case of a skyline matrix.
- void [set](#) ([SpMatrix](#)< T_ > &A, const [Vect](#)< T_ > &b, [Vect](#)< T_ > &x)
Set matrix, right-hand side and initial guess.
- void [setSolver](#) ([Iteration](#) s, [Preconditioner](#) p=DIAG_PREC)
Set solver and preconditioner.
- [Iteration](#) [getSolver](#) () const
Return solver code.
- [Preconditioner](#) [getPreconditioner](#) () const
Return solver preconditioner.

- `int solve (SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x, Iteration s, Preconditioner p=DIAG.PREC)`
Solve equations using system data, prescribed solver and preconditioner.
- `int solve (Iteration s, Preconditioner p=DIAG.PREC)`
Solve equations using prescribed solver and preconditioner.
- `int solve ()`
Solve equations all arguments must have been given by other member functions.
- `void setFact ()`
Factorize matrix.
- `void setNoFact ()`
Do not factorize matrix.
- `int getNbIter () const`
Get number of performed iterations.

7.65.1 Detailed Description

`template<class T_>class OFELI::LinearSolver< T_ >`

Class to solve systems of linear equations by iterative methods.

7.65.2 Constructor & Destructor Documentation

`LinearSolver ()`

Default Constructor.

Initializes default parameters and pointers to 0.

`LinearSolver (int max_it, real_t tolerance)`

Constructor with iteration parameters.

Parameters

<code>in</code>	<code>max_it</code>	Maximal number of iterations
<code>in</code>	<code>tolerance</code>	Tolerance for convergence (measured in relative weighted 2-↔ Norm) in input, effective discrepancy in output.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

`LinearSolver (SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x)`

Constructor using matrix, right-hand side and solution vector.

Parameters

in	A	Reference to instance of class SpMatrix
in	b	Vect instance that contains the right-hand side
in,out	x	Vect instance that contains initial guess on input and solution on output

LinearSolver (SkMatrix< T_ > & A, const Vect< T_ > & b, Vect< T_ > & x)

Constructor using skyline-stored matrix, right-hand side and solution vector.

Parameters

in	A	SkMatrix instance that contains matrix
in	b	Vect instance that contains the right-hand side
in,out	x	Vect instance that contains initial guess on input and solution on output

LinearSolver (TrMatrix< T_ > & A, const Vect< T_ > & b, Vect< T_ > & x)

Constructor using a tridiagonal matrix, right-hand side and solution vector.

Parameters

in	A	TrMatrix instance that contains matrix
in	b	Vect instance that contains the right-hand side
in,out	x	Vect instance that contains initial guess on input and solution on output

LinearSolver (BMatrix< T_ > & A, const Vect< T_ > & b, Vect< T_ > & x)

Constructor using a banded matrix, right-hand side and solution vector.

Parameters

in	A	BMatrix instance that contains matrix
in	b	Vect instance that contains the right-hand side
in,out	x	Vect instance that contains initial guess on input and solution on output

LinearSolver (DMatrix< T_ > & A, const Vect< T_ > & b, Vect< T_ > & x)

Constructor using a dense matrix, right-hand side and solution vector.

Parameters

in	A	DMatrix instance that contains matrix
in	b	Vect instance that contains the right-hand side
in,out	x	Vect instance that contains initial guess on input and solution on output

LinearSolver (DSMatrix< T_ > & A, const Vect< T_ > & b, Vect< T_ > & x)

Constructor using a dense symmetric matrix, right-hand side and solution vector.

Parameters

in	A	DSMatrix instance that contains matrix
in	b	Vect instance that contains the right-hand side
in,out	x	Vect instance that contains initial guess on input and solution on output

LinearSolver (SkSMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x)

Constructor using skyline-stored symmetric matrix, right-hand side and solution vector.

Parameters

in	A	SkMatrix instance that contains matrix
in	b	Vect instance that contains the right-hand side
in,out	x	Vect instance that contains initial guess on input and solution on output

LinearSolver (SkMatrix< T_ > &A, Vect< T_ > &b, Vect< T_ > &x)

Constructor using matrix, right-hand side.

Parameters

in	A	SkMatrix instance that contains matrix
in	b	Vect instance that contains the right-hand side
in,out	x	Vect instance that contains the initial guess on input and solution on output

7.65.3 Member Function Documentation

void setMaxIter (int m)

Set Maximum number of iterations.

Default value is 1000

void setMatrix (OFELI::Matrix< T_ > *A)

Set matrix in the case of a pointer to [Matrix](#).

Parameters

in	A	Pointer to abstract Matrix class
----	-----	--

void setMatrix (SpMatrix< T_ > &A)

Set matrix in the case of a pointer to matrix.

Parameters

in	A	Pointer to abstract Matrix class
----	-----	--

void setMatrix (SkMatrix< T_ > &A)

Set matrix in the case of a skyline matrix.

Parameters

in	A	Matrix as instance of class SkMatrix
----	-----	--

void set (SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x)

Set matrix, right-hand side and initial guess.

Parameters

in	A	Reference to matrix as a SpMatrix instance
in	b	Vector containing right-hand side
in,out	x	Vector containing initial guess on input and solution on output

void setSolver (Iteration s, Preconditioner p = DIAG_PREC)

Set solver and preconditioner.

Parameters

in	s	Solver identification parameter. To be chosen in the enumeration variable Iteration: DIRECT_SOLVER, CG_SOLVER, CGS_SOLVER, BICG_SOLVER, BICG_ST↔ AB_SOLVER, GMRES_SOLVER, QMR_SOLVER
in	p	Preconditioner identification parameter. By default, the diagonal preconditioner is used. To be chosen in the enumeration variable Preconditioner: IDENT_PREC, DIAG_PREC, SSOR_PREC, ILU_PREC [Default: ILU_PREC]

Note

The argument p has no effect if the solver is DIRECT_SOLVER

int solve (SpMatrix< T_ > &A, const Vect< T_ > &b, Vect< T_ > &x, Iteration s, Preconditioner p = DIAG_PREC)

Solve equations using system data, prescribed solver and preconditioner.

Parameters

in	A	Reference to matrix as a SpMatrix instance
in	b	Vector containing right-hand side
in,out	x	Vector containing initial guess on input and solution on output
in	s	Solver identification parameter To be chosen in the enumeration variable Iteration: DIRECT_SOLVER, CG_SOLVER, CGS_SOLVER, BICG_SOLVER, BICG_ST↔ AB_SOLVER, GMRES_SOLVER, QMR_SOLVER [Default: CGS_SOLVER]
in	p	Preconditioner identification parameter. To be chosen in the enumeration variable Preconditioner: IDENT_PREC, DIAG_PREC, SSOR_PREC, ILU_PREC, DILU_PRE↔ C [Default: DIAG_PREC]

Remarks

The argument p has no effect if the solver is DIRECT_SOLVER

Warning

If the library `eigen` is used, only the preconditioners `IDENT_PREC`, `DIAG_PREC` and `ILU_PREC` are available.

int solve (Iteration *s*, Preconditioner *p* = DIAG_PREC)

Solve equations using prescribed solver and preconditioner.

Parameters

in	<i>s</i>	Solver identification parameter To be chosen in the enumeration variable Iteration: DIRECT_SOLVER, CG_SOLVER, CGS_SOLVER, BICG_SOLVER, BICG_STAB_SOLVER, GMRES_SOLVER, QMR_SOLVER [Default: CGS_SOLVER]
in	<i>p</i>	Preconditioner identification parameter. To be chosen in the enumeration variable Preconditioner: IDENT_PREC, DIAG_PREC, SSOR_PREC, DILU_PREC, ILU_PREC [Default: DIAG_PREC]

Note

The argument *p* has no effect if the solver is `DIRECT_SOLVER`

int solve ()

Solve equations all arguments must have been given by other member functions.

Solver and preconditioner parameters must have been set by function `setSolver`. Otherwise, default values are set.

7.66 LocalMatrix< T_, NR_, NC_ > Class Template Reference

Handles small size matrices like element matrices, with a priori known size.

Public Member Functions

- [LocalMatrix](#) ()
Default constructor.
- [LocalMatrix](#) (const [LocalMatrix](#)< T_, NR_, NC_ > &m)
Copy constructor.
- [LocalMatrix](#) (Element *el, const [SpMatrix](#)< T_ > &a)
Constructor of a local matrix associated to element from a [SpMatrix](#).
- [LocalMatrix](#) (Element *el, const [SkMatrix](#)< T_ > &a)
Constructor of a local matrix associated to element from a [SkMatrix](#).
- [LocalMatrix](#) (Element *el, const [SkSMatrix](#)< T_ > &a)
Constructor of a local matrix associated to element from a [SkSMatrix](#).
- [~LocalMatrix](#) ()
Destructor.
- T_ & [operator\(\)](#) (size_t i, size_t j)
Operator () (Non constant version)
- T_ [operator\(\)](#) (size_t i, size_t j) const

- Operator () (Constant version)
- void **Localize** (**Element** *el, const **SpMatrix**< T_ > &a)
 - Initialize matrix as element matrix from global **SpMatrix**.*
- void **Localize** (**Element** *el, const **SkMatrix**< T_ > &a)
 - Initialize matrix as element matrix from global **SkMatrix**.*
- void **Localize** (**Element** *el, const **SkSMatrix**< T_ > &a)
 - Initialize matrix as element matrix from global **SkSMatrix**.*
- **LocalMatrix**< T_, NR_, NC_ > & **operator=** (const **LocalMatrix**< T_, NR_, NC_ > &m)
 - Operator =*
- **LocalMatrix**< T_, NR_, NC_ > & **operator=** (const T_ &x)
 - Operator =*
- **LocalMatrix**< T_, NR_, NC_ > & **operator+=** (const **LocalMatrix**< T_, NR_, NC_ > &m)
 - Operator +=*
- **LocalMatrix**< T_, NR_, NC_ > & **operator-=** (const **LocalMatrix**< T_, NR_, NC_ > &m)
 - Operator -=*
- **LocalVect**< T_, NR_ > **operator*** (**LocalVect**< T_, NC_ > &x)
 - Operator **
- **LocalMatrix**< T_, NR_, NC_ > & **operator+=** (const T_ &x)
 - Operator +=*
- **LocalMatrix**< T_, NR_, NC_ > & **operator-=** (const T_ &x)
 - Operator -=*
- **LocalMatrix**< T_, NR_, NC_ > & **operator*=** (const T_ &x)
 - Operator *=*
- **LocalMatrix**< T_, NR_, NC_ > & **operator/=** (const T_ &x)
 - Operator /=*
- void **MultAdd** (const **LocalVect**< T_, NC_ > &x, **LocalVect**< T_, NR_ > &y)
 - Multiply matrix by vector and add result to vector.*
- void **MultAddScal** (const T_ &a, const **LocalVect**< T_, NC_ > &x, **LocalVect**< T_, NR_ > &y)
 - Multiply matrix by scaled vector and add result to vector.*
- void **Mult** (const **LocalVect**< T_, NC_ > &x, **LocalVect**< T_, NR_ > &y)
 - Multiply matrix by vector.*
- void **Symmetrize** ()
 - Symmetrize matrix.*
- int **Factor** ()
 - Factorize matrix.*
- int **solve** (**LocalVect**< T_, NR_ > &b)
 - Forward and backsubstitute to solve a linear system.*
- int **FactorAndSolve** (**LocalVect**< T_, NR_ > &b)
 - Factorize matrix and solve linear system.*
- void **Invert** (**LocalMatrix**< T_, NR_, NC_ > &A)
 - Calculate inverse of matrix.*
- T_ **getInnerProduct** (const **LocalVect**< T_, NC_ > &x, const **LocalVect**< T_, NR_ > &y)
 - Calculate inner product with respect to matrix.*
- T_ * **get** ()
 - Return pointer to matrix as a C-array.*

7.66.1 Detailed Description

template<class T_, size_t NR_, size_t NC_>class OFELI::LocalMatrix< T_, NR_, NC_ >

Handles small size matrices like element matrices, with a priori known size.

The template class [LocalMatrix](#) treats small size matrices. Typically, this class is recommended to store element and side arrays.

Internally, no dynamic storage is used.

Template Parameters

<i>T_</i>	Data type (double, float, complex<double>, ...)
<i>NR_</i>	number of rows of matrix
<i>NC_</i>	number of columns of matrix

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.66.2 Constructor & Destructor Documentation

LocalMatrix ()

Default constructor.

Constructs a matrix with 0 rows and 0 columns

LocalMatrix (Element * *el*, const SpMatrix< T_ > & *a*)

Constructor of a local matrix associated to element from a [SpMatrix](#).

Parameters

in	<i>el</i>	Pointer to Element
in	<i>a</i>	Global matrix as instance of class SpMatrix .

LocalMatrix (Element * *el*, const SkMatrix< T_ > & *a*)

Constructor of a local matrix associated to element from a [SkMatrix](#).

Parameters

in	<i>el</i>	Pointer to Element
in	<i>a</i>	Global matrix as instance of class SkMatrix .

LocalMatrix (Element * *el*, const SkSMatrix< T_ > & *a*)

Constructor of a local matrix associated to element from a [SkSMatrix](#).

Parameters

in	<i>el</i>	Pointer to Element
in	<i>a</i>	Global matrix as instance of class SkSMatrix .

7.66.3 Member Function Documentation

T_& operator() (size_t *i*, size_t *j*)

Operator () (Non constant version)
Returns entry at row *i* and column *j*.

T_ operator() (size_t *i*, size_t *j*) const

Operator () (Constant version)
Returns entry at row *i* and column *j*.

void Localize (Element * *el*, const SpMatrix< T_ > & *a*)

Initialize matrix as element matrix from global [SpMatrix](#).
Parameters

in	<i>el</i>	Pointer to Element
in	<i>a</i>	Global matrix as instance of class SpMatrix . This function is called by its corresponding constructor.

void Localize (Element * *el*, const SkMatrix< T_ > & *a*)

Initialize matrix as element matrix from global [SkMatrix](#).
Parameters

in	<i>el</i>	Pointer to Element
in	<i>a</i>	Global matrix as instance of class SkMatrix . This function is called by its corresponding constructor.

void Localize (Element * *el*, const SkSMatrix< T_ > & *a*)

Initialize matrix as element matrix from global [SkSMatrix](#).
Parameters

in	<i>el</i>	Pointer to Element
in	<i>a</i>	Global matrix as instance of class SkSMatrix . This function is called by its corresponding constructor.

LocalMatrix<T_,NR_,NC_>& operator= (const LocalMatrix< T_, NR_, NC_ > & *m*)

Operator =
Copy instance *m* into current instance.

LocalMatrix<T_,NR_,NC_>& operator= (const T_ & *x*)

Operator =
Assign matrix to identity times *x*

LocalMatrix<T_,NR_,NC_>& operator+= (const LocalMatrix< T_, NR_, NC_ > & *m*)

Operator +=
Add *m* to current matrix.

LocalMatrix<T_,NR_,NC_>& operator-= (const LocalMatrix< T_, NR_, NC_ > & m)

Operator -=

Subtract m from current matrix.

LocalVect<T_,NR_> operator* (LocalVect< T_, NC_ > & x)

Operator *

Return a [Vect](#) instance as product of current matrix by vector x.

LocalMatrix<T_,NR_,NC_>& operator+= (const T_ & x)

Operator +=

Add constant x to current matrix entries.

LocalMatrix<T_,NR_,NC_>& operator-= (const T_ & x)

Operator -=

Subtract x from current matrix entries.

LocalMatrix<T_,NR_,NC_>& operator*= (const T_ & x)

Operator *=

Multiply matrix entries by constant x.

LocalMatrix<T_,NR_,NC_>& operator/= (const T_ & x)

Operator /=

Divide by x current matrix entries.

void MultAdd (const LocalVect< T_, NC_ > & x, LocalVect< T_, NR_ > & y)

Multiply matrix by vector and add result to vector.

Parameters

in	x	Vector to multiply matrix by.
out	y	Resulting vector (y += a * x)

void MultAddScal (const T_ & a, const LocalVect< T_, NC_ > & x, LocalVect< T_, NR_ > & y)

Multiply matrix by scaled vector and add result to vector.

Parameters

in	a	Constant to premultiply by vector x.
in	x	(Scaled) vector to multiply matrix by.
out	y	Resulting vector (y += a * x)

void Mult (const LocalVect< T_, NC_ > & x, LocalVect< T_, NR_ > & y)

Multiply matrix by vector.

Parameters

in	x	Vector to multiply matrix by.
out	y	Resulting vector.

void Symmetrize ()

Symmetrize matrix.

Fill upper triangle to form a symmetric matrix.

int Factor ()

Factorize matrix.

Performs a LU factorization.

Returns

- 0: Factorization has ended normally,
- n: n-th pivot was zero.

int solve (LocalVect< T_, NR_ > & b)

Forward and backsubstitute to solve a linear system.

Parameters

in	b	Right-hand side in input and solution vector in output.
----	-----	---

Returns

- 0: Solution was performed normally.
- n: n-th pivot is zero.

Note

Matrix must have been factorized at first.

int FactorAndSolve (LocalVect< T_, NR_ > & b)

Factorize matrix and solve linear system.

Parameters

in,out	b	Right-hand side in input and solution vector in output.
--------	-----	---

Returns

0 if solution was performed normally. n if n-th pivot is zero. This function simply calls **Factor()** then **Solve(b)**.

void Invert (LocalMatrix< T_, NR_, NC_ > & A)

Calculate inverse of matrix.

Parameters

out	A	Inverse of matrix
-----	---	-------------------

T_ getInnerProduct (const LocalVect< T_, NC_ > & x, const LocalVect< T_, NR_ > & y)

Calculate inner product with respect to matrix.

Returns the product $x^T A y$

Parameters

in	x	Left vector
in	y	Right vector

Returns

Resulting product

7.67 LocalVect< T_, N_ > Class Template Reference

Handles small size vectors like element vectors.

Public Member Functions

- [LocalVect](#) ()
Default constructor.
- [LocalVect](#) (const T_ *a)
Constructor using a C-array.
- [LocalVect](#) (const [Element](#) *el)
Constructor using [Element](#) pointer.
- [LocalVect](#) (const [Side](#) *sd)
Constructor using [Side](#) pointer.
- [LocalVect](#) (const [LocalVect](#)< T_, N_ > &v)
Copy constructor.
- [LocalVect](#) (const [Element](#) *el, const [Vect](#)< T_ > &v, int opt=0)
Constructor of an element vector from a global [Vect](#) instance.
- [LocalVect](#) (const [Element](#) &el, const [Vect](#)< T_ > &v, int opt=0)
Constructor of an element vector from a global [Vect](#) instance.
- [LocalVect](#) (const [Side](#) *sd, const [Vect](#)< T_ > &v, int opt=0)
Constructor of a side vector from a global [Vect](#) instance.
- [~LocalVect](#) ()
Destructor.
- void [getLocal](#) (const [Element](#) &el, const [Vect](#)< T_ > &v, int type)
Localize an element vector from a global [Vect](#) instance.
- void [Localize](#) (const [Element](#) *el, const [Vect](#)< T_ > &v, size_t k=0)
Localize an element vector from a global [Vect](#) instance.
- void [Localize](#) (const [Side](#) *sd, const [Vect](#)< T_ > &v, size_t k=0)
Localize a side vector from a global [Vect](#) instance.
- T_ & [operator\[\]](#) (size_t i)
Operator [] (Non constant version).

- `T_ operator[] (size_t i) const`
Operator [] (Constant version).
- `T_ & operator() (size_t i)`
Operator () (Non constant version).
- `T_ operator() (size_t i) const`
Operator () (Constant version).
- `Element * El ()`
Return pointer to [Element](#) if vector was constructed using an element and `nullptr` otherwise.
- `Side * Sd ()`
Return pointer to [Side](#) if vector was constructed using a side and `nullptr` otherwise.
- `LocalVect< T_, N_ > & operator= (const LocalVect< T_, N_ > &v)`
Operator =
- `LocalVect< T_, N_ > & operator= (const T_ &x)`
Operator =
- `LocalVect< T_, N_ > & operator+= (const LocalVect< T_, N_ > &v)`
Operator +=
- `LocalVect< T_, N_ > & operator+= (const T_ &a)`
Operator +=
- `LocalVect< T_, N_ > & operator-= (const LocalVect< T_, N_ > &v)`
Operator -=
- `LocalVect< T_, N_ > & operator-= (const T_ &a)`
Operator -=
- `LocalVect< T_, N_ > & operator*= (const T_ &a)`
*Operator *=*
- `LocalVect< T_, N_ > & operator/= (const T_ &a)`
Operator /=
- `T_ * get ()`
Return pointer to vector as a C-Array.
- `T_ operator, (const LocalVect< T_, N_ > &v) const`
Return Dot (scalar) product of two vectors.

7.67.1 Detailed Description

`template<class T_, size_t N_>class OFELI::LocalVect< T_, N_ >`

Handles small size vectors like element vectors.

The template class [LocalVect](#) treats small size vectors. Typically, this class is recommended to store element and side arrays. Operators `=`, `[]` and `()` are overloaded so that one can write for instance:

```
LocalVect<double,10> u, v;
v = -1.0;
u = v;
u(3) = -2.0;
```

to set vector `v` entries to `-1`, copy vector `v` into vector `u` and assign third entry of `v` to `-2`. Notice that entries of `v` are here `v(1)`, `v(2)`, ..., `v(10)`, *i.e.* vector entries start at index 1. Internally, no dynamic storage is used.

Template Parameters

$T_$	Data type (double, float, complex<double>, ...)
$N_$	Vector size

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.67.2 Constructor & Destructor Documentation**LocalVect (const Element * *el*, const Vect< T_ > & *v*, int *opt* = 0)**

Constructor of an element vector from a global Vect instance.

The constructed vector has local numbering of nodes

Parameters

in	<i>el</i>	Pointer to Element to localize
in	<i>v</i>	Global vector to localize
in	<i>opt</i>	Option for DOF treatment <ul style="list-style-type: none"> • = 0, Normal case [Default] • Any other value : only one DOF is handled (Local vector has as dimension number of degrees of freedom)

LocalVect (const Element & *el*, const Vect< T_ > & *v*, int *opt* = 0)

Constructor of an element vector from a global Vect instance.

The constructed vector has local numbering of nodes

Parameters

in	<i>el</i>	Reference to Element instance to localize
in	<i>v</i>	Global vector to localize
in	<i>opt</i>	Option for DOF treatment <ul style="list-style-type: none"> • = 0, Normal case [Default] • Any other value : only one DOF is handled (Local vector has as dimension number of degrees of freedom)

LocalVect (const Side * *sd*, const Vect< T_ > & *v*, int *opt* = 0)

Constructor of a side vector from a global Vect instance.

The constructed vector has local numbering of nodes

Parameters

in	<i>sd</i>	Pointer to Side to localize
in	<i>v</i>	Global vector to localize
in	<i>opt</i>	Option for DOF treatment <ul style="list-style-type: none"> • = 0, Normal case [Default] • Any other value : only one DOF is handled (Local vector has as dimension number of degrees of freedom)

7.67.3 Member Function Documentation

void getLocal (const Element & *el*, const Vect< T_ > & *v*, int *type*)

Localize an element vector from a global [Vect](#) instance.

The constructed vector has local numbering of nodes This function is called by the constructor↵
: **LocalVect**(const Element **el*, const Vect<T_> &*v*)

Parameters

in	<i>el</i>	Pointer to Element to localize
in	<i>v</i>	Global vector to localize
in	<i>type</i>	Type of element. This is to be chosen among enumerated values: LINE2, TRIANG3, QUAD4, TETRA4, HEXA8, PENTA6

void Localize (const Element * *el*, const Vect< T_ > & *v*, size_t *k* = 0)

Localize an element vector from a global [Vect](#) instance.

The constructed vector has local numbering of nodes This function is called by the constructor↵
: **LocalVect**(const Element **el*, const Vect<T_> &*v*)

Parameters

in	<i>el</i>	Pointer to Side to localize
in	<i>v</i>	Global vector to localize
in	<i>k</i>	Degree of freedom to localize [Default: All degrees of freedom are stored]

void Localize (const Side * *sd*, const Vect< T_ > & *v*, size_t *k* = 0)

Localize a side vector from a global [Vect](#) instance.

The constructed vector has local numbering of nodes This function is called by the constructor↵
: **LocalVect**(const Side **sd*, const Vect<T_> &*v*)

Parameters

in	<i>sd</i>	Pointer to Side to localize
in	<i>v</i>	Global vector to localize
in	<i>k</i>	Degree of freedom to localize [Default: All degrees of freedom are stored]

T_& operator[] (size_t *i*)

Operator [] (Non constant version).

v[*i*] starts at *v*[0] to *v*[size()-1]

T_ operator[] (size_t i) const

Operator [] (Constant version).

v[i] starts at v[0] to v[size()-1]

T_& operator() (size_t i)

Operator () (Non constant version).

v(i) starts at v(1) to v(size()). v(i) is the same element as v[i-1]

T_ operator() (size_t i) const

Operator () (Constant version).

v(i) starts at v(1) to v(size()) v(i) is the same element as v[i-1]

LocalVect<T_,N_>& operator= (const LocalVect< T_, N_ > & v)

Operator =

Copy a [LocalVect](#) instance to the current one

LocalVect<T_,N_>& operator= (const T_ & x)

Operator =

Assign value x to all vector entries

LocalVect<T_,N_>& operator+= (const LocalVect< T_, N_ > & v)

Operator +=

Add vector v to this instance

LocalVect<T_,N_>& operator+= (const T_ & a)

Operator +=

Add constant a to vector entries

LocalVect<T_,N_>& operator-= (const LocalVect< T_, N_ > & v)

Operator -=

Subtract vector v from this instance

LocalVect<T_,N_>& operator-= (const T_ & a)

Operator -=

Subtract constant a from vector entries

LocalVect<T_,N_>& operator*= (const T_ & a)

Operator *=

Multiply vector by constant a

LocalVect<T_,N_>& operator/= (const T_ & a)

Operator /=

Divide vector by constant a

T_ operator, (const LocalVect< T_, N_ > & v) const

Return Dot (scalar) product of two vectors.

A typical use of this operator is `double a = (v,w)` where `v` and `w` are 2 instances of `LocalVect<double,n>`

Parameters

in	<i>v</i>	<code>LocalVect</code> instance by which the current instance is multiplied
----	----------	---

7.68 LPSolver Class Reference

To solve a linear programming problem.

Public Types

- enum `Setting` {
`OBJECTIVE` = 0,
`LE_CONSTRAINT` = 1,
`GE_CONSTRAINT` = 2,
`EQ_CONSTRAINT` = 3 }

Public Member Functions

- `LPSolver` ()
Default constructor.
- `LPSolver` (int nv, int nb_le, int nb_ge, int nb_eq)
Constructor using Linear Program data.
- `~LPSolver` ()
Destructor.
- void `setSize` (int nv, int nb_le, int nb_ge, int nb_eq)
Set optimization parameters.
- void `set` (`Vect< real_t >` &x)
vector of optimization variables
- void `set` (`Setting` opt, const `Vect< real_t >` &a, `real_t` b=0.0)
Set optimization data.
- int `run` ()
Run the linear program solver.
- `real_t` `getObjective` () const
Return objective.

Friends

- ostream & `operator<<` (ostream &s, const `LPSolver` &os)
Output class information.

7.68.1 Detailed Description

To solve a linear programming problem.

The Linear Program reads:

```
Minimise: d(1)*x(1) + ... + d(n)*x(n) + e
Subject to the constraints:
    A(i,1)*x(1) + ... + A(i,n)*x(n) <= a(i)  i=1,...,n_le
    B(i,1)*x(1) + ... + B(i,n)*x(n) >= b(i)  i=1,...,n_ge
    C(i,1)*x(1) + ... + C(i,n)*x(n) =  c(i)  i=1,...,n_eq
    x(i) >= 0, 1<=i<=n
```

Solution is held by the Simplex method Reference: "Numerical Recipes By W.H. Press, B. P. Flannery, S.A. Teukolsky and W.T. Vetterling, Cambridge University Press, 1986"

C-implementation copied from J-P Moreau, Paris

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.68.2 Member Enumeration Documentation

enum Setting

Selects setting option: Objective or Constraints

Enumerator

OBJECTIVE Objective function coefficients
LE_CONSTRAINT 'Less or Equal' constraint coefficients
GE_CONSTRAINT 'Greater or Equal' constraint coefficients
EQ_CONSTRAINT 'Equality' constraint coefficients

7.68.3 Constructor & Destructor Documentation

LPSolver (int *nv*, int *nb_le*, int *nb_ge*, int *nb_eq*)

Constructor using Linear Program data.

Parameters

in	<i>nv</i>	Number of optimization variables
in	<i>nb_le</i>	Number of '<=' inequality constraints
in	<i>nb_ge</i>	Number of '>=' inequality constraints
in	<i>nb_eq</i>	Number of '=' equality constraints

7.68.4 Member Function Documentation

void setSize (int *nv*, int *nb_le*, int *nb_ge*, int *nb_eq*)

Set optimization parameters.

Parameters

in	<i>nv</i>	Number of optimization variables
in	<i>nb_le</i>	Number of '<=' inequality constraints
in	<i>nb_ge</i>	Number of '>=' inequality constraints
in	<i>nb_eq</i>	Number of '=' equality constraints

void set (Vect< real.t > & x)

vector of optimization variables

Parameters

in	<i>x</i>	Vector of optimization variables. Its size must be at least equal to number of optimization variables
----	----------	---

void set (Setting *opt*, const Vect< real.t > & *a*, real.t *b* = 0.0)

Set optimization data.

This function enables providing all optimization data. It has to be used for the objective function and once for each constraint.

Parameters

in	<i>opt</i>	Option for data, to choose among enumerated values: <ul style="list-style-type: none"> • OBJECTIVE To set objective function to minimize • LE_CONSTRAINT To set a '<=' inequality constraint • GE_CONSTRAINT To set a '>=' inequality constraint • EQ_CONSTRAINT To set an equality constraint
in	<i>a</i>	Vector coefficients if the chosen function. If <i>opt</i> ==OBJECTIVE, vector components are the coefficients multiplying the variables in the objective function. if <i>xx</i> _CONSTRAINT, vector components are the coefficients multiplying the variables in the corresponding constraint.
in	<i>b</i>	Constant value in the objective function or in a constraint. Its default value is 0.0

int run ()

Run the linear program solver.

This function runs the linear programming solver using the Simplex algorithm

Returns

0 if process is complete, >0 otherwise

real.t getObjective () const

Return objective.

Once execution is complete, this function returns optimal value of objective

7.69 Material Class Reference

To treat material data. This class enables reading material data in material data files. It also returns these informations by means of its members.

Public Member Functions

- [Material](#) ()
Default constructor.
- [Material](#) (const [Material](#) &m)
Copy constructor.
- [~Material](#) ()
Destructor.
- int [set](#) (int m, const string &name)
Associate to material code number n the material named $name$
- string [getName](#) (int m) const
Return material name for material with code m
- int [getCode](#) (size_t i) const
Return material code for i -th material.
- size_t [getNbMat](#) () const
Return Number of read materials.
- void [setCode](#) (int m)
Associate code m to current material.
- int [check](#) (int c)
- [real_t](#) [Density](#) ()
Return constant density.
- [real_t](#) [Density](#) (const [Point](#)< [real_t](#) > &x, [real_t](#) t)
Return density at point x and time t
- [real_t](#) [SpecificHeat](#) ()
Return constant specific heat.
- [real_t](#) [SpecificHeat](#) (const [Point](#)< [real_t](#) > &x, [real_t](#) t)
Return specific heat at point x and time t
- [real_t](#) [ThermalConductivity](#) ()
Return constant thermal conductivity.
- [real_t](#) [ThermalConductivity](#) (const [Point](#)< [real_t](#) > &x, [real_t](#) t)
Return thermal conductivity at point x and time t
- [real_t](#) [MeltingTemperature](#) ()
Return constant melting temperature.
- [real_t](#) [MeltingTemperature](#) (const [Point](#)< [real_t](#) > &x, [real_t](#) t)
Return melting temperature at point x and time t
- [real_t](#) [EvaporationTemperature](#) ()
Return constant evaporation temperature.
- [real_t](#) [EvaporationTemperature](#) (const [Point](#)< [real_t](#) > &x, [real_t](#) t)
Return evaporation temperature at point x and time t
- [real_t](#) [ThermalExpansion](#) ()
Return constant thermal expansion coefficient.
- [real_t](#) [ThermalExpansion](#) (const [Point](#)< [real_t](#) > &x, [real_t](#) t)

- Return thermal expansion coefficient at point x and time t*

 - `real_t LatentHeatForMelting ()`

Return constant latent heat for melting.

 - `real_t LatentHeatForMelting (const Point< real_t > &x, real_t t)`

Return latent heat for melting at point x and time t

 - `real_t LatentHeatForEvaporation ()`

Return constant latent heat for evaporation.

 - `real_t LatentHeatForEvaporation (const Point< real_t > &x, real_t t)`

Return latent heat for evaporation at point x and time t

 - `real_t DielectricConstant ()`

Return constant dielectric constant.

 - `real_t DielectricConstant (const Point< real_t > &x, real_t t)`

Return dielectric constant at point x and time t

 - `real_t ElectricConductivity ()`

Return constant electric conductivity.

 - `real_t ElectricConductivity (const Point< real_t > &x, real_t t)`

Return electric conductivity at point x and time t

 - `real_t ElectricResistivity ()`

Return constant electric resistivity.

 - `real_t ElectricResistivity (const Point< real_t > &x, real_t t)`

Return electric resistivity at point x and time t

 - `real_t MagneticPermeability ()`

Return constant magnetic permeability.

 - `real_t MagneticPermeability (const Point< real_t > &x, real_t t)`

Return magnetic permeability at point x and time t

 - `real_t Viscosity ()`

Return constant viscosity.

 - `real_t Viscosity (const Point< real_t > &x, real_t t)`

Return viscosity at point x and time t

 - `real_t YoungModulus ()`

Return constant Young modulus.

 - `real_t YoungModulus (const Point< real_t > &x, real_t t)`

Return Young modulus at point x and time t

 - `real_t PoissonRatio ()`

Return constant Poisson ratio.

 - `real_t PoissonRatio (const Point< real_t > &x, real_t t)`

Return Poisson ratio at point x and time t

 - `real_t Property (int i)`

Return constant i -th property.

 - `real_t Property (int i, const Point< real_t > &x, real_t t)`

Return i -th property at point x and time t

 - `Material & operator= (const Material &m)`

Operator =.

7.69.1 Detailed Description

To treat material data. This class enables reading material data in material data files. It also returns these informations by means of its members.

7.69.2 Constructor & Destructor Documentation

Material ()

Default constructor.

It initializes the class and searches for the path where are material data files.

7.69.3 Member Function Documentation

int set (int *m*, const string & *name*)

Associate to material code number *n* the material named *name*

Returns

Number of materials

string getName (int *m*) const

Return material name for material with code *m*

If such a material is not found, return a blank string.

int check (int *c*)

Check if material code *c* is present.


Returns

0 if succeeded, 1 if not.

7.70 Matrix< T_ > Class Template Reference

Virtual class to handle matrices for all storage formats.

Inheritance diagram for Matrix< T_ >:



Public Member Functions

- [Matrix](#) ()
Default constructor.
- [Matrix](#) (const [Matrix](#)< T_ > &*m*)
Copy Constructor.
- virtual [~Matrix](#) ()
Destructor.
- virtual void [reset](#) ()
Set matrix to 0 and reset factorization parameter.
- size_t [getNbRows](#) () const
Return number of rows.
- size_t [getNbColumns](#) () const

- Return number of columns.*

 - void **setPenal** (real_t p)

Set Penalty Parameter (For boundary condition prescription).
- void **setDiagonal** ()

Set the matrix as diagonal.
- T_ **getDiag** (size_t k) const

Return k-th diagonal entry of matrix.
- size_t **size** () const

Return matrix dimension (Number of rows and columns).
- virtual void **MultAdd** (const Vect< T_ > &x, Vect< T_ > &y) const =0

Multiply matrix by vector x and add to y
- virtual void **MultAdd** (T_ a, const Vect< T_ > &x, Vect< T_ > &y) const =0

*Multiply matrix by vector a*x and add to y*
- virtual void **Mult** (const Vect< T_ > &x, Vect< T_ > &y) const =0

Multiply matrix by vector x and save in y
- virtual void **TMult** (const Vect< T_ > &v, Vect< T_ > &w) const =0

Multiply transpose of matrix by vector x and save in y
- virtual void **Axpy** (T_ a, const Matrix< T_ > *x)=0

Add to matrix the product of a matrix by a scalar.
- void **setDiagonal** (Mesh &mesh)

Initialize matrix storage in the case where only diagonal terms are stored.
- virtual void **clear** ()

brief Set all matrix entries to zero
- void **Assembly** (const Element &el, T_ *a)

Assembly of element matrix into global matrix.
- void **Assembly** (const Side &sd, T_ *a)

Assembly of side matrix into global matrix.
- void **Prescribe** (Vect< T_ > &b, const Vect< T_ > &u, int flag=0)

Impose by a penalty method an essential boundary condition, using the Mesh instance provided by the constructor.
- void **Prescribe** (int dof, int code, Vect< T_ > &b, const Vect< T_ > &u, int flag=0)

Impose by a penalty method an essential boundary condition to a given degree of freedom for a given code.
- void **Prescribe** (Vect< T_ > &b, int flag=0)

Impose by a penalty method a homogeneous (=0) essential boundary condition.
- void **Prescribe** (size_t dof, Vect< T_ > &b, const Vect< T_ > &u, int flag=0)

Impose by a penalty method an essential boundary condition when only one DOF is treated.
- void **PrescribeSide** ()

Impose by a penalty method an essential boundary condition when DOFs are supported by sides.
- virtual void **add** (size_t i, size_t j, const T_ &val)=0

Add val to entry (i, j).
- virtual int **Factor** ()=0

Factorize matrix. Available only if the storage class enables it.
- virtual int **solve** (Vect< T_ > &b, bool fact=true)=0

Solve the linear system.
- virtual int **solve** (const Vect< T_ > &b, Vect< T_ > &x, bool fact=true)=0

Solve the linear system.
- int **FactorAndSolve** (Vect< T_ > &b)

- Factorize matrix and solve the linear system.*
- int **FactorAndSolve** (const **Vect**< T_ > &b, **Vect**< T_ > &x)
 - Factorize matrix and solve the linear system.*
- size_t **getLength** () const
 - Return number of stored terms in matrix.*
- int **isDiagonal** () const
 - Say if matrix is diagonal or not.*
- int **isFactorized** () const
 - Say if matrix is factorized or not.*
- virtual size_t **getColInd** (size_t i) const
 - Return Column index for column i (See the description for class **SpMatrix**).*
- virtual size_t **getRowPtr** (size_t i) const
 - Return Row pointer for row i (See the description for class **SpMatrix**).*
- virtual void **set** (size_t i, size_t j, const T_ &val)=0
 - Assign a value to an entry of the matrix.*
- virtual T_ & **operator**() (size_t i, size_t j)=0
 - Operator () (Non constant version).*
- virtual T_ **operator**() (size_t i, size_t j) const =0
 - Operator () (Non constant version).*
- T_ **operator**() (size_t i) const
 - Operator () with one argument (Constant version).*
- T_ & **operator**() (size_t i)
 - Operator () with one argument (Non Constant version).*
- T_ & **operator**[] (size_t k)
 - Operator [] (Non constant version).*
- T_ **operator**[] (size_t k) const
 - Operator [] (Constant version).*
- **Matrix** & **operator=** (**Matrix**< T_ > &m)
 - Operator =.*
- **Matrix** & **operator+=** (const **Matrix**< T_ > &m)
 - Operator +=.*
- **Matrix** & **operator-=** (const **Matrix**< T_ > &m)
 - Operator -=.*
- **Matrix** & **operator=** (const T_ &x)
 - Operator =.*
- **Matrix** & **operator*=** (const T_ &x)
 - Operator *.=.*
- **Matrix** & **operator+=** (const T_ &x)
 - Operator +=.*
- **Matrix** & **operator-=** (const T_ &x)
 - Operator -=.*
- virtual T_ **get** (size_t i, size_t j) const =0
 - Return entry (i, j) of matrix if this one is stored, 0 else.*

7.70.1 Detailed Description

template<class T_>class OFELI::Matrix< T_ >

Virtual class to handle matrices for all storage formats.

This class enables storing and manipulating dense matrices. The template parameter is the type of matrix entries. Any matrix entry can be accessed by the () operator: For instance, if A is an instance of this class, A(i, j) stands for the entry at the i-th row and j-th column, i and j starting from 1. Entries of A can be assigned a value by the same operator.

Template Parameters

<T_>	Data type (real_t, float, complex<real_t>, ...)
------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.70.2 Constructor & Destructor Documentation

Matrix ()

Default constructor.

Initializes a zero-size matrix.

7.70.3 Member Function Documentation

virtual void reset () [virtual]

Set matrix to 0 and reset factorization parameter.

Warning

This function must be used if after a factorization, the matrix has been modified

Reimplemented in [DMatrix< T_ >](#), and [DMatrix< real_t >](#).

T_ getDiag (size_t k) const

Return k-th diagonal entry of matrix.

First entry is given by **getDiag(1)**.

virtual void Axy (T_ a, const Matrix< T_ > * x) [pure virtual]

Add to matrix the product of a matrix by a scalar.

Parameters

in	a	Scalar to premultiply
in	x	Matrix by which a is multiplied. The result is added to current instance

Implemented in [SpMatrix< T_ >](#), [SpMatrix< real_t >](#), [DSMatrix< T_ >](#), [DSMatrix< real_t >](#), [DMatrix< T_ >](#), [DMatrix< real_t >](#), [SkSMMatrix< T_ >](#), [SkMatrix< T_ >](#), [TrMatrix< T_ >](#), [BMatrix< T_ >](#), and [BMatrix< real_t >](#).

void setDiagonal (Mesh & mesh)

Initialize matrix storage in the case where only diagonal terms are stored.

This member function is to be used for explicit time integration schemes

void Assembly (const Element & el, T_ * a)

Assembly of element matrix into global matrix.

Case where element matrix is given by a C-array.

Parameters

in	<i>el</i>	Pointer to element instance
in	<i>a</i>	Element matrix as a C-array

void Assembly (const Side & sd, T_ * a)

Assembly of side matrix into global matrix.

Case where side matrix is given by a C-array.

Parameters

in	<i>sd</i>	Pointer to side instance
in	<i>a</i>	Side matrix as a C-array instance

void Prescribe (Vect< T_ > & b, const Vect< T_ > & u, int flag = 0)

Impose by a penalty method an essential boundary condition, using the [Mesh](#) instance provided by the constructor.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. The penalty parameter is defined by default equal to 1.e20. It can be modified by member function `setPenal(..)`.

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side.
in	<i>u</i>	Vect instance that contains imposed valued at DOFs where they are to be imposed.
in	<i>flag</i>	Parameter to determine whether only the right-hand side is to be modified (dof>0) or both matrix and right-hand side (dof=0, default value).

void Prescribe (int dof, int code, Vect< T_ > & b, const Vect< T_ > & u, int flag = 0)

Impose by a penalty method an essential boundary condition to a given degree of freedom for a given code.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. The penalty parameter is defined by default equal to 1.e20. It can be modified by member function `setPenal(..)`.

Parameters

in	dof	Degree of freedom for which a boundary condition is to be enforced
in	code	Code for which a boundary condition is to be enforced
in,out	b	Vect instance that contains right-hand side.
in	u	Vect instance that contains imposed valued at DOFs where they are to be imposed.
in	flag	Parameter to determine whether only the right-hand side is to be modified (dof>0) or both matrix and right-hand side (dof=0, default value).

void Prescribe ([Vect](#)< T_ > & b, int flag = 0)

Impose by a penalty method a homegeneous (=0) essential boundary condition.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. The penalty parameter is defined by default equal to 1.e20. It can be modified by member function **setPenal(..)**.

Parameters

in,out	b	Vect instance that contains right-hand side.
in	flag	Parameter to determine whether only the right-hand side is to be modified (dof>0) or both matrix and right-hand side (dof=0, default value).

void Prescribe (size_t dof, [Vect](#)< T_ > & b, const [Vect](#)< T_ > & u, int flag = 0)

Impose by a penalty method an essential boundary condition when only one DOF is treated.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. This gunction is to be used if only one DOF per node is treated in the linear system. The penalty parameter is by default equal to 1.e20. It can be modified by member function **setPenal**.

Parameters

in	dof	Label of the concerned degree of freedom (DOF).
in,out	b	Vect instance that contains right-hand side.
in	u	Vect instance that conatins imposed valued at DOFs where they are to be imposed.
in	flag	Parameter to determine whether only the right-hand side is to be modified (dof>0) or both matrix and right-hand side (dof=0, default value).

void PrescribeSide ()

Impose by a penalty method an essential boundary condition when DOFs are supported by sides.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. The penalty parameter is defined by default equal to 1.e20. It can be modified by member function **setPenal(..)**.

virtual int solve (Vect< T_ > & b, bool fact = true) [pure virtual]

Solve the linear system.

If the inherited class is [SpMatrix](#), the function uses an iterative method once this one has been chosen. Otherwise, the method solves the linear system by factorization.

Implemented in [DMatrix< T_ >](#), [DMatrix< real.t >](#), [SkSMatrix< T_ >](#), [SkMatrix< T_ >](#), [DSMatrix< T_ >](#), [DSMatrix< real.t >](#), [BMatrix< T_ >](#), [BMatrix< real.t >](#), and [TrMatrix< T_ >](#).

virtual int solve (const Vect< T_ > & b, Vect< T_ > & x, bool fact = true) [pure virtual]

Solve the linear system.

If the inherited class is [SpMatrix](#), the function uses an iterative method once this one has been chosen. Otherwise, the method solves the linear system by factorization.

Parameters

in	<i>b</i>	Vect instance that contains right-hand side
out	<i>x</i>	Vect instance that contains solution
in	<i>fact</i>	Set to true if factorization is to be performed, false if not. [Default: true]

Returns

- 0 if solution was normally performed
- *n* if the *n*-th pivot is null
Solution is performed only if factorization has previously been invoked.

Implemented in [SpMatrix< T_ >](#), [SpMatrix< real.t >](#), [DMatrix< T_ >](#), [DMatrix< real.t >](#), [SkSMatrix< T_ >](#), [SkMatrix< T_ >](#), [DSMatrix< T_ >](#), [DSMatrix< real.t >](#), [BMatrix< T_ >](#), [BMatrix< real.t >](#), and [TrMatrix< T_ >](#).

int FactorAndSolve (Vect< T_ > & b)

Factorize matrix and solve the linear system.

This is available only if the storage class enables it.

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side on input and solution on output
--------	----------	---

int FactorAndSolve (const Vect< T_ > & b, Vect< T_ > & x)

Factorize matrix and solve the linear system.

This is available only if the storage class enables it.

Parameters

in	<i>b</i>	Vect instance that contains right-hand side
out	<i>x</i>	Vect instance that contains solution

Returns

- 0 if solution was normally performed
- *n* if the *n*-th pivot is nul

int isFactorized () const

Say if matrix is factorized or not.

If the matrix was not factorized, the class does not allow solving by a direct solver.

virtual void set (size_t i, size_t j, const T_ & val) [pure virtual]

Assign a value to an entry of the matrix.

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index
in	<i>val</i>	Value to assign

Implemented in [SpMatrix< T_ >](#), [SpMatrix< real_t >](#), [SkSMatrix< T_ >](#), [DMatrix< T_ >](#), [DMatrix< real_t >](#), [SkSMatrix< T_ >](#), [TrMatrix< T_ >](#), [BMatrix< T_ >](#), [BMatrix< real_t >](#), [DSMatrix< T_ >](#), and [DSMatrix< real_t >](#).

virtual T_ & operator() (size_t i, size_t j) [pure virtual]

Operator () (Non constant version).

Returns the (i, j) entry of the matrix.

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implemented in [SpMatrix< T_ >](#), [SpMatrix< real_t >](#), [DMatrix< T_ >](#), [DMatrix< real_t >](#), [SkSMatrix< T_ >](#), [SkMatrix< T_ >](#), [DSMatrix< T_ >](#), [DSMatrix< real_t >](#), [TrMatrix< T_ >](#), [BMatrix< T_ >](#), and [BMatrix< real_t >](#).

virtual T_ operator() (size_t i, size_t j) const [pure virtual]

Operator () (Non constant version).

Returns the (i, j) entry of the matrix.

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implemented in [SpMatrix< T_ >](#), [SpMatrix< real_t >](#), [DMatrix< T_ >](#), [DMatrix< real_t >](#), [SkSMatrix< T_ >](#), [SkMatrix< T_ >](#), [DSMatrix< T_ >](#), [DSMatrix< real_t >](#), [TrMatrix< T_ >](#), [BMatrix< T_ >](#), and [BMatrix< real_t >](#).

T_ operator() (size_t i) const

Operator () with one argument (Constant version).

Returns i-th position in the array storing matrix entries. The first entry is at location 1. Entries are stored row by row.

Parameters

in	<i>i</i>	entry index
----	----------	-------------

T_ & operator() (size_t i)

Operator () with one argument (Non Constant version).

Returns i-th position in the array storing matrix entries. The first entry is at location 1. Entries are stored row by row.

Parameters

<code>in</code>	<code>i</code>	entry index
-----------------	----------------	-------------

`T_& operator[] (size_t k)`

Operator [] (Non constant version).

Returns k-th stored element in matrix Index k starts at 0.

`T_ operator[] (size_t k) const`

Operator [] (Constant version).

Returns k-th stored element in matrix Index k starts at 0.

`Matrix& operator= (Matrix< T_ > & m)`

Operator =.

Copy matrix m to current matrix instance.

`Matrix& operator+= (const Matrix< T_ > & m)`

Operator +=.

Add matrix m to current matrix instance.

`Matrix& operator-= (const Matrix< T_ > & m)`

Operator -=.

Subtract matrix m from current matrix instance.

`Matrix& operator= (const T_ & x)`

Operator =.

Assign constant value x to all matrix entries.

`Matrix& operator*= (const T_ & x)`

Operator *.

Premultiply matrix entries by constant value x

`Matrix& operator+= (const T_ & x)`

Operator +=.

Add constant value x to all matrix entries.

`Matrix& operator-= (const T_ & x)`

Operator -=.

Subtract constant value x from all matrix entries.

7.71 Mesh Class Reference

To store and manipulate finite element meshes.

Public Member Functions

- **Mesh** ()
Default constructor (Empty mesh)
- **Mesh** (const string &file, bool bc=false, int opt=NODE_DOF, int nb_dof=1)
Constructor using a mesh file.
- **Mesh** (real_t xmin, real_t xmax, size_t nb_el, size_t p=1, size_t nb_dof=1)
Constructor for a 1-D mesh. The domain is the interval [xmin,xmax].
- **Mesh** (const **Grid** &g, int opt=QUADRILATERAL)
*Constructor for a uniform finite difference grid given by and instance of class **Grid**.*
- **Mesh** (const **Grid** &g, int shape, int opt)
*Constructor of dual mesh for a uniform finite difference grid given by and instance of class **Grid**.*
- **Mesh** (real_t xmin, real_t xmax, size_t ne, int c1, int c2, int p=1, size_t nb_dof=1)
Constructor for a uniform 1-D finite element mesh.
- **Mesh** (real_t xmin, real_t xmax, real_t ymin, real_t ymax, size_t nx, size_t ny, int cx0, int cxN, int cy0, int cyN, int opt=0, size_t nb_dof=1)
Constructor for a uniform 2-D structured finite element mesh.
- **Mesh** (real_t xmin, real_t xmax, real_t ymin, real_t ymax, real_t zmin, real_t zmax, size_t nx, size_t ny, size_t nz, int cx0, int cxN, int cy0, int cyN, int cz0, int czN, int opt=0, size_t nb_dof=1)
Constructor for a uniform 3-D structured finite element mesh.
- **Mesh** (const **Mesh** &m, const **Point**< real_t > &x.bl, const **Point**< real_t > &x.tr)
Constructor that extracts the mesh of a rectangular region from an initial mesh.
- **Mesh** (const **Mesh** &mesh, int opt, size_t dof1, size_t dof2, bool bc=false)
Constructor that copies the input mesh and selects given degrees of freedom.
- **Mesh** (const **Mesh** &ms)
Copy Constructor.
- **~Mesh** ()
Destructor.
- void **setDim** (size_t dim)
Define space dimension. Normally, between 1 and 3.
- void **Add** (**Node** *nd)
Add a node to mesh.
- void **Add** (**Element** *el)
Add an element to mesh.
- void **Add** (**Side** *sd)
Add a side to mesh.
- void **Add** (**Edge** *ed)
Add an edge to mesh.
- **Mesh** & **operator*=** (real_t a)
*Operator *=*
- void **get** (const string &mesh_file)
Read mesh data in file.
- void **get** (const string &mesh_file, int ff, int nb_dof=1)
Read mesh data in file with giving its format.
- void **setDOFSupport** (int opt, int nb_nodes=1)
Define supports of degrees of freedom.
- void **setNbDOFPerNode** (size_t nb_dof=1)

- Define number of degrees of freedom for each node.*

 - void `setPointInDomain` (`Point`< `real_t` > x)

Define a point in the domain. This function makes sense only if boundary mesh is given without internal mesh (Case of Boundary Elements)
- void `removeImposedDOF` ()

Eliminate equations corresponding to imposed DOF.
- size_t `NumberEquations` (size_t dof=0)

Renumber Equations.
- size_t `NumberEquations` (size_t dof, int c)

Renumber Equations.
- int `getAllSides` (int opt=0)

Determine all mesh sides.
- size_t `getNbSideNodes` () const

Return the number of nodes on each side.
- size_t `getNbElementNodes` () const

Return the number of nodes in each element.
- int `getBoundarySides` ()

Determine all boundary sides.
- int `createBoundarySideList` ()

Create list of boundary sides.
- int `getBoundaryNodes` ()

Determine all boundary nodes.
- int `createInternalSideList` ()

Create list of internal sides (not on the boundary).
- int `getAllEdges` ()

Determine all edges.
- void `getNodeNeighborElements` ()

Create node neighboring elements.
- void `getElementNeighborElements` ()

Create element neighboring elements.
- void `setMaterial` (int code, const string &mname)

Associate material to code of element.
- void `Reorder` (size_t m=GRAPH_MEMORY)

Renumber mesh nodes according to reverse Cuthill Mc Kee algorithm.
- void `Add` (size_t num, `real_t` *x)

Add a node by giving its label and an array containing its coordinates.
- void `DeleteNode` (size_t label)

Remove a node given by its label.
- void `DeleteElement` (size_t label)

Remove an element given by its label.
- void `DeleteSide` (size_t label)

Remove a side given by its label.
- void `Delete` (`Node` *nd)

Remove a node given by its pointer.
- void `Delete` (`Element` *el)

Remove a node given by its pointer.
- void `Delete` (`Side` *sd)

- Remove a side given by its pointer.*

 - void [Delete](#) ([Edge](#) *ed)
- Remove an edge given by its pointer.*

 - void [RenumberNode](#) (size_t n1, size_t n2)
- Renumber a node.*

 - void [RenumberElement](#) (size_t n1, size_t n2)
- Renumber an element.*

 - void [RenumberSide](#) (size_t n1, size_t n2)
- Renumber a side.*

 - void [RenumberEdge](#) (size_t n1, size_t n2)
- Renumber an edge.*

 - void [setList](#) (const std::vector< [Node](#) * > &nl)
- Initialize list of mesh nodes using the input vector.*

 - void [setList](#) (const std::vector< [Element](#) * > &el)
- Initialize list of mesh elements using the input vector.*

 - void [setList](#) (const std::vector< [Side](#) * > &sl)
- Initialize list of mesh sides using the input vector.*

 - void [Rescale](#) (real_t sx, real_t sy=0., real_t sz=0.)
- Rescale mesh by multiplying node coordinates by constants.*

 - size_t [getDim](#) () const
- Return space dimension.*

 - size_t [getNbNodes](#) () const
- Return number of nodes.*

 - size_t [getNbMarkedNodes](#) () const
- Return number of marked nodes.*

 - size_t [getNbVertices](#) () const
- Return number of vertices.*

 - size_t [getNbDOF](#) () const
- Return total number of degrees of freedom (DOF)*

 - size_t [getNbEq](#) () const
- Return number of equations.*

 - size_t [getNbEq](#) (int i) const
- Return number of equations for the i-th set of degrees of freedom.*

 - size_t [getNbElements](#) () const
- Return number of elements.*

 - size_t [getNbSides](#) () const
- Return number of sides.*

 - size_t [getNbEdges](#) () const
- Return number of sides.*

 - size_t [getNbBoundarySides](#) () const
- Return number of boundary sides.*

 - size_t [getNbInternalSides](#) () const
- Return number of internal sides.*

 - size_t [getNbMat](#) () const
- Return number of materials.*

 - void [AddMidNodes](#) (int g=0)

- Add mid-side nodes.*

 - `Point< real_t > getMaxCoord () const`
Return maximum coordinates of nodes.
 - `Point< real_t > getMinCoord () const`
Return minimum coordinates of nodes.
 - `void set (Node *nd)`
Replace node in the mesh.
 - `void set (Element *el)`
Replace element in the mesh.
 - `void set (Side *sd)`
Choose side in the mesh.
 - `bool NodesAreDOF () const`
Return information about DOF type.
 - `bool SidesAreDOF () const`
Return information about DOF type.
 - `bool EdgesAreDOF () const`
Return information about DOF type.
 - `bool ElementsAreDOF () const`
Return information about DOF type.
 - `int getDOFSupport () const`
Return information on dof support Return an integer according to enumerated values: NODE_DOF, EL↔EMENT_DOF SIDE_DOF.
 - `void Deform (const Vect< real_t > &u, real_t rate=0.2)`
Deform mesh according to a displacement vector.
 - `void put (const string &mesh_file) const`
Write mesh data on file.
 - `void save (const string &mesh_file) const`
Write mesh data on file in various formats.
 - `bool withImposedDOF () const`
Return true if imposed DOF count in equations, false if not.
 - `bool isStructured () const`
Return true is mesh is structured, false if not.
 - `size_t getNodeNewLabel (size_t n) const`
Return new label of node of a renumbered node.
 - `void getList (vector< Node * > &nl) const`
Fill vector nl with list of pointers to nodes.
 - `void getList (vector< Element * > &el) const`
Fill vector el with list of pointers to elements.
 - `void getList (vector< Side * > &sl) const`
Fill vector sl with list of pointers to sides.
 - `Node * getPtrNode (size_t i) const`
Return pointer to node with label i.
 - `Node & getNode (size_t i) const`
Return refernce to node with label i
 - `Element * getPtrElement (size_t i) const`
Return pointer to element with label i
 - `Element & getElement (size_t i) const`

- Return reference to element with label i*

 - `Side * getPtrSide (size_t i) const`

Return pointer to side with label i

- `Side & getSide (size_t i) const`

Return reference to side with label i

- `Edge * getPtrEdge (size_t i) const`

Return pointer to edge with label i

- `Edge & getEdge (size_t i) const`

Return reference to edge with label i

- `size_t getNodeLabel (size_t i) const`

Return label of i -th node.

- `size_t getElementLabel (size_t i) const`

Return label of i -th element.

- `size_t getSideLabel (size_t i) const`

Return label of i -th side.

- `size_t getEdgeLabel (size_t i) const`

Return label of i -th edge.

- `void topNode () const`

Reset list of nodes at its top position (Non constant version)

- `void topBoundaryNode () const`

Reset list of boundary nodes at its top position (Non constant version)

- `void topMarkedNode () const`

Reset list of marked nodes at its top position (Non constant version)

- `void topElement () const`

Reset list of elements at its top position (Non constant version)

- `void topSide () const`

Reset list of sides at its top position (Non constant version)

- `void topBoundarySide () const`

Reset list of boundary sides at its top position (Non constant version)

- `void topInternalSide () const`

Reset list of intrrenal sides at its top position (Non constant version)

- `void topEdge () const`

Reset list of edges at its top position (Non constant version)

- `void topBoundaryEdge () const`

Reset list of boundary edges at its top position (Non constant version)

- `Node * getNode () const`

Return pointer to current node and move to next one (Non constant version)

- `Node * getBoundaryNode () const`

Return pointer to current boundary node and move to next one (Non constant version)

- `Node * getMarkedNode () const`

Return pointer to current marked node and move to next one (Non constant version)

- `Element * getElement () const`

Return pointer to current element and move to next one (Non constant version)

- `Element * getActiveElement () const`

Return pointer to current element and move to next one (Non constant version)

- `Side * getSide () const`

- Return pointer to current side and move to next one (Non constant version)*

 - `Side * getBoundarySide () const`

Return pointer to current boundary side and move to next one (Non constant version)

- `Side * getInternalSide () const`

Return pointer to current internal side and move to next one (Non constant version)

- `Edge * getEdge () const`

Return pointer to current edge and move to next one (Non constant version)

- `Edge * getBoundaryEdge () const`

Return pointer to current boundary edge and move to next one (Non constant version)

- `int getShape () const`

Determine shape of elements Return Shape index (see enum ElementShape) if all elements have the same shape, 0 if not.

- `Element * operator() (size_t i) const`

Operator () : Return pointer to i-th element.

- `Node * operator[] (size_t i) const`

Operator [] : Return pointer to i-th node.

- `size_t operator() (size_t i, size_t n) const`

Operator () : Return pointer to i-th node of n-th element.

- `Mesh & operator= (Mesh &ms)`

Operator = : Assign a Mesh instance.

Friends

- `void Refine (Mesh &in_mesh, Mesh &out_mesh)`
- Refine mesh. Subdivide each triangle into 4 subtriangles. This member function is valid for 2-D triangular meshes only.*

7.71.1 Detailed Description

To store and manipulate finite element meshes.

Class `Mesh` enables defining as an object a finite element mesh. A finite element mesh is characterized by its nodes, elements and sides. Each of these types of data constitutes a class in the `OFELI` library.

The standard procedure to introduce the finite element mesh is to provide an input file containing its data. For this, we have defined our own mesh data file (following the XML syntax). Of course, a developer can write his own function to read his finite element mesh file using the methods in `Mesh`.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.71.2 Constructor & Destructor Documentation

`Mesh (const string & file, bool bc = false, int opt = NODE_DOF, int nb_dof = 1)`

Constructor using a mesh file.

Parameters

in	<i>file</i>	File containing mesh data. The extension of the file yields the file format: The extension .m implies OFELI file format and .msh implies GMSH msh file.
in	<i>bc</i>	Flag to remove (true) or not (false) imposed Degrees of Freedom [default: false]
in	<i>opt</i>	Type of DOF support: To choose among enumerated values NO↔DE_DOF, SIDE_DOF or ELEMENT_DOF. Say if degrees of freedom (unknowns) are supported by nodes, sides or elements.
in	<i>nb_dof</i>	Number of degrees of freedom per node [Default: 1].

Mesh (real_t xmin, real_t xmax, size_t nb_el, size_t p = 1, size_t nb_dof = 1)

Constructor for a 1-D mesh. The domain is the interval [xmin,xmax].

Parameters

in	<i>xmin</i>	Value of xmin
in	<i>xmax</i>	Value of xmax
in	<i>nb_el</i>	Number of elements to generate
in	<i>p</i>	Degree of finite element polynomial (Default = 1)
in	<i>nb_dof</i>	Number of degrees of freedom for each node (Default = 1)

Mesh (const Grid & g, int opt = QUADRILATERAL)

Constructor for a uniform finite difference grid given by and instance of class [Grid](#).

Parameters

in	<i>g</i>	Grid instance
in	<i>opt</i>	Optional value to say which type of elements to generate <ul style="list-style-type: none"> • TRIANGLE: Mesh elements are triangles • QUADRILATERAL: Mesh elements are quadrilaterals [default]

Mesh (const Grid & g, int shape, int opt)

Constructor of dual mesh for a uniform finite difference grid given by and instance of class [Grid](#).

Parameters

in	<i>g</i>	Grid instance
in	<i>shape</i>	Value to say which type of elements to generate <ul style="list-style-type: none"> • TRIANGLE: Mesh elements are triangles • QUADRILATERAL: Mesh elements are quadrilaterals [default]
in	<i>opt</i>	This argument can take any value. It is here only to distinguish from the other constructor using Grid instance.

Remarks

This constructor is to be used to obtain a dual mesh from a structured grid. It is mainly useful if a cell centered finite volume method is used.

Mesh (real_t xmin, real_t xmax, size_t ne, int c1, int c2, int p = 1, size_t nb_dof = 1)

Constructor for a uniform 1-D finite element mesh.

The domain is the line (xmin,xmax)

Parameters

in	<i>xmin</i>	Minimal coordinate
in	<i>xmax</i>	Maximal coordinate
in	<i>ne</i>	Number of elements
in	<i>c1</i>	Code for the first node (x=xmin)
in	<i>c2</i>	Code for the last node (x=xmax)
in	<i>p</i>	Degree of approximation polynomial [Default: 1].
in	<i>nb_dof</i>	Number of degrees of freedom per node [Default: 1].

Remarks

The option p can be set to 1 if the user intends to use finite differences.

Mesh (real_t xmin, real_t xmax, real_t ymin, real_t ymax, size_t nx, size_t ny, int cx0, int cxN, int cy0, int cyN, int opt = 0, size_t nb_dof = 1)

Constructor for a uniform 2-D structured finite element mesh.

The domain is the rectangle (xmin,xmax)x(ymin,ymax)

Parameters

in	<i>xmin</i>	Minimal x-coordinate
in	<i>xmax</i>	Maximal x-coordinate
in	<i>ymin</i>	Minimal y-coordinate
in	<i>ymax</i>	Maximal y-coordinate
in	<i>nx</i>	Number of subintervals on the x-axis
in	<i>ny</i>	Number of subintervals on the y-axis
in	<i>cx0</i>	Code for nodes generated on the line x=x0 if >0, for sides on this line if <0
in	<i>cxN</i>	Code for nodes generated on the line x=xN if >0, for sides on this line if <0
in	<i>cy0</i>	Code for nodes generated on the line y=y0 if >0, for sides on this line if <0
in	<i>cyN</i>	Code for nodes generated on the line y=yN if >0, for sides on this line if <0
in	<i>opt</i>	Flag to generate elements as well (if not zero) [Default: 0]. If the flag is not 0, it can take one of the enumerated values: TRIANGLE or QUADRILATERAL, with obvious meaning.
in	<i>nb_dof</i>	Number of degrees of freedom per node [Default: 1].

Remarks

The option opt can be set to 0 if the user intends to use finite differences.

Mesh (real.t xmin, real.t xmax, real.t ymin, real.t ymax, real.t zmin, real.t zmax, size.t nx, size.t ny, size.t nz, int cx0, int cxN, int cy0, int cyN, int cz0, int czN, int opt = 0, size.t nb_dof = 1)

Constructor for a uniform 3-D structured finite element mesh.

The domain is the parallepiped (xmin,xmax)x(ymin,ymax)x(zmin,zmax)

Parameters

in	xmin	Minimal x-coordinate
in	xmax	Maximal x-coordinate
in	ymin	Minimal y-coordinate
in	ymax	Maximal y-coordinate
in	zmin	Minimal z-coordinate
in	zmax	Maximal z-coordinate
in	nx	Number of subintervals on the x-axis
in	ny	Number of subintervals on the y-axis
in	nz	Number of subintervals on the z-axis
in	cx0	Code for nodes generated on the line x=xmin if >0, for sides on this line if <0
in	cxN	Code for nodes generated on the line x=xmax if >0, for sides on this line if <0
in	cy0	Code for nodes generated on the line y=ymin if >0, for sides on this line if <0
in	cyN	Code for nodes generated on the line y=ymax if >0, for sides on this line if <0
in	cz0	Code for nodes generated on the line z=zmin if >0, for sides on this line if <0
in	czN	Code for nodes generated on the line z=zmax if >0, for sides on this line if <0
in	opt	Flag to generate elements as well (if not zero) [Default: 0]. If the flag is not 0, it can take one of the enumerated values: HEXAHEDRON or TETRAHEDRON, with obvious meaning.
in	nb_dof	Number of degrees of freedom per node [Default: 1].

Remarks

The option opt can be set to 0 if the user intends to use finite differences.

Mesh (const Mesh & m, const Point< real.t > & x_bl, const Point< real.t > & x_tr)

Constructor that extracts the mesh of a rectangular region from an initial mesh.

This constructor is useful for zooming purposes for instance.

Parameters

in	m	Initial mesh from which the submesh is extracted
in	x_bl	Coordinate of bottom left vertex of the rectangle
in	x_tr	Coordinate of top right vertex of the rectangle

Mesh (const Mesh & mesh, int opt, size.t dof1, size.t dof2, bool bc = false)

Constructor that copies the input mesh and selects given degrees of freedom.

This constructor is to be used for coupled problems where each subproblem uses a choice of degrees of freedom.

Parameters

in	<i>mesh</i>	Initial mesh from which the submesh is extracted
in	<i>opt</i>	Type of DOF support: To choose among enumerated values NO↔DE_DOF, SIDE_DOF or ELEMENT_DOF.
in	<i>dof1</i>	Label of first degree of freedom to select to the output mesh
in	<i>dof2</i>	Label of last degree of freedom to select to the output mesh
in	<i>bc</i>	Flag to remove (true) or not (false) imposed Degrees of Freedom [Default: false]

Mesh (const Mesh & *ms*)

Copy Constructor.

Parameters

in	<i>ms</i>	Mesh instance to copy
----	-----------	---------------------------------------

7.71.3 Member Function Documentation

void setDim (size_t *dim*)

Define space dimension. Normally, between 1 and 3.

Parameters

in	<i>dim</i>	Space dimension to set (must be between 1 and 3)
----	------------	--

void Add (Node * *nd*)

Add a node to mesh.

Parameters

in	<i>nd</i>	Pointer to Node to add
----	-----------	--

void Add (Element * *el*)

Add an element to mesh.

Parameters

in	<i>el</i>	Pointer to Element to add
----	-----------	---

void Add (Side * *sd*)

Add a side to mesh.

Parameters

in	<i>sd</i>	Pointer to Side to add
----	-----------	--

void Add (Edge * *ed*)

Add an edge to mesh.

Parameters

<code>in</code>	<code>ed</code>	Pointer to Edge to add
-----------------	-----------------	--

Mesh& operator*= (real_t a)

Operator *=

Rescale mesh coordinates by multiplying by a factor

Parameters

<code>in</code>	<code>a</code>	Value to multiply by
-----------------	----------------	----------------------

void get (const string & mesh_file)

Read mesh data in file.

[Mesh](#) file must be in [OFELI](#) format. See "File Formats" page

Parameters

<code>in</code>	<code>mesh_file</code>	Mesh file name
-----------------	------------------------	--------------------------------

void get (const string & mesh_file, int ff, int nb_dof = 1)

Read mesh data in file with giving its format.

File format can be chosen among a variety of choices. See "File Formats" page

Parameters

<code>in</code>	<code>mesh_file</code>	Mesh file name
<code>in</code>	<code>ff</code>	File format: Integer to chose among enumerated values: OFELI_FF , GMSH , MATLAB , EASYMESH , GAMBIT , BAMG , NETGEN , TRIANGLE_FF
<code>in</code>	<code>nb_dof</code>	Number of degrees of freedom per node (Default value: 1)

void setDOFSupport (int opt, int nb_nodes = 1)

Define supports of degrees of freedom.

Parameters

<code>in</code>	<code>opt</code>	DOF type: <ul style="list-style-type: none"> • NODE_DOF: Degrees of freedom are supported by nodes • SIDE_DOF: Degrees of freedom are supported by sides • EDGE_DOF: Degrees of freedom are supported by edges • ELEMENT_DOF: Degrees of freedom are supported by elements
<code>in</code>	<code>nb_nodes</code>	Number of nodes on sides or elements (default=1). This parameter is useful only if dofs are supported by sides or elements

Note

This member function creates all mesh sides if the option [ELEMENT_DOF](#) or [SIDE_DOF](#) is selected. So it not necessary to call [getAllSides\(\)](#) after

void setNbDOFPerNode (*size_t nb_dof* = 1)

Define number of degrees of freedom for each node.

Parameters

in	<i>nb_dof</i>	Number of degrees of freedom (unknowns) for each mesh node (Default value is 1)
-----------	---------------	---

Note

This function first declares nodes as unknown supports, sets the number of degrees of freedom and rennumbers equations

void setPointInDomain (Point< real.t > x)

Define a point in the domain. This function makes sense only if boundary mesh is given without internal mesh (Case of Boundary Elements)

Parameters

in	<i>x</i>	Coordinates of point to define
-----------	----------	--------------------------------

size.t NumberEquations (size.t dof = 0)

Renummer Equations.

Parameters

in	<i>dof</i>	Label of degree of freedom for which numbering is performed. Default value (0) means that all degrees of freedom are taken into account
-----------	------------	---

size.t NumberEquations (size.t dof, int c)

Renummer Equations.

Parameters

in	<i>dof</i>	Label of degree of freedom for which numbering is performed.
in	<i>c</i>	code for which degrees of freedom are enforced.

int getAllSides (int opt = 0)

Determine all mesh sides.

Returns

Number of all sides.

int getBoundarySides ()

Determine all boundary sides.

Returns

Number of boundary sides.

int createBoundarySideList ()

Create list of boundary sides.

This function is useful to loop over boundary sides without testing. Once this one is called, the function [getNbBoundarySides\(\)](#) is available. Moreover, looping over boundary sides is available via the member functions [topBoundarySide\(\)](#) and [getBoundarySide\(\)](#)

Returns

Number of boundary sides.

int getBoundaryNodes ()

Determine all boundary nodes.

Returns

n Number of boundary nodes.

int createInternalSideList ()

Create list of internal sides (not on the boundary).

This function is useful to loop over internal sides without testing. Once this one is called, the function [getNbInternalSides\(\)](#) is available. Moreover, looping over internal sides is available via the member functions [topInternalSide\(\)](#) and [getInternalSide\(\)](#)

Returns

n Number of internal sides.

int getAllEdges ()

Determine all edges.

Returns

Number of all edges.

void getNodeNeighborElements ()

Create node neighboring elements.

This function is generally useful when, for a numerical method, one looks for a given node to the list of elements that share this node. Once this function is invoked, one can retrieve the list of neighboring elements of any node ([Node::getNeigEl](#))

void getElementNeighborElements ()

Create element neighboring elements.

This function creates for each element the list of elements that share a side with it. Once this function is invoked, one can retrieve the list of neighboring elements of any element ([Element::getNeighborElement](#))

void setMaterial (int code, const string & mname)

Associate material to code of element.

Parameters

in	<i>code</i>	Element code for which material is assigned
in	<i>mname</i>	Name of material

void Reorder (size_t *m* = GRAPH_MEMORY)

Renummer mesh nodes according to reverse Cuthill Mc Kee algorithm.

Parameters

in	<i>m</i>	Memory size needed for matrix graph (default value is GRAPH_MEMORY, see OFELI_Config.h)
-----------	----------	---

void Add (size_t *num*, real_t * *x*)

Add a node by giving its label and an array containing its coordinates.

Parameters

in	<i>num</i>	Label of node to add
in	<i>x</i>	C-array of node coordinates

void DeleteNode (size_t *label*)

Remove a node given by its label.

This function does not release the space previously occupied

Parameters

in	<i>label</i>	Label of node to delete
-----------	--------------	-------------------------

void DeleteElement (size_t *label*)

Remove an element given by its label.

This function does not release the space previously occupied

Parameters

in	<i>label</i>	Label of element to delete
-----------	--------------	----------------------------

void DeleteSide (size_t *label*)

Remove a side given by its label.

This function does not release the space previously occupied

Parameters

in	<i>label</i>	Label of side to delete
-----------	--------------	-------------------------

void Delete (Node * *nd*)

Remove a node given by its pointer.

This function does not release the space previously occupied

Parameters

in	<i>nd</i>	Pointer to node to delete
-----------	-----------	---------------------------

void Delete (Element * *el*)

Remove a node given by its pointer.

This function does not release the space previously occupied

Parameters

in	<i>el</i>	Pointer to element to delete
-----------	-----------	------------------------------

void Delete (Side * *sd*)

Remove a side given by its pointer.

This function does not release the space previously occupied

Parameters

in	<i>sd</i>	Pointer to side to delete
-----------	-----------	---------------------------

void Delete (Edge * *ed*)

Remove an edge given by its pointer.

This function does not release the space previously occupied

Parameters

in	<i>ed</i>	Pointer to edge to delete
-----------	-----------	---------------------------

void RenumberNode (size_t *n1*, size_t *n2*)

Renumber a node.

Parameters

in	<i>n1</i>	Old label
in	<i>n2</i>	New label

void RenumberElement (size_t *n1*, size_t *n2*)

Renumber an element.

Parameters

in	<i>n1</i>	Old label
in	<i>n2</i>	New label

void RenumberSide (size_t *n1*, size_t *n2*)

Renumber a side.

Parameters

in	<i>n1</i>	Old label
in	<i>n2</i>	New label

void RenumberEdge (size_t *n1*, size_t *n2*)

Renumber an edge.

Parameters

in	<i>n1</i>	Old label
in	<i>n2</i>	New label

void setList (const std::vector< Node * > & nl)

Initialize list of mesh nodes using the input vector.

Parameters

in	<i>nl</i>	vector instance that contains the list of pointers to nodes
-----------	-----------	---

void setList (const std::vector< Element * > & el)

Initialize list of mesh elements using the input vector.

Parameters

in	<i>el</i>	vector instance that contains the list of pointers to elements
-----------	-----------	--

void setList (const std::vector< Side * > & sl)

Initialize list of mesh sides using the input vector.

Parameters

in	<i>sl</i>	vector instance that contains the list of pointers to sides
-----------	-----------	---

void Rescale (real_t sx, real_t sy = 0., real_t sz = 0.)

Rescale mesh by multiplying node coordinates by constants.

This function can be used e.g. for changing coordinate units

Parameters

in	<i>sx</i>	Factor to multiply by x coordinates
in	<i>sy</i>	Factor to multiply by y coordinates [Default: <i>sx</i>]
in	<i>sz</i>	Factor to multiply by z coordinates [Default: <i>sx</i>]

size_t getNbBoundarySides () const

Return number of boundary sides.

This function is valid if member function **getAllSides** or **getBoundarySides** has been invoked before

size_t getNbInternalSides () const

Return number of internal sides.

This function is valid if member functions **getAllSides** and **createInternalSideList** have been invoked before

void AddMidNodes (int g = 0)

Add mid-side nodes.

This is function is valid for triangles only

Parameters

<i>in</i>	<i>g</i>	Option to say of barycentre node is to be added (>0) or not (=0)
-----------	----------	--

void set (Node * *nd*)

Replace node in the mesh.

If the node label exists already, the existing node pointer will be replaced by the current one. If not, an error message is displayed.

Parameters

<i>in</i>	<i>nd</i>	Pointer to node
-----------	-----------	-----------------

void set (Element * *el*)

Replace element in the mesh.

If the element label exists already, the existing element pointer will be replaced by the current one. If not, an error message is displayed.

Parameters

<i>in</i>	<i>el</i>	Pointer to element
-----------	-----------	--------------------

void set (Side * *sd*)

Choose side in the mesh.

If the side label exists already, the existing side pointer will be replaced by the current one. If not, an error message is displayed.

Parameters

<i>in</i>	<i>sd</i>	Pointer to side
-----------	-----------	-----------------

bool NodesAreDOF () const

Return information about DOF type.

Returns

true if DOF are supported by nodes, false otherwise

bool SidesAreDOF () const

Return information about DOF type.

Returns

true if DOF are supported by sides, false otherwise

bool EdgesAreDOF () const

Return information about DOF type.

Returns

true if DOF are supported by edges, false otherwise

bool ElementsAreDOF () const

Return information about DOF type.

Returns

true if DOF are supported by elements, false otherwise

void Deform (const Vect< real_t > & u, real_t rate = 0.2)

Deform mesh according to a displacement vector.

This function modifies node coordinates according to given displacement vector and given rate

Parameters

in	<i>u</i>	Displacement vector
in	<i>rate</i>	Maximal rate of deformation of resulting mesh. Its default value is 0.2, <i>i.e.</i> The resulting mesh has a maximum of deformation rate of 20%

void put (const string & mesh_file) const

Write mesh data on file.

Parameters

in	<i>mesh_file</i>	Mesh file name
----	------------------	----------------

void save (const string & mesh_file) const

Write mesh data on file in various formats.

File format depends on the extension in file name

Parameters

in	<i>mesh_file</i>	Mesh file name If the extension is '.m', the output file is an OFELI file If the extension is '.gpl', the output file is a Gnuplot file If the extension is '.msh' or '.geo', the output file is a Gmsh file If the extension is '.vtk', the output file is a VTK file
----	------------------	--

void getList (vector< Node * > & nl) const

Fill vector nl with list of pointers to nodes.

Parameters

out	<i>nl</i>	Instance of class vector that contain on output the list
-----	-----------	--

void getList (vector< Element * > & el) const

Fill vector el with list of pointers to elements.

Parameters

out	<i>el</i>	Instance of class vector that contain on output the list
-----	-----------	--

void getList (vector< Side * > &sl) const

Fill vector sl with list of pointers to sides.

Parameters

out	<i>sl</i>	Instance of class vector that contain on output the list
-----	-----------	--

size_t getNodeLabel (size_t i) const

Return label of i-th node.

Parameters

in	<i>i</i>	Node index
----	----------	----------------------------

size_t getElementLabel (size_t i) const

Return label of i-th element.

Parameters

in	<i>i</i>	Element index
----	----------	-------------------------------

size_t getSideLabel (size_t i) const

Return label of i-th side.

Parameters

in	<i>i</i>	Side index
----	----------	----------------------------

size_t getEdgeLabel (size_t i) const

Return label of i-th edge.

Parameters

in	<i>i</i>	Edge index
----	----------	----------------------------

Element* getActiveElement () const

Return pointer to current element and move to next one (Non constant version)

This function returns pointer to the current element only if this one is active. Otherwise it goes to the next active element (To be used when adaptive meshing is involved)

7.71.4 Friends And Related Function Documentation

void Refine (Mesh & *in_mesh*, Mesh & *out_mesh*) [friend]

Refine mesh. Subdivide each triangle into 4 subtriangles. This member function is valid for 2-D triangular meshes only.

Parameters

in	<i>in_mesh</i>	Input mesh
out	<i>out_mesh</i>	Output mesh

7.72 MeshAdapt Class Reference

To adapt mesh in function of given solution.

Public Member Functions

- [MeshAdapt](#) ()
Default constructor.
- [MeshAdapt](#) ([Mesh](#) &ms)
Constructor using initial mesh.
- [MeshAdapt](#) ([Domain](#) &dom)
Constructor using a reference to class [Domain](#).
- [~MeshAdapt](#) ()
Destructor.
- [Domain](#) & [getDomain](#) () const
Get reference to [Domain](#) instance.
- [Mesh](#) & [getMesh](#) () const
Get reference to current mesh.
- void [set](#) ([Domain](#) &dom)
Set reference to [Domain](#) instance.
- void [set](#) ([Mesh](#) &ms)
Set reference to [Mesh](#) instance.
- void [setSolution](#) (const [Vect](#)< [real_t](#) > &u)
Define label of node.
- void [setJacobi](#) (int n)
Set number of Jacobi iterations for smoothing.
- void [setSmooth](#) (int n)
Set number of smoothing iterations.
- void [AbsoluteError](#) ()
Metric is constructed with absolute error.
- void [RelativeError](#) ()
Metric is constructed with relative error.
- void [setError](#) ([real_t](#) err)
Set error threshold for adaption.
- void [setHMin](#) ([real_t](#) h)
Set minimal mesh size.
- void [setHMax](#) ([real_t](#) h)
Set maximal mesh size.
- void [setHMinAnisotropy](#) ([real_t](#) h)
Set minimal mesh size and set anisotropy.
- void [setRelaxation](#) ([real_t](#) omega)
Set relaxation parameter for smoothing.
- void [setAnisotropic](#) ()
Set that adapted mesh construction is anisotropic.
- void [MaxAnisotropy](#) ([real_t](#) a)
Set maximum ratio of anisotropy.
- void [setMaxSubdiv](#) ([real_t](#) s)
Change the metric such that the maximal subdivision of a background's edge is bounded by the given number (always limited by 10)
- void [setMaxNbVertices](#) ([size_t](#) n)
Set maximum number of vertices.

- void **setRatio** (**real_t** r)
Set ratio for a smoothing of the metric.
- void **setNoScaling** ()
Do not scale solution before metric computation.
- void **setNoKeep** ()
Do not keep old vertices.
- void **setHessian** ()
set computation of the Hessian
- void **setOutputMesh** (string file)
Create mesh output file.
- void **setGeoFile** (string file)
Set Geometry file.
- void **setGeoError** (**real_t** e)
Set error on geometry.
- void **setBackgroundMesh** (string bgm)
Set background mesh.
- void **SplitBoundaryEdges** ()
Split edges with two vertices on boundary.
- void **CreateMetricFile** (string mf)
Create a metric file.
- void **setMetricFile** (string mf)
Set Metric file.
- void **getSolutionMbb** (string mbb)
Set solution defined on background mesh for metric construction.
- void **getSolutionMBB** (string mBB)
Set solution defined on background mesh for metric construction.
- void **getSolutionbb** (string rbb)
Read solution defined on the background mesh in bb file.
- void **getSolutionBB** (string rBB)
Read solution defined on the background mesh in BB file.
- void **getSolution** (**Vect**< **real_t** > &u, int is=1)
Get the interpolated solution on the new mesh.
- void **getInterpolatedSolutionbb** ()
Write the file of interpolation of the solutions in bb file.
- void **getInterpolatedSolutionBB** ()
Write the file of interpolation of the solutions in BB file.
- void **setTheta** (**real_t** theta)
Set angular limit for a corner (in degrees)
- void **Split** ()
Split triangles into 4 triangles.
- void **saveMbb** (string file, const **Vect**< **real_t** > &u)
Save a solution in metric file.
- int **run** ()
Run adaptation process.
- int **run** (const **Vect**< **real_t** > &u)
Run adaptation process using a solution vector.
- int **run** (const **Vect**< **real_t** > &u, **Vect**< **real_t** > &v)
Run adaptation process using a solution vector and interpolates solution on the adapted mesh.

7.72.1 Detailed Description

To adapt mesh in function of given solution.

Class [MeshAdapt](#) enables modifying mesh according to a solution vector defining at nodes. It concerns 2-D triangular meshes only.

Remarks

Class [MeshAdapt](#) is mainly based on the software 'Bamg' developed by F. Hecht, Universite Pierre et Marie Curie, Paris. We warmly thank him for accepting incorporation of Bamg in the [OFELI](#) package

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.72.2 Constructor & Destructor Documentation

MeshAdapt (Mesh & *ms*)

Constructor using initial mesh.

Parameters

<i>in</i>	<i>ms</i>	Reference to initial mesh
-----------	-----------	---------------------------

MeshAdapt (Domain & *dom*)

Constructor using a reference to class [Domain](#).

Parameters

<i>in</i>	<i>dom</i>	Reference to Domain class
-----------	------------	---

7.72.3 Member Function Documentation

void setRelaxation (real.t *omega*)

Set relaxation parameter for smoothing.

Default value for relaxation parameter is 1.8

void setMaxNbVertices (size.t *n*)

Set maximum number of vertices.

Default value is 500000

void setRatio (real.t *r*)

Set ratio for a smoothing of the metric.

Parameters

<code>in</code>	<code>r</code>	Ratio value.
-----------------	----------------	--------------

Note

If `r` is 0 then no smoothing is performed, if `r` lies in $[1.1, 10]$ then the smoothing changes the metric such that the largest geometrical progression (speed of mesh size variation in mesh is bounded by `r`) (by default no smoothing)

void setNoScaling ()

Do not scale solution before metric computation.

By default, solution is scaled (between 0 and 1)

void setNoKeep ()

Do not keep old vertices.

By default, old vertices are kept

void getSolutionbb (string *rbb*)

Read solution defined on the background mesh in `bb` file.

Solution is interpolated on created mesh

void getSolutionBB (string *rBB*)

Read solution defined on the background mesh in `BB` file.

Solution is interpolated on created mesh

void getSolution (Vect< real_t > & *u*, int *is* = 1)

Get the interpolated solution on the new mesh.

The solution must have been saved on an output `bb` file

Parameters

<code>out</code>	<code>u</code>	Vector that contains on output the obtained solutions. This vector is resized before being initialized
<code>in</code>	<code>is</code>	[Default: 1]

void setTheta (real_t *theta*)

Set angular limit for a corner (in degrees)

The angle is defined from 2 normals of 2 consecutive edges

void saveMbb (string *file*, const Vect< real_t > & *u*)

Save a solution in metric file.

Parameters

in	<i>file</i>	File name where the metric is stored
in	<i>u</i>	Solution vector to store

int run ()

Run adaptation process.

Returns

Return code:

- = 0: Adaptation has been normally completed
- = 1: An error occurred

int run (const Vect< real_t > &u)

Run adaptation process using a solution vector.

Parameters

in	<i>u</i>	Solution vector defined on the input mesh
----	----------	---

Returns

Return code:

- = 0: Adaptation has been normally completed
- = 1: An error occurred

int run (const Vect< real_t > &u, Vect< real_t > &v)

Run adaptation process using a solution vector and interpolates solution on the adapted mesh.

Parameters

in	<i>u</i>	Solution vector defined on the input mesh
in	<i>v</i>	Solution vector defined on the (adapted) output mesh

Returns


Return code:

- = 0: Adaptation has been normally completed
- = 1: An error occurred

7.73 Muscl Class Reference

Parent class for hyperbolic solvers with Muscl scheme.

Inheritance diagram for Muscl:



Public Types

- enum `Method` {
`FIRST_ORDER_METHOD` = 0,
`MULTI_SLOPE_Q_METHOD` = 1,
`MULTI_SLOPE_M_METHOD` = 2 }

Enumeration for flux choice.

- enum `Limiter` {
`MINMOD_LIMITER` = 0,
`VANLEER_LIMITER` = 1,
`SUPERBEE_LIMITER` = 2,
`VANALBADA_LIMITER` = 3,
`MAX_LIMITER` = 4 }

Enumeration of flux limiting methods.

- enum `SolverType` {
`ROE_SOLVER` = 0,
`VFROE_SOLVER` = 1,
`LF_SOLVER` = 2,
`RUSANOV_SOLVER` = 3,
`HLL_SOLVER` = 4,
`HLLC_SOLVER` = 5,
`MAX_SOLVER` = 6 }

Enumeration of various solvers for the Riemann problem.

Public Member Functions

- `Muscl` (`Mesh` &m)
Constructor using mesh instance.
- virtual `~Muscl` ()
Destructor.
- void `setTimeStep` (`real_t` dt)
Assign time step value.
- `real_t` `getTimeStep` () const
Return time step value.
- void `setCFL` (`real_t` CFL)
Assign CFL value.
- `real_t` `getCFL` () const
Return CFL value.
- void `setReferenceLength` (`real_t` dx)
Assign reference length value.
- `real_t` `getReferenceLength` () const
Return reference length.
- `Mesh` & `getMesh` () const
Return reference to `Mesh` instance.
- void `setVerbose` (int v)
Set verbosity parameter.
- bool `setReconstruction` (const `Vect`< `real_t` > &U, `Vect`< `real_t` > &LU, `Vect`< `real_t` > &RU, size_t dof)
Function to reconstruct by the `Muscl` method.
- void `setMethod` (const `Method` &s)

Choose a flux solver.

- void `setSolidZoneCode` (int c)

Choose a code for solid zone.

- bool `getSolidZone` () const

Return flag for presence of solid zones.

- int `getSolidZoneCode` () const

Return code of solid zone, 0 if this one is not present.

- void `setLimiter` (Limiter l)

Choose a flux limiter.

7.73.1 Detailed Description

Parent class for hyperbolic solvers with Muscl scheme.

Everything here is common for both 2D and 3D muscl methods ! Virtual functions are implemented in Muscl2D and Muscl3D classes

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.73.2 Member Enumeration Documentation

enum Method

Enumeration for flux choice.

Enumerator

FIRST_ORDER_METHOD First Order upwind method

MULTI_SLOPE_Q_METHOD Multislope Q method

MULTI_SLOPE_M_METHOD Multislope M method

enum Limiter

Enumeration of flux limiting methods.

Enumerator

MINMOD_LIMITER MinMod limiter

VANLEER_LIMITER Van Leer limiter

SUPERBEE_LIMITER Superbee limiter

VANALBADA_LIMITER Van Albada limiter

MAX_LIMITER Max limiter

enum SolverType

Enumeration of various solvers for the Riemann problem.

Enumerator

ROE_SOLVER Roe solver
VFROE_SOLVER Finite Volume Roe solver
LF_SOLVER LF solver
RUSANOV_SOLVER Rusanov solver
HLL_SOLVER HLL solver
HLLC_SOLVER HLLC solver
MAX_SOLVER Max solver

7.73.3 Member Function Documentation**void setTimeStep (real_t dt)**

Assign time step value.

Parameters

in	dt	Time step value
----	----	-----------------

void setCFL (real_t CFL)

Assign CFL value.

Parameters

in	CFL	Value of CFL
----	-----	--------------

void setReferenceLength (real_t dx)

Assign reference length value.

Parameters

in	dx	Value of reference length
----	----	---------------------------

void setVerbose (int v)

Set verbosity parameter.

Parameters

in	v	Value of verbosity parameter
----	---	------------------------------

bool setReconstruction (const Vect< real_t > & U, Vect< real_t > & LU, Vect< real_t > & RU, size_t dof)

Function to reconstruct by the [Muscl](#) method.

Parameters

in	U	Field to reconstruct
out	LU	Left gradient vector
out	RU	Right gradient vector
in	dof	Label of dof to reconstruct

void setMethod (const Method & s)

Choose a flux solver.

Parameters

in	s	Solver to choose
----	-----	------------------

void setLimiter (Limiter l)

Choose a flux limiter.


Parameters

in	l	Limiter to choose
----	-----	-------------------

7.74 Muscl1D Class Reference

Class for 1-D hyperbolic solvers with [Muscl](#) scheme.

Inheritance diagram for Muscl1D:



Public Member Functions

- [Muscl1D](#) ([Mesh](#) &m)
Constructor using mesh instance.
- [~Muscl1D](#) ()
Destructor.
- [real.t getMeanLength](#) () const
Return mean length.
- [real.t getMaximumLength](#) () const
Return maximal length.
- [real.t getMinimumLength](#) () const
Return mimal length.
- [real.t getTauLim](#) () const
Return mean length.
- void [print_mesh_stat](#) ()
Output mesh information.

Additional Inherited Members

7.74.1 Detailed Description

Class for 1-D hyperbolic solvers with [Muscl](#) scheme.

Author

S. Clain, V. Clauzon


Copyright

GNU Lesser Public License

7.75 Muscl2DT Class Reference

Class for 2-D hyperbolic solvers with [Muscl](#) scheme.

Inheritance diagram for Muscl2DT:



Public Member Functions

- [Muscl2DT](#) ([Mesh](#) &m)
Constructor using mesh.
- [~Muscl2DT](#) ()
Destructor.
- bool [setReconstruction](#) (const [Vect](#)< [real_t](#) > &U, [Vect](#)< [real_t](#) > &LU, [Vect](#)< [real_t](#) > &RU, [size_t](#) dof)
Function to reconstruct by the [Muscl](#) method.

Protected Member Functions

- void [Initialize](#) ()
Construction of normals to sides.

Additional Inherited Members

7.75.1 Detailed Description

Class for 2-D hyperbolic solvers with [Muscl](#) scheme.

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.75.2 Member Function Documentation

bool setReconstruction (const Vect< real.t > &U, Vect< real.t > &LU, Vect< real.t > &RU, size.t dof)

Function to reconstruct by the [Muscl](#) method.

Parameters

in	<i>U</i>	Field to reconstruct
out	<i>LU</i>	Left gradient vector
out	<i>RU</i>	Right gradient vector
in	<i>dof</i>	Label of dof to reconstruct

void Initialize () [protected]


Construction of normals to sides.

Convention: for a given side, getPtrElement(1) is the left element and getPtrElement(2) is the right element. The normal goes from left to right. For boundary sides, the normal points outward.

7.76 Muscl3DT Class Reference

Class for 3-D hyperbolic solvers with [Muscl](#) scheme using tetrahedra.

Inheritance diagram for Muscl3DT:



Public Member Functions

- [Muscl3DT](#) ([Mesh](#) &m)
Constructor using mesh.
- [~Muscl3DT](#) ()
Destructor.
- bool [setReconstruction](#) (const [Vect< real.t >](#) &U, [Vect< real.t >](#) &LU, [Vect< real.t >](#) &RU, size.t dof)
Function to reconstruct by the [Muscl](#) method.
- [real.t getMinimumFaceArea](#) () const
Return minimum area of faces in the mesh.
- [real.t getMinimumElementVolume](#) () const
Return minimum volume of elements in the mesh.
- [real.t getMaximumFaceArea](#) () const

- Return maximum area of faces in the mesh.*

 - `real.t getMaximumElementVolume () const`

Return maximum volume of elements in the mesh.
- `real.t getMeanFaceArea () const`

Return mean area of faces in the mesh.
- `real.t getMeanElementVolume () const`

Return mean volume of elements in the mesh.
- `real.t getMinimumEdgeLength () const`

Return minimum length of edges in the mesh.
- `real.t getMinimumVolumebyArea () const`

Return minimum volume by area in the mesh.
- `real.t getMaximumEdgeLength () const`

Return maximum length of edges in the mesh.
- `real.t getTauLim () const`

Return value of tau lim.
- `real.t getComega () const`

Return value of Comega.
- `void setbetalim (real.t bl)`

Assign value of beta lim.

Additional Inherited Members

7.76.1 Detailed Description

Class for 3-D hyperbolic solvers with [Muscl](#) scheme using tetrahedra.

Author

S. Clain, V. Clauzon

Copyright

GNU Lesser Public License

7.76.2 Member Function Documentation

`bool setReconstruction (const Vect< real.t > & U, Vect< real.t > & LU, Vect< real.t > & RU, size.t dof)`

Function to reconstruct by the [Muscl](#) method.

Parameters

in	<i>U</i>	Field to reconstruct
out	<i>LU</i>	Left gradient vector
out	<i>RU</i>	Right gradient vector
in	<i>dof</i>	Label of dof to reconstruct

7.77 MyNLAS Class Reference

Abstract class to define by user specified function.

Public Member Functions

- [MyNLAS](#) ()
Default Constructor.
- [MyNLAS](#) (const [Mesh](#) &mesh)
Constructor using mesh instance.
- virtual [~MyNLAS](#) ()
Destructor.
- virtual [real_t Function](#) (const [Vect](#)< [real_t](#) > &x, int i=1)=0
Virtual member function to define nonlinear function to zeroe.
- virtual [real_t Gradient](#) (const [Vect](#)< [real_t](#) > &x, int i=1, int j=1)
Virtual member function to define partial derivatives of function.

7.77.1 Detailed Description

Abstract class to define by user specified function.

The user has to implement a class that inherits from the present one where the virtual functions are implemented.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.77.2 Constructor & Destructor Documentation

MyNLAS (const [Mesh](#) & *mesh*)

Constructor using mesh instance.

Parameters

<i>mesh</i>	Reference to Mesh instance
-------------	--

7.77.3 Member Function Documentation

virtual [real_t Function](#) (const [Vect](#)< [real_t](#) > &*x*, int *i* = 1) [pure virtual]

Virtual member function to define nonlinear function to zeroe.

Parameters

in	<i>x</i>	Vector of variables
in	<i>i</i>	component of function to define [Default: 1].

Returns

Value of function

Warning

The component must not be larger than vector size

virtual [real_t Gradient](#) (const [Vect](#)< [real_t](#) > &*x*, int *i* = 1, int *j* = 1) [virtual]

Virtual member function to define partial derivatives of function.

Parameters

in	x	Vector of variables
in	i	Function component [Default: 1]
in	j	Index of partial derivative [Default: 1]

Returns

Value of partial derivative

7.78 MyOpt Class Reference

Abstract class to define by user specified optimization function.

Public Member Functions

- [MyOpt \(\)](#)
Default Constructor.
- [MyOpt \(Mesh &mesh\)](#)
Constructor using mesh instance.
- [virtual ~MyOpt \(\)](#)
Destructor.
- [virtual real_t Objective \(Vect< real_t > &x\)=0](#)
Virtual member function to define objective.
- [virtual void Gradient \(Vect< real_t > &x, Vect< real_t > &g\)](#)
Virtual member function to define gradient vector of objective.
- [void setEquation \(AbsEqua< real_t > *eq\)](#)
Define equation instance.
- [AbsEqua< real_t > * getEquation \(\) const](#)
Get pointer to equation instance.

7.78.1 Detailed Description

Abstract class to define by user specified optimization function.

The user has to implement a class that inherits from the present one where the virtual functions are implemented.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.78.2 Constructor & Destructor Documentation

MyOpt (Mesh & mesh)

Constructor using mesh instance.

Parameters

<i>mesh</i>	Reference to Mesh instance
-------------	--

7.78.3 Member Function Documentation

virtual real_t Objective (Vect< real_t > & x) [pure virtual]

Virtual member function to define objective.

Parameters

in	<i>x</i>	Vector of optimization variables
-----------	----------	----------------------------------

Returns

Value of objective

virtual void Gradient (Vect< real_t > & x, Vect< real_t > & g) [virtual]

Virtual member function to define gradient vector of objective.

Parameters

in	<i>x</i>	Vector of optimization variables
out	<i>g</i>	Gradient vector

void setEquation (AbsEqua< real_t > * eq)

Define equation instance.

Parameters

in	<i>eq</i>	Pointer to equation instance
-----------	-----------	------------------------------

Remarks

This member function is to be invoked in the user class defining the optimization problem

AbsEqua<real_t>* getEquation () const

Get pointer to equation instance.

Returns

Pointer to equation instance

7.79 NLASSolver Class Reference

To solve a system of nonlinear algebraic equations of the form $f(u) = 0$.

Public Member Functions

- [NLASSolver](#) ()
Default constructor.
- [NLASSolver](#) (NonLinearIter nl, int nb_eq=1)
Constructor defining the iterative method to solve the equation.

- **NLASSolver** ([real_t](#) &x, NonLinearIter nl=NEWTON)
Constructor defining a one-variable problem.
- **NLASSolver** ([Vect](#)< [real_t](#) > &x, NonLinearIter nl=NEWTON)
Constructor defining a multi-variable problem.
- **NLASSolver** ([MyNLAS](#) &my_nlas, NonLinearIter nl=NEWTON)
Constructor using a user defined class.
- **~NLASSolver** ()
Destructor.
- void **setMaxIter** (int max_it)
Set Maximal number of iterations.
- void **setTolerance** ([real_t](#) toler)
Set tolerance value for convergence.
- void **set** (NonLinearIter nl)
Define an iterative procedure To be chosen among the enumerated values: BISECTION, REGULA_FALSI or NEWTON.
- void **setFunction** (function< [real_t](#)([real_t](#))> f)
Define the function associated to the equation to solve.
- void **setFunction** (function< [Vect](#)< [real_t](#) >(< [Vect](#)< [real_t](#) >)> f)
Define the function associated to the equation to solve.
- void **setGradient** (function< [real_t](#)([real_t](#))> g)
Define the function associated to the derivative of the equation to solve.
- void **setGradient** (function< [Vect](#)< [real_t](#) >(< [Vect](#)< [real_t](#) >)> g)
Define the function associated to the gradient of the equation to solve.
- void **setf** (string exp)
Set function for which zero is sought (case of one equation)
- void **setDf** (string exp, int i=1, int j=1)
Set pztial derivative of function for which zero is sought (case of many equations)
- void **setPDE** ([AbsEqua](#)< [real_t](#) > &eq)
Define a PDE.
- void **setInitial** ([Vect](#)< [real_t](#) > &u)
Set initial guess for the iterations.
- void **setInitial** ([real_t](#) &x)
Set initial guess for a unique unknown.
- void **setInitial** ([real_t](#) a, [real_t](#) b)
Set initial guesses bisection or Regula falsi algorithms.
- void **run** ()
Run the solution procedure.
- [real_t](#) **get** () const
Return solution (Case of a scalar equation)
- void **get** ([Vect](#)< [real_t](#) > &u) const
Return solution (case of a nonlinear system of equations)
- int **getNbIter** () const
Return number of iterations.

7.79.1 Detailed Description

To solve a system of nonlinear algebraic equations of the form $f(u) = 0$.

Features:

- The nonlinear problem is solved by the Newton's method in the general case, and in the one variable case, either by the bisection or the Regula Falsi method
- The function and its gradient are given:
 - Either by regular expressions
 - Or by user defined functions
 - Or by a user defined class. This feature enables defining the function and its gradient through a PDE class for instance

7.79.2 Constructor & Destructor Documentation

NLASSolver (NonLinearIter *nl*, int *nb_eq* = 1)

Constructor defining the iterative method to solve the equation.

Parameters

in	<i>nl</i>	Choose an iterative procedure to solve the nonlinear system of equations: To be chosen among the enumerated values: BISECTION, REGULA_FALSI or NEWTON.
in	<i>nb_eq</i>	Number of equations [Default: 1]

NLASSolver (real_t & *x*, NonLinearIter *nl* = NEWTON)

Constructor defining a one-variable problem.

Parameters

in	<i>x</i>	Variable containing on input initial guess and on output solution, if convergence is achieved
in	<i>nl</i>	Iterative procedure to solve the nonlinear system of equations: To be chosen among the enumerated values: BISECTION, REGULA_FALSI or NEWTON.

NLASSolver (Vect< real_t > & *x*, NonLinearIter *nl* = NEWTON)

Constructor defining a multi-variable problem.

Parameters

in	<i>x</i>	Variable containing on input initial guess and on output solution, if convergence is achieved
in	<i>nl</i>	Iterative procedure to solve the nonlinear system of equations: The only possible value (default one) in the current version is NEWTON.

NLASSolver (MyNLAS & *my_nlas*, NonLinearIter *nl* = NEWTON)

Constructor using a user defined class.

Parameters

in	<i>my_nlas</i>	Reference to instance of user defined class. This class inherits from abstract class MyNLAS . It must contain the member function <code>Vect<double> Function(const Vect<double>& x)</code> which returns the value of the nonlinear function, as a vector, for a given solution vector x. The user defined class must contain, if the iterative scheme requires it the member function <code>Vect<double> Gradient(const Vect<real.t>& x)</code> which returns the gradient as a $n \times n$ vector, each index (i,j) containing the j-th partial derivative of the i-th function.
in	<i>nl</i>	Iterative procedure to solve the nonlinear system of equations: To be chosen among the enumerated values: BISECTION, REGULA_F, ALSI or NEWTON.

7.79.3 Member Function Documentation

void setMaxIter (int *max_it*)

Set Maximal number of iterations.

Default value of this parameter is 100

void setTolerance (real.t *toler*)

Set tolerance value for convergence.

Default value of this parameter is 1.e-8

void setFunction (function< real.t(real.t)> *f*)

Define the function associated to the equation to solve.

This function can be used in the case where a user defined function is to be given. To be used in the one-variable case.

Parameters

in	<i>f</i>	Function given as a function of one real variable and returning a real number. This function can be defined by the calling program as a C-function and then cast to an instance of class function
----	----------	---

void setFunction (function< Vect< real.t >(Vect< real.t >)> *f*)

Define the function associated to the equation to solve.

This function can be used in the case where a user defined function is to be given.

Parameters

in	<i>f</i>	Function given as a function of many variables, stored in an input vector, and returns a vector. This function can be defined by the calling program as a C-function and then cast to an instance of class function
----	----------	---

void setGradient (function< real.t(real.t)> *g*)

Define the function associated to the derivative of the equation to solve.

Parameters

in	g	Function given as a function of one real variable and returning a real number. This function can be defined by the calling program as a C-function and then cast to an instance of class function
-----------	----------	---

void setGradient (function< Vect< real.t >(Vect< real.t >)> g)

Define the function associated to the gradient of the equation to solve.

Parameters

in	g	Function given as a function of many variables, stored in an input vector. and returns a n*n vector (n is the number of variables). This function can be defined by the calling program as a C-function and then cast to an instance of class function
-----------	----------	---

void setf (string exp)

Set function for which zero is sought (case of one equation)

Parameters

in	exp	Regular expression defining the function using the symbol x as a variable
-----------	------------	---

void setDf (string exp, int i = 1, int j = 1)

Set partial derivative of function for which zero is sought (case of many equations)

Parameters

in	exp	Regular expression defining the partial derivative. In this expression, the variables are x1, x2, ... x10 (up to 10 variables)
in	i	Component of function [Default: =1]
in	j	Index of the partial derivative [Default: =1]

void setPDE (AbsEqua< real.t > & eq)

Define a PDE.

The solver can be used to solve a nonlinear PDE. In this case, the PDE is defined as an instance of a class inheriting of [AbsEqua](#).

Parameters

in	eq	Pointer to equation instance
-----------	-----------	------------------------------

void setInitial (Vect< real.t > & u)

Set initial guess for the iterations.

Parameters

<code>in</code>	<code>u</code>	Vector containing initial guess for the unknown
-----------------	----------------	---

void setInitial (real_t & x)

Set initial guess for a unique unknown.

Parameters

<code>in</code>	<code>x</code>	Rference to value of initial guess
-----------------	----------------	------------------------------------

void setInitial (real_t a, real_t b)

Set initial guesses bisection or Regula falsi algorithms.

Parameters

<code>in</code>	<code>a</code>	Value of first initial guess
<code>in</code>	<code>b</code>	Value of second initial guess

Note

The function has to have opposite signs at these values i . e . $f(a)f(b)<0$.

Warning

This function makes sense only in the case of a unique function of one variable

void get (Vect< real_t > & u) const

Return solution (case of a nonlinear system of equations)

Parameters

<code>out</code>	<code>u</code>	Vector that contains on output the solution
------------------	----------------	---

7.80 Node Class Reference

To describe a node.

Public Member Functions

- [Node](#) ()
Default constructor.
- [Node](#) (size_t label, const [Point](#)< real_t > &x)
Constructor with label and coordinates.
- [Node](#) (const [Node](#) &node)
Copy Constructor.
- [~Node](#) ()
Destructor.
- void [setLabel](#) (size_t label)
Define label of node.
- void [setNbDOF](#) (size_t n)

- Define number of DOF.*

 - void **setFirstDOF** (size_t n)
- Define First DOF.*

 - void **setCode** (size_t dof, int code)
- Define code for a given DOF of node.*

 - void **setCode** (const vector< int > &code)
- Define codes for all node DOFs.*

 - void **setCode** (int *code)
- Define codes for all node DOFs.*

 - void **setCode** (const string &exp, int code, size_t dof=1)
- Define code by a boolean algebraic expression invoking node coordinates.*

 - void **setCoord** (size_t i, real_t x)
- Set i-th coordinate.*

 - void **DOF** (size_t i, size_t dof)
- Define label of DOF.*

 - void **setDOF** (size_t &first_dof, size_t nb_dof)
- Define number of DOF.*

 - void **setOnBoundary** ()
- Set node as boundary node.*

 - size_t **n** () const
- Return label of node.*

 - size_t **getNbDOF** () const
- Return number of degrees of freedom (DOF)*

 - int **getCode** (size_t dof=1) const
- Return code for a given DOF of node.*

 - real_t **getCoord** (size_t i) const
- Return i-th coordinate of node. i = 1..3.*

 - **Point**< real_t > **getCoord** () const
- Return coordinates of node.*

 - real_t **getX** () const
- Return x-coordinate of node.*

 - real_t **getY** () const
- Return y-coordinate of node.*

 - real_t **getZ** () const
- Return z-coordinate of node.*

 - **Point**< real_t > **getXYZ** () const
- Return coordinates of node.*

 - size_t **getDOF** (size_t i) const
- Return label of i-th dof.*

 - size_t **getNbNeigEl** () const
- Return number of neighbor elements.*

 - **Element** * **getNeigEl** (size_t i) const
- Return i-th neighbor element.*

 - size_t **getFirstDOF** () const
- Return label of first DOF of node.*

 - bool **isOnBoundary** () const

Say if node is a boundary node.

- void **Add** (**Element** *el)

Add element pointed by el as neighbor element to node.

- void **setLevel** (int level)

Assign a level to current node.

- int **getLevel** () const

Return node level.

7.80.1 Detailed Description

To describe a node.

A node is characterized by its label, its coordinates, its number of degrees of freedom (DOF) and codes that are associated to each DOF.

Remarks

Once the mesh is constructed, information on neighboring elements of node can be retrieved (see appropriate member functions). However, the member function `getNode↔NeighborElements` of **Mesh** must have been called before. If this is not the case, the program crashes down since no preliminary checking is done for efficiency reasons.

7.80.2 Constructor & Destructor Documentation

Node ()

Default constructor.

Initialize data to zero

Node (**size_t** label, const **Point**< **real_t** > &x)

Constructor with label and coordinates.

Parameters

in	label	Label of node
in	x	Node coordinates

7.80.3 Member Function Documentation

void setCode (**size_t** dof, int code)

Define code for a given DOF of node.

Parameters

in	dof	DOF index
in	code	Code to assign to DOF

void setCode (const **vector**< int > &code)

Define codes for all node DOFs.

Parameters

in	<i>code</i>	vector instance that contains code for each DOF of current node
-----------	-------------	---

void setCode (int * *code*)

Define codes for all node DOFs.

Parameters

in	<i>code</i>	C-array that contains code for each DOF of current node
-----------	-------------	---

void setCode (const string & *exp*, int *code*, size_t *dof* = 1)

Define code by a boolean algebraic expression invoking node coordinates.

Parameters

in	<i>exp</i>	Boolean algebraic expression as required by fparser
in	<i>code</i>	Code to assign to node if the algebraic expression is true
in	<i>dof</i>	Degree of Freedom for which code is assigned [Default: 1]

void setCoord (size_t *i*, real_t *x*)

Set i-th coordinate.

Parameters

in	<i>i</i>	Coordinate index (1..3)
in	<i>x</i>	Coordinate value

void DOF (size_t *i*, size_t *dof*)

Define label of DOF.

Parameters

in	<i>i</i>	DOF index
in	<i>dof</i>	Label of DOF

void setDOF (size_t & *first_dof*, size_t *nb_dof*)

Define number of DOF.

Parameters

in,out	<i>first_dof</i>	Label of the first DOF in input that is actualized
in	<i>nb_dof</i>	Number of DOF

void setOnBoundary ()

Set node as boundary node.

This function is mostly internally used (Especially in class [Mesh](#))

int getCode (size_t *dof* = 1) const

Return code for a given DOF of node.

Parameters

in	<i>dof</i>	label of degree of freedom for which code is to be returned. Default value is 1.
-----------	------------	--

Point<real_t> getCoord () const

Return coordinates of node.

Return value is an instance of class [Point](#)

Point<real_t> getXYZ () const

Return coordinates of node.

Return value is an instance of class [Point](#)

size_t getNbNeigEl () const

Return number of neighbor elements.

Neighbor elements are those that share node. Note that the returned information is valid only if the [Mesh](#) member function **getNodeNeighborElements()** has been invoked before

Element* getNeigEl (size_t i) const

Return i-th neighbor element.

Note that the returned information is valid only if the [Mesh](#) member function **getNodeNeighborElements()** has been invoked before

bool isOnBoundary () const

Say if node is a boundary node.

Note this information is available only if boundary sides (and nodes) were determined (See class [Mesh](#)).

void setLevel (int level)

Assign a level to current node.

This member function is useful for mesh adaption.

Default node's level is zero

int getLevel () const

Return node level.

[Node](#) level decreases when element is refined (starting from 0). If the level is 0, then the element has no parents

7.81 NodeList Class Reference

Class to construct a list of nodes having some common properties.

Public Member Functions

- [NodeList](#) ([Mesh](#) &ms)
Constructor using a [Mesh](#) instance.
- [~NodeList](#) ()
Destructor.
- void [selectCode](#) (int code, int dof=1)
Select nodes having a given code for a given degree of freedom.
- void [unselectCode](#) (int code, int dof=1)
Unselect nodes having a given code for a given degree of freedom.
- void [selectCoordinate](#) ([real.t](#) x, [real.t](#) y=ANY, [real.t](#) z=ANY)
Select nodes having given coordinates.
- [size_t](#) [getNbNodes](#) () const
Return number of selected nodes.
- void [top](#) ()
Reset list of nodes at its top position (Non constant version)
- void [top](#) () const
Reset list of nodes at its top position (Constant version)
- [Node](#) * [get](#) ()
Return pointer to current node and move to next one (Non constant version)
- [Node](#) * [get](#) () const
Return pointer to current node and move to next one (Constant version)

7.81.1 Detailed Description

Class to construct a list of nodes having some common properties.

This class enables choosing multiple selection criteria by using function `select...`. However, the intersection of these properties must be empty.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.81.2 Member Function Documentation

void selectCode (int code, int dof = 1)

Select nodes having a given code for a given degree of freedom.

Parameters

in	code	Code that nodes share
in	dof	Degree of Freedom label [Default: 1]

void unselectCode (int code, int dof = 1)

Unselect nodes having a given code for a given degree of freedom.

Parameters

in	<i>code</i>	Code of nodes to exclude
in	<i>dof</i>	Degree of Freedom label [Default: 1]

void selectCoordinate (real_t x, real_t y = ANY, real_t z = ANY)

Select nodes having given coordinates.

Parameters


in	<i>x</i>	x-coordinate that share the selected nodes
in	<i>y</i>	y-coordinate that share the selected nodes [Default: ANY]
in	<i>z</i>	z-coordinate that share the selected nodes [Default: ANY]

Coordinates can be assigned the value ANY. This means that any coordinate value is accepted. For instance, to select all nodes with x=0, use **selectCoordinate(0.,ANY,ANY)**;

7.82 NSP2DQ41 Class Reference

Builds finite element arrays for incompressible Navier-Stokes equations in 2-D domains using Q_1/P_0 element and a penalty formulation for the incompressibility condition.

Inheritance diagram for NSP2DQ41:



Public Member Functions

- **NSP2DQ41 (Mesh &ms)**
Constructor using mesh data.
- **NSP2DQ41 (Mesh &ms, Vect< real_t > &u)**
Constructor using mesh data and velocity vector.
- **~NSP2DQ41 ()**
Destructor.
- **void setPenalty (real_t lambda)**
Define penalty parameter.
- **void setInput (EqDataType opt, Vect< real_t > &u)**
Set equation input data.
- **void Periodic (real_t coef=1.e20)**
Add contribution of periodic boundary condition (by a penalty technique).
- **void build ()**
Build the linear system of equations.
- **int runOneTimeStep ()**
Run one time step.

7.82.1 Detailed Description

Builds finite element arrays for incompressible Navier-Stokes equations in 2-D domains using Q_1/P_0 element and a penalty formulation for the incompressibility condition.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.82.2 Constructor & Destructor Documentation

NSP2DQ41 (Mesh & *ms*)

Constructor using mesh data.

Parameters

<i>in</i>	<i>ms</i>	Mesh instance
-----------	-----------	-------------------------------

NSP2DQ41 (Mesh & *ms*, Vect< real.t > & *u*)

Constructor using mesh data and velocity vector.

Parameters

<i>in</i>	<i>ms</i>	Mesh instance
<i>in,out</i>	<i>u</i>	Velocity vector

7.82.3 Member Function Documentation

void setPenalty (real.t *lambda*)

Define penalty parameter.

Penalty parameter is used to enforce the incompressibility constraint

Parameters

<i>in</i>	<i>lambda</i>	Penalty parameter: Large value [Default: 1.e07]
-----------	---------------	---

void setInput (EqDataType *opt*, Vect< real.t > & *u*)

Set equation input data.

Parameters

<i>in</i>	<i>opt</i>	Parameter that selects data type for input. This parameter is to be chosen in the enumerated variable EqDataType
<i>in</i>	<i>u</i>	Vect instance that contains input vector data List of data types contains INITIAL_FIELD, BOUNDARY_CONDITION_DATA, SOURCE_DATA or FLUX with obvious meaning

void Periodic (real.t *coef* = 1.e20)

Add contribution of periodic boundary condition (by a penalty technique).

Boundary nodes where periodic boundary conditions are to be imposed must have codes equal to PERIODIC.A on one side and PERIODIC.B on the opposite side.

Parameters

<code>in</code>	<code>coef</code>	Value of penalty parameter [Default: 1.e20].
-----------------	-------------------	--

void build ()

Build the linear system of equations.

Before using this function, one must have properly selected appropriate options for:

- The choice of a steady state or transient analysis. By default, the analysis is stationary
- In the case of transient analysis, the choice of a time integration scheme and a lumped or consistent capacity matrix. If transient analysis is chosen, the lumped capacity matrix option is chosen by default, and the implicit Euler scheme is used by default for time integration.

int runOneTimeStep ()

Run one time step.

This function performs one time step, once a time integration scheme has been selected.

7.83 ODESolver Class Reference

To solve a system of ordinary differential equations.

Public Member Functions

- [ODESolver](#) ()
Default constructor.
- [ODESolver](#) (size_t nb_eq)
Constructor providing the number of equations.
- [ODESolver](#) (TimeScheme s, real_t time_step=theTimeStep, real_t final_time=theFinalTime, size_t nb_eq=1)
Constructor using time discretization data.
- [~ODESolver](#) ()
Destructor.
- void [set](#) (TimeScheme s, real_t time_step=theTimeStep, real_t final_time=theFinalTime)
Define data of the differential equation or system.
- void [setNbEq](#) (size_t nb_eq)
Set the number of equations [Default: 1].
- void [setCoef](#) (real_t a0, real_t a1, real_t a2, real_t f)
Define coefficients in the case of a scalar differential equation.
- void [setCoef](#) (string a0, string a1, string a2, string f)
Define coefficients in the case of a scalar differential equation.
- void [setLinear](#) ()
Claim that ODE is linear.
- void [setF](#) (string f)
Set time derivative, given as an algebraic expression, for a nonlinear ODE.
- void [setF](#) (string f, int i)
Set time derivative, given as an algebraic expression, for a nonlinear ODE.

- void `setDF` (string df, int i, int j)
Set time derivative of the function defining the ODE.
- void `setdFdt` (string df, int i)
Set time derivative of the function defining the ODE.
- void `setRK4RHS` (real_t f)
Set intermediate right-hand side vector for the Runge-Kutta method.
- void `setRK4RHS` (Vect< real_t > &f)
Set intermediate right-hand side vector for the Runge-Kutta method.
- void `setInitial` (Vect< real_t > &u)
Set initial condition for a first-order system of differential equations.
- void `setInitial` (real_t u, int i)
Set initial condition for a first-order system of differential equations.
- void `setInitial` (Vect< real_t > &u, Vect< real_t > &v)
Set initial condition for a second-order system of differential equations.
- void `setInitialRHS` (Vect< real_t > &f)
Set initial RHS for a system of differential equations.
- void `setInitial` (real_t u, real_t v)
Set initial condition for a second-order ordinary differential equation.
- void `setInitial` (real_t u)
Set initial condition for a first-order ordinary differential equation.
- void `setInitialRHS` (real_t f)
Set initial right-hand side for a single differential equation.
- void `setMatrices` (DMatrix< real_t > &A0, DMatrix< real_t > &A1)
Define matrices for a system of first-order ODEs.
- void `setMatrices` (DMatrix< real_t > &A0, DMatrix< real_t > &A1, DMatrix< real_t > &A2)
Define matrices for a system of second-order ODEs.
- void `seODEVectors` (Vect< real_t > &a0, Vect< real_t > &a1)
Define matrices for an implicit nonlinear system of first-order ODEs.
- void `seODEVectors` (Vect< real_t > &a0, Vect< real_t > &a1, Vect< real_t > &a2)
Define matrices for an implicit nonlinear system of second-order ODEs.
- void `setRHS` (Vect< real_t > &b)
Set right-hand side vector for a system of ODE.
- void `setRHS` (real_t f)
Set right-hand side for a linear ODE.
- void `setRHS` (string f)
Set right-hand side value for a linear ODE.
- void `setNewmarkParameters` (real_t beta, real_t gamma)
Define parameters for the Newmark scheme.
- void `setConstantMatrix` ()
Say that matrix problem is constant.
- void `setNonConstantMatrix` ()
Say that matrix problem is variable.
- void `setLinearSolver` (Iteration s=DIRECT_SOLVER, Preconditioner p=DIAG_PREC)
Set linear solver data.
- void `setMaxIter` (int max_it)
Set maximal number of iterations.

- void `setTolerance` (`real_t` toler)
Set tolerance value for convergence.
- `real_t` `runOneTimeStep` ()
Run one time step.
- void `run` (bool opt=false)
Run the time stepping procedure.
- `size_t` `getNbEq` () const
Return number of equations.
- `LinearSolver`< `real_t` > & `getLSolver` ()
Return `LinearSolver` instance.
- `real_t` `getTimeDerivative` (int i=1) const
Get time derivative of solution.
- void `getTimeDerivative` (`Vect`< `real_t` > &y) const
Get time derivative of solution (for a system)
- `real_t` `get` () const
Return solution in the case of a scalar equation.

7.83.1 Detailed Description

To solve a system of ordinary differential equations.

The class `ODESolver` enables solving by a numerical scheme a system or ordinary differential equations taking one of the forms:

- A linear system of differential equations of the first-order:
 $A_1(t)u'(t) + A_0(t)u(t) = f(t)$
- A linear system of differential equations of the second-order:
 $A_2(t)u''(t) + A_1(t)u'(t) + A_0(t)u(t) = f(t)$
- A system of ordinary differential equations of the form:
 $u'(t) = f(t, u(t))$

The following time integration schemes can be used:

- Forward Euler scheme (value: `FORWARD_EULER`) for first-order systems
- Backward Euler scheme (value: `BACKWARD_EULER`) for first-order linear systems
- Crank-Nicolson (value: `CRANK_NICOLSON`) for first-order linear systems
- Heun (value: `HEUN`) for first-order systems
- 2nd Order Adams-Bashforth (value: `AB2`) for first-order systems
- 4-th order Runge-Kutta (value: `RK4`) for first-order systems
- 2nd order Backward Differentiation Formula (value: `BDF2`) for linear first-order systems
- Newmark (value: `NEWMARK`) for linear second-order systems with constant matrices

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.83.2 Constructor & Destructor Documentation

ODESolver (*TimeScheme* *s*, *real.t time_step* = *theTimeStep*, *real.t final_time* = *theFinalTime*,
size.t nb_eq = 1)

Constructor using time discretization data.

Parameters

in	<i>s</i>	Choice of the scheme: To be chosen in the enumerated variable <i>Scheme</i> (see the presentation of the class)
in	<i>time_step</i>	Value of the time step. This value will be modified if an adaptive method is used. The default value for this parameter is the value given by the global variable <code>theTimeStep</code>
in	<i>final_time</i>	Value of the final time (time starts at 0). The default value for this parameter is the value given by the global variable <code>theFinalTime</code>
in	<i>nb_eq</i>	Number of differential equations (size of the system) [Default: 1]

7.83.3 Member Function Documentation

void set (TimeScheme *s*, real.t *time_step* = `theTimeStep`, real.t *final_time* = `theFinalTime`)

Define data of the differential equation or system.

Parameters

in	<i>s</i>	Choice of the scheme: To be chosen in the enumerated variable <i>Scheme</i> (see the presentation of the class)
in	<i>time_step</i>	Value of the time step. This value will be modified if an adaptive method is used. The default value for this parameter is the value given by the global variable <code>theTimeStep</code>
in	<i>final_time</i>	Value of the final time (time starts at 0). The default value for this parameter is the value given by the global variable <code>theFinalTime</code>

void setNbEq (size.t *nb_eq*)

Set the number of equations [Default: 1].

This function is to be used if the default constructor was used

void setCoef (real.t *a0*, real.t *a1*, real.t *a2*, real.t *f*)

Define coefficients in the case of a scalar differential equation.

This function enables giving coefficients of the differential equation as an algebraic expression of time *t* (see the function `fparse`)

Parameters

in	<i>a0</i>	Coefficient of the 0-th order term
in	<i>a1</i>	Coefficient of the 1-st order term
in	<i>a2</i>	Coefficient of the 2-nd order term
in	<i>f</i>	Value of the right-hand side

Note

Naturally, the equation is of the first order if *a2*=0

void setCoef (string *a0*, string *a1*, string *a2*, string *f*)

Define coefficients in the case of a scalar differential equation.

Parameters

in	$a0$	Coefficient of the 0-th order term
in	$a1$	Coefficient of the 1-st order term
in	$a2$	Coefficient of the 2-nd order term
in	f	Value of the right-hand side

Note

Naturally, the equation is of the first order if $a2=0$

void setLinear ()

Claim that ODE is linear.

Claim that the defined ODE (or system of ODEs) is linear

void setF (string f)

Set time derivative, given as an algebraic expression, for a nonlinear ODE.

This function enables prescribing the value of the 1-st derivative for a 1st order ODE or the 2nd one for a 2nd-order ODE. It is to be used for nonlinear ODEs of the form $y'(t) = f(t, y(t))$ or $y''(t) = f(t, y(t), y'(t))$

In the case of a system of ODEs, this function can be called once for each equation, given in the order of the unknowns

Parameters

in	f	Expression of the function
----	-----	----------------------------

void setF (string f , int i)

Set time derivative, given as an algebraic expression, for a nonlinear ODE.

This function enables prescribing the value of the 1-st derivative for a 1st order ODE or the 2nd one for a 2nd-order ODE. It is to be used for nonlinear ODEs of the form $y'(t) = f(t, y(t))$ or $y''(t) = f(t, y(t), y'(t))$

This function is to be used for the i -th equation of a system of ODEs

Parameters

in	f	Expression of the function
in	i	Index of equation. Must be not larger than the number of equations

void setDF (string df , int i , int j)

Set time derivative of the function defining the ODE.

This function enables prescribing the value of the 1-st derivative for a 1st order ODE or the 2nd one for a 2nd-order ODE. It is to be used for nonlinear ODEs of the form $y'(t) = f(t, y(t))$ or $y''(t) = f(t, y(t), y'(t))$

In the case of a system of ODEs, this function can be called once for each equation, given in the order of the unknowns

void setdFdt (string *df*, int *i*)

Set time derivative of the function defining the ODE.

This function enables prescribing the value of the 1-st derivative for a 1st order ODE or the 2nd one for a 2nd-order ODE. It is to be used for nonlinear ODEs of the form $y'(t) = f(t, y(t))$ or $y''(t) = f(t, y(t), y'(t))$

In the case of a system of ODEs, this function can be called once for each equation, given in the order of the unknowns

void setRK4RHS (real_t *f*)

Set intermediate right-hand side vector for the Runge-Kutta method.

Parameters

in	<i>f</i>	Value of right-hand side
----	----------	--------------------------

void setRK4RHS (Vect< real_t > &*f*)

Set intermediate right-hand side vector for the Runge-Kutta method.

Parameters

in	<i>f</i>	right-hand side vector
----	----------	------------------------

void setInitial (Vect< real_t > &*u*)

Set initial condition for a first-order system of differential equations.

Parameters

in	<i>u</i>	Vector containing initial condition for the unknown
----	----------	---

void setInitial (real_t *u*, int *i*)

Set initial condition for a first-order system of differential equations.

Parameters

in	<i>u</i>	Initial condition for an unknown
in	<i>i</i>	Index of the unknown

void setInitial (Vect< real_t > &*u*, Vect< real_t > &*v*)

Set initial condition for a second-order system of differential equations.

Giving the right-hand side at initial time is sometimes required for high order methods like Runge-Kutta

Parameters

in	<i>u</i>	Vector containing initial condition for the unknown
in	<i>v</i>	Vector containing initial condition for the time derivative of the unknown

void setInitialRHS (Vect< real,t > &f)

Set initial RHS for a system of differential equations.

Giving the right-hand side at initial time is sometimes required for high order methods like Runge-Kutta

Parameters

<code>in</code>	f	Vector containing right-hand side at initial time. This vector is helpful for high order methods
-----------------	-----	--

void setInitial (real_t u , real_t v)

Set initial condition for a second-order ordinary differential equation.

Parameters

<code>in</code>	u	Initial condition (unknown) value
<code>in</code>	v	Initial condition (time derivative of the unknown) value

void setInitial (real_t u)

Set initial condition for a first-order ordinary differential equation.

Parameters

<code>in</code>	u	Initial condition (unknown) value
-----------------	-----	-----------------------------------

void setInitialRHS (real_t f)

Set initial right-hand side for a single differential equation.

Parameters

<code>in</code>	f	Value of right-hand side at initial time. This value is helpful for high order methods
-----------------	-----	--

void setMatrices (DMatrix< real_t > & $A0$, DMatrix< real_t > & $A1$)

Define matrices for a system of first-order ODEs.

Matrices are given as references to class [DMatrix](#).

Parameters

<code>in</code>	$A0$	Reference to matrix in front of the 0-th order term (no time derivative)
<code>in</code>	$A1$	Reference to matrix in front of the 1-st order term (first time derivative)

Remarks

This function has to be called at each time step

void setMatrices (DMatrix< real_t > & $A0$, DMatrix< real_t > & $A1$, DMatrix< real_t > & $A2$)

Define matrices for a system of second-order ODEs.

Matrices are given as references to class [DMatrix](#).

Parameters

in	$A0$	Reference to matrix in front of the 0-th order term (no time derivative)
in	$A1$	Reference to matrix in front of the 1-st order term (first time derivative)
in	$A2$	Reference to matrix in front of the 2-nd order term (second time derivative)

Remarks

This function has to be called at each time step

void seODEVectors (Vect< real.t > & a0, Vect< real.t > & a1)

Define matrices for an implicit nonlinear system of first-order ODEs.

The system has the nonlinear implicit form $a1(u)' + a0(u) = 0$ Vectors a0, a1 are given as references to class [Vect](#).

Parameters

in	$a0$	Reference to vector in front of the 0-th order term (no time derivative)
in	$a1$	Reference to vector in front of the 1-st order term (first time derivative)

Remarks

This function has to be called at each time step

void seODEVectors (Vect< real.t > & a0, Vect< real.t > & a1, Vect< real.t > & a2)

Define matrices for an implicit nonlinear system of second-order ODEs.

The system has the nonlinear implicit form $a2(u)'' + a1(u)' + a0(u) = 0$ Vectors a0, a1, a2 are given as references to class [Vect](#).

Parameters

in	$a0$	Reference to vector in front of the 0-th order term (no time derivative)
in	$a1$	Reference to vector in front of the 1-st order term (first time derivative)
in	$a2$	Reference to vector in front of the 2-nd order term (second time derivative)

Remarks

This function has to be called at each time step

void setRHS (Vect< real.t > & b)

Set right-hand side vector for a system of ODE.

Parameters

in	<i>b</i>	Vect instance containing right-hand side for a linear system of ordinary differential equations
----	----------	---

void setRHS (real.t *f*)

Set right-hand side for a linear ODE.

Parameters

in	<i>f</i>	Value of the right-hand side for a linear ordinary differential equation
----	----------	--

void setNewmarkParameters (real.t *beta*, real.t *gamma*)

Define parameters for the Newmark scheme.

Parameters

in	<i>beta</i>	Parameter beta [Default: 0.25]
in	<i>gamma</i>	Parameter gamma [Default: 0.5]

void setConstantMatrix ()

Say that matrix problem is constant.

This is useful if the linear system is solved by a factorization method but has no effect otherwise

void setNonConstantMatrix ()

Say that matrix problem is variable.

This is useful if the linear system is solved by a factorization method but has no effect otherwise

void setLinearSolver (Iteration *s* = DIRECT_SOLVER, Preconditioner *p* = DIAG_PREC)

Set linear solver data.

Parameters

in	<i>s</i>	Solver identification parameter. To be chosen in the enumeration variable Iteration: DIRECT_SOLVER, CG_SOLVER, CGS_SOLVER, BICG_SOLVER, BICG_STAB_SOLVER, GMRES_SOLVER, QMR_SOLVE← R [Default: DIRECT_SOLVER]
in	<i>p</i>	Preconditioner identification parameter. To be chosen in the enumeration variable Preconditioner: IDENT_PREC, DIAG_PREC, ILU_PREC [Default: DIAG_PREC]

Note

The argument *p* has no effect if the solver is DIRECT_SOLVER

void setMaxIter (int *max.it*)

Set maximal number of iterations.

This function is useful for a non linear ODE (or system of ODEs) if an implicit scheme is used

Parameters

<code>in</code>	<code>max_it</code>	Maximal number of iterations [Default: 100]
-----------------	---------------------	---

void setTolerance (`real_t toler`)

Set tolerance value for convergence.

This function is useful for a non linear ODE (or system of ODEs) if an implicit scheme is used

Parameters

<code>in</code>	<code>toler</code>	Tolerance value [Default: 1.e-8]
-----------------	--------------------	----------------------------------

real_t runOneTimeStep ()

Run one time step.

Returns

Value of new time step if this one is updated

void run (`bool opt = false`)

Run the time stepping procedure.

Parameters

<code>in</code>	<code>opt</code>	Flag to say if problem matrix is constant while time stepping (true) or not (Default value is false)
-----------------	------------------	--

Note

This argument is not used if the time stepping scheme is explicit

real_t getTimeDerivative (`int i = 1`) const

Get time derivative of solution.

Return approximate time derivative of solution in the case of a single equation

Parameters

<code>in</code>	<code>i</code>	Index of component whose time derivative is sought
-----------------	----------------	--

Returns

Time derivative of the i-th component of the solution

Remarks

If we are solving one equation, this parameter is not used.

void getTimeDerivative (`Vect< real_t > & y`) const

Get time derivative of solution (for a system)

Get approximate time derivative of solution in the case of an ODE system

Parameters

out	y	Vector containing time derivative of solution
-----	---	---

7.84 OFELIException Class Reference

To handle exceptions in [OFELI](#).

Inherits `runtime_error`.

Public Member Functions

- [OFELIException](#) (const std::string &s)
This form will be used most often in a throw.
- [OFELIException](#) ()
Throw with no error message.

7.84.1 Detailed Description

To handle exceptions in [OFELI](#).

This class enables using exceptions in programs using [OFELI](#)

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.85 OptSolver Class Reference

To solve an optimization problem with bound constraints.

Public Types

- enum [OptMethod](#) {
[GRADIENT](#) = 0,
[TRUNCATED_NEWTON](#) = 1,
[SIMULATED_ANNEALING](#) = 2,
[NELDER_MEAD](#) = 3,
[NEWTON](#) = 4 }
Choose optimization algorithm.

Public Member Functions

- [OptSolver](#) ()
Default constructor.
- [OptSolver](#) (Vect< [real_t](#) > &x)
Constructor using vector of optimization variables.
- [OptSolver](#) (MyOpt &opt, Vect< [real_t](#) > &x)
Constructor using vector of optimization variables.

- `~OptSolver ()`
Destructor.
- `void set (Vect< real.t > &x)`
Set Solution vector.
- `int getNbFctEval () const`
Return the total number of function evaluations.
- `void setOptMethod (OptMethod m)`
Choose optimization method.
- `void setBC (const Vect< real.t > &bc)`
Prescribe boundary conditions as constraints.
- `void setObjective (string exp)`
Define the objective function to minimize by an algebraic expression.
- `void setGradient (string exp, int i=1)`
Define a component of the gradient of the objective function to minimize by an algebraic expression.
- `void setHessian (string exp, int i=1, int j=1)`
Define an entry of the Hessian matrix.
- `void setIneqConstraint (string exp, real.t penal=1./OFELI.TOLERANCE)`
Impose an inequality constraint by a penalty method.
- `void setEqConstraint (string exp, real.t penal=1./OFELI.TOLERANCE)`
Impose an equality constraint by a penalty method.
- `void setOptClass (MyOpt &opt)`
Choose user defined optimization class.
- `void setUpperBound (real.t ub)`
Define upper bound for optimization variable.
- `void setUpperBounds (Vect< real.t > &ub)`
Define upper bounds for optimization variables.
- `void setLowerBound (real.t lb)`
Define lower bound for optimization variable.
- `void setLowerBounds (Vect< real.t > &lb)`
Define lower bounds for optimization variables.
- `void setSAOpt (real.t rt, int ns, int nt, int &neps, int maxevl, real.t t, Vect< real.t > &vm, Vect< real.t > &xopt, real.t &fopt)`
Set Simulated annealing options.
- `void setTolerance (real.t toler)`
Set error tolerance.
- `void setMaxIterations (int n)`
Set maximal number of iterations.
- `int getNbObjEval () const`
Return number of objective function evaluations.
- `real.t getTemperature () const`
Return the final temperature.
- `int getNbAcc () const`
Return the number of accepted objective function evaluations.
- `int getNbOutOfBounds () const`
Return the total number of trial function evaluations that would have been out of bounds.
- `real.t getOptObj () const`
Return Optimal value of the objective.

- `int run ()`
Run the optimization algorithm.
- `int run (real_t toler, int max_it)`
Run the optimization algorithm.
- `real_t getSolution () const`
Return solution in the case of a one variable optimization.
- `void getSolution (Vect< real_t > &x) const`
Get solution vector.

Friends

- `ostream & operator<< (ostream &s, const OptSolver &os)`
Output class information.

7.85.1 Detailed Description

To solve an optimization problem with bound constraints.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.85.2 Member Enumeration Documentation

`enum OptMethod`

Choose optimization algorithm.

Enumerator

GRADIENT Gradient method

TRUNCATED_NEWTON Truncated Newton method

SIMULATED_ANNEALING Simulated annealing global optimization method

NELDER_MEAD Nelder-Mead global optimization method

NEWTON Newton's method

7.85.3 Constructor & Destructor Documentation

`OptSolver (Vect< real_t > &x)`

Constructor using vector of optimization variables.

Parameters

<code>in</code>	<code>x</code>	Vector having as size the number of optimization variables. It contains the initial guess for the optimization algorithm.
-----------------	----------------	---

Remarks

After using the member function `run`, the vector `x` contains the obtained solution if the optimization procedure was successful

OptSolver (**MyOpt** & *opt*, **Vect**< **real_t** > & *x*)

Constructor using vector of optimization variables.

Parameters

in	<i>opt</i>	Reference to instance of user defined optimization class. This class inherits from abstract class MyOpt . It must contain the member function <code>double Objective(Vect<double> &x)</code> which returns the value of the objective for a given solution vector <i>x</i> . The user defined class must contain, if the optimization algorithm requires it the member function <code>Gradient(Vect<double> &x, Vect<double> &g)</code> which stores the gradient of the objective in the vector <i>g</i> for a given optimization vector <i>x</i> . The user defined class must also contain, if the optimization algorithm requires it the member function
in	<i>x</i>	Vector having as size the number of optimization variables. It contains the initial guess for the optimization algorithm.

Remarks

After using the member function `run`, the vector *x* contains the obtained solution if the optimization procedure was successful

7.85.4 Member Function Documentation

`void setOptMethod (OptMethod m)`

Choose optimization method.

Parameters

in	<i>m</i>	<p>Enumerated value to choose the optimization algorithm to use. Must be chosen among the enumerated values:</p> <ul style="list-style-type: none"> • GRADIENT: Gradient steepest descent method with projection for bounded constrained problems • TRUNCATED_NEWTON: The Nash's Truncated Newton Algorithm, due to S.G. Nash (Newton-type Minimization via the Lanczos method, SIAM J. Numer. Anal. 21 (1984) 770-778). • SIMULATED_ANNEALING: Global optimization simulated annealing method. See Corana et al.'s article: "← Minimizing Multimodal Functions of Continuous Variables with the Simulated Annealing Algorithm" in the September 1987 (vol. 13, no. 3, pp. 262-280) issue of the ACM Transactions on Mathematical Software. • NELDER_MEAD: Global optimization Nelder-Mead method due to John Nelder, Roger Mead (A simplex method for function minimization, Computer Journal, Volume 7, 1965, pages 308-313). As implemented by R. ONeill (Algorithm AS 47: Function Minimization Using a Simplex Procedure, Applied Statistics, Volume 20, Number 3, 1971, pages 338-345).
----	----------	---

`void setBC (const Vect< real_t > &bc)`

Prescribe boundary conditions as constraints.

This member function is useful in the case of optimization problems where the optimization variable vector is the solution of a partial differential equation. For this case, Dirichlet boundary conditions can be prescribed as constraints for the optimization problem

Parameters

<code>in</code>	<code>bc</code>	Vector containing the values to impose on degrees of freedom. This vector must have been constructed using the Mesh instance.
-----------------	-----------------	---

Remarks

Only degrees of freedom with positive code are taken into account as prescribed

void setObjective (string *exp*)

Define the objective function to minimize by an algebraic expression.

Parameters

<code>in</code>	<code>exp</code>	Regular expression defining the objective function
-----------------	------------------	--

void setGradient (string *exp*, int *i* = 1)

Define a component of the gradient of the objective function to minimize by an algebraic expression.

Parameters

<code>in</code>	<code>exp</code>	Regular expression defining the objective function
<code>in</code>	<code>i</code>	Component of gradient [Default: 1]

void setHessian (string *exp*, int *i* = 1, int *j* = 1)

Define an entry of the Hessian matrix.

Parameters

<code>in</code>	<code>exp</code>	Regular expression defining the Hessian matrix entry
<code>in</code>	<code>i</code>	<i>i</i> -th row of Hessian matrix [Default: 1]
<code>in</code>	<code>j</code>	<i>j</i> -th column of Hessian matrix [Default: 1]

void setIneqConstraint (string *exp*, real *t* *penal* = 1./OFELI_TOLERANCE)

Impose an inequality constraint by a penalty method.

The constraint is of the form $F(x) \leq 0$ where F is any function of the optimization variable vector v

Parameters

<code>in</code>	<code>exp</code>	Regular expression defining the constraint (the function F
<code>in</code>	<code>penal</code>	Penalty parameter (large number) [Default: 1./DBL_EPSILON]

void setEqConstraint (string *exp*, real *t* *penal* = 1./OFELI_TOLERANCE)

Impose an equality constraint by a penalty method.

The constraint is of the form $F(x) = 0$ where F is any function of the optimization variable vector v

Parameters

in	<i>exp</i>	Regular expression defining the constraint (the function F
in	<i>penal</i>	Penalty parameter (large number) [Default: 1./DBL_EPSILON]

void setOptClass (MyOpt & opt)

Choose user defined optimization class.

Parameters

in	<i>opt</i>	Reference to inherited user specified optimization class
----	------------	--

void setUpperBound (real_t ub)

Define upper bound for optimization variable.

Case of a one-variable problem

Parameters

in	<i>ub</i>	Upper bound
----	-----------	-------------

void setUpperBounds (Vect< real_t > & ub)

Define upper bounds for optimization variables.

Parameters

in	<i>ub</i>	Vector containing upper values for variables
----	-----------	--

void setLowerBound (real_t lb)

Define lower bound for optimization variable.

Case of a one-variable problem

Parameters

in	<i>lb</i>	Lower value
----	-----------	-------------

void setLowerBounds (Vect< real_t > & lb)

Define lower bounds for optimization variables.

Parameters

in	<i>lb</i>	Vector containing lower values for variables
----	-----------	--

void setSAOpt (real_t rt, int ns, int nt, int & neps, int maxevl, real_t t, Vect< real_t > & vm, Vect< real_t > & xopt, real_t & fopt)

Set Simulated annealing options.

Remarks

This member function is useful only if simulated annealing is used.

Parameters

in	<i>rt</i>	The temperature reduction factor. The value suggested by Corana et al. is .85. See Goffe et al. for more advice.
in	<i>ns</i>	Number of cycles. After <i>ns*nb.var</i> function evaluations, each element of <i>vm</i> is adjusted so that approximately half of all function evaluations are accepted. The suggested value is 20.
in	<i>nt</i>	Number of iterations before temperature reduction. After <i>nt*ns*n</i> function evaluations, temperature (t) is changed by the factor <i>rt</i> . Value suggested by Corana et al. is <i>max(100,5*nb.var)</i> . See Goffe et al. for further advice.
in	<i>neps</i>	Number of final function values used to decide upon termination. See <i>eps</i> . Suggested value is 4
in	<i>maxevl</i>	The maximum number of function evaluations. If it is exceeded, the return <i>code=1</i> .
in	<i>t</i>	The initial temperature. See Goffe et al. for advice.
in	<i>vm</i>	The step length vector. On input it should encompass the region of interest given the starting value <i>x</i> . For point <i>x[i]</i> , the next trial point is selected is from <i>x[i]-vm[i]</i> to <i>x[i]+vm[i]</i> . Since <i>vm</i> is adjusted so that about half of all points are accepted, the input value is not very important (i.e. is the value is off, <i>OptimSA</i> adjusts <i>vm</i> to the correct value).
out	<i>xopt</i>	optimal values of optimization variables
out	<i>fopt</i>	Optimal value of objective

void setTolerance (real_t toler)

Set error tolerance.

Parameters

in	<i>toler</i>	Error tolerance for termination. If the final function values from the last <i>neps</i> temperatures differ from the corresponding value at the current temperature by less than <i>eps</i> and the final function value at the current temperature differs from the current optimal function value by less than <i>toler</i> , execution terminates and the value 0 is returned.
----	--------------	---

real_t getTemperature () const

Return the final temperature.

This function is meaningful only if the Simulated Annealing algorithm is used

int getNbAcc () const

Return the number of accepted objective function evaluations.

This function is meaningful only if the Simulated Annealing algorithm is used

int getNbOutOfBounds () const

Return the total number of trial function evaluations that would have been out of bounds.

This function is meaningful only if the Simulated Annealing algorithm is used

int run ()

Run the optimization algorithm.

This function runs the optimization procedure using default values for parameters. To modify these values, use the function run with arguments

int run (real.t toler, int max.it)

Run the optimization algorithm.

Parameters

in	<i>toler</i>	Tolerance value for convergence testing
in	<i>max.it</i>	Maximal number of iterations to achieve convergence

real.t getSolution () const

Return solution in the case of a one variable optimization.

In the case of a one variable problem, the solution value is returned, if the optimization procedure was successful

void getSolution (Vect< real.t > & x) const

Get solution vector.

The vector x contains the solution of the optimization problem. Note that if the constructor using an initial vector was used, the vector will contain the solution once the member function run has been used (If the optimization procedure was successful)

Parameters

out	x	solution vector
-----	-----	-----------------

7.86 Partition Class Reference

To partition a finite element mesh into balanced submeshes.

Public Member Functions

- [Partition \(\)](#)
Default constructor.
- [Partition \(Mesh &mesh, size.t n\)](#)
Constructor to partition a mesh into submeshes.
- [Partition \(Mesh &mesh, int n, vector< int > &epart\)](#)
Constructor using already created submeshes.
- [~Partition \(\)](#)
Destructor.
- [size.t getNbSubMeshes \(\) const](#)
Return number of submeshes.
- [size.t getNbNodes \(size.t i\) const](#)
Return number of nodes in given submesh.
- [size.t getNbElements \(size.t i\) const](#)
Return number of elements in given submesh.
- [Mesh * getMesh \(\)](#)

- Return the global [Mesh](#) instance.*

 - [Mesh](#) * [getMesh](#) (size_t i)
- Return the submesh of label i*

 - size_t [getNodeLabelInSubMesh](#) (size_t sm, size_t label) const

Return node label in subdomain by giving its label in initial mesh.
- size_t [getElementLabelInSubMesh](#) (size_t sm, size_t label) const

Return element label in subdomain by giving its label in initial mesh.
- size_t [getNodeLabelInMesh](#) (size_t sm, size_t label) const

Return node label in initial mesh by giving its label in submesh.
- size_t [getElementLabelInMesh](#) (size_t sm, size_t label) const

Return element label in initial mesh by giving its label in submesh.
- size_t [getNbInterfaceSides](#) (size_t sm) const

Return Number of interface sides for a given sub-mesh.
- size_t [getSubMesh](#) (size_t sm, size_t i) const

Return index of submesh that contains the i-th side label in sub-mesh sm
- [Mesh](#) & [getSubMesh](#) (size_t i) const

Return reference to submesh.
- size_t [getFirstSideLabel](#) (size_t sm, size_t i) const

Return i-th side label in a given submesh.
- size_t [getSecondSideLabel](#) (size_t sm, size_t i) const

Return side label in the neighbouring submesh corresponding to i-th side label in sub-mesh sm
- int [getNbConnectInSubMesh](#) (int n, int s) const

Get number of connected nodes in a submesh.
- int [getNbConnectOutSubMesh](#) (int n, int s) const

Get number of connected nodes out of a submesh.
- void [put](#) (size_t n, string file) const

Save a submesh in file.
- void [set](#) ([Mesh](#) &mesh, size_t n)

Set [Mesh](#) instance.

Friends

- ostream & [operator<<](#) (ostream &s, const [Partition](#) &p)
- Output class information.*

7.86.1 Detailed Description

To partition a finite element mesh into balanced submeshes.

Class [Partition](#) enables partitioning a given mesh into a given number of submeshes with a minimal connectivity. [Partition](#) uses the well known `metis` library that is included in the [OFELI](#) library. A more detailed description of `metis` can be found in the web site:

http://www.csit.fsu.edu/~burkardt/c_src/metis/metis.html

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.86.2 Constructor & Destructor Documentation**Partition (Mesh & *mesh*, size_t *n*)**

Constructor to partition a mesh into submeshes.

Parameters

in	<i>mesh</i>	Mesh instance
in	<i>n</i>	Number of submeshes

Partition (Mesh & *mesh*, int *n*, vector< int > & *epart*)

Constructor using already created submeshes.

Parameters

in	<i>mesh</i>	Mesh instance
in	<i>n</i>	Number of submeshes
in	<i>epart</i>	Vector containing for each element its submesh label (Running from 0 to n-1)

7.86.3 Member Function Documentation

size_t getNodeLabelInSubMesh (size_t *sm*, size_t *label*) const

Return node label in subdomain by giving its label in initial mesh.

Parameters

in	<i>sm</i>	Label of submesh
in	<i>label</i>	Label of node in initial mesh

size_t getNodeLabelInMesh (size_t *sm*, size_t *label*) const

Return node label in initial mesh by giving its label in submesh.

Parameters

in	<i>sm</i>	Label of submesh
in	<i>label</i>	Node label

size_t getSubMesh (size_t *sm*, size_t *i*) const

Return index of submesh that contains the i-th side label in sub-mesh *sm*

Parameters

in	<i>sm</i>	Submesh index
in	<i>i</i>	Side label

Returns

Index of submesh

Mesh& getSubMesh (size_t *i*) const

Return reference to submesh.

Parameters

in	<i>i</i>	Submesh index
----	----------	---------------

Returns

Reference to corresponding [Mesh](#) instance

size_t getFirstSideLabel (size_t *sm*, size_t *i*) const

Return i-th side label in a given submesh.

Parameters

in	<i>sm</i>	Index of submesh
in	<i>i</i>	Label of side

size_t getSecondSideLabel (size_t *sm*, size_t *i*) const

Return side label in the neighbouring submesh corresponding to i-th side label in sub-mesh *sm*

Parameters

in	<i>sm</i>	Label of submesh
in	<i>i</i>	Side label

int getNbConnectInSubMesh (int *n*, int *s*) const

Get number of connected nodes in a submesh.

Parameters

in	<i>n</i>	Label of node for which connections are counted
in	<i>s</i>	Label of submesh (starting from 0)

int getNbConnectOutSubMesh (int *n*, int *s*) const

Get number of connected nodes out of a submesh.

Parameters

in	<i>n</i>	Label of node for which connections are counted
in	<i>s</i>	Label of submesh (starting from 0)

void put (size_t *n*, string *file*) const

Save a submesh in file.


Parameters

in	<i>n</i>	Label of submesh
in	<i>file</i>	Name of file in which submesh is saved

7.87 Penta6 Class Reference

Defines a 6-node pentahedral finite element using P_1 interpolation in local coordinates (*s.x*, *s.y*) and Q_1 isoparametric interpolation in local coordinates (*s.x*, *s.z*) and (*s.y*, *s.z*).

Inheritance diagram for Penta6:



Public Member Functions

- **Penta6** ()
Default Constructor.
- **Penta6** (const **Element** *element)
*Constructor when data of **Element** el are given.*
- **~Penta6** ()
Destructor.
- void **set** (const **Element** *el)
Choose element by giving its pointer.
- void **setLocal** (const **Point**< **real.t** > &cs)
Initialize local point coordinates in element.
- vector< **Point**< **real.t** > > **DSh** () const
Return partial derivatives of shape functions of element nodes.
- **real.t** **getMaxEdgeLength** () const
Return Maximum length of pentahedron edges.
- **real.t** **getMinEdgeLength** () const
Return Mimimum length of pentahedron edges.

7.87.1 Detailed Description

Defines a 6-node pentahedral finite element using P_1 interpolation in local coordinates $(s.x, s.y)$ and Q_1 isoparametric interpolation in local coordinates $(s.x, s.z)$ and $(s.y, s.z)$.

The reference element is the cartesian product of the standard reference triangle with the line $[-1, 1]$. The nodes are ordered as follows: **Node** 1 in reference element is at $s=(1,0,0)$ **Node** 2 in reference element is at $s=(0,1,0)$ **Node** 3 in reference element is at $s=(0,0,0)$ **Node** 4 in reference element is at $s=(1,0,1)$ **Node** 5 in reference element is at $s=(0,1,1)$ **Node** 6 in reference element is at $s=(0,0,1)$

The user must take care to the fact that determinant of jacobian and other quantities depend on the point in the reference element where they are calculated. For this, before any utilization of shape functions or jacobian, function **setLocal()** must be invoked.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.87.2 Constructor & Destructor Documentation

Penta6 (const **Element** * element)

Constructor when data of **Element** el are given.

Parameters

in	element	Pointer to Element
----	---------	------------------------------------

7.87.3 Member Function Documentation

void setLocal (const Point< real_t > & s)

Initialize local point coordinates in element.

Parameters

in	s	Point in the reference element This function computes jacobian, shape functions and their partial derivatives at s. Other member functions only return these values.
----	---	--

vector<Point<real_t>> > DSh () const

Return partial derivatives of shape functions of element nodes.

Returns

[LocalVect](#) instance of partial derivatives of shape functions *e.g.* dsh(i).x, dsh(i).y, are partial derivatives of the *i*-th shape function.

Note

The local point at which the derivatives are computed must be chosen before by using the member function setLocal

7.88 PhaseChange Class Reference

This class enables defining phase change laws for a given material.

Public Member Functions

- virtual [~PhaseChange](#) ()
Destructor.
- int [E2T](#) (real_t &H, real_t &T, real_t &gamma)
Calculate temperature from enthalpy.
- virtual int [EnthalpyToTemperature](#) (real_t &H, real_t &T, real_t &gamma)
Virtual function to calculate temperature from enthalpy.
- void [setMaterial](#) ([Material](#) &m, int code)
Choose [Material](#) instance and material code.
- [Material](#) & [getMaterial](#) () const
Return reference to [Material](#) instance.

7.88.1 Detailed Description

This class enables defining phase change laws for a given material.

These laws are predefined for a certain number of materials. The user can set himself a specific behavior for his own materials by defining a class that inherits from [PhaseChange](#). The derived class must has at least the member function

int [EnthalpyToTemperature](#)(real_t &H, real_t &T, real_t &gamma)

7.88.2 Member Function Documentation

int E2T (real_t & *H*, real_t & *T*, real_t & *gamma*)

Calculate temperature from enthalpy.

This member function is to be called in any equation class that needs phase change laws.

Parameters

in	<i>H</i>	Enthalpy value
out	<i>T</i>	Calculated temperature value
out	<i>gamma</i>	Maximal slope of the curve $H \rightarrow T$

virtual int EnthalpyToTemperature (real_t & *H*, real_t & *T*, real_t & *gamma*) [virtual]

Virtual function to calculate temperature from enthalpy.

This member function must be implemented in any derived class in order to define user's own material laws.

Parameters

in	<i>H</i>	Enthalpy value
out	<i>T</i>	Calculated temperature value
out	<i>gamma</i>	Maximal slope of the curve $H \rightarrow T$

7.89 Point< T_ > Class Template Reference

Defines a point with arbitrary type coordinates.

Public Member Functions

- **Point ()**
Default constructor.
- **Point (T_ a, T_ b=T_(0), T_ c=T_(0))**
Constructor that assigns a, b to x-, y- and z-coordinates respectively.
- **Point (const Point< T_ > &p)**
Copy constructor.
- **T_ & operator() (size_t i)**
Operator (): Non constant version.
- **const T_ & operator() (size_t i) const**
Operator (): Constant version.
- **T_ & operator[] (size_t i)**
Operator []: Non constant version.
- **const T_ & operator[] (size_t i) const**
Operator []: Constant version.
- **Point< T_ > & operator+= (const Point< T_ > &p)**
Operator +=
- **Point< T_ > & operator-= (const Point< T_ > &p)**
Operator -=
- **Point< T_ > & operator= (const T_ &a)**
Operator =
- **Point< T_ > & operator+= (const T_ &a)**

- Operator +=*
- `Point< T_ > & operator+=(const T_ &a)`
- Operator -=*
- `Point< T_ > & operator-=(const T_ &a)`
- Operator *=*
- `Point< T_ > & operator/=(const T_ &a)`
- Operator /=*
- `bool operator==(const Point< T_ > &p)`
- Operator ==*
- `bool operator!=(const Point< T_ > &p)`
- Operator !=*
- `double NNorm () const`
Return squared euclidean norm of vector.
- `double Norm () const`
Return norm (length) of vector.
- `void Normalize ()`
Normalize vector.
- `Point< double > Director (const Point< double > &p) const`
Return Director (Normalized vector)
- `bool isCloseTo (const Point< double > &a, double toler=OFELI_TOLERANCE) const`
Return true if current point is close to instance a (up to tolerance toler)
- `T_ operator, (const Point< T_ > &p) const`
Return Dot (scalar) product of two vectors.

Public Attributes

- `T_ x`
First coordinate.
- `T_ y`
Second coordinate.
- `T_ z`
Third coordinate.

7.89.1 Detailed Description

template<class T_>class OFELI::Point< T_ >

Defines a point with arbitrary type coordinates.

Operators = and () are overloaded.

Template Parameters

<code>T_</code>	Data type (double, float, complex<double>, ...)
-----------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.89.2 Constructor & Destructor Documentation

Point (T_ a, T_ b = T_ (0), T_ c = T_ (0))

Constructor that assigns a, b to x-, y- and z-coordinates respectively.
Default values for b and c are 0

7.89.3 Member Function Documentation

T_& operator() (size_t i)

Operator (): Non constant version.
Values i = 1, 2, 3 correspond to x, y and z respectively

const T_& operator() (size_t i) const

Operator (): Constant version.
Values i = 1, 2, 3 correspond to x, y and z respectively

T_& operator[] (size_t i)

Operator []: Non constant version.
Values i = 0, 1, 2 correspond to x, y and z respectively

const T_& operator[] (size_t i) const

Operator []: Constant version.
Values i = 0, 1, 2 correspond to x, y and z respectively

Point<T_>& operator+=(const Point< T_ > & p)

Operator +=
Add point p to current instance

Point<T_>& operator-=(const Point< T_ > & p)

Operator -=
Subtract point p from current instance

Point<T_>& operator= (const T_ & a)

Operator =
Assign constant a to current instance coordinates

Point<T_>& operator+=(const T_ & a)

Operator +=
Add constant a to current instance coordinates

Point<T_>& operator-=(const T_ & a)

Operator -=
Subtract constant a from current instance coordinates

Point<T_>& operator*= (const T_ & a)

Operator *=

Multiply constant a by current instance coordinates

Point<T_>& operator/= (const T_ & a)

Operator /=

Divide current instance coordinates by a

bool operator==(const Point< T_ > & p)

Operator ==

Return true if current instance is equal to p, false otherwise.

bool operator!=(const Point< T_ > & p)

Operator !=

Return false if current instance is equal to p, true otherwise.

void Normalize ()

Normalize vector.

Divide vector components by its 2-norm

bool isCloseTo (const Point< double > & a, double toler = OFELI_TOLERANCE) const

Return true if current point is close to instance a (up to tolerance toler)

Default value for toler is the OFELI_TOLERANCE constant.

T_ operator, (const Point< T_ > & p) const

Return Dot (scalar) product of two vectors.

A typical use of this operator is `double a = (p,q)` where p and q are 2 instances of `Point<double>`

Parameters

in	p	Point instance by which the current instance is multiplied
----	---	--

7.90 Point2D< T_ > Class Template Reference

Defines a 2-D point with arbitrary type coordinates.

Public Member Functions

- [Point2D](#) ()
Default constructor.
- [Point2D](#) (T_ a, T_ b=T_(0))
Constructor that assigns a, b to x-, y- and y-coordinates respectively.
- [Point2D](#) (T_ *a)
Initialize point coordinates with C-array a.
- [Point2D](#) (const [Point2D](#)< T_ > &pt)
Copy constructor.

- **Point2D** (const **Point**< T_ > &pt)
*Copy constructor from class **Point**.*
- T_ & **operator()** (size_t i)
Operator() : Non constant version.
- const T_ & **operator()** (size_t i) const
Operator() : Constant version.
- T_ & **operator[]** (size_t i)
Operator []: Non constant version.
- const T_ & **operator[]** (size_t i) const
Operator [] Constant version.
- **Point2D**< T_ > & **operator=** (const **Point2D**< T_ > &p)
Operator =
- **Point2D**< T_ > & **operator+=** (const **Point2D**< T_ > &p)
Operator +=
- **Point2D**< T_ > & **operator-=** (const **Point2D**< T_ > &p)
Operator -=
- **Point2D**< T_ > & **operator=** (const T_ &a)
Operator =
- **Point2D**< T_ > & **operator+=** (const T_ &a)
Operator +=
- **Point2D**< T_ > & **operator-=** (const T_ &a)
Operator -=
- **Point2D**< T_ > & **operator*=** (const T_ &a)
*Operator *=*
- **Point2D**< T_ > & **operator/=** (const T_ &a)
Operator /=
- bool **operator==** (const **Point2D**< T_ > &p)
Operator ==
- bool **operator!=** (const **Point2D**< T_ > &p)
Operator !=
- **real_t** **CrossProduct** (const **Point2D**< **real_t** > &lp, const **Point2D**< **real_t** > &rp)
Return Cross product of two vectors lp and rp
- **real_t** **NNorm** () const
Return squared norm (length) of vector.
- **real_t** **Norm** () const
Return norm (length) of vector.
- **Point2D**< **real_t** > **Director** (const **Point2D**< **real_t** > &p) const
Return Director (Normalized vector)
- bool **isCloseTo** (const **Point2D**< **real_t** > &a, **real_t** toler=**OFELI.TOLERANCE**) const
Return true if current point is close to instance a (up to tolerance toler)

Public Attributes

- T_ **x**
First coordinate of point.
- T_ **y**
Second coordinate of point.

7.90.1 Detailed Description

template<class T_>class OFELI::Point2D< T_ >

Defines a 2-D point with arbitrary type coordinates.

Operators = and () are overloaded. The actual
Template Parameters

<i>T_</i>	Data type (double, float, complex<double>, ...)
-----------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.90.2 Constructor & Destructor Documentation

Point2D (T_ *a*, T_ *b* = T_ (0))

Constructor that assigns *a*, *b* to x-, y- and y-coordinates respectively.
Default value for *b* is 0

7.90.3 Member Function Documentation

T_& operator() (size_t *i*)

Operator() : Non constant version.
Values *i* = 1, 2 correspond to x and y respectively

const T_& operator() (size_t *i*) const

Operator() : Constant version.
Values *i*=1, 2 correspond to x and y respectively

T_& operator[] (size_t *i*)

Operator[] : Non constant version.
Values *i*=0, 1 correspond to x and y respectively

const T_& operator[] (size_t *i*) const

Operator[] Constant version.
Values *i*=0, 1 correspond to x and y respectively

Point2D<T_>& operator= (const Point2D< T_ > & *p*)

Operator =
Assign point *p* to current instance

Point2D<T_>& operator+= (const Point2D< T_ > & *p*)

Operator +=
Add point *p* to current instance

Point2D<T_>& operator-= (const Point2D< T_ > & p)

Operator -=

Subtract point p from current instance

Point2D<T_>& operator= (const T_ & a)

Operator =

Assign constant a to current instance coordinates

Point2D<T_>& operator+= (const T_ & a)

Operator +=

Add constant a to current instance coordinates

Point2D<T_>& operator-= (const T_ & a)

Operator -=

Subtract constant a from current instance coordinates

Point2D<T_>& operator*= (const T_ & a)

Operator *=

Multiply constant a by current instance coordinates

Point2D<T_>& operator/= (const T_ & a)

Operator /=

Divide current instance coordinates by a

bool operator== (const Point2D< T_ > & p)

Operator ==

Return true if current instance is equal to p, false otherwise.

bool operator!= (const Point2D< T_ > & p)


Operator !=

Return false if current instance is equal to p, true otherwise.

7.91 Polygon Class Reference

To store and treat a polygonal figure.

Inheritance diagram for Polygon:



Public Member Functions

- `polygon ()`
Default constructor.
- `Polygon (const Vect< Point< real_t > > &v, int code=1)`
Constructor.
- `void setVertices (const Vect< Point< real_t > > &v)`
Assign vertices of polygon.
- `real_t getSignedDistance (const Point< real_t > &p) const`
Return signed distance of a given point from the current polygon.
- `Polygon & operator+= (Point< real_t > a)`
Operator +=.
- `Polygon & operator+= (real_t a)`
*Operator *+=.*

7.91.1 Detailed Description

To store and treat a polygonal figure.

7.91.2 Constructor & Destructor Documentation

Polygon (const Vect< Point< real_t > > &v, int code = 1)

Constructor.

Parameters

in	<i>v</i>	Vect instance containing list of coordinates of polygon vertices
in	<i>code</i>	Code to assign to the generated domain (Default value = 1)

7.91.3 Member Function Documentation

void setVertices (const Vect< Point< real_t > > &v)

Assign vertices of polygon.

Parameters

in	<i>v</i>	Vector containing vertices coordinates in counter clockwise order
----	----------	---

real_t getSignedDistance (const Point< real_t > &p) const [virtual]

Return signed distance of a given point from the current polygon.

The computed distance is negative if p lies in the polygon, negative if it is outside, and 0 on its boundary

Parameters

in	<i>p</i>	Point<double> instance
----	----------	------------------------

Reimplemented from [Figure](#).

Polygon& operator+= (Point< real_t > a)

Operator +=.

Translate polygon by a vector a

Polygon& operator+= (real_t a)

Operator *+=.

Scale polygon by a factor a

7.92 `Prec< T_ >` Class Template Reference

To set a preconditioner.

Public Member Functions

- `Prec()`
Default constructor.
- `Prec(int type)`
Constructor that chooses preconditioner.
- `Prec(const SpMatrix< T_ > &A, int type=DIAG_PREC)`
Constructor using matrix of the linear system to precondition.
- `Prec(const Matrix< T_ > *A, int type=DIAG_PREC)`
Constructor using matrix of the linear system to precondition.
- `~Prec()`
Destructor.
- `void setType(int type)`
Define preconditioner type.
- `void setMatrix(const Matrix< T_ > *A)`
Define pointer to matrix for preconditioning (if this one is abstract)
- `void setMatrix(const SpMatrix< T_ > &A)`
Define the matrix for preconditioning.
- `void solve(Vect< T_ > &x) const`
Solve a linear system with preconditioning matrix.
- `void solve(const Vect< T_ > &b, Vect< T_ > &x) const`
Solve a linear system with preconditioning matrix.
- `void TransSolve(Vect< T_ > &x) const`
Solve a linear system with transposed preconditioning matrix.
- `void TransSolve(const Vect< T_ > &b, Vect< T_ > &x) const`
Solve a linear system with transposed preconditioning matrix.
- `T_ &getPivot(size_t i) const`
Return i-th pivot of preconditioning matrix.

7.92.1 Detailed Description

template<class T_>class OFELI::Prec< T_ >

To set a preconditioner.

The preconditioner type is chosen in the constructor

Template Parameters

<code><T_></code>	Data type (real_t, float, complex<real_t>, ...)
-------------------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.92.2 Constructor & Destructor Documentation

`Prec (int type)`

Constructor that chooses preconditioner.

Parameters

<code>in</code>	<i>type</i>	Preconditioner type:
		<ul style="list-style-type: none"> • <code>IDENT_PREC</code>: Identity preconditioner (No preconditioning) • <code>DIAG_PREC</code>: Diagonal preconditioner • <code>DILU_PREC</code>: Diagonal Incomplete factorization preconditioner • <code>ILU_PREC</code>: Incomplete factorization preconditioner • <code>SSOR_PREC</code>: SSOR (Symmetric Successive Over Relaxation) preconditioner

`Prec (const SpMatrix< T_ > & A, int type = DIAG_PREC)`

Constructor using matrix of the linear system to precondition.

Parameters

<code>in</code>	<i>A</i>	Matrix to precondition
<code>in</code>	<i>type</i>	Preconditioner type:
		<ul style="list-style-type: none"> • <code>IDENT_PREC</code>: Identity preconditioner (No preconditioning) • <code>DIAG_PREC</code>: Diagonal preconditioner • <code>DILU_PREC</code>: Diagonal Incomplete factorization preconditioner • <code>ILU_PREC</code>: Incomplete factorization preconditioner • <code>SSOR_PREC</code>: SSOR (Symmetric Successive Over Relaxation) preconditioner

`Prec (const Matrix< T_ > * A, int type = DIAG_PREC)`

Constructor using matrix of the linear system to precondition.

Parameters

<code>in</code>	A	Pointer to abstract Matrix class to precondition
<code>in</code>	<i>type</i>	Preconditioner type: <ul style="list-style-type: none"> • <code>IDENT.PREC</code>: Identity preconditioner (No preconditioning) • <code>DIAG.PREC</code>: Diagonal preconditioner • <code>DILU.PREC</code>: Diagonal Incomplete factorization preconditioner • <code>ILU.PREC</code>: Incomplete factorization preconditioner • <code>SSOR.PREC</code>: SSOR (Symmetric Successive Over Relaxation) preconditioner

7.92.3 Member Function Documentation

void setType (int *type*)

Define preconditioner type.

Parameters

<code>in</code>	<i>type</i>	Preconditioner type: <ul style="list-style-type: none"> • <code>IDENT.PREC</code>: Identity preconditioner (No preconditioning) • <code>DIAG.PREC</code>: Diagonal preconditioner • <code>DILU.PREC</code>: Diagonal Incomplete factorization preconditioner • <code>ILU.PREC</code>: Incomplete factorization preconditioner • <code>SSOR.PREC</code>: SSOR (Symmetric Successive Over Relaxation) preconditioner
-----------------	-------------	---

void setMatrix (const $\text{Matrix} < T_> * A$)

Define pointer to matrix for preconditioning (if this one is abstract)

Parameters

<code>in</code>	A	Matrix to precondition
-----------------	-----	------------------------

void setMatrix (const $\text{SpMatrix} < T_> \& A$)

Define the matrix for preconditioning.

Parameters

<code>in</code>	A	Matrix to precondition (instance of class SpMatrix)
-----------------	-----	--

void solve ($\text{Vect} < T_> \& x$) const

Solve a linear system with preconditioning matrix.

Parameters

in,out	x	Right-hand side on input and solution on output.
--------	-----	--

void solve (const Vect< T_ > & b, Vect< T_ > & x) const

Solve a linear system with preconditioning matrix.

Parameters

in	b	Right-hand side
out	x	Solution vector

void TransSolve (Vect< T_ > & x) const

Solve a linear system with transposed preconditioning matrix.

Parameters

in,out	x	Right-hand side in input and solution in output.
--------	-----	--

void TransSolve (const Vect< T_ > & b, Vect< T_ > & x) const

Solve a linear system with transposed preconditioning matrix.

Parameters

in	b	Right-hand side vector
out	x	Solution vector

7.93 Prescription Class Reference

To prescribe various types of data by an algebraic expression. Data may consist in boundary conditions, forces, tractions, fluxes, initial condition. All these data types can be defined through an enumerated variable.

Public Member Functions

- [Prescription](#) ()
Default constructor.
- [Prescription](#) ([Mesh](#) &mesh, const std::string &file)
Constructor that gives an instance of class [Mesh](#) and the data file name.
- [~Prescription](#) ()
Destructor.
- int [get](#) (EqDataType type, Vect< real_t > &v, real_t time=0, size_t dof=0)

7.93.1 Detailed Description

To prescribe various types of data by an algebraic expression. Data may consist in boundary conditions, forces, tractions, fluxes, initial condition. All these data types can be defined through an enumerated variable.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.93.2 Constructor & Destructor Documentation

Prescription (**Mesh** & *mesh*, const std::string & *file*)

Constructor that gives an instance of class [Mesh](#) and the data file name.

It reads parameters in [Prescription](#) Format from this file.

Parameters

in	<i>mesh</i>	Mesh instance
in	<i>file</i>	Name of Prescription file

7.93.3 Member Function Documentation

int **get** (EqDataType *type*, Vect< real.t > & *v*, real.t *time* = 0, size.t *dof* = 0)

Read data in the given file and stores in a [Vect](#) instance for a chosen DOF. The input value type determines the type of data to read.

Parameters


in	<i>type</i>	<p>Type of data to seek. To choose among the enumerated values:</p> <ul style="list-style-type: none"> • BOUNDARY_CONDITION: Read values for (Dirichlet) boundary conditions • BOUNDARY_FORCE: Read values for boundary force (Neumann boundary condition). The values TRACTION and FLUX have the same effect. • BODY_FORCE: Read values for body (or volume) forces. The value SOURCE has the same effect. • POINT_FORCE: Read values for pointwise forces • CONTACT_DISTANCE: Read values for contact distance (for contact mechanics) • INITIAL_FIELD: Read values for initial solution • SOLUTION: Read values for a solution vector
----	-------------	---

in,out	v	Vect instance that is instantiated on input and filled on output
in	$time$	Value of time for which data is read [Default: 0].
in	dof	DOF to store (Default is 0: All DOFs are chosen).

7.94 Quad4 Class Reference

Defines a 4-node quadrilateral finite element using Q_1 isoparametric interpolation.

Inheritance diagram for Quad4:



Public Member Functions

- [Quad4](#) ()
Default Constructor.
- [Quad4](#) (const [Element](#) *element)
Constructor when data of [Element](#) el are given.
- [Quad4](#) (const [Side](#) *side)
Constructor when data of [Side](#) sd are given.
- [~Quad4](#) ()
Destructor.
- void [set](#) (const [Element](#) *el)
Choose element by giving its pointer.
- void [set](#) (const [Side](#) *sd)
Choose side by giving its pointer.
- void [setLocal](#) (const [Point](#)< [real_t](#) > &cs)
Initialize local point coordinates in element.
- void [atGauss](#) (int n, std::vector< [real_t](#) > &sh, std::vector< [Point](#)< [real_t](#) > > &dsh, std::vector< [real_t](#) > &w)
Calculate shape functions and their partial derivatives and integration weights.
- [Point](#)< [real_t](#) > [Grad](#) (const [LocalVect](#)< [real_t](#), 4 > &u, const [Point](#)< [real_t](#) > &cs)
Return gradient of a function defined at element nodes.
- [real_t](#) [getMaxEdgeLength](#) () const
Return maximal edge length of quadrilateral.
- [real_t](#) [getMinEdgeLength](#) () const
Return minimal edge length of quadrilateral.

7.94.1 Detailed Description

Defines a 4-node quadrilateral finite element using Q_1 isoparametric interpolation.

The reference element is the square $[-1, 1] \times [-1, 1]$. The user must take care to the fact that determinant of jacobian and other quantities depend on the point in the reference element where they are calculated. For this, before any utilization of shape functions or jacobian, function [setLocal0](#) must be invoked.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.94.2 Constructor & Destructor Documentation

Quad4 (const Element * *element*)

Constructor when data of [Element](#) e1 are given.

Parameters

in	<i>element</i>	Pointer to Element
----	----------------	------------------------------------

Quad4 (const Side * *side*)

Constructor when data of [Side](#) sd are given.

Parameters

in	<i>side</i>	Pointer to Side
----	-------------	---------------------------------

7.94.3 Member Function Documentation

void setLocal (const Point< real_t > & s)

Initialize local point coordinates in element.

Parameters

in	<i>s</i>	Point in the reference element This function computes jacobian, shape functions and their partial derivatives at s. Other member functions only return these values.
----	----------	--

void atGauss (int *n*, std::vector< real_t > & *sh*, std::vector< Point< real_t > > & *dsh*, std::vector< real_t > & *w*)

Calculate shape functions and their partial derivatives and integration weights.

Parameters

in	<i>n</i>	Number of Gauss-Legendre integration points in each direction
in	<i>sh</i>	Vector of shape functions at Gauss points
in	<i>dsh</i>	Vector of shape function derivatives at Gauss points
in	<i>w</i>	Weights of integration formula at Gauss points

Point<real_t> Grad (const LocalVect< real_t, 4 > & *u*, const Point< real_t > & s)

Return gradient of a function defined at element nodes.

Parameters

in	u	Vector of values at nodes
in	s	Local coordinates (in $[-1, 1] * [-1, 1]$) of point where the gradient is evaluated

Returns

Value of gradient

Note

If the derivatives of shape functions were not computed before calling this function (by calling `setLocal`), this function will compute them

7.95 Reconstruction Class Reference

To perform various reconstruction operations.

Public Member Functions

- [Reconstruction](#) ()
Default constructor.
- [Reconstruction](#) (const [Mesh](#) &ms)
Constructor using a reference to a [Mesh](#) instance.
- [~Reconstruction](#) ()
Destructor.
- void [setMesh](#) (const [Mesh](#) &ms)
Provide [Mesh](#) instance.
- void [P0toP1](#) (const [Vect](#)< [real_t](#) > &u, [Vect](#)< [real_t](#) > &v)
Smooth an elementwise field to obtain a nodewise field by L^2 projection.
- void [DP1toP1](#) (const [Vect](#)< [real_t](#) > &u, [Vect](#)< [real_t](#) > &v)
Smooth an Discontinuous P_1 field to obtain a nodewise (Continuous P_1) field by L^2 projection.

7.95.1 Detailed Description

To perform various reconstruction operations.

This class enables various reconstruction operations like smoothing, projections, ...

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.95.2 Member Function Documentation

void P0toP1 (const [Vect](#)< [real_t](#) > &u, [Vect](#)< [real_t](#) > &v)

Smooth an elementwise field to obtain a nodewise field by L^2 projection.

Parameters

in	u	Vect instance that contains field to smooth
out	v	Vect instance that contains on output smoothed field

void DP1toP1 (const [Vect](#)< real.t > & u , [Vect](#)< real.t > & v)

Smooth an Discontinuous P1 field to obtain a nodewise (Continuous P₁) field by L^2 projection.

Parameters

in	u	Vect instance that contains field to smooth
out	v	Vect instance that contains on output smoothed field


Warning

This function is valid for P₁ triangles (2-D) only.

7.96 Rectangle Class Reference

To store and treat a rectangular figure.

Inheritance diagram for Rectangle:



Public Member Functions

- [Rectangle](#) ()
Default constructor.
- [Rectangle](#) (const [Point](#)< real.t > &bbm, const [Point](#)< real.t > &bbM, int code=1)
Constructor.
- void [setBoundingBox](#) (const [Point](#)< real.t > &bbm, const [Point](#)< real.t > &bbM)
Assign bounding box of the rectangle.
- [Point](#)< real.t > [getBoundingBox1](#) () const
Return first point of bounding box.
- [Point](#)< real.t > [getBoundingBox2](#) () const
Return second point of bounding box.
- real.t [getSignedDistance](#) (const [Point](#)< real.t > &p) const
Return signed distance of a given point from the current rectangle.
- [Rectangle](#) & [operator+=](#) ([Point](#)< real.t > a)
Operator +=.
- [Rectangle](#) & [operator+=](#) (real.t a)
*Operator *+=.*

7.96.1 Detailed Description

To store and treat a rectangular figure.

7.96.2 Constructor & Destructor Documentation

Rectangle (const Point< real_t > & *bbm*, const Point< real_t > & *bbM*, int *code* = 1)

Constructor.

Parameters

in	<i>bbm</i>	Left Bottom point of rectangle
in	<i>bbM</i>	Right Top point of rectangle
in	<i>code</i>	Code to assign to rectangle

7.96.3 Member Function Documentation

void setBoundingBox (const Point< real.t > & *bbm*, const Point< real.t > & *bbM*)

Assign bounding box of the rectangle.

Parameters

in	<i>bbm</i>	Left Bottom point
in	<i>bbM</i>	Right Top point

real.t getSignedDistance (const Point< real.t > & *p*) const [virtual]

Return signed distance of a given point from the current rectangle.

The computed distance is negative if *p* lies in the rectangle, negative if it is outside, and 0 on its boundary

Parameters

in	<i>p</i>	Point<double> instance
----	----------	------------------------

Reimplemented from [Figure](#).

Rectangle& operator+=(Point< real.t > *a*)

Operator +=.

Translate rectangle by a vector *a*

Rectangle& operator+=(real.t *a*)

Operator *+=.

Scale rectangle by a factor *a*

7.97 Side Class Reference

To store and treat finite element sides (edges in 2-D or faces in 3-D)

Public Types

- enum [SideType](#) {
[INTERNAL_SIDE](#) = 0,
[EXTERNAL_BOUNDARY](#) = 1,
[INTERNAL_BOUNDARY](#) = 2 }

Public Member Functions

- [Side](#) ()
Default Constructor.
- [Side](#) (size_t label, const string &shape)
Constructor initializing side label and shape.

- **Side** (size_t label, int shape)
Constructor initializing side label and shape.
- **Side** (const **Side** &sd)
Copy constructor.
- **~Side** ()
Destructor.
- void **Add** (**Node** *node)
Insert a node at end of list of nodes of side.
- void **Add** (**Edge** *edge)
Insert an edge at end of list of edges of side.
- void **setLabel** (size_t i)
Define label of side.
- void **setFirstDOF** (size_t n)
Define First DOF.
- void **setNbDOF** (size_t nb_dof)
Set number of degrees of freedom (DOF).
- void **DOF** (size_t i, size_t dof)
Define label of DOF.
- void **setDOF** (size_t &first_dof, size_t nb_dof)
Define number of DOF.
- void **setCode** (size_t dof, int code)
Assign code to a DOF.
- void **Replace** (size_t label, **Node** *node)
Replace a node at a given local label.
- void **Add** (**Element** *el)
Set pointer to neighbor element.
- void **set** (**Element** *el, size_t i)
Set pointer to neighbor element.
- void **setNode** (size_t i, **Node** *node)
Assign a node given by its pointer as the i-th node of side.
- void **setOnBoundary** ()
Say that the side is on the boundary.
- int **getShape** () const
Return side's shape.
- size_t **getLabel** () const
Return label of side.
- size_t **n** () const
Return label of side.
- size_t **getNbNodes** () const
Return number of side nodes.
- size_t **getNbVertices** () const
Return number of side vertices.
- size_t **getNbEq** () const
Return number of side equations.
- size_t **getNbDOF** () const
Return number of DOF.

- `int getCode (size_t dof=1) const`
Return code for a given DOF of node.
- `size_t getDOF (size_t i) const`
*Return label of *i*-th dof.*
- `size_t getFirstDOF () const`
Return label of first dof of node.
- `Node * getPtrNode (size_t i) const`
*Return pointer to node of local label *i*.*
- `Node * operator() (size_t i) const`
Operator ().
- `size_t getNodeLabel (size_t i) const`
Return global label of node with given local label.
- `Element * getNeighborElement (size_t i) const`
*Return pointer to *i*-th side neighboring element.*
- `Element * getOtherNeighborElement (Element *el) const`
Return pointer to other neighboring element than given one.
- `Point< real_t > getNormal () const`
Return normal vector to side.
- `Point< real_t > getUnitNormal () const`
Return unit normal vector to side.
- `int isOnBoundary () const`
Boundary side or not.
- `int isReferenced ()`
Say if side has a nonzero code or not.
- `real_t getMeasure () const`
Return measure of side.
- `Point< real_t > getCenter () const`
Return coordinates of center of side.
- `size_t Contains (const Node *nd) const`
Say if a given node belongs to current side.
- `void setActive (bool opt=true)`
*Set side is active (default) or not if argument is *false**
- `bool isActive () const`
*Return *true* or *false* whether side is active or not.*
- `int getLevel () const`
Return side level Side level increases when side is refined (starting from 0). If the level is 0, then the element has no father.
- `void setChild (Side *sd)`
Assign side as child of current one and assign current side as father.
- `Side * getParent () const`
Return pointer to parent side Return null if no parent.
- `Side * getChild (size_t i) const`
*Return pointer to *i*-th child side Returns null pointer is no childs.*
- `size_t getNbChilds () const`
Return number of children of side.

7.97.1 Detailed Description

To store and treat finite element sides (edges in 2-D or faces in 3-D)

Defines a side of a finite element mesh. The sides are given in particular by their shapes and a list of nodes. Each node can be accessed by the member function [getPtrNode\(\)](#). The string defining the element shape must be chosen according to the following list:

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.97.2 Member Enumeration Documentation

enum SideType

To select side type (boundary side or not).

Enumerator

INTERNAL_SIDE Internal side

EXTERNAL_BOUNDARY [Side](#) on external boundary

INTERNAL_BOUNDARY [Side](#) on internal boundary

7.97.3 Constructor & Destructor Documentation

Side (*size_t label*, *const string & shape*)

Constructor initializing side label and shape.

Parameters

<i>in</i>	<i>label</i>	Label to assign to side.
<i>in</i>	<i>shape</i>	Shape of side (See class description).

Side (*size_t label*, *int shape*)

Constructor initializing side label and shape.

Parameters

<i>in</i>	<i>label</i>	to assign to side.
<i>in</i>	<i>shape</i>	of side (See enum ElementShape in Mesh).

7.97.4 Member Function Documentation

void DOF (*size_t i*, *size_t dof*)

Define label of DOF.

Parameters

in	<i>i</i>	DOF index
in	<i>dof</i>	Its label

void setDOF (size_t & *first_dof*, size_t *nb_dof*)

Define number of DOF.

Parameters

in,out	<i>first_dof</i>	Label of the first DOF in input that is actualized
in	<i>nb_dof</i>	Number of DOF

void setCode (size_t *dof*, int *code*)

Assign code to a DOF.

Parameters

in	<i>dof</i>	DOF to which code is assigned
in	<i>code</i>	Code to assign

void Add (Element * *el*)

Set pointer to neighbor element.

Parameters

in	<i>el</i>	Pointer to element to add as a neighbor element
----	-----------	---

Remarks

This function adds the pointer *el* only if this one is not a null pointer

void set (Element * *el*, size_t *i*)

Set pointer to neighbor element.

Parameters

in	<i>el</i>	Pointer to element to set as a neighbor element
in	<i>i</i>	Local number of neighbor element

Remarks

This function differs from the Add by the fact that the local label of neighbor element is given

int getCode (size_t *dof* = 1) const

Return code for a given DOF of node.

Parameters

<i>in</i>	<i>dof</i>	Local label of degree of freedom. [Default: 1]
-----------	------------	--

Node* operator() (size_t *i*) const

Operator ().

Return pointer to node of local label *i*.

Element* getNeighborElement (size_t *i*) const

Return pointer to *i*-th side neighboring element.

Parameters

<i>in</i>	<i>i</i>	Local label of neighbor element (must be equal to 1 or 2).
-----------	----------	--

Element* getOtherNeighborElement (Element * *el*) const

Return pointer to other neighboring element than given one.

Parameters

<i>in</i>	<i>el</i>	Pointer to a given neighbor element
-----------	-----------	-------------------------------------

Remarks

If the side is on the boundary this function returns null pointer

Point<real_t> getNormal () const

Return normal vector to side.

The normal vector is oriented from the first neighbor element to the second one.

Warning

The norm of this vector is equal to the measure of the side (length of the edge in 2-D and area of the face in 3-D), and To get the unit normal, use rather the member function `getUnitNormal`.

Point<real_t> getUnitNormal () const

Return unit normal vector to side.

The unit normal vector is oriented from the first neighbor element to the second one.

Remarks

The norm of this vector is equal to one.

int isOnBoundary () const

Boundary side or not.

Returns 1 or -1 if side is on boundary Depending on whether the first or the second neighbor element is defined Returns 0 if side is an inner one

Remarks

This member function is valid only if member function `Mesh::getAllSides()` or `Mesh::getBoundarySides()` has been called before.

real_t getMeasure () const

Return measure of side.

This member function returns length or area of side. In case of quadrilaterals it returns determinant of Jacobian of mapping between reference and actual side

size_t Contains (const Node * nd) const

Say if a given node belongs to current side.

Parameters

in	nd	Pointer to searched node
----	----	--------------------------

Returns

index (local label) of node if found, 0 if not

void setChild (Side * sd)

Assign side as child of current one and assign current side as father.

This function is principally used when refining is invoked (*e.g.* for mesh adaption)

Parameters

in	sd	Pointer to side to assign
----	----	---------------------------

7.98 SideList Class Reference

Class to construct a list of sides having some common properties.

Public Member Functions

- [SideList](#) ([Mesh](#) &ms)
Constructor using a [Mesh](#) instance.
- [~SideList](#) ()
Destructor.
- void [selectCode](#) (int code, int dof=1)
Select sides having a given code for a given degree of freedom.
- void [unselectCode](#) (int code, int dof=1)
Unselect sides having a given code for a given degree of freedom.
- size_t [getNbSides](#) () const
Return number of selected sides.
- void [top](#) ()
Reset list of sides at its top position (Non constant version)
- void [top](#) () const
Reset list of sides at its top position (Constant version)
- [Side](#) * [get](#) ()
Return pointer to current side and move to next one (Non constant version)
- [Side](#) * [get](#) () const
Return pointer to current side and move to next one (Constant version)

7.98.1 Detailed Description

Class to construct a list of sides having some common properties.

This class enables choosing multiple selection criteria by using function `select...`. However, the intersection of these properties must be empty.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.98.2 Member Function Documentation

void selectCode (int *code*, int *dof* = 1)

Select sides having a given code for a given degree of freedom.

Parameters

in	<i>code</i>	Code that sides share
in	<i>dof</i>	Degree of Freedom label [Default: 1]

void unselectCode (int *code*, int *dof* = 1)

Unselect sides having a given code for a given degree of freedom.


Parameters

in	<i>code</i>	Code of sides to exclude
in	<i>dof</i>	Degree of Freedom label [Default: 1]

7.99 SkMatrix< T_ > Class Template Reference

To handle square matrices in skyline storage format.

Inheritance diagram for SkMatrix< T_ >:



Public Member Functions

- [SkMatrix](#) ()
Default constructor.
- [SkMatrix](#) (size_t [size](#), int is_diagonal=false)
Constructor that initializes a dense symmetric matrix.
- [SkMatrix](#) ([Mesh](#) &mesh, size_t dof=0, int is_diagonal=false)
Constructor using mesh to initialize skyline structure of matrix.
- [SkMatrix](#) (const [Vect](#)< size_t > &ColHt)

- Constructor that initializes skyline structure of matrix using vector of column heights.

 - `SkMatrix` (const `SkMatrix`< T_ > &m)

Copy Constructor.
- `~SkMatrix` ()

Destructor.
- void `setMesh` (`Mesh` &mesh, size_t dof=0)

Determine mesh graph and initialize matrix.
- void `setSkyline` (`Mesh` &mesh)

Determine matrix structure.
- void `setDiag` ()

Store diagonal entries in a separate internal vector.
- void `setDOF` (size_t i)

Choose DOF to activate.
- void `set` (size_t i, size_t j, const T_ &val)

Assign a value to an entry of the matrix.
- void `Axpy` (T_ a, const `SkMatrix`< T_ > &m)

Add to matrix the product of a matrix by a scalar.
- void `Axpy` (T_ a, const `Matrix`< T_ > *m)

Add to matrix the product of a matrix by a scalar.
- void `MultAdd` (const `Vect`< T_ > &x, `Vect`< T_ > &y) const

Multiply matrix by vector *x* and add to *y*.
- void `TMultAdd` (const `Vect`< T_ > &x, `Vect`< T_ > &y) const

Multiply transpose of matrix by vector *x* and add to *y*.
- void `MultAdd` (T_ a, const `Vect`< T_ > &x, `Vect`< T_ > &y) const

Multiply matrix by a vector and add to another one.
- void `Mult` (const `Vect`< T_ > &x, `Vect`< T_ > &y) const

Multiply matrix by vector *x* and save in *y*.
- void `TMult` (const `Vect`< T_ > &x, `Vect`< T_ > &y) const

Multiply transpose of matrix by vector *x* and save in *y*.
- void `add` (size_t i, size_t j, const T_ &val)

Add a constant value to an entry of the matrix.
- size_t `getColHeight` (size_t i) const

Return column height.
- T_ `operator()` (size_t i, size_t j) const

Operator () (Constant version).
- T_ & `operator()` (size_t i, size_t j)

Operator () (Non constant version).
- void `DiagPrescribe` (`Mesh` &mesh, `Vect`< T_ > &b, const `Vect`< T_ > &u, int flag=0)

Impose an essential boundary condition.
- void `DiagPrescribe` (`Vect`< T_ > &b, const `Vect`< T_ > &u, int flag=0)

Impose an essential boundary condition using the `Mesh` instance provided by the constructor.
- `SkMatrix`< T_ > & `operator=` (const `SkMatrix`< T_ > &m)

Operator =.
- `SkMatrix`< T_ > & `operator=` (const T_ &x)

Operator =.
- `SkMatrix`< T_ > & `operator+=` (const `SkMatrix`< T_ > &m)

- Operator +=.*
- `SkMatrix< T_ > & operator+= (const T_ &x)`
- Operator +=.*
- `SkMatrix< T_ > & operator*= (const T_ &x)`
- Operator *=.*
- `int setLU ()`
- Factorize the matrix (LU factorization)*
- `int solve (Vect< T_ > &b, bool fact=true)`
- Solve linear system.*
- `int solve (const Vect< T_ > &b, Vect< T_ > &x, bool fact=true)`
- Solve linear system.*
- `T_ * get () const`
- Return C-Array.*
- `T_ get (size_t i, size_t j) const`
- Return entry (i, j) of matrix if this one is stored, 0 else.*

7.99.1 Detailed Description

template<class T_>class OFELI::SkMatrix< T_ >

To handle square matrices in skyline storage format.

This template class allows storing and manipulating a matrix in skyline storage format.

The matrix entries are stored in 2 vectors column by column as in the following example:

```

/          \          /          \
| 10         . |      | u0   u1   0   0   u7 |
| 11  12      . |      |   u2   u3   0   u8 |
| 0  13  14     . |      | ...      u4   u5   u9 |
| 0  0  15  16    |      |           u6  u10 |
| 17  18  19 110 111 |    |           u11 |
\          /          \          /

```

Template Parameters

<code>T_</code>	Data type (double, float, complex<double>, ...)
-----------------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.99.2 Constructor & Destructor Documentation

SkMatrix ()

Default constructor.

Initializes a zero-dimension matrix

SkMatrix (size_t size, int is_diagonal = false)

Constructor that initializes a dense symmetric matrix.

Normally, for a dense matrix this is not the right class.

Parameters

in	<i>size</i>	Number of matrix rows (and columns).
in	<i>is_diagonal</i>	Boolean to select if the matrix is diagonal or not [Default: false]

SkMatrix (Mesh & mesh, size_t dof = 0, int is_diagonal = false)

Constructor using mesh to initialize skyline structure of matrix.

Parameters

in	<i>mesh</i>	Mesh instance for which matrix graph is determined.
in	<i>dof</i>	Option parameter, with default value 0. dof=1 means that only one degree of freedom for each node (or element or side) is taken to determine matrix structure. The value dof=0 means that matrix structure is determined using all DOFs.
in	<i>is_diagonal</i>	Boolean argument to say is the matrix is actually a diagonal matrix or not.

SkMatrix (const Vect< size_t > & ColHt)

Constructor that initializes skyline structure of matrix using vector of column heights.

Parameters

in	<i>ColHt</i>	Vect instance that contains rows lengths of matrix.
----	--------------	---

7.99.3 Member Function Documentation

void setMesh (Mesh & mesh, size_t dof = 0)

Determine mesh graph and initialize matrix.

This member function is called by constructor with the same arguments

Parameters

in	<i>mesh</i>	Mesh instance for which matrix graph is determined.
in	<i>dof</i>	Option parameter, with default value 0. dof=1 means that only one degree of freedom for each node (or element or side) is taken to determine matrix structure. The value dof=0 means that matrix structure is determined using all DOFs.

void setSkyline (Mesh & mesh)

Determine matrix structure.

This member function calculates matrix structure using a [Mesh](#) instance.

Parameters

in	<i>mesh</i>	Mesh instance
----	-------------	-------------------------------

void setDOF (size_t i)

Choose DOF to activate.

This function is available only if variable dof is equal to 1 in the constructor

Parameters

in	<i>i</i>	Index of the DOF
----	----------	------------------

void set (size_t *i*, size_t *j*, const T_ & *val*) [virtual]

Assign a value to an entry of the matrix.

Parameters

in	<i>i</i>	Row index (starting at i=1)
in	<i>j</i>	Column index (starting at i=1)
in	<i>val</i>	Value to assign to entry a(<i>i</i> , <i>j</i>)

Implements [Matrix< T_ >](#).

void Axy (T_ *a*, const SkMatrix< T_ > & *m*)

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which <i>a</i> is multiplied. The result is added to current instance

void Axy (T_ *a*, const Matrix< T_ > * *m*) [virtual]

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which <i>a</i> is multiplied. The result is added to current instance

Implements [Matrix< T_ >](#).

void MultAdd (const Vect< T_ > & *x*, Vect< T_ > & *y*) const [virtual]

Multiply matrix by vector *x* and add to *y*.

Parameters

in	<i>x</i>	Vector to multiply by matrix
in,out	<i>y</i>	Vector to add to the result. <i>y</i> contains on output the result.

Implements [Matrix< T_ >](#).

void TMultAdd (const Vect< T_ > & *x*, Vect< T_ > & *y*) const

Multiply transpose of matrix by vector *x* and add to *y*.

Parameters

in	<i>x</i>	Vector to multiply by matrix
in,out	<i>y</i>	Vector to add to the result. <i>y</i> contains on output the result.

void MultAdd (T_ *a*, const Vect< T_ > & *x*, Vect< T_ > & *y*) const [virtual]

Multiply matrix by a vector and add to another one.

Parameters

in	a	Constant to multiply by matrix
in	x	Vector to multiply by matrix
in,out	y	Vector to add to the result. y contains on output the result.

Implements [Matrix< T_ >](#).

void Mult (const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply matrix by vector x and save in y.

Parameters

in	x	Vector to multiply by matrix
out	y	Vector that contains on output the result.

Implements [Matrix< T_ >](#).

void TMult (const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply transpose of matrix by vector x and save in y.

Parameters

in	x	Vector to multiply by matrix
out	y	Vector that contains on output the result.

Implements [Matrix< T_ >](#).

void add (size_t i, size_t j, const T_ & val) [virtual]

Add a constant value to an entry of the matrix.

Parameters

in	i	Row index
in	j	Column index
in	val	Constant value to add to a(i, j)

Implements [Matrix< T_ >](#).

size_t getColHeight (size_t i) const

Return column height.

Column height at entry i is returned.

T_ operator() (size_t i, size_t j) const [virtual]

Operator () (Constant version).

Parameters

in	i	Row index
in	j	Column index

Implements [Matrix< T_ >](#).

T_ & operator() (size_t i, size_t j) [virtual]

Operator () (Non constant version).

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index

Implements [Matrix< T_ >](#).

void DiagPrescribe (Mesh & *mesh*, Vect< T_ > & *b*, const Vect< T_ > & *u*, int *flag* = 0)

Impose an essential boundary condition.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. It can be modified by member function **setPenal**(..).

Parameters

in	<i>mesh</i>	Mesh instance from which information is extracted.
in	<i>b</i>	Vect instance that contains right-hand side.
in	<i>u</i>	Vect instance that contains imposed values at DOFs where they are to be imposed.
in	<i>flag</i>	Parameter to determine whether only the right-hand side is to be modified (dof>0) or both matrix and right-hand side (dof=0, default value).

void DiagPrescribe (Vect< T_ > & *b*, const Vect< T_ > & *u*, int *flag* = 0)

Impose an essential boundary condition using the [Mesh](#) instance provided by the constructor.

This member function modifies diagonal terms in matrix and terms in vector that correspond to degrees of freedom with nonzero code in order to impose a boundary condition. It can be modified by member function **setPenal**(..).

Parameters

in	<i>b</i>	Vect instance that contains right-hand side.
in	<i>u</i>	Vect instance that contains imposed values at DOFs where they are to be imposed.
in	<i>flag</i>	Parameter to determine whether only the right-hand side is to be modified (dof>0) or both matrix and right-hand side (dof=0, default value).

SkMatrix<T_>& operator= (const SkMatrix< T_ > & *m*)

Operator =.

Copy matrix *m* to current matrix instance.

SkMatrix<T_>& operator= (const T_ & *x*)

Operator =.

define the matrix as a diagonal one with all diagonal entries equal to *x*.

SkMatrix<T_>& operator+= (const SkMatrix< T_ > & *m*)

Operator +=.

Add matrix *m* to current matrix instance.

SkMatrix<T_>& operator+= (const T_ & x)

Operator +=.

Add constant value x to matrix entries.

SkMatrix<T_>& operator*= (const T_ & x)

Operator *.

Premultiply matrix entries by constant value x.

int setLU ()

Factorize the matrix (LU factorization)

LU factorization of the matrix is realized. Note that since this is an in place factorization, the contents of the matrix are modified.

Returns

- 0 if factorization was normally performed,
- n if the n-th pivot is null.

Remarks

A flag in this class indicates after factorization that this one has been realized, so that, if the member function solve is called after this no further factorization is done.

int solve (Vect< T_ > & b, bool fact = true) [virtual]

Solve linear system.

The linear system having the current instance as a matrix is solved by using the LU decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents is a factorization is performed. Naturally, if the the matrix has been modified after using this function, the user has to refactorize it using the function setLU. This is because the class has no non-expensive way to detect if the matrix has been modified. The function setLU realizes the factorization step only.

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side on input and solution on output.
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- n if the n-th pivot is null.

Implements [Matrix< T_ >](#).

int solve (const Vect< T_ > & b, Vect< T_ > & x, bool fact = true) [virtual]

Solve linear system.

The linear system having the current instance as a matrix is solved by using the LU decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents if a factorization is performed. Naturally, if the matrix has been modified after using this function, the user has to refactorize it using the function setLU. This is because the class has no non-expensive way to detect if the matrix has been modified. The function setLU realizes the factorization step only.

Parameters

in	b	Vect instance that contains right-hand side.
out	x	Vect instance that contains solution
in	$fact$	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- n if the n-th pivot is null.

Implements [Matrix< T_ >](#).

T_* get () const


Return C-Array.

Skyline of matrix is stored row by row.

7.100 SkSMatrix< T_ > Class Template Reference

To handle symmetric matrices in skyline storage format.

Inheritance diagram for SkSMatrix< T_ >:



Public Member Functions

- [SkSMatrix](#) ()
Default constructor.
- [SkSMatrix](#) (size_t [size](#), int is_diagonal=false)
Constructor that initializes a dense symmetric matrix.
- [SkSMatrix](#) ([Mesh](#) &mesh, size_t dof=0, int is_diagonal=false)
Constructor using mesh to initialize skyline structure of matrix.
- [SkSMatrix](#) (const [Vect](#)< size_t > &ColHt)
Constructor that initializes skyline structure of matrix using vector of column height.
- [SkSMatrix](#) (const [Vect](#)< size_t > &I, const [Vect](#)< size_t > &J, int opt=1)
Constructor for a square matrix using non zero row and column indices.
- [SkSMatrix](#) (const [Vect](#)< size_t > &I, const [Vect](#)< size_t > &J, const [Vect](#)< T_ > &a, int opt=1)
Constructor for a square matrix using non zero row and column indices.
- [SkSMatrix](#) (const [SkSMatrix](#)< T_ > &m)
Copy Constructor.
- [~SkSMatrix](#) ()
Destructor.
- void [setMesh](#) ([Mesh](#) &mesh, size_t dof=0)
Determine mesh graph and initialize matrix.
- void [setSkyline](#) ([Mesh](#) &mesh)

- Determine matrix structure.*

 - void **setDiag** ()
 - Store diagonal entries in a separate internal vector.*
 - void **set** (size_t i, size_t j, const T_ &val)
 - Assign a value to an entry of the matrix.*
 - void **Axpy** (T_ a, const SkSMatrix< T_ > &m)
 - Add to matrix the product of a matrix by a scalar.*
 - void **Axpy** (T_ a, const Matrix< T_ > *m)
 - Add to matrix the product of a matrix by a scalar.*
 - void **MultAdd** (const Vect< T_ > &x, Vect< T_ > &y) const
 - Multiply matrix by vector x and add to y.*
 - void **MultAdd** (T_ a, const Vect< T_ > &x, Vect< T_ > &y) const
 - Multiply matrix by vector a*x and add to y.*
 - void **Mult** (const Vect< T_ > &x, Vect< T_ > &y) const
 - Multiply matrix by vector x and save in y*
 - void **TMult** (const Vect< T_ > &x, Vect< T_ > &y) const
 - Multiply transpose of matrix by vector x and save in y.*
 - void **add** (size_t i, size_t j, const T_ &val)
 - Add a constant to an entry of the matrix.*
 - size_t **getColHeight** (size_t i) const
 - Return column height.*
 - Vect< T_ > **getColumn** (size_t j) const
 - Get j-th column vector.*
 - Vect< T_ > **getRow** (size_t i) const
 - Get i-th row vector.*
 - T_ & **operator()** (size_t i, size_t j)
 - Operator () (Non constant version).*
 - T_ **operator()** (size_t i, size_t j) const
 - Operator () (Constant version).*
 - SkSMatrix< T_ > & **operator=** (const SkSMatrix< T_ > &m)
 - Operator =.*
 - SkSMatrix< T_ > & **operator=** (const T_ &x)
 - Operator =.*
 - SkSMatrix< T_ > & **operator+=** (const SkSMatrix< T_ > &m)
 - Operator +=.*
 - SkSMatrix< T_ > & **operator*=** (const T_ &x)
 - Operator *=.*
 - int **setLDLt** ()
 - Factorize matrix (LDLt (Crout) factorization).*
 - int **solveLDLt** (const Vect< T_ > &b, Vect< T_ > &x)
 - Solve a linear system using the LDLt (Crout) factorization.*
 - int **solve** (Vect< T_ > &b, bool fact=true)
 - Solve linear system.*
 - int **solve** (const Vect< T_ > &b, Vect< T_ > &x, bool fact=true)
 - Solve linear system.*
 - T_ * **get** () const

- Return C-Array.*
- void `set` (size_t i, T_ x)
Assign a value to the i-th entry of C-array containing matrix.
 - T_ `get` (size_t i, size_t j) const
Return entry (i, j) of matrix if this one is stored, 0 else.

7.100.1 Detailed Description

`template<class T_>class OFELI::SkSMatrix< T_ >`

To handle symmetric matrices in skyline storage format.
This template class allows storing and manipulating a symmetric matrix in skyline storage format.
The matrix entries are stored column by column as in the following example:

```
/
| a0  a1  0  0  a7 |
|   a2  a3  0  a8 |
| ...   a4  a5  a9 |
|           a6  a10 |
|               a11 |
\
```

Template Parameters

<code>T_</code>	Data type (double, float, complex<double>, ...)
-----------------	---

Author
Rachid Touzani

Copyright
GNU Lesser Public License

7.100.2 Constructor & Destructor Documentation

`SkSMatrix ()`

Default constructor.
Initializes a zero-dimension matrix

`SkSMatrix (size_t size, int is_diagonal = false)`

Constructor that initializes a dense symmetric matrix.
Normally, for a dense matrix this is not the right class.

Parameters

<code>in</code>	<code>size</code>	Number of matrix rows (and columns).
<code>in</code>	<code>is_diagonal</code>	Boolean to select if the matrix is diagonal or not [Default: false]

`SkSMatrix (Mesh & mesh, size_t dof = 0, int is_diagonal = false)`

Constructor using mesh to initialize skyline structure of matrix.

Parameters

in	<i>mesh</i>	Mesh instance for which matrix graph is determined.
in	<i>dof</i>	Option parameter, with default value 0. dof=1 means that only one degree of freedom for each node (or element or side) is taken to determine matrix structure. The value dof=0 means that matrix structure is determined using all DOFs.
in	<i>is_diagonal</i>	Boolean argument to say is the matrix is actually a diagonal matrix or not.

SkSMatrix (const Vect< size_t > & ColHt)

Constructor that initializes skyline structure of matrix using vector of column height.

Parameters

in	<i>ColHt</i>	Vect instance that contains rows lengths of matrix.
----	--------------	---

SkSMatrix (const Vect< size_t > & I, const Vect< size_t > & J, int opt = 1)

Constructor for a square matrix using non zero row and column indices.

Parameters

in	<i>I</i>	Vector containing row indices
in	<i>J</i>	Vector containing column indices
in	<i>opt</i>	Flag indicating if vectors I and J are cleaned and ordered (opt=1) or not (opt=0). In the latter case, these vectors can contain the same contents more than once and are not necessarily ordered.

SkSMatrix (const Vect< size_t > & I, const Vect< size_t > & J, const Vect< T_ > & a, int opt = 1)

Constructor for a square matrix using non zero row and column indices.

Parameters

in	<i>I</i>	Vector containing row indices
in	<i>J</i>	Vector containing column indices
in	<i>a</i>	Vector containing matrix entries in the same order than the one given by I and J
in	<i>opt</i>	Flag indicating if vectors I and J are cleaned and ordered (opt=1) or not (opt=0). In the latter case, these vectors can contain the same contents more than once and are not necessarily ordered

7.100.3 Member Function Documentation

void setMesh (Mesh & mesh, size_t dof = 0)

Determine mesh graph and initialize matrix.

This member function is called by constructor with the same arguments

Parameters

in	<i>mesh</i>	Mesh instance for which matrix graph is determined.
in	<i>dof</i>	Option parameter, with default value 0. dof=1 means that only one degree of freedom for each node (or element or side) is taken to determine matrix structure. The value dof=0 means that matrix structure is determined using all DOFs.

void setSkyline (Mesh & *mesh*)

Determine matrix structure.

This member function calculates matrix structure using [Mesh](#) instance *mesh*.

void set (size_t *i*, size_t *j*, const T_ & *val*) [virtual]

Assign a value to an entry of the matrix.

Parameters

in	<i>i</i>	Row index
in	<i>j</i>	Column index
in	<i>val</i>	Value to assign to a(<i>i</i> , <i>j</i>)

Implements [Matrix< T_ >](#).

void Axy (T_ *a*, const SkSMatrix< T_ > & *m*)

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Matrix by which <i>a</i> is multiplied. The result is added to current instance

void Axy (T_ *a*, const Matrix< T_ > * *m*) [virtual]

Add to matrix the product of a matrix by a scalar.

Parameters

in	<i>a</i>	Scalar to premultiply
in	<i>m</i>	Pointer to Matrix by which <i>a</i> is multiplied. The result is added to current instance

Implements [Matrix< T_ >](#).

void MultAdd (const Vect< T_ > & *x*, Vect< T_ > & *y*) const [virtual]

Multiply matrix by vector *x* and add to *y*.

Parameters

in	<i>x</i>	Vector to multiply by matrix
in,out	<i>y</i>	Vector to add to the result. <i>y</i> contains on output the result.

Implements [Matrix< T_ >](#).

void MultAdd (T_ *a*, const Vect< T_ > & *x*, Vect< T_ > & *y*) const [virtual]

Multiply matrix by vector *a***x* and add to *y*.

Parameters

in	a	Constant to multiply by matrix
in	x	Vector to multiply by matrix
in,out	y	Vector to add to the result. y contains on output the result.

Implements [Matrix< T_ >](#).

void Mult (const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply matrix by vector x and save in y

Parameters

in	x	Vector to multiply by matrix
out	y	Vector that contains on output the result.

Implements [Matrix< T_ >](#).

void TMult (const Vect< T_ > & x, Vect< T_ > & y) const [virtual]

Multiply transpose of matrix by vector x and save in y.

Parameters

in	x	Vector to multiply by matrix
out	y	Vector that contains on output the result.

Implements [Matrix< T_ >](#).

void add (size_t i, size_t j, const T_ & val) [virtual]

Add a constant to an entry of the matrix.

Parameters

in	i	Row index
in	j	Column index
in	val	Constant value to add to a(i, j)

Implements [Matrix< T_ >](#).

size_t getColHeight (size_t i) const

Return column height.

Column height at entry i is returned.

T_ & operator() (size_t i, size_t j) [virtual]

Operator () (Non constant version).

Parameters

in	i	Row index
in	j	Column index

Warning

To modify a value of an entry of the matrix it is safer not to modify both lower and upper triangles. Otherwise, wrong values will be assigned. If not sure, use the member functions set or add.

Implements [Matrix< T_ >](#).

T_ operator() (size_t *i*, size_t *j*) const [virtual]

Operator () (Constant version).

Parameters

in	i	Row index
in	j	Column index

Implements [Matrix< T_ >](#).

SkSMatrix<T_>& operator= (const SkSMatrix< T_ > & m)

Operator =.

Copy matrix *m* to current matrix instance.

SkSMatrix<T_>& operator= (const T_ & x)

Operator =.

define the matrix as a diagonal one with all diagonal entries equal to *x*.

SkSMatrix<T_>& operator+= (const SkSMatrix< T_ > & m)

Operator +=.

Add matrix *m* to current matrix instance.

SkSMatrix<T_>& operator*= (const T_ & x)

Operator *.

Premultiply matrix entries by constant value *x*.

int setLDLt ()

Factorize matrix (LDLt (Crout) factorization).

Returns

- 0 if factorization was normally performed
- *n* if the *n*-th pivot is null

int solveLDLt (const Vect< T_ > & b, Vect< T_ > & x)

Solve a linear system using the LDLt (Crout) factorization.

This function solves a linear system. The LDLt factorization is performed if this was not already done using the function setLU.

Parameters

in	b	Vect instance that contains right-hand side
out	x	Vect instance that contains solution

Returns

- 0 if solution was normally performed,
- *n* if the *n*-th pivot is null

Solution is performed only if factorization has previously been invoked.

```
int solve ( Vect< T_ > & b, bool fact = true ) [virtual]
```

Solve linear system.

The linear system having the current instance as a matrix is solved by using the LDLt decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents is a factorization is performed. Naturally, if the the matrix has been modified after using this function, the user has to refactorize it using the function setLU. This is because the class has no non-expensive way to detect if the matrix has been modified. The function setLDLt realizes the factorization step only.

Parameters

in,out	<i>b</i>	Vect instance that contains right-hand side on input and solution on output.
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- n if the n-th pivot is null.

Implements [Matrix< T_ >](#).

```
int solve ( const Vect< T_ > & b, Vect< T_ > & x, bool fact = true ) [virtual]
```

Solve linear system.

The linear system having the current instance as a matrix is solved by using the LDLt decomposition. Solution is thus realized after a factorization step and a forward/backward substitution step. The factorization step is realized only if this was not already done.

Note that this function modifies the matrix contents is a factorization is performed. Naturally, if the the matrix has been modified after using this function, the user has to refactorize it using the function setLDLt. This is because the class has no non-expensive way to detect if the matrix has been modified. The function setLDLt realizes the factorization step only.

Parameters

in	<i>b</i>	Vect instance that contains right-hand side.
out	<i>x</i>	Vect instance that contains solution
in	<i>fact</i>	Set true if matrix is to be factorized (Default value), false if not

Returns

- 0 if solution was normally performed,
- n if the n-th pivot is null.

Implements [Matrix< T_ >](#).

```
T_* get ( ) const
```


Return C-Array.

Skyline of matrix is stored row by row.

7.101 Sphere Class Reference

To store and treat a sphere.

Inheritance diagram for Sphere:



Public Member Functions

- `Sphere ()`
Default constructor.
- `Sphere (const Point< real_t > &c, real_t r, int code=1)`
Constructor.
- `void setRadius (real_t r)`
Assign radius of sphere.
- `real_t getRadius () const`
Return radius of sphere.
- `void setCenter (const Point< real_t > &c)`
Assign coordinates of center of sphere.
- `Point< real_t > getCenter () const`
Return coordinates of center of sphere.
- `real_t getSignedDistance (const Point< real_t > &p) const`
Return signed distance of a given point from the current sphere.
- `Sphere & operator+= (Point< real_t > a)`
Operator +=.
- `Sphere & operator*= (real_t a)`
*Operator *.=.*

7.101.1 Detailed Description

To store and treat a sphere.

7.101.2 Constructor & Destructor Documentation

`Sphere (const Point< real_t > &c, real_t r, int code = 1)`

Constructor.

Parameters

in	<i>c</i>	Coordinates of center of sphere
in	<i>r</i>	Radius
in	<i>code</i>	Code to assign to the generated sphere [Default: 1]

7.101.3 Member Function Documentation

`real_t getSignedDistance (const Point< real_t > &p) const` [virtual]

Return signed distance of a given point from the current sphere.

The computed distance is negative if p lies in the ball, positive if it is outside, and 0 on the sphere

Parameters

in	p	Point<double> instance
----	-----	------------------------

Reimplemented from [Figure](#).

Sphere& operator+= (Point< real_t > a)

Operator +=.

Translate sphere by a vector a

Sphere& operator+= (real_t a)


Operator *+=.

Scale sphere by a factor a

7.102 SpMatrix< T_ > Class Template Reference

To handle matrices in sparse storage format.

Inheritance diagram for SpMatrix< T_ >:



Public Member Functions

- [SpMatrix](#) ()
Default constructor.
- [SpMatrix](#) (size_t nr, size_t nc)
Constructor that initializes current instance as a dense matrix.
- [SpMatrix](#) (size_t size, int is_diagonal=false)
Constructor that initializes current instance as a dense matrix.
- [SpMatrix](#) (Mesh &mesh, size_t dof=0, int is_diagonal=false)
Constructor using a [Mesh](#) instance.
- [SpMatrix](#) (const Vect< RC > &I, int opt=1)
Constructor for a square matrix using non zero row and column indices.
- [SpMatrix](#) (const Vect< RC > &I, const Vect< T_ > &a, int opt=1)
Constructor for a square matrix using non zero row and column indices.
- [SpMatrix](#) (size_t nr, size_t nc, const vector< size_t > &row_ptr, const vector< size_t > &col_ind)
Constructor for a rectangle matrix.
- [SpMatrix](#) (size_t nr, size_t nc, const vector< size_t > &row_ptr, const vector< size_t > &col_ind, const vector< T_ > &a)
Constructor for a rectangle matrix.
- [SpMatrix](#) (const vector< size_t > &row_ptr, const vector< size_t > &col_ind)
Constructor for a rectangle matrix.
- [SpMatrix](#) (const vector< size_t > &row_ptr, const vector< size_t > &col_ind, const vector< T_ > &a)

- Constructor for a rectangle matrix.

 - [SpMatrix](#) (const [SpMatrix](#) &m)
- Copy constructor.

 - [~SpMatrix](#) ()
- Destructor.

 - void [Identity](#) ()
- Define matrix as identity.

 - void [Dense](#) ()
- Define matrix as a dense one.

 - void [Diagonal](#) ()
- Define matrix as a diagonal one.

 - void [Diagonal](#) (const T_ &a)
- Define matrix as a diagonal one with diagonal entries equal to a

 - void [Laplace1D](#) (size_t n, real_t h)
- Sets the matrix as the one for the Laplace equation in 1-D.

 - void [Laplace2D](#) (size_t nx, size_t ny)
- Sets the matrix as the one for the Laplace equation in 2-D.

 - void [setMesh](#) ([Mesh](#) &mesh, size_t dof=0)
- Determine mesh graph and initialize matrix.

 - void [setOneDOF](#) ()
- Activate 1-DOF per node option.

 - void [setSides](#) ()
- Activate Sides option.

 - void [setDiag](#) ()
- Store diagonal entries in a separate internal vector.

 - void [DiagPrescribe](#) ([Mesh](#) &mesh, [Vect](#)< T_ > &b, const [Vect](#)< T_ > &u)
- Impose by a diagonal method an essential boundary condition.

 - void [DiagPrescribe](#) ([Vect](#)< T_ > &b, const [Vect](#)< T_ > &u)
- Impose by a diagonal method an essential boundary condition using the [Mesh](#) instance provided by the constructor.

 - void [setSize](#) (size_t size)
- Set size of matrix (case where it's a square matrix).

 - void [setSize](#) (size_t nr, size_t nc)
- Set size (number of rows) of matrix.

 - void [setGraph](#) (const [Vect](#)< RC > &I, int opt=1)
- Set graph of matrix by giving a vector of its nonzero entries.

 - [Vect](#)< T_ > [getRow](#) (size_t i) const
- Get i-th row vector.

 - [Vect](#)< T_ > [getColumn](#) (size_t j) const
- Get j-th column vector.

 - T_ & [operator\(\)](#) (size_t i, size_t j)
- Operator () (Non constant version)

 - T_ [operator\(\)](#) (size_t i, size_t j) const
- Operator () (Constant version)

 - T_ [operator\(\)](#) (size_t i) const
- Operator () with one argument (Constant version)

 - T_ [operator\[\]](#) (size_t i) const

- Operator [] (Constant version).
- `Vect< T_ > operator*` (const `Vect< T_ > &x`) const
Operator * to multiply matrix by a vector.
- `SpMatrix< T_ > & operator*=` (const `T_ &a`)
Operator *= to premultiply matrix by a constant.
- void `getMesh` (`Mesh &mesh`)
Get mesh instance whose reference will be stored in current instance of `SpMatrix`.
- void `Mult` (const `Vect< T_ > &x`, `Vect< T_ > &y`) const
Multiply matrix by vector and save in another one.
- void `MultAdd` (const `Vect< T_ > &x`, `Vect< T_ > &y`) const
Multiply matrix by vector `x` and add to `y`.
- void `MultAdd` (`T_ a`, const `Vect< T_ > &x`, `Vect< T_ > &y`) const
Multiply matrix by vector `a*x` and add to `y`.
- void `TMult` (const `Vect< T_ > &x`, `Vect< T_ > &y`) const
Multiply transpose of matrix by vector `x` and save in `y`.
- void `Axpy` (`T_ a`, const `SpMatrix< T_ > &m`)
Add to matrix the product of a matrix by a scalar.
- void `Axpy` (`T_ a`, const `Matrix< T_ > *m`)
Add to matrix the product of a matrix by a scalar.
- void `set` (size_t `i`, size_t `j`, const `T_ &val`)
Assign a value to an entry of the matrix.
- void `add` (size_t `i`, size_t `j`, const `T_ &val`)
Add a value to an entry of the matrix.
- void `operator=` (const `T_ &x`)
Operator =.
- size_t `getColInd` (size_t `i`) const
Return storage information.
- size_t `getRowPtr` (size_t `i`) const
Return Row pointer at position `i`.
- int `solve` (const `Vect< T_ > &b`, `Vect< T_ > &x`, bool `fact=false`)
Solve the linear system of equations.
- void `setSolver` (`Iteration solver=CG_SOLVER`, `Preconditioner prec=DIAG_PREC`, int `max_it=1000`, `real_t toler=1.e-8`)
Choose solver and preconditioner for an iterative procedure.
- void `clear` ()
brief Set all matrix entries to zero
- `T_ * get` () const
Return C-Array.
- `T_ get` (size_t `i`, size_t `j`) const
Return entry (`i, j`) of matrix if this one is stored, 0 otherwise.

Friends

- template<class `TT_` >
ostream & `operator<<` (ostream &`s`, const `SpMatrix< TT_ > &A`)

7.102.1 Detailed Description

template<class T_>class OFELI::SpMatrix< T_ >

To handle matrices in sparse storage format.

This template class enables storing and manipulating a sparse matrix, i.e. only nonzero terms are stored. Internally, the matrix is stored as a vector instance and uses for the definition of its graph a [Vect<size_t>](#) instance `row_ptr` and a [Vect<size_t>](#) instance `col_ind` that contains respectively addresses of first element of each row and column indices.

To illustrate this, consider the matrix

```

1  2  0
3  4  0
0  5  0

```

Such a matrix is stored in the `vector<real_t>` instance `{1,2,3,4,5}`. The vectors `row_ptr` and `col_ind` are respectively: `{0,2,4,5}`, `{1,2,1,2,2}`

When the library `eigen` is used in conjunction with [OFELI](#), the class uses the sparse matrix class of `eigen` and enables then access to specific solvers (see class [LinearSolver](#))

Template Parameters

<code>T_</code>	Data type (double, float, <code>complex<double></code> , ...)
-----------------	---

Author

Rachid Touzani


Copyright

GNU Lesser Public License

7.103 SteklovPoincare2DBE Class Reference

Solver of the Steklov Poincare problem in 2-D geometries using piecewise constant boundary element.

Inheritance diagram for `SteklovPoincare2DBE`:



Public Member Functions

- [SteklovPoincare2DBE](#) ()
Default Constructor.
- [SteklovPoincare2DBE](#) ([Mesh](#) &ms)
Constructor using mesh data.
- [SteklovPoincare2DBE](#) ([Mesh](#) &ms, [Vect< real_t >](#) &u)
Constructor that solves the Steklov Poincare problem.
- [~SteklovPoincare2DBE](#) ()
Destructor.
- void [setMesh](#) ([Mesh](#) &ms)

- *set [Mesh](#) instance*
- `void setExterior ()`
Choose domain of the Laplace equation as exterior one.
- `int run ()`
Solve Setklov-Poincare problem.

7.103.1 Detailed Description

Solver of the Steklov Poincare problem in 2-D geometries using piecewise constant boundary elemen.

[SteklovPoincare2DBE](#) solves the Steklov Poincare problem in 2-D: Given the trace of a harmonic function on the boundary of a given (inner or outer) domain, this class computes the normal derivative of the function. The normal is considered as oriented out of the bounded (inner) domain in both inner and outer configurations. The numerical approximation uses piecewise constant (P_0) approximation on edges of the boundary. Solution is obtained from the GMRES iterative solver without preconditioning. The given data is the vector (instance of class [Vect](#)) of piecewise constant values of the harmonic function on the boundary and the returned solution is piecewise constant value of the normal derivative considered either as a [Vect](#) instance.

Note

Although the mesh of the inner domain is not necessary to solve the problem, this one must be provided in order to calculate the outward normal.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.103.2 Constructor & Destructor Documentation

[SteklovPoincare2DBE](#) ([Mesh](#) & *ms*)

Constructor using mesh data.

Parameters

<i>in</i>	<i>ms</i>	Reference to Mesh instance.
-----------	-----------	---

[SteklovPoincare2DBE](#) ([Mesh](#) & *ms*, [Vect](#)< `real_t` > & *u*)

Constructor that solves the Steklov Poincare problem.

This constructor calls member function `setMesh` and `Solve`.

Parameters

<i>in</i>	<i>ms</i>	Reference to mesh instance.
<i>in</i>	<i>u</i>	Reference to solution vector. It contains the solution (normal derivative on boundary, once problem is solved

7.103.3 Member Function Documentation

`void setMesh (Mesh & ms)`

set [Mesh](#) instance

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
-----------------	-----------------	-------------------------------

void setExterior ()

Choose domain of the Laplace equation as exterior one.

By default the domain where the Laplace equation is considered is the interior domain, *i.e.* bounded. This function chooses the exterior of a bounded domain

int run ()

Solve Setklov-Poincare problem.

This member function builds and solves the Steklov-Poincare equation.

7.104 Tabulation Class Reference

To read and manipulate tabulated functions.

Public Member Functions

- [Tabulation](#) ()
Default constructor.
- [Tabulation](#) (string file)
Constructor using file name.
- [~Tabulation](#) ()
Destructor.
- void [setFile](#) (string file)
Set file name.
- [real_t](#) [getValue](#) (string funct, [real_t](#) v)
Return the calculated value of the function.
- [real_t](#) [getDerivative](#) (string funct, [real_t](#) v)
Return the derivative of the function at a given point.
- [real_t](#) [getValue](#) (string funct, [real_t](#) v1, [real_t](#) v2)
Return the calculated value of the function.
- [real_t](#) [getValue](#) (string funct, [real_t](#) v1, [real_t](#) v2, [real_t](#) v3)
Return the calculated value of the function.

7.104.1 Detailed Description

To read and manipulate tabulated functions.

This class enables reading a tabulated function of one to three variables and calculating the value of the function using piecewise multilinear interpolation.

The file defining the function is an XML file where any function is introduced via the tag "`<Function`".

Author

Rachid Touzani


Copyright

GNU Lesser Public License

7.105 Tetra4 Class Reference

Defines a three-dimensional 4-node tetrahedral finite element using P_1 interpolation.

Inheritance diagram for Tetra4:



Public Member Functions

- [Tetra4](#) ()
Default Constructor.
- [Tetra4](#) (const [Element](#) *el)
Constructor when data of [Element](#) el are given.
- [~Tetra4](#) ()
Destructor.
- void [set](#) (const [Element](#) *el)
Choose element by giving its pointer.
- [real_t](#) [Sh](#) (size_t i, [Point](#)< [real_t](#) > s) const
Calculate shape function of node i at a given point s.
- [real_t](#) [getVolume](#) () const
Return volume of element.
- [Point](#)< [real_t](#) > [getRefCoord](#) (const [Point](#)< [real_t](#) > &x) const
Return reference coordinates of a point x in element.
- bool [isIn](#) (const [Point](#)< [real_t](#) > &x)
Check whether point x is in current tetrahedron or not.
- [real_t](#) [getInterpolate](#) (const [Point](#)< [real_t](#) > &x, const [LocalVect](#)< [real_t](#), 4 > &v)
Return interpolated value at point of coordinate x
- [Point](#)< [real_t](#) > [EdgeSh](#) (size_t k, [Point](#)< [real_t](#) > s)
Return edge shape function.
- [Point](#)< [real_t](#) > [CurlEdgeSh](#) (size_t k)
Return curl of edge shape function.
- [real_t](#) [getMaxEdgeLength](#) () const
Return maximal edge length of tetrahedron.
- [real_t](#) [getMinEdgeLength](#) () const
Return minimal edge length of tetrahedron.
- std::vector< [Point](#)< [real_t](#) > > [DSH](#) () const
Calculate partial derivatives of shape functions at element nodes.

7.105.1 Detailed Description

Defines a three-dimensional 4-node tetrahedral finite element using P_1 interpolation.

The reference element is the right tetrahedron with four unit edges interpolation.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.105.2 Member Function Documentation

real_t Sh (size_t i, Point< real_t > s) const

Calculate shape function of node *i* at a given point *s*.
s is a point in the reference tetrahedron.

Point<real_t> EdgeSh (size_t k, Point< real_t > s)

Return edge shape function.

Parameters

in	<i>k</i>	Local edge number for which the edge shape function is computed
in	<i>s</i>	Local coordinates in element

Remarks

[Element](#) edges are ordered as follows: [Edge](#) *k* has end vertices *k* and *k*+1

Point<real_t> CurlEdgeSh (size_t k)

Return curl of edge shape function.

Parameters

in	<i>k</i>	Local edge number for which the curl of the edge shape function is computed
----	----------	---

Remarks

[Element](#) edges are ordered as follows: [Edge](#) *k* has end vertices *k* and *k*+1

std::vector<Point<real_t> > DSh () const

Calculate partial derivatives of shape functions at element nodes.

Returns

Vector of partial derivatives of shape functions *e.g.* *dsh*[*i*-1].*x*, *dsh*[*i*-1].*y*, are partial derivatives of the *i*-th shape function

7.106 Timer Class Reference

To handle elapsed time counting.

Public Member Functions

- **Timer** ()
Default constructor.
- **~Timer** ()
Destructor.
- **bool Started** () const
Say if time counter has started.
- **void Start** ()
Start (or resume) time counting.
- **void Stop** ()
Stop time counting.
- **void Clear** ()
Clear time value (Set to zero)
- **real_t get** () const
Return elapsed time (in seconds)
- **real_t getTime** () const
Return elapsed time (in seconds)

7.106.1 Detailed Description

To handle elapsed time counting.

This class is to be used when testing program performances. A normal usage of the class is, once an instance is constructed, to use alternatively, Start, Stop and Resume. Elapsed time can be obtained once the member function Stop is called.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.106.2 Member Function Documentation

bool Started () const

Say if time counter has started.

Return true if time has started, false if not

void Start ()

Start (or resume) time counting.

This member function is to be used to start or resume time counting

void Stop ()

Stop time counting.

This function interrupts time counting. This one can be resumed by the function Start

real_t getTime () const

Return elapsed time (in seconds)

Identical to get

7.107 TimeStepping Class Reference

To solve time stepping problems, i.e. systems of linear ordinary differential equations of the form $[A2]\{y''\} + [A1]\{y'\} + [A0]\{y\} = \{b\}$.

Public Member Functions

- [TimeStepping](#) ()
Default constructor.
- [TimeStepping](#) (TimeScheme s, [real_t](#) time_step=[theTimeStep](#), [real_t](#) final_time=[theFinalTime](#))
Constructor using time discretization data.
- [~TimeStepping](#) ()
Destructor.
- void [set](#) (TimeScheme s, [real_t](#) time_step=[theTimeStep](#), [real_t](#) final_time=[theFinalTime](#))
Define data of the differential equation or system.
- void [setLinearSolver](#) (LinearSolver< [real_t](#) > &ls)
Set reference to [LinearSolver](#) instance.
- void [setPDE](#) (AbsEqua< [real_t](#) > &eq, bool nl=false)
Define partial differential equation to solve.
- void [setRK4RHS](#) (Vect< [real_t](#) > &f)
Set intermediate right-hand side vector for the Runge-Kutta method.
- void [setRK3_TVDRHS](#) (Vect< [real_t](#) > &f)
Set intermediate right-hand side vector for the TVD Runge-Kutta 3 method.
- void [setInitial](#) (Vect< [real_t](#) > &u)
Set initial condition for the system of differential equations.
- void [setInitial](#) (Vect< [real_t](#) > &u, Vect< [real_t](#) > &v)
Set initial condition for a system of differential equations.
- void [setInitialRHS](#) (Vect< [real_t](#) > &f)
Set initial RHS for a system of differential equations when the used scheme requires it.
- void [setRHS](#) (Vect< [real_t](#) > &b)
Set right-hand side vector.
- void [setRHS](#) (string exp)
Set right-hand side as defined by a regular expression.
- void [setBC](#) (Vect< [real_t](#) > &u)
Set vector containing boundary condition to enforce.
- void [setBC](#) (int code, string exp)
Set boundary condition as defined by a regular expression.
- void [setNewmarkParameters](#) ([real_t](#) beta, [real_t](#) gamma)
Define parameters for the Newmark scheme.
- void [setConstantMatrix](#) ()
Say that matrix problem is constant.
- void [setNonConstantMatrix](#) ()

Say that matrix problem is variable.

- void `setLinearSolver` (Iteration s=`DIRECT_SOLVER`, Preconditioner p=`DIAG_PREC`)
Set linear solver data.
- void `setNLTerm0` (Vect< real.t > &a0, Matrix< real.t > &A0)
Set vectors defining a nonlinear first order system of ODEs.
- void `setNLTerm` (Vect< real.t > &a0, Vect< real.t > &a1, Vect< real.t > &a2)
Set vectors defining a nonlinear second order system of ODEs.
- `real.t runOneTimeStep` ()
Run one time step.
- void `run` (bool opt=false)
Run the time stepping procedure.
- void `Assembly` (const Element &el, real.t *b, real.t *A0, real.t *A1, real.t *A2=nullptr)
Assemble element arrays into global matrix and right-hand side.
- void `SAssembly` (const Side &sd, real.t *b, real.t *A=nullptr)
Assemble side arrays into global matrix and right-hand side.
- `LinearSolver< real.t > &getLSolver` ()
Return LinearSolver instance.

7.107.1 Detailed Description

To solve time stepping problems, i.e. systems of linear ordinary differential equations of the form $[A2]\{y''\} + [A1]\{y'\} + [A0]\{y\} = \{b\}$.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

Features:

- The system may be first or second order (first and/or second order time derivatives)
- The following time integration schemes can be used:
 - For first order systems: The following schemes are implemented Forward Euler (value↵ : `FORWARD_EULER`)
Backward Euler (value: `BACKWARD_EULER`)
Crank-Nicolson (value: `CRANK_NICOLSON`)
Heun (value: `HEUN`)
2nd Order Adams-Bashforth (value: `AB2`)
4-th order Runge-Kutta (value: `RK4`)
2nd order Backward Differentiation Formula (value: `BDF2`)
 - For second order systems: The following schemes are implemented Newmark (value↵ : `NEWMARK`)

7.107.2 Constructor & Destructor Documentation

`TimeStepping` (TimeScheme s, real.t time_step = theTimeStep, real.t final_time = theFinalTime)

Constructor using time discretization data.

Parameters

in	<i>s</i>	Choice of the scheme: To be chosen in the enumerated variable <i>TimeScheme</i> (see the presentation of the class)
in	<i>time_step</i>	Value of the time step. This value will be modified if an adaptive method is used. The default value for this parameter is the value given by the global variable <code>theTimeStep</code>
in	<i>final_time</i>	Value of the final time (time starts at 0). The default value for this parameter is the value given by the global variable <code>theFinalTime</code>

7.107.3 Member Function Documentation

void set (*TimeScheme* *s*, *real.t* *time_step* = `theTimeStep`, *real.t* *final_time* = `theFinalTime`)

Define data of the differential equation or system.

Parameters

in	<i>s</i>	Choice of the scheme: To be chosen in the enumerated variable <i>TimeScheme</i> (see the presentation of the class)
in	<i>time_step</i>	Value of the time step. This value will be modified if an adaptive method is used. The default value for this parameter is the value given by the global variable <code>theTimeStep</code>
in	<i>final_time</i>	Value of the final time (time starts at 0). The default value for this parameter is the value given by the global variable <code>theFinalTime</code>

void setLinearSolver (*LinearSolver*< *real.t* > & *ls*)

Set reference to [LinearSolver](#) instance.

Parameters

in	<i>ls</i>	Reference to LinearSolver instance
----	-----------	--

void setPDE (*AbsEqua*< *real.t* > & *eq*, *bool* *nl* = *false*)

Define partial differential equation to solve.

The used equation class must have been constructed using the [Mesh](#) instance

Parameters

in	<i>eq</i>	Reference to equation instance
in	<i>nl</i>	Toggle to say if the considered equation is linear [Default: 0] or not

void setRK4RHS (*Vect*< *real.t* > & *f*)

Set intermediate right-hand side vector for the Runge-Kutta method.

Parameters

in	<i>f</i>	Vector containing the RHS
----	----------	---------------------------

void setRK3_TVDRHS (*Vect*< *real.t* > & *f*)

Set intermediate right-hand side vector for the TVD Runge-Kutta 3 method.

Parameters

<code>in</code>	<code>f</code>	Vector containing the RHS
-----------------	----------------	---------------------------

void setInitial (Vect< real_t > &u)

Set initial condition for the system of differential equations.

Parameters

<code>in</code>	<code>u</code>	Vector containing initial condition for the unknown
-----------------	----------------	---

Remarks

If a second-order differential equation is to be solved, use the the same function with two initial vectors (one for the unknown, the second for its time derivative)

void setInitial (Vect< real_t > &u, Vect< real_t > &v)

Set initial condition for a system of differential equations.

Parameters

<code>in</code>	<code>u</code>	Vector containing initial condition for the unknown
<code>in</code>	<code>v</code>	Vector containing initial condition for the time derivative of the unknown

Note

This function can be used to provide solution at previous time step if a restarting procedure is used.

This member function is to be used only in the case of a second order system

void setInitialRHS (Vect< real_t > &f)

Set initial RHS for a system of differential equations when the used scheme requires it.

Giving the right-hand side at initial time is sometimes required for high order methods like Runge-Kutta

Parameters

<code>in</code>	<code>f</code>	Vector containing right-hand side at initial time. This vector is helpful for high order methods
-----------------	----------------	--

Note

This function can be used to provide solution at previous time step if a restarting procedure is used.

void setRHS (string exp)

Set right-hand side as defined by a regular expression.

Parameters

in	<i>exp</i>	Regular expression as a function of x, y, z and t
-----------	------------	---

void setBC (int *code*, string *exp*)

Set boundary condition as defined by a regular expression.

Parameters

in	<i>code</i>	Code for which expression is assigned
in	<i>exp</i>	Regular expression to assign as a function of x, y, z and t

void setNewmarkParameters (real.t *beta*, real.t *gamma*)

Define parameters for the Newmark scheme.

Parameters

in	<i>beta</i>	Parameter beta [Default: 0.25]
in	<i>gamma</i>	Parameter gamma [Default: 0.5]

void setConstantMatrix ()

Say that matrix problem is constant.

This is useful if the linear system is solved by a factorization method but has no effect otherwise

void setNonConstantMatrix ()

Say that matrix problem is variable.

This is useful if the linear system is solved by a factorization method but has no effect otherwise

void setLinearSolver (Iteration *s* = DIRECT_SOLVER, Preconditioner *p* = DIAG_PREC)

Set linear solver data.

Parameters

in	<i>s</i>	Solver identification parameter. To be chosen in the enumeration variable Iteration: DIRECT_SOLVER, CG_SOLVER, CGS_SOLVER, BICG_SOLVER, BICG_STAB_SOLVER, GMRES_SOLVER, QMR_SOLVE← R [Default: DIRECT_SOLVER]
in	<i>p</i>	Preconditioner identification parameter. To be chosen in the enumeration variable Preconditioner: IDENT_PREC, DIAG_PREC, ILU_PREC [Default: DIAG_PREC]

Note

The argument *p* has no effect if the solver is DIRECT_SOLVER

void setNLTerm0 (Vect< real.t > &*a0*, Matrix< real.t > &*A0*)

Set vectors defining a nonlinear first order system of ODEs.

The ODE system has the form $a1(u)' + a0(u) = 0$

Parameters

<code>in</code>	<code>a0</code>	Reference to Vect instance defining the 0-th order term
<code>in</code>	<code>A0</code>	Reference to Matrix instance

void setNLTerm (Vect< real.t > & a0, Vect< real.t > & a1, Vect< real.t > & a2)

Set vectors defining a nonlinear second order system of ODEs.

The ODE system has the form $a2(u)'' + a1(u)' + a0(u) = 0$

Parameters

<code>in</code>	<code>a0</code>	Reference to Vect instance defining the 0-th order term
<code>in</code>	<code>a1</code>	Reference to Vect instance defining the first order term
<code>in</code>	<code>a2</code>	Reference to Vect instance defining the second order term

real.t runOneTimeStep ()

Run one time step.

Returns

Value of new time step if this one is updated

void run (bool opt = false)

Run the time stepping procedure.

Parameters

<code>in</code>	<code>opt</code>	Flag to say if problem matrix is constant while time stepping (true) or not (Default value is false)
-----------------	------------------	--

Note

This argument is not used if the time stepping scheme is explicit

void Assembly (const Element & el, real.t * b, real.t * A0, real.t * A1, real.t * A2 = nullptr)

Assemble element arrays into global matrix and right-hand side.

This member function is to be called from finite element equation classes

Parameters

<code>in</code>	<code>el</code>	Reference to Element class
<code>in</code>	<code>b</code>	Pointer to element right-hand side
<code>in</code>	<code>A0</code>	Pointer to matrix of 0-th order term (involving no time derivative)
<code>in</code>	<code>A1</code>	Pointer to matrix of first order term (involving time first derivative)
<code>in</code>	<code>A2</code>	Pointer to matrix of second order term (involving time second derivative) [Default: nullptr]

void SAssembly (const Side & sd, real.t * b, real.t * A = nullptr)

Assemble side arrays into global matrix and right-hand side.

This member function is to be called from finite element equation classes


Parameters

in	<i>sd</i>	Reference to Side class
in	<i>b</i>	Pointer to side right-hand side
in	<i>A</i>	Pointer to matrix [Default: nullptr]

7.108 TINS2DT3S Class Reference

Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 2-D domains. Numerical approximation uses stabilized 3-node triangle finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.

Inheritance diagram for TINS2DT3S:



Public Member Functions

- [TINS2DT3S](#) ()
Default Constructor.
- [TINS2DT3S](#) ([Mesh](#) &mesh)
Constructor using mesh.
- [TINS2DT3S](#) ([Mesh](#) &mesh, [Vect](#)< [real_t](#) > &u)
Constructor using mesh and velocity.
- [~TINS2DT3S](#) ()
Destructor.
- void [setInput](#) (EqDataType opt, [Vect](#)< [real_t](#) > &u)
Set equation input data.
- int [runOneTimeStep](#) ()
Run one time step.
- int [run](#) ()
Run (in the case of one step run)

7.108.1 Detailed Description

Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 2-D domains. Numerical approximation uses stabilized 3-node triangle finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.108.2 Constructor & Destructor Documentation

TINS2DT3S (*Mesh* & *mesh*)

Constructor using mesh.

Parameters

<i>in</i>	<i>mesh</i>	Mesh instance
-----------	-------------	-------------------------------

TINS2DT3S (*Mesh* & *mesh*, *Vect*< *real.t* > & *u*)

Constructor using mesh and velocity.

Parameters

<i>in</i>	<i>mesh</i>	Mesh instance
<i>in,out</i>	<i>u</i>	Vect instance containing initial velocity. This vector is updated during computations and will therefore contain velocity at each time step

7.108.3 Member Function Documentation

void setInput (*EqDataType opt*, *Vect*< *real.t* > & *u*)

Set equation input data.


Parameters

<i>in</i>	<i>opt</i>	Parameter to select type of input (enumerated values) <ul style="list-style-type: none"> INITIAL_FIELD: Initial temperature BOUNDARY_CONDITION: Boundary condition (Dirichlet) SOURCE: Body force applied to fluid TRACTION: Heat flux (Neumann boundary condition) VELOCITY_FIELD: Velocity vector (for the convection term)
<i>in</i>	<i>u</i>	Vector containing input data (Vect instance)

7.109 TINS3DT4S Class Reference

Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 3-D domains. Numerical approximation uses stabilized 4-node tetrahedral finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.

Inheritance diagram for TINS3DT4S:



Public Member Functions

- [TINS3DT4S \(\)](#)
Default Constructor.
- [TINS3DT4S \(Mesh &ms\)](#)
Constructor using mesh.
- [TINS3DT4S \(Mesh &ms, Vect< real_t > &u\)](#)
Constructor using mesh and velocity.
- [~TINS3DT4S \(\)](#)
Destructor.
- void [setInput](#) (EqDataType opt, [Vect< real_t > &u](#))
Set equation input data.
- int [runOneTimeStep](#) ()
Run one time step.
- int [run](#) ()
Run (in the case of one step run)

7.109.1 Detailed Description

Builds finite element arrays for transient incompressible fluid flow using Navier-Stokes equations in 3-D domains. Numerical approximation uses stabilized 4-node tetrahedral finite elements for velocity and pressure. 2nd-order projection scheme is used for time integration.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.109.2 Constructor & Destructor Documentation

TINS3DT4S (Mesh & ms)

Constructor using mesh.

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
-----------------	-----------------	-------------------------------

TINS3DT4S ([Mesh](#) & `ms`, `Vect< real.t > & u`)

Constructor using mesh and velocity.

Parameters

<code>in</code>	<code>ms</code>	Mesh instance
<code>in,out</code>	<code>u</code>	Vect instance containing initial velocity. This vector is updated during computations and will therefore contain velocity at each time step

7.109.3 Member Function Documentation

void setInput (`EqDataType opt`, `Vect< real.t > & u`)

Set equation input data.


Parameters

<code>in</code>	<code>opt</code>	Parameter to select type of input (enumerated values) <ul style="list-style-type: none"> INITIAL_FIELD: Initial temperature BOUNDARY_CONDITION_DATA: Boundary condition (Dirichlet) SOURCE_DATA: Heat source FLUX_DATA: Heat flux (Neumann boundary condition). NOT IMPLEMENTED VELOCITY_FIELD: Velocity vector (for the convection term)
<code>in</code>	<code>u</code>	Vector containing input data (Vect instance)

7.110 Triang3 Class Reference

Defines a 3-Node (P_1) triangle.

Inheritance diagram for Triang3:



Public Member Functions

- [Triang3](#) ()

Default Constructor.

- **Triang3** (const **Element** *el)
Constructor for an element.
- **Triang3** (const **Side** *sd)
Constructor for a side.
- **~Triang3** ()
Destructor.
- void **set** (const **Element** *el)
Choose element by giving its pointer.
- void **set** (const **Side** *sd)
Choose side by giving its pointer.
- **real_t** **Sh** (size_t i, **Point**< **real_t** > s) const
Calculate shape function of node at a given point.
- std::vector< **Point**< **real_t** > > **DSh** () const
Return partial derivatives of shape functions of element nodes.
- **real_t** **getInterpolate** (const **Point**< **real_t** > &x, const **LocalVect**< **real_t**, 3 > &v)
Return interpolated value at point of coordinate x
- **real_t** **check** () const
Check element area and number of nodes.
- **Point**< **real_t** > **Grad** (const **LocalVect**< **real_t**, 3 > &u) const
Return constant gradient vector in triangle.
- **real_t** **getMaxEdgeLength** () const
Return maximal edge length of triangle.
- **real_t** **getMinEdgeLength** () const
Return minimal edge length of triangle.

7.110.1 Detailed Description

Defines a 3-Node (P_1) triangle.

The reference element is the rectangle triangle with two unit edges.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.110.2 Constructor & Destructor Documentation

Triang3 (const **Element** * el)

Constructor for an element.

The constructed triangle is an element in a 2-D mesh.

Triang3 (const **Side** * sd)

Constructor for a side.

The constructed triangle is a side in a 3-D mesh.

7.110.3 Member Function Documentation

real_t **Sh** (size_t i, **Point**< **real_t** > s) const

Calculate shape function of node at a given point.

Parameters

in	i	Label (local) of node
in	s	Natural coordinates of node where to evaluate

std::vector<Point<real_t> > DSh () const

Return partial derivatives of shape functions of element nodes.

Returns

Vector of partial derivatives of shape functions *e.g.* `dsh[i-1].x`, `dsh[i-1].y`, are partial derivatives of the i -th shape function.

real_t check () const

Check element area and number of nodes.

Returns

- > 0 : m is the length
- $= 0$: zero length (\Rightarrow Error)

Point<real_t> Grad (const LocalVect< real_t, 3 > &u) const

Return constant gradient vector in triangle.


Parameters

in	u	Local vector for which the gradient is evaluated
----	-----	--

7.111 Triang6S Class Reference

Defines a 6-Node straight triangular finite element using P_2 interpolation.

Inheritance diagram for Triang6S:



Public Member Functions

- [Triang6S \(\)](#)
Default Constructor.
- [Triang6S \(const Element *el\)](#)
Constructor for an element.
- [~Triang6S \(\)](#)
Destructor.

- `void Sh (real_t s, real_t t, real_t *sh) const`
Calculate shape functions.
- `Point< real_t > getCenter () const`
Return coordinates of center of element.
- `real_t getMaxEdgeLength () const`
Return maximal edge length of triangle.
- `real_t getMinEdgeLength () const`
Return minimal edge length of triangle.
- `void setLocal (real_t s, real_t t)`
Initialize local point coordinates in element.
- `void atMidEdges (std::vector< Point< real_t > > &dsh, std::vector< real_t > &w)`
Compute partial derivatives of shape functions at mid edges of triangles.
- `std::vector< Point< real_t > > DSh () const`
Return partial derivatives of shape functions of element nodes.

7.111.1 Detailed Description

Defines a 6-Node straight triangular finite element using P_2 interpolation.

The reference element is the rectangle triangle with two unit edges.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.111.2 Constructor & Destructor Documentation

Triang6S (const Element * el)

Constructor for an element.

The constructed triangle is an element in a 2-D mesh.

Parameters

in	el	Pointer to Element instance
----	----	---

7.111.3 Member Function Documentation

void Sh (real_t s, real_t t, real_t * sh) const

Calculate shape functions.

Parameters

in	s	Local first coordinate of the point where the gradient of the shape functions are evaluated
in	t	Local second coordinate of the point where the gradient of the shape functions are evaluated
out	sh	Array of of shape functions at (s,t)

void setLocal (real_t s, real_t t)

Initialize local point coordinates in element.

Parameters

in	s	Local first coordinate of the point where the gradient of the shape functions are evaluated
in	t	Local second coordinate of the point where the gradient of the shape functions are evaluated

void atMidEdges (std::vector< Point< real_t > > & dsh, std::vector< real_t > & w)

Compute partial derivatives of shape functions at mid edges of triangles.

This member function can be called for integrations using partial derivatives of shape functions and approximated by midedge integration formula

Parameters

out	dsh	Vector containing partial derivatives of shape functions
out	w	Vector containing weights for the integration formula

std::vector<Point<real_t> > DSh () const

Return partial derivatives of shape functions of element nodes.

Returns

[LocalVect](#) instance of partial derivatives of shape functions *e.g.* `dsh(i).x`, `dsh(i).y`, are partial derivatives of the *i*-th shape function.


Note

The local point at which the derivatives are computed must be chosen before by using the member function `setLocal`

7.112 Triangle Class Reference

To store and treat a triangle.

Inheritance diagram for Triangle:



Public Member Functions

- [Triangle](#) ()
Default constructor.
- [Triangle](#) (const [Point](#)< [real_t](#) > &v1, const [Point](#)< [real_t](#) > &v2, const [Point](#)< [real_t](#) > &v3, int code=1)
Constructor with vertices and code.
- void [setVertex1](#) (const [Point](#)< [real_t](#) > &v)
Assign first vertex of triangle.

- void **setVertex2** (const **Point**< **real.t** > &v)
Assign second vertex of triangle.
- void **setVertex3** (const **Point**< **real.t** > &v)
Assign third vertex of triangle.
- **real.t** **getSignedDistance** (const **Point**< **real.t** > &p) const
Return signed distance of a given point from the current triangle.
- **Triangle** & **operator+=** (**Point**< **real.t** > a)
Operator +=.
- **Triangle** & **operator+=** (**real.t** a)
*Operator *+=.*

7.112.1 Detailed Description

To store and treat a triangle.

7.112.2 Constructor & Destructor Documentation

Triangle ()

Default constructor.

Constructs a unit triangle with vertices (0,0), (1,0) and (0,1)

Triangle (const **Point**< **real.t** > &*v1*, const **Point**< **real.t** > &*v2*, const **Point**< **real.t** > &*v3*,
int *code* = 1)

Constructor with vertices and code.

Parameters

in	<i>v1</i>	Coordinates of first vertex of triangle
in	<i>v2</i>	Coordinates of second vertex of triangle
in	<i>v3</i>	Coordinates of third vertex of triangle
in	<i>code</i>	Code to assign to the generated figure [Default: 1]

Remarks

Vertices must be given in counterclockwise order

7.112.3 Member Function Documentation

real.t **getSignedDistance** (const **Point**< **real.t** > &*p*) const [virtual]

Return signed distance of a given point from the current triangle.

The computed distance is negative if *p* lies in the triangle, positive if it is outside, and 0 on its boundary

Parameters

in	<i>p</i>	Point <double> instance
----	----------	--------------------------------

Reimplemented from [Figure](#).

Triangle& **operator+=** (**Point**< **real.t** > *a*)

Operator +=.

Translate triangle by a vector *a*

Triangle& operator+= (real_t a)


Operator *+=.

Scale triangle by a factor a

7.113 triangle Class Reference

Defines a triangle. The reference element is the rectangle triangle with two unit edges.

Inheritance diagram for triangle:



Public Member Functions

- **triangle ()**
Default Constructor.
- **triangle (const Element *el)**
Constructor for an element.
- **triangle (const Side *sd)**
Constructor for a side.
- **virtual ~triangle ()**
Destructor.
- **real_t getArea ()**
Return element area.
- **Point< real_t > getCenter () const**
Return coordinates of center of element.
- **Point< real_t > getCircumcenter () const**
Return coordinates of circumcenter of element.
- **real_t getCircumRadius () const**
Return radius of circumscribed circle of triangle.
- **real_t getInRadius () const**
Return radius of inscribed circle of triangle.
- **Point< real_t > getRefCoord (const Point< real_t > &x) const**
Return reference coordinates of a point x in element.
- **real_t getMaxEdgeLength () const**
Return maximal edge length of triangle.
- **real_t getMinEdgeLength () const**
Return minimal edge length of triangle.
- **bool isIn (const Point< real_t > &x) const**
Check whether point x is in current triangle or not.
- **bool isStrictlyIn (const Point< real_t > &x) const**
Check whether point x is strictly in current triangle (not on the boundary) or not.

7.113.1 Detailed Description

Defines a triangle. The reference element is the rectangle triangle with two unit edges.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.113.2 Constructor & Destructor Documentation

triangle (const Element * *el*)

Constructor for an element.

The constructed triangle is an element in a 2-D mesh.

triangle (const Side * *sd*)


Constructor for a side.

The constructed triangle is a side in a 3-D mesh.

7.114 TrMatrix< T_ > Class Template Reference

To handle tridiagonal matrices.

Inheritance diagram for TrMatrix< T_ >:



Public Member Functions

- [TrMatrix](#) ()
Default constructor.
- [TrMatrix](#) (size_t [size](#))
*Constructor for a tridiagonal matrix with *size* rows.*
- [TrMatrix](#) (const [TrMatrix](#) &*m*)
Copy Constructor.
- [~TrMatrix](#) ()
Destructor.
- void [Identity](#) ()
Define matrix as identity matrix.
- void [Diagonal](#) ()
Define matrix as a diagonal one.
- void [Diagonal](#) (const T_ &*a*)
*Define matrix as a diagonal one and assign value *a* to all diagonal entries.*
- void [Laplace1D](#) (real_t *h*)

Define matrix as the one of 3-point finite difference discretization of the second derivative.

- void **setSize** (size_t size)
Set size (number of rows) of matrix.
- void **MultAdd** (const Vect< T_ > &x, Vect< T_ > &y) const
Multiply matrix by vector x and add result to y .
- void **MultAdd** (T_ a, const Vect< T_ > &x, Vect< T_ > &y) const
Multiply matrix by vector $a*x$ and add result to y .
- void **Mult** (const Vect< T_ > &x, Vect< T_ > &y) const
Multiply matrix by vector x and save result in y .
- void **TMult** (const Vect< T_ > &x, Vect< T_ > &y) const
Multiply transpose of matrix by vector x and save result in y .
- void **Axpy** (T_ a, const TrMatrix< T_ > &m)
Add to matrix the product of a matrix by a scalar.
- void **Axpy** (T_ a, const Matrix< T_ > *m)
Add to matrix the product of a matrix by a scalar.
- void **set** (size_t i, size_t j, const T_ &val)
Assign constant val to an entry (i, j) of the matrix.
- void **add** (size_t i, size_t j, const T_ &val)
Add constant val value to an entry (i, j) of the matrix.
- T_ **operator()** (size_t i, size_t j) const
Operator $()$ (Constant version).
- T_ &**operator()** (size_t i, size_t j)
Operator $()$ (Non constant version).
- TrMatrix< T_ > &**operator=** (const TrMatrix< T_ > &m)
Operator $=$.
- TrMatrix< T_ > &**operator=** (const T_ &x)
Operator $=$ Assign matrix to identity times x .
- TrMatrix< T_ > &**operator*=** (const T_ &x)
Operator $*=$.
- int **solve** (Vect< T_ > &b, bool fact=true)
Solve a linear system with current matrix (forward and back substitution).
- int **solve** (const Vect< T_ > &b, Vect< T_ > &x, bool fact=false)
Solve a linear system with current matrix (forward and back substitution).
- T_ * **get** () const
Return C-Array.
- T_ **get** (size_t i, size_t j) const
Return entry (i, j) of matrix.

7.114.1 Detailed Description

template<class T_>class OFELI::TrMatrix< T_ >

To handle tridiagonal matrices.

This class enables storing and manipulating tridiagonal matrices. The template parameter is the type of matrix entries. Any matrix entry can be accessed by the $()$ operator: For instance, if A is an instance of this class, $A(i, j)$ stands for the entry at the i -th row and j -th column, i and j starting from 1. If i is difference from $i-1$, i or $i+1$, the returned value is 0. Entries of A can be assigned a value by the same operator. Only nonzero entries can be assigned.

Template Parameters

$T_$	Data type (double, float, complex<double>, ...)
------	---

Author

Rachid Touzani

Copyright

GNU Lesser Public License

7.115 Vect< T_ > Class Template Reference

To handle general purpose vectors.

Inherits vector< T_ >.

Public Member Functions

- [Vect](#) ()
Default Constructor. Initialize a zero-length vector.
- [Vect](#) (size_t n)
Constructor setting vector size.
- [Vect](#) (size_t nx, size_t ny)
Constructor of a 2-D index vector.
- [Vect](#) (size_t nx, size_t ny, size_t nz)
Constructor of a 3-D index vector.
- [Vect](#) (size_t n, T_ *x)
Create an instance of class Vect as an image of a C/C++ array.
- [Vect](#) (Grid &g)
Constructor with a Grid instance.
- [Vect](#) (Mesh &m, DOFSupport dof_type=NODE.DOF, int nb_dof=0)
Constructor with a mesh instance.
- [Vect](#) (Mesh &m, DOFSupport dof_type, string name, int nb_dof=0, real_t t=0.0)
Constructor with a mesh instance giving name and time for vector.
- [Vect](#) (const Element *el, const Vect< T_ > &v)
Constructor of an element vector.
- [Vect](#) (const Side *sd, const Vect< T_ > &v)
Constructor of a side vector.
- [Vect](#) (const Vect< T_ > &v, const Vect< T_ > &bc)
Constructor using boundary conditions.
- [Vect](#) (const Vect< T_ > &v, size_t nb_dof, size_t first_dof)
Constructor to select some components of a given vector.
- [Vect](#) (const Vect< T_ > &v)
Copy constructor.
- [Vect](#) (const Vect< T_ > &v, size_t n)
Constructor to select one component from a given 2 or 3-component vector.
- [Vect](#) (size_t d, const Vect< T_ > &v, const string &name=" ")
Constructor that extracts some degrees of freedom (components) from given instance of Vect.

- `~Vect ()`
Destructor.
- `void set (const T_ *v, size_t n)`
Initialize vector with a c-array.
- `void select (const Vect< T_ > &v, size_t nb_dof=0, size_t first_dof=1)`
Initialize vector with another Vect instance.
- `void set (const string &exp, size_t dof=1)`
Initialize vector with an algebraic expression.
- `void set (const string &exp, const Vect< real_t > &x)`
Initialize vector with an algebraic expression.
- `void set (Mesh &ms, const string &exp, size_t dof=1)`
Initialize vector with an algebraic expression with providing mesh data.
- `void set (const Vect< real_t > &x, const string &exp)`
Initialize vector with an algebraic expression.
- `void setMesh (Mesh &m, DOFSupport dof_type=NODE_DOF, size_t nb_dof=0)`
Define mesh class to size vector.
- `size_t size () const`
Return vector (global) size.
- `void setSize (size_t nx, size_t ny=1, size_t nz=1)`
Set vector size (for 1-D, 2-D or 3-D cases)
- `void resize (size_t n)`
Set vector size.
- `void resize (size_t n, T_ v)`
Set vector size and initialize to a constant value.
- `void setDOFType (DOFSupport dof_type)`
Set DOF type of vector.
- `void setDG (int degree=1)`
Set Discontinuous Galerkin type vector.
- `bool isGrid () const`
Say if vector is constructed for a grid.
- `size_t getNbDOF () const`
Return vector number of degrees of freedom.
- `size_t getNb () const`
Return vector number of entities (nodes, elements or sides)
- `Mesh & getMesh () const`
Return Mesh instance.
- `bool WithMesh () const`
Return true if vector contains a Mesh pointer, false if not.
- `DOFSupport getDOFType () const`
- `void setTime (real_t t)`
Set time value for vector.
- `real_t getTime () const`
Get time value for vector.
- `void setName (string name)`
Set name of vector.
- `string getName () const`

- Get name of vector.*
- `real_t Norm (NormType t) const`
Compute a norm of vector.
- `real_t getNorm1 () const`
Calculate 1-norm of vector.
- `real_t getNorm2 () const`
Calculate 2-norm (Euclidean norm) of vector.
- `real_t getNormMax () const`
Calculate Max-norm (Infinite norm) of vector.
- `real_t getWNorm1 () const`
Calculate weighted 1-norm of vector The wighted 1-norm is the 1-Norm of the vector divided by its size.
- `real_t getWNorm2 () const`
Calculate weighted 2-norm of vector.
- `T_ getMin () const`
Calculate Min value of vector entries.
- `T_ getMax () const`
Calculate Max value of vector entries.
- `size_t getNx () const`
Return number of grid points in the x-direction if grid indexing is set.
- `size_t getNy () const`
Return number of grid points in the y-direction if grid indexing is set.
- `size_t getNz () const`
Return number of grid points in the z-direction if grid indexing is set.
- `void setIJK (const string &exp)`
Assign a given function (given by an interpretable algebraic expression) of indices components of vector.
- `void setNodeBC (Mesh &m, int code, T_ val, size_t dof)`
Assign a given value to components of vector with given code.
- `void setNodeBC (Mesh &m, int code, T_ val)`
Assign a given value to components of vector with given code.
- `void setSideBC (Mesh &m, int code, T_ val, size_t dof)`
Assign a given value to components of vector corresponding to sides with given code.
- `void setNodeBC (Mesh &m, int code, const string &exp, size_t dof)`
Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.
- `void setNodeBC (Mesh &m, int code, const string &exp)`
Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.
- `void setSideBC (Mesh &m, int code, const string &exp, size_t dof)`
Assign a given function (given by an interpretable algebraic expression) to components of vector corresponding to sides with given code.
- `void setSideBC (Mesh &m, int code, const string &exp)`
Assign a given function (given by an interpretable algebraic expression) to components of vector corresponding to sides with given code.
- `void setNodeBC (int code, T_ val, size_t dof)`
Assign a given value to components of vector with given code.
- `void setNodeBC (int code, T_ val)`
Assign a given value to components of vector with given code.

- void **setNodeBC** (int code, const string &exp, size_t dof)
Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.
- void **setNodeBC** (int code, const string &exp)
Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.
- void **setSideBC** (int code, const string &exp, size_t dof)
Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.
- void **setSideBC** (int code, const string &exp)
Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.
- void **setSideBC** (int code, T_ val, size_t dof)
Assign a given value to components of vector with given code.
- void **setSideBC** (int code, T_ val)
Assign a given value to components of vector with given code.
- void **removeBC** (const Mesh &ms, const Vect< T_ > &v, int dof=0)
Remove boundary conditions.
- void **removeBC** (const Vect< T_ > &v, int dof=0)
Remove boundary conditions.
- void **transferBC** (const Vect< T_ > &bc, int dof=0)
Transfer boundary conditions to the vector.
- void **insertBC** (Mesh &m, const Vect< T_ > &v, const Vect< T_ > &bc, int dof=0)
Insert boundary conditions.
- void **insertBC** (Mesh &m, const Vect< T_ > &v, int dof=0)
Insert boundary conditions.
- void **insertBC** (const Vect< T_ > &v, const Vect< T_ > &bc, int dof=0)
Insert boundary conditions.
- void **insertBC** (const Vect< T_ > &v, int dof=0)
Insert boundary conditions.
- void **Assembly** (const Element &el, const Vect< T_ > &b)
Assembly of element vector into current instance.
- void **Assembly** (const Element &el, const T_ *b)
Assembly of element vector (as C-array) into Vect instance.
- void **Assembly** (const Side &sd, const Vect< T_ > &b)
Assembly of side vector into Vect instance.
- void **Assembly** (const Side &sd, const T_ *b)
Assembly of side vector (as C-array) into Vect instance.
- void **getGradient** (class Vect< T_ > &v)
Evaluate the discrete Gradient vector of the current vector.
- void **getGradient** (Vect< Point< T_ > > &v)
Evaluate the discrete Gradient vector of the current vector.
- void **getCurl** (Vect< T_ > &v)
Evaluate the discrete curl vector of the current vector.
- void **getCurl** (Vect< Point< T_ > > &v)
Evaluate the discrete curl vector of the current vector.
- void **getSCurl** (Vect< T_ > &v)

- Evaluate the discrete scalar curl in 2-D of the current vector.*

 - void **getDivergence** (**Vect**< T_ > &**v**)

Evaluate the discrete Divergence of the current vector.

 - **real_t** **getAverage** (const **Element** &**el**, int type) const

Return average value of vector in a given element.

 - **Vect**< T_ > & **MultAdd** (const **Vect**< T_ > &**x**, const T_ &**a**)

Multiply by a constant then add to a vector.

 - void **Axpy** (T_ **a**, const **Vect**< T_ > &**x**)

Add to vector the product of a vector by a scalar.

 - void **set** (size_t **i**, T_ **val**)

Assign a value to an entry for a 1-D vector.

 - void **set** (size_t **i**, size_t **j**, T_ **val**)

Assign a value to an entry for a 2-D vector.

 - void **set** (size_t **i**, size_t **j**, size_t **k**, T_ **val**)

Assign a value to an entry for a 3-D vector.

 - void **add** (size_t **i**, T_ **val**)

Add a value to an entry for a 1-index vector.

 - void **add** (size_t **i**, size_t **j**, T_ **val**)

Add a value to an entry for a 2-index vector.

 - void **add** (size_t **i**, size_t **j**, size_t **k**, T_ **val**)

Assign a value to an entry for a 3-index vector.

 - void **clear** ()

Clear vector: Set all its elements to zero.

 - T_ & **operator()** (size_t **i**)

Operator () (Non constant version)

 - T_ **operator()** (size_t **i**) const

Operator () (Constant version)

 - T_ & **operator()** (size_t **i**, size_t **j**)

Operator () with 2-D indexing (Non constant version, case of a grid vector).

 - T_ **operator()** (size_t **i**, size_t **j**) const

Operator () with 2-D indexing (Constant version).

 - T_ & **operator()** (size_t **i**, size_t **j**, size_t **k**)

Operator () with 3-D indexing (Non constant version).

 - T_ **operator()** (size_t **i**, size_t **j**, size_t **k**) const

Operator () with 3-D indexing (Constant version).

 - **Vect**< T_ > & **operator=** (const **Vect**< T_ > &**v**)

Operator = between vectors.

 - void **operator=** (string **s**)

Operator =

 - void **setUniform** (T_ **vmin**, T_ **vmax**, size_t **n**)

Initialize vector entries by setting extremal values and interval.

 - **Vect**< T_ > & **operator=** (const T_ &**a**)

Operator =

 - **Vect**< T_ > & **operator+=** (const **Vect**< T_ > &**v**)

Operator +=

 - **Vect**< T_ > & **operator+=** (const T_ &**a**)

- Operator +=*
- Vect< T_ > & operator+=(const Vect< T_ > &v)
- Operator -=*
- Vect< T_ > & operator-=(const T_ &a)
- Operator *=*
- Vect< T_ > & operator*=(const T_ &a)
- Operator /=*
- Vect< T_ > & operator/=(const T_ &a)
- void push.back (const T_ &v)*
- Add an entry to the vector.*
- const Mesh & getMeshPtr () const
- Return reference to Mesh instance.*
- T_ operator, (const Vect< T_ > &v) const
- Return Dot (scalar) product of two vectors.*
- Vect< complex_t > getFFT ()
- Compute FFT transform of vector.*
- Vect< complex_t > getInvFFT ()
- Compute Inverse FFT transform of vector.*

7.115.1 Detailed Description

template<class T_>class OFELI::Vect< T_ >

To handle general purpose vectors.

Author

Rachid Touzani

Copyright

GNU Lesser Public License

This template class enables defining and manipulating vectors of various data types. It inherits from the class std::vector An instance of class Vect can be:

- A simple vector of given size
- A vector with up to three indices, *i.e.*, an entry of the vector can be a(i), a(i, j) or a(i, j, k). This feature is useful, for instance, in the case of a structured grid
- A vector associate to a finite element mesh. In this case, a constructor uses a reference to the Mesh instance. The size of the vector is by default equal to the number of nodes x the number of degrees of freedom by node. If the degrees of freedom are supported by elements or sides, then the vector is sized accordingly

Operators =, [] and () are overloaded so that one can write for instance:

```
Vect<real_t> u(10), v(10);
v = -1.0;
u = v;
u(3) = -2.0;
```

to set vector v entries to -1, copy vector v into vector u and assign third entry of v to -2. Note that entries of v are here v(1), v(2), ..., v(10), *i.e.* vector entries start at index 1.

Template Parameters

<i>T_</i>	Data type (real_t, float, complex<real_t>, ...)
-----------	---

7.115.2 Constructor & Destructor Documentation**Vect (size_t *n*)**

Constructor setting vector size.

Parameters

in	<i>n</i>	Size of vector
----	----------	----------------

Vect (size_t *nx*, size_t *ny*)

Constructor of a 2-D index vector.

This constructor can be used for instance for a 2-D grid vector

Parameters

in	<i>nx</i>	Size for the first index
in	<i>ny</i>	Size for the second index

Remarks

The size of resulting vector is nx*ny

Vect (size_t *nx*, size_t *ny*, size_t *nz*)

Constructor of a 3-D index vector.

This constructor can be used for instance for a 3-D grid vector

Parameters

in	<i>nx</i>	Size for the first index
in	<i>ny</i>	Size for the second index
in	<i>nz</i>	Size for the third index

Remarks

The size of resulting vector is nx*ny*nz

Vect (size_t *n*, T_ * *x*)

Create an instance of class [Vect](#) as an image of a C/C++ array.

Parameters

in	<i>n</i>	Dimension of vector to construct
in	<i>x</i>	C-array to copy

Vect (Grid & *g*)

Constructor with a [Grid](#) instance.

The constructed vector has as size the total number of grid nodes

Parameters

in	<i>g</i>	Grid instance
----	----------	-------------------------------

Vect (Mesh & *m*, DOFSupport *dof_type* = *NODE_DOF*, int *nb_dof* = 0)

Constructor with a mesh instance.

Parameters

in	<i>m</i>	Mesh instance
in	<i>dof_type</i>	Type of degrees of freedom. To be given among the enumerated values: <i>NODE_DOF</i> , <i>ELEMENT_DOF</i> , <i>SIDE_DOF</i> or <i>EDGE_DOF</i> (Default↵ : <i>NODE_DOF</i>)
in	<i>nb_dof</i>	Number of degrees of freedom per node, element or side If <i>nb_dof</i> is set to 0 (default value) the constructor picks this number from the Mesh instance

Vect (Mesh & *m*, DOFSupport *dof_type*, string *name*, int *nb_dof* = 0, real_t *t* = 0.0)

Constructor with a mesh instance giving name and time for vector.

Parameters

in	<i>m</i>	Mesh instance
in	<i>dof_type</i>	Type of degrees of freedom. To be given among the enumerated values: <i>NODE_DOF</i> , <i>ELEMENT_DOF</i> , <i>SIDE_DOF</i> or <i>EDGE_DOF</i>
in	<i>name</i>	Name of the vector
in	<i>nb_dof</i>	Number of degrees of freedom per node, element or side If <i>nb↵_dof</i> is set to 0 the constructor picks this number from the Mesh instance
in	<i>t</i>	Time value for the vector [Default 0.0]

Vect (const Element * *el*, const Vect< T_ > & *v*)

Constructor of an element vector.

The constructed vector has local numbering of nodes

Parameters

in	<i>el</i>	Pointer to Element to localize
in	<i>v</i>	Global vector to localize

Vect (const Side * *sd*, const Vect< T_ > & *v*)

Constructor of a side vector.

The constructed vector has local numbering of nodes

Parameters

in	<i>sd</i>	Pointer to Side to localize
in	<i>v</i>	Global vector to localize

Vect (const Vect< T_ > & *v*, const Vect< T_ > & *bc*)

Constructor using boundary conditions.

Boundary condition values contained in *bc* are reported to vector *v*

Parameters

in	<i>v</i>	Vect instance to update
in	<i>bc</i>	Vect instance containing imposed valued at desired DOF

Vect (const Vect< T_ > & *v*, size_t *nb_dof*, size_t *first_dof*)

Constructor to select some components of a given vector.

Parameters

in	<i>v</i>	Vect instance to extract from
in	<i>nb_dof</i>	Number of DOF to extract
in	<i>first_dof</i>	First DOF to extract For instance, a choice <i>first_dof</i> =2 and <i>nb_dof</i> =1 means that the second DOF of each node is copied in the vector

Vect (const Vect< T_ > & *v*, size_t *n*)

Constructor to select one component from a given 2 or 3-component vector.

Parameters

in	<i>v</i>	Vect instance to extract from
in	<i>n</i>	Component to extract (must be > 1 and < 4 or).

Vect (size_t *d*, const Vect< T_ > & *v*, const string & *name* = " ")

Constructor that extracts some degrees of freedom (components) from given instance of [Vect](#).

This constructor enables constructing a subvector of a given [Vect](#) instance. It selects a given list of degrees of freedom and put it according to a given order in the instance to construct.

Parameters

in	<i>d</i>	Integer number giving the list of degrees of freedom. This number is made of n digits where n is the number of degrees of freedom. Let us give an example: Assume that the instance <i>v</i> has 3 DOF by entity (node, element or side). The choice <i>d</i> =201 means that the constructed instance has 2 DOF where the first DOF is the third one of <i>v</i> , and the second DOF is the first one of <i>v</i> . Consequently, no digit can be larger than the number of DOF the constructed instance. In this example, a choice <i>d</i> =103 would produce an error message.
in	<i>v</i>	Vect instance from which extraction is performed.
in	<i>name</i>	Name to assign to vector instance (Default value is " ").

Warning

Don't give zeros as first digits for the argument *d*. The number is in this case interpreted as octal !!

7.115.3 Member Function Documentation

void set (const T_ * *v*, size_t *n*)

Initialize vector with a c-array.

Parameters

in	<i>v</i>	c-array (pointer) to initialize Vect
in	<i>n</i>	size of array

void select (const Vect< T_ > & v, size_t nb_dof = 0, size_t first_dof = 1)

Initialize vector with another [Vect](#) instance.

Parameters

in	<i>v</i>	Vect instance to extract from
in	<i>nb_dof</i>	Number of DOF per node, element or side (By default, 0: Number of degrees of freedom extracted from the Mesh instance)
in	<i>first_dof</i>	First DOF to extract (Default: 1) For instance, a choice <code>first_dof=2</code> and <code>nb_dof=1</code> means that the second DOF of each node is copied in the vector

void set (const string & exp, size_t dof = 1)

Initialize vector with an algebraic expression.

This function is to be used is a [Mesh](#) instance is associated to the vector

Parameters

in	<i>exp</i>	Regular algebraic expression that defines a function of <i>x</i> , <i>y</i> , <i>z</i> which are coordinates of nodes and <i>t</i> which is the time value.
in	<i>dof</i>	Degree of freedom to which the value is assigned [Default: 1]

Warning

If the time variable *t* is involved in the expression, the time value associated to the vector instance must be defined (Default value is 0) either by using the appropriate constructor or by the member function `setTime`.

void set (const string & exp, const Vect< real_t > & x)

Initialize vector with an algebraic expression.

This function can be used for instance in 1-D

Parameters

in	<i>exp</i>	Regular algebraic expression that defines a function of <i>x</i> which are values of vector. This expression must use the variable <i>x</i> as coordinate of vector.
----	------------	--

Warning

If the time variable *t* is involved in the expression, the time value associated to the vector instance must be defined (Default value is 0) either by using the appropriate constructor or by the member function `setTime`.

Parameters

in	x	Vector that defines coordinates
----	-----	---------------------------------

void set (Mesh & ms , const string & exp , size_t $dof = 1$)

Initialize vector with an algebraic expression with providing mesh data.

Parameters

in	ms	Mesh instance
in	exp	Regular algebraic expression that defines a function of x , y and z which are coordinates of nodes.
in	dof	Degree of freedom to which the value is assigned [Default: 1]

void set (const Vect< real_t > & x , const string & exp)

Initialize vector with an algebraic expression.

Parameters

in	x	Vect instance that contains coordinates of points
in	exp	Regular algebraic expression that defines a function of x and i which are coordinates. Consider for instance that we want to initialize the Vect instance with the values $v[i] = \exp(1+x[i])$; then, we use this member function as follows <code>v.set("exp("1+x",x);</code>

void setMesh (Mesh & m , DOFSupport $dof_type = NODE_DOF$, size_t $nb_dof = 0$)

Define mesh class to size vector.

Parameters

in	m	Mesh instance
in	dof_type	Parameter to precise the type of degrees of freedom. To be chosen among the enumerated values: <code>NODE_DOF</code> , <code>ELEMENT_DOF</code> , <code>SIDE_DOF</code> , <code>EDGE_DOF</code> [Default: <code>NODE_DOF</code>]
in	nb_dof	Number of degrees of freedom per node, element or side. If nb_dof is set to 0 the constructor picks this number from the Mesh instance [Default: 0]

void setSize (size_t nx , size_t $ny = 1$, size_t $nz = 1$)

Set vector size (for 1-D, 2-D or 3-D cases)

This function allocates memory for the vector but does not initialize its components

Parameters

in	nx	Number of grid points in x-direction
in	ny	Number of grid points in y-direction [Default: 1]
in	nz	Number of grid points in z-direction [Default: 1]

void resize (size_t n)

Set vector size.

This function allocates memory for the vector but does not initialize its components

Parameters

in	<i>n</i>	Size of vector
-----------	----------	----------------

void resize (size_t *n*, T_ *v*)

Set vector size and initialize to a constant value.

This function allocates memory for the vector

Parameters

in	<i>n</i>	Size of vector
in	<i>v</i>	Value to assign to vector entries

void setDOFType (DOFSupport *dof_type*)

Set DOF type of vector.

The DOF type combined with number of DOF per component enable determining the size of vector

Parameters

in	<i>dof_type</i>	Type of degrees of freedom. Value to be chosen among the enumerated values: NODE_DOF, ELEMENT_DOF, SIDE_DOF or EDGE_DOF
-----------	-----------------	---

void setDG (int *degree* = 1)

Set Discontinuous Galerkin type vector.

When the vector is associated to a mesh, this one is sized differently if the [DG](#) method is used.

Parameters

in	<i>degree</i>	Polynomial degree of the DG method [Default: 1]
-----------	---------------	---

bool isGrid () const

Say if vector is constructed for a grid.

Vectors constructed for grids are defined with the help of a [Grid](#) instance

Returns

true if vector is constructed with a [Grid](#) instance

bool WithMesh () const

Return true if vector contains a [Mesh](#) pointer, false if not.

A [Vect](#) instance can be constructed using mesh information

DOFSupport getDOFType () const

Return DOF type of vector

Returns

dof_type Type of degrees of freedom. Value among the enumerated values: NODE_DOF, ELEMENT_DOF, SIDE_DOF or EDGE_DOF

real_t Norm (NormType *t*) const

Compute a norm of vector.

Parameters

in	t	Norm type to compute: To choose among enumerate values↵ : NORM1: 1-norm WNORM1: Weighted 1-norm (Discrete L1-norm) NORM2: 2-norm WNORM2: Weighted 2-norm (Discrete L2-norm) NORM_MAX: max norm (Infinity norm)
-----------	----------	---

Returns

Value of norm

Warning

This function is available for real valued vectors only

real_t getNorm1 () const

Calculate 1-norm of vector.

Remarks

This function is available only if the template parameter is double or complex<double>

real_t getNorm2 () const

Calculate 2-norm (Euclidean norm) of vector.

Remarks

This function is available only if the template parameter is double or complex<double>

real_t getNormMax () const

Calculate Max-norm (Infinite norm) of vector.

Remarks

This function is available only if the template parameter is double or complex<double>

real_t getWNorm2 () const

Calculate weighted 2-norm of vector.

The weighted 2-norm is the 2-Norm of the vector divided by the square root of its size

void setIJK (const string & exp)

Assign a given function (given by an interpretable algebraic expression) of indices components of vector.

This function enable assigning a value to vector entries as function of indices

Parameters

in	<i>exp</i>	Regular algebraic expression to assign. It must involve the variables i, j and/or k.
-----------	------------	--

void setNodeBC (Mesh & *m*, int *code*, T_ *val*, size_t *dof*)

Assign a given value to components of vector with given code.

Vector components are assumed nodewise

Parameters

in	<i>m</i>	Mesh instance
in	<i>code</i>	The value is assigned if the node has this code
in	<i>val</i>	Value to assign
in	<i>dof</i>	Degree of freedom to assign

void setNodeBC (Mesh & *m*, int *code*, T_ *val*)

Assign a given value to components of vector with given code.

Vector components are assumed nodewise. Here all dofs of nodes with given code will be assigned

Parameters

in	<i>m</i>	Mesh instance
in	<i>code</i>	The value is assigned if the node has this code
in	<i>val</i>	Value to assign

void setSideBC (Mesh & *m*, int *code*, T_ *val*, size_t *dof*)

Assign a given value to components of vector corresponding to sides with given code.

Vector components are assumed nodewise

Parameters

in	<i>m</i>	Instance of mesh
in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>val</i>	Value to prescribe
in	<i>dof</i>	Degree of Freedom for which the value is assigned [default: 1]

void setNodeBC (Mesh & *m*, int *code*, const string & *exp*, size_t *dof*)

Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.

Vector components are assumed nodewise

Parameters

in	<i>m</i>	Instance of mesh
in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>exp</i>	Regular algebraic expression to prescribe
in	<i>dof</i>	Degree of Freedom for which the value is assigned

void setNodeBC (Mesh & *m*, int *code*, const string & *exp*)

Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.

Vector components are assumed nodewise. Case of 1-DOF problem

Parameters

in	<i>m</i>	Instance of mesh
in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>exp</i>	Regular algebraic expression to prescribe

void setSideBC (Mesh & *m*, int *code*, const string & *exp*, size_t *dof*)

Assign a given function (given by an interpretable algebraic expression) to components of vector corresponding to sides with given code.

Vector components are assumed nodewise

Parameters

in	<i>m</i>	Instance of mesh
in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>exp</i>	Regular algebraic expression to prescribe
in	<i>dof</i>	Degree of Freedom for which the value is assigned

void setSideBC (Mesh & *m*, int *code*, const string & *exp*)

Assign a given function (given by an interpretable algebraic expression) to components of vector corresponding to sides with given code.

Vector components are assumed nodewise. Case of 1-DOF problem

Parameters

in	<i>m</i>	Instance of mesh
in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>exp</i>	Regular algebraic expression to prescribe

void setNodeBC (int *code*, T_ *val*, size_t *dof*)

Assign a given value to components of vector with given code.

Vector components are assumed nodewise

Parameters

in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>val</i>	Value to prescribe
in	<i>dof</i>	Degree of Freedom for which the value is assigned [default: 1]

void setNodeBC (int *code*, T_ *val*)

Assign a given value to components of vector with given code.

Vector components are assumed nodewise. Concerns 1-DOF problems

Parameters

<code>in</code>	<code>code</code>	Code for which nodes will be assigned prescribed value
<code>in</code>	<code>val</code>	Value to prescribe

void setNodeBC (int *code*, const string & *exp*, size_t *dof*)

Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.

Vector components are assumed nodewise

Parameters

<code>in</code>	<code>code</code>	Code for which nodes will be assigned prescribed value
<code>in</code>	<code>exp</code>	Regular algebraic expression to prescribe
<code>in</code>	<code>dof</code>	Degree of Freedom for which the value is assigned [default: 1]

Warning

This member function is to be used in the case where a constructor with a [Mesh](#) has been used

void setNodeBC (int *code*, const string & *exp*)

Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.

Vector components are assumed nodewise. Concerns 1-DOF problems

Parameters

<code>in</code>	<code>code</code>	Code for which nodes will be assigned prescribed value
<code>in</code>	<code>exp</code>	Regular algebraic expression to prescribe

Warning

This member function is to be used in the case where a constructor with a [Mesh](#) has been used

void setSideBC (int *code*, const string & *exp*, size_t *dof*)

Assign a given function (given by an interpretable algebraic expression) to components of vector with given code.

Vector components are assumed nodewise

Parameters

<code>in</code>	<code>code</code>	Code for which nodes will be assigned prescribed value
<code>in</code>	<code>exp</code>	Regular algebraic expression to prescribe
<code>in</code>	<code>dof</code>	Degree of Freedom for which the value is assigned

Warning

This member function is to be used in the case where a constructor with a [Mesh](#) has been used

void setSideBC (int *code*, const string & *exp*)

Assign a given function (given by an interpreter algebraic expression) to components of vector with given code.

Vector components are assumed nodewise. Case of 1-DOF problem

Parameters

in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>exp</i>	Regular algebraic expression to prescribe

Warning

This member function is to be used in the case where a constructor with a [Mesh](#) has been used

void setSideBC (int *code*, T_ *val*, size_t *dof*)

Assign a given value to components of vector with given code.

Vector components are assumed nodewise

Parameters

in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>val</i>	Value to prescribe
in	<i>dof</i>	Degree of Freedom for which the value is assigned

Warning

This member function is to be used in the case where a constructor with a [Mesh](#) has been used

void setSideBC (int *code*, T_ *val*)

Assign a given value to components of vector with given code.

Vector components are assumed nodewise. Concerns 1-DOF problems

Parameters

in	<i>code</i>	Code for which nodes will be assigned prescribed value
in	<i>val</i>	Value to prescribe

Warning

This member function is to be used in the case where a constructor with a [Mesh](#) has been used

void removeBC (const Mesh & *ms*, const Vect< T_ > & *v*, int *dof* = 0)

Remove boundary conditions.

This member function copies to current vector a vector where only non imposed DOF are retained.

Parameters

in	<i>ms</i>	Mesh instance
in	<i>v</i>	Vector (Vect instance to copy from)
in	<i>dof</i>	Parameter to say if all degrees of freedom are concerned (=0, Default) or if only one degree of freedom (<i>dof</i>) is inserted into vector <i>v</i> which has only one degree of freedom

void removeBC (const Vect< T_ > & v, int dof = 0)

Remove boundary conditions.

This member function copies to current vector a vector where only non imposed DOF are retained.

Parameters

in	<i>v</i>	Vector (Vect instance to copy from)
in	<i>dof</i>	Parameter to say if all degrees of freedom are concerned [Default: 0] or if only one degree of freedom (<i>dof</i>) is inserted into vector <i>v</i> which has only one degree of freedom.

Warning

This member function is to be used in the case where a constructor with a [Mesh](#) has been used

void transferBC (const Vect< T_ > & bc, int dof = 0)

Transfer boundary conditions to the vector.

Parameters

in	<i>bc</i>	Vect instance from which imposed degrees of freedom are copied to current instance
in	<i>dof</i>	Parameter to say if all degrees of freedom are concerned (=0, Default) or if only one degree of freedom (<i>dof</i>) is inserted into vector <i>v</i> which has only one degree of freedom.

void insertBC (Mesh & m, const Vect< T_ > & v, const Vect< T_ > & bc, int dof = 0)

Insert boundary conditions.

Parameters

in	<i>m</i>	Mesh instance.
in	<i>v</i>	Vect instance from which free degrees of freedom are copied to current instance.
in	<i>bc</i>	Vect instance from which imposed degrees of freedom are copied to current instance.
in	<i>dof</i>	Parameter to say if all degrees of freedom are concerned (=0, Default) or if only one degree of freedom (<i>dof</i>) is inserted into vector <i>v</i> which has only one degree of freedom by node or side

void insertBC (Mesh & m, const Vect< T_ > & v, int dof = 0)

Insert boundary conditions.

DOF with imposed boundary conditions are set to zero.

Parameters

in	<i>m</i>	Mesh instance.
in	<i>v</i>	Vect instance from which free degrees of freedom are copied to current instance.
in	<i>dof</i>	Parameter to say if all degrees of freedom are concerned (=0, Default) or if only one degree of freedom (<i>dof</i>) is inserted into vector <i>v</i> which has only one degree of freedom by node or side

void insertBC (const Vect< T_ > & v, const Vect< T_ > & bc, int dof = 0)

Insert boundary conditions.

Parameters

in	<i>v</i>	Vect instance from which free degrees of freedom are copied to current instance.
in	<i>bc</i>	Vect instance from which imposed degrees of freedom are copied to current instance.
in	<i>dof</i>	Parameter to say if all degrees of freedom are concerned (=0, Default) or if only one degree of freedom (<i>dof</i>) is inserted into vector <i>v</i> which has only one degree of freedom by node or side

void insertBC (const Vect< T_ > & v, int dof = 0)

Insert boundary conditions.

DOF with imposed boundary conditions are set to zero.

Parameters

in	<i>v</i>	Vect instance from which free degrees of freedom are copied to current instance.
in	<i>dof</i>	Parameter to say if all degrees of freedom are concerned (=0, Default) or if only one degree of freedom (<i>dof</i>) is inserted into vector <i>v</i> which has only one degree of freedom by node or side

Warning

This member function is to be used in the case where a constructor with a [Mesh](#) has been used

void Assembly (const Element & el, const Vect< T_ > & b)

Assembly of element vector into current instance.

Parameters

in	<i>el</i>	Reference to Element instance
in	<i>b</i>	Local vector to assemble (Instance of class Vect)

void Assembly (const Element & el, const T_ * b)

Assembly of element vector (as C-array) into [Vect](#) instance.

Parameters

in	<i>el</i>	Reference to Element instance
in	<i>b</i>	Local vector to assemble (C-Array)

void Assembly (const Side & *sd*, const Vect< T_ > & *b*)

Assembly of side vector into [Vect](#) instance.

Parameters

in	<i>sd</i>	Reference to Side instance
in	<i>b</i>	Local vector to assemble (Instance of class Vect)

void Assembly (const Side & *sd*, const T_ * *b*)

Assembly of side vector (as C-array) into [Vect](#) instance.

Parameters

in	<i>sd</i>	Reference to Side instance
in	<i>b</i>	Local vector to assemble (C-Array)

void getGradient (class Vect< T_ > & *v*)

Evaluate the discrete Gradient vector of the current vector.

The resulting gradient is stored in a [Vect](#) instance. This function handles node vectors assuming P_1 approximation. The gradient is then a constant vector for each element.

Parameters

in	<i>v</i>	Vect instance that contains the gradient, where $v(n,1)$, $v(n,2)$ and $v(n,3)$ are respectively the x and y and z derivatives at element n.
----	----------	---

void getGradient (Vect< Point< T_ > > & *v*)

Evaluate the discrete Gradient vector of the current vector.

The resulting gradient is stored in an [Vect](#) instance. This function handles node vectors assuming P_1 approximation. The gradient is then a constant vector for each element.

Parameters

in	<i>v</i>	Vect instance that contains the gradient, where $v(n,1).x$, $v(n,2).y$ and $v(n,3).z$ are respectively the x and y and z derivatives at element n.
----	----------	---

void getCurl (Vect< T_ > & *v*)

Evaluate the discrete curl vector of the current vector.

The resulting curl is stored in a [Vect](#) instance. This function handles node vectors assuming P_1 approximation. The curl is then a constant vector for each element.

Parameters

<code>in</code>	<code>v</code>	<code>Vect</code> instance that contains the curl, where $v(n,1)$, $v(n,2)$ and $v(n,3)$ are respectively the x and y and z curl components at element n .
-----------------	----------------	---

void getCurl (Vect< Point< T_ > > & v)

Evaluate the discrete curl vector of the current vector.

The resulting curl is stored in a `Vect` instance. This function handles node vectors assuming P_1 approximation. The curl is then a constant vector for each element.

Parameters

<code>in</code>	<code>v</code>	<code>Vect</code> instance that contains the curl, where $v(n,1) \cdot x$, $v(n,2) \cdot y$ and $v(n,3) \cdot z$ are respectively the x and y and z curl components at element n .
-----------------	----------------	---

void getSCurl (Vect< T_ > & v)

Evaluate the discrete scalar curl in 2-D of the current vector.

The resulting curl is stored in a `Vect` instance. This function handles node vectors assuming P_1 approximation. The curl is then a constant vector for each element.

Parameters

<code>in</code>	<code>v</code>	<code>Vect</code> instance that contains the scalar curl.
-----------------	----------------	---

void getDivergence (Vect< T_ > & v)

Evaluate the discrete Divergence of the current vector.

The resulting divergence is stored in a `Vect` instance. This function handles node vectors assuming P_1 approximation. The divergence is then a constant vector for each element.

Parameters

<code>in</code>	<code>v</code>	<code>Vect</code> instance that contains the divergence.
-----------------	----------------	--

real_t getAverage (const Element & el, int type) const

Return average value of vector in a given element.

Parameters

<code>in</code>	<code>el</code>	<code>Element</code> instance
<code>in</code>	<code>type</code>	Type of element. This is to be chosen among enumerated values: LINE2, TRIANG3, QUAD4, TETRA4, HEXA8, PENTA6

Vect<T_>& MultAdd (const Vect< T_ > & x, const T_ & a)

Multiply by a constant then add to a vector.

Parameters

<code>in</code>	<code>x</code>	<code>Vect</code> instance to add
<code>in</code>	<code>a</code>	Constant to multiply before adding

void Axy (T_ *a*, const Vect< T_ > & *x*)

Add to vector the product of a vector by a scalar.

Parameters

<code>in</code>	<code>a</code>	Scalar to premultiply
<code>in</code>	<code>x</code>	Vect instance by which a is multiplied. The result is added to current instance

void set (size_t i, T_ val)

Assign a value to an entry for a 1-D vector.

Parameters

<code>in</code>	<code>i</code>	Rank index in vector (starts at 1)
<code>in</code>	<code>val</code>	Value to assign

void set (size_t i, size_t j, T_ val)

Assign a value to an entry for a 2-D vector.

Parameters

<code>in</code>	<code>i</code>	First index in vector (starts at 1)
<code>in</code>	<code>j</code>	Second index in vector (starts at 1)
<code>in</code>	<code>val</code>	Value to assign

void set (size_t i, size_t j, size_t k, T_ val)

Assign a value to an entry for a 3-D vector.

Parameters

<code>in</code>	<code>i</code>	First index in vector (starts at 1)
<code>in</code>	<code>j</code>	Second index in vector (starts at 1)
<code>in</code>	<code>k</code>	Third index in vector (starts at 1)
<code>in</code>	<code>val</code>	Value to assign

void add (size_t i, T_ val)

Add a value to an entry for a 1-index vector.

Parameters

<code>in</code>	<code>i</code>	Rank index in vector (starts at 1)
<code>in</code>	<code>val</code>	Value to assign

void add (size_t i, size_t j, T_ val)

Add a value to an entry for a 2-index vector.

Parameters

<code>in</code>	<code>i</code>	First index in vector (starts at 1)
<code>in</code>	<code>j</code>	Second index in vector (starts at 1)
<code>in</code>	<code>val</code>	Value to assign

void add (size_t *i*, size_t *j*, size_t *k*, T_ *val*)

Assign a value to an entry for a 3-index vector.

Parameters

in	<i>i</i>	First index in vector (starts at 1)
in	<i>j</i>	Second index in vector (starts at 1)
in	<i>k</i>	Third index in vector (starts at 1)
in	<i>val</i>	Value to assign

T_& operator() (size_t i)

Operator () (Non constant version)

Parameters

in	<i>i</i>	Rank index in vector (starts at 1) <ul style="list-style-type: none"> • v(i) starts at v(1) to v(size()) • v(i) is the same element as v[i-1]
----	----------	---

T_ operator() (size_t i) const

Operator () (Constant version)

Parameters

in	<i>i</i>	Rank index in vector (starts at 1) <ul style="list-style-type: none"> • v(i) starts at v(1) to v(size()) • v(i) is the same element as v[i-1]
----	----------	---

T_& operator() (size_t i, size_t j)

Operator () with 2-D indexing (Non constant version, case of a grid vector).

Parameters

in	<i>i</i>	first index in vector (Number of vector components in the x-grid)
in	<i>j</i>	second index in vector (Number of vector components in the y-grid) v(i, j) starts at v(1,1) to v(getNx() , getNy())

T_ operator() (size_t i, size_t j) const

Operator () with 2-D indexing (Constant version).

Parameters

in	<i>i</i>	first index in vector (Number of vector components in the x-grid)
in	<i>j</i>	second index in vector (Number of vector components in the y-grid) v(i, j) starts at v(1,1) to v(getNx() , getNy())

T_& operator() (size_t i, size_t j, size_t k)

Operator () with 3-D indexing (Non constant version).

Parameters

in	<i>i</i>	first index in vector (Number of vector components in the x-grid)
in	<i>j</i>	second index in vector (Number of vector components in the y-grid)
in	<i>k</i>	third index in vector (Number of vector components in the z-grid) v(<i>i</i> , <i>j</i> , <i>k</i>) starts at v(1,1,1) to v(getNx() , getNy() , getNz())

T_ operator() (size_t *i*, size_t *j*, size_t *k*) const

Operator () with 3-D indexing (Constant version).

Parameters

in	<i>i</i>	first index in vector (Number of vector components in the x-grid)
in	<i>j</i>	second index in vector (Number of vector components in the y-grid)
in	<i>k</i>	third index in vector (Number of vector components in the z-grid) v(<i>i</i> , <i>j</i> , <i>k</i>) starts at v(1,1,1) to v(getNx() , getNy() , getNz())

void operator= (string *s*)

Operator =

Assign an algebraic expression to vector entries. This operator has the same effect as the member function set(*s*)

Parameters

in	<i>s</i>	String defining the algebraic expression as a function of coordinates and time
----	----------	--

Warning

A [Mesh](#) instance must have been introduced before (e.g. by a constructor)

void setUniform (T_ *vmin*, T_ *vmax*, size_t *n*)

Initialize vector entries by setting extremal values and interval.

Parameters

in	<i>vmin</i>	Minimal value to assign to the first entry
in	<i>vmax</i>	Maximal value to assign to the last entry
in	<i>n</i>	Number of points (including extremities)

Remarks

The vector has a size of *n*. It is sized in this function

Vect<T_>& operator= (const T_ & *a*)

Operator =

Assign a constant to vector entries

Parameters

in	<i>a</i>	Value to set
----	----------	--------------

Vect<T_>& operator+= (const Vect< T_ > & *v*)

Operator +=

Add vector *x* to current vector instance.

Parameters

in	<i>v</i>	Vect instance to add to instance
----	----------	--

Vect<T_>& operator+= (const T_ & *a*)

Operator +=

Add a constant to current vector entries.

Parameters

in	<i>a</i>	Value to add to vector entries
----	----------	--------------------------------

Vect<T_>& operator-= (const Vect< T_ > & *v*)

Operator -=

Parameters

in	<i>v</i>	Vect instance to subtract from
----	----------	--

Vect<T_>& operator-= (const T_ & *a*)

Operator -=

Subtract constant from vector entries.

Parameters

in	<i>a</i>	Value to subtract from
----	----------	------------------------

Vect<T_>& operator*= (const T_ & *a*)

Operator *=

Parameters

in	<i>a</i>	Value to multiply by
----	----------	----------------------

Vect<T_>& operator/= (const T_ & *a*)

Operator /=

Parameters

in	<i>a</i>	Value to divide by
----	----------	--------------------

void push_back (const T_ & v)

Add an entry to the vector.

This function is an overload of the member function push_back of the parent class vector. It adjusts in addition some vector parameters

Parameters

in	v	Entry value to add
----	-----	--------------------

T_ operator, (const Vect< T_ > & v) const

Return Dot (scalar) product of two vectors.

A typical use of this operator is double $a = (v, w)$ where v and w are 2 instances of Vect<double>

Parameters

in	v	Vect instance by which the current instance is multiplied
----	-----	---

Vect<complex.t> getFFT ()

Compute FFT transform of vector.

This member function computes the FFT (Fast Fourier Transform) of the vector contained in the instance and returns it

Returns

Vect<complex<double> > instance containing the FFT

Remarks

The size of Vect instance must be a power of two and must not exceed the value of $2^{\text{MAX_X_FFT_SIZE}}$ (This value is set in the header "constants.h")

The Vect instance can be either a Vect<double> or Vec<complex<double> >

Vect<complex.t> getInvFFT ()

Compute Inverse FFT transform of vector.

This member function computes the inverse FFT (Fast Fourier Transform) of the vector contained in the instance and returns it

Returns

Vect<complex<double> > instance containing the FFT

Remarks


The size of Vect instance must be a power of two and must not exceed the value of $2^{\text{MAX_X_FFT_SIZE}}$ (This value is set in the header "constants.h")

The Vect instance can be either a Vect<double> or Vec<complex<double> >

7.116 WaterPorous2D Class Reference

To solve water flow equations in porous media (1-D)

Inheritance diagram for WaterPorous2D:



Public Member Functions

- [WaterPorous2D](#) ()
Default Constructor.
- [WaterPorous2D](#) ([Mesh](#) &ms)
Constructor.
- [~WaterPorous2D](#) ()
Destructor.
- void [setCoef](#) ([real_t](#) cw, [real_t](#) phi, [real_t](#) rho, [real_t](#) Kx, [real_t](#) Ky, [real_t](#) mu)
Set constant coefficients.
- void [Mass](#) ()
Add mass term contribution the element matrix.
- void [Mobility](#) ()
Add mobility term contribution the element matrix.
- void [BodyRHS](#) (const [Vect](#)< [real_t](#) > &bf)
Add source right-hand side term to right-hand side.
- void [BoundaryRHS](#) (const [Vect](#)< [real_t](#) > &sf)
Add boundary right-hand side term to right-hand side.

Additional Inherited Members

7.116.1 Detailed Description

To solve water flow equations in porous media (1-D)

To solve water flow equations in porous media (2-D)

Class [WaterPorous2D](#) solves the fluid flow equations of water or any incompressible or slightly compressible fluid in a porous medium in two-dimensional configurations.

Porous media flows are modelled here by the Darcy law. The water, or any other fluid is considered as slightly compressible, i.e., its compressibility coefficient is constant.

Space discretization uses the P_1 (2-Node line) finite element method. Time integration uses class [TimeStepping](#) that provides various well known time integration schemes.

Class [WaterPorous2D](#) solves the fluid flow equations of water or any incompressible or slightly compressible fluid in a porous medium in two-dimensional configurations.

Porous media flows are modelled here by the Darcy law. The water, or any other fluid is considered as slightly compressible, i.e., its compressibility coefficient is constant.

Space discretization uses the P_1 (3-Node triangle) finite element method. Time integration uses class [TimeStepping](#) that provides various well known time integration schemes.

7.116.2 Constructor & Destructor Documentation

WaterPorous2D ()

Default Constructor.

Constructs an empty equation.

WaterPorous2D (Mesh & *ms*)

Constructor.

This constructor uses mesh and reservoir information

Parameters

in	<i>ms</i>	Mesh instance
----	-----------	-------------------------------

7.116.3 Member Function Documentation

void setCoef (real_t *cw*, real_t *phi*, real_t *rho*, real_t *Kx*, real_t *Ky*, real_t *mu*)

Set constant coefficients.

Parameters

in	<i>cw</i>	Compressibility coefficient
in	<i>phi</i>	Porosity
in	<i>rho</i>	Density
in	<i>Kx</i>	x-Absolute permeability
in	<i>Ky</i>	y-Absolute permeability
in	<i>mu</i>	Viscosity

void BodyRHS (const Vect< real_t > & *bf*) [virtual]

Add source right-hand side term to right-hand side.

Parameters

in	<i>bf</i>	Vector containing source at nodes.
----	-----------	------------------------------------

Reimplemented from [Equa.Porous< real_t, 3, 3, 2, 2 >](#).

void BoundaryRHS (const Vect< real_t > & *sf*) [virtual]

Add boundary right-hand side term to right-hand side.

Parameters

in	<i>sf</i>	Vector containing source at nodes.
----	-----------	------------------------------------

Reimplemented from [Equa.Porous< real_t, 3, 3, 2, 2 >](#).

Index

- A
 - OFELI, [139](#)
- AB2
 - OFELI, [137](#)
- ADAMS_BASHFORTH
 - OFELI, [137](#)
- AbsEqua< T_ >, [187](#)
- ActiveElementLoop
 - Finite Element Mesh, [85](#)
- Add
 - OFELI::Element, [281](#), [282](#)
 - OFELI::Mesh, [425](#), [428](#)
 - OFELI::Side, [511](#)
- add
 - OFELI, [152](#)
 - OFELI::DMatrix, [235](#)
 - OFELI::DSMatrix, [250](#)
 - OFELI::SkMatrix, [519](#)
 - OFELI::SkSMatrix, [527](#)
 - OFELI::Vect, [583](#)
- AddMidNodes
 - OFELI::Mesh, [431](#)
- Analysis
 - OFELI, [137](#)
- areClose
 - Utilities, [47](#)
- Assembly
 - OFELI::EigenProblemSolver, [264](#)
 - OFELI::Matrix, [410](#)
 - OFELI::TimeStepping, [548](#)
 - OFELI::Vect, [580](#), [581](#)
- atGauss
 - OFELI::Hexa8, [333](#)
 - OFELI::Quad4, [503](#)
- atMidEdges
 - OFELI::Triang6S, [556](#)
- AxbAssembly
 - OFELI::Equation, [310](#)
- AxialForce
 - OFELI::Beam3DL2, [197](#)
- Axpy
 - OFELI, [151](#), [154](#)
 - OFELI::BMatrix, [205](#)
 - OFELI::DMatrix, [235](#), [236](#)
 - OFELI::DSMatrix, [251](#), [252](#)
 - OFELI::Matrix, [408](#)
 - OFELI::SkMatrix, [518](#)
 - OFELI::SkSMatrix, [526](#)
 - OFELI::Vect, [582](#)
 - Utilities, [64](#), [65](#)
- b
 - OFELI, [139](#)
- BACKWARD_EULER
 - OFELI, [137](#)
- BAND
 - OFELI, [138](#)
- BCType
 - OFELI, [138](#)
- BDF2
 - OFELI, [137](#)
- BICG_SOLVER
 - OFELI, [138](#)
- BICG_STAB_SOLVER
 - OFELI, [138](#)
- BMatrix
 - OFELI::BMatrix, [204](#)
- BMatrix< T_ >, [203](#)
- BOUNDARY_TRACTION
 - OFELI, [136](#)
- BSpline
 - Utilities, [62](#)
- BUILTIN
 - OFELI, [137](#)
- BUOYANCY
 - OFELI, [137](#)
- banner
 - Utilities, [63](#)
- Bar2DL2, [191](#)
 - OFELI::Bar2DL2, [192](#), [194](#)
- Beam3DL2, [195](#)
 - OFELI::Beam3DL2, [196](#), [197](#)
- BendingMoment
 - OFELI::Beam3DL2, [198](#)
- BiCG
 - Solver, [104](#), [105](#)
- BiCGStab
 - Solver, [105](#), [106](#)
- BiotSavart, [198](#)

OFELI::BiotSavart, [199](#), [200](#)

BodyRHS

OFELI::DC1DL2, [212](#)
 OFELI::DC2DT3, [216](#)
 OFELI::DC2DT6, [221](#)
 OFELI::DC3DAT3, [223](#)
 OFELI::DC3DT4, [227](#)
 OFELI::Elas2DQ4, [268](#)
 OFELI::Elas2DT3, [272](#)
 OFELI::Elas3DH8, [275](#)
 OFELI::Elas3DT4, [276](#)
 OFELI::Equa.Laplace, [291](#)
 OFELI::Equa.Porous, [294](#)
 OFELI::Equa.Therm, [299](#)
 OFELI::Laplace1DL2, [361](#)
 OFELI::Laplace1DL3, [363](#)
 OFELI::Laplace2DT3, [365](#)
 OFELI::Laplace2DT6, [367](#)
 OFELI::WaterPorous2D, [591](#)

BoundaryNodeLoop

Finite Element Mesh, [86](#)

BoundaryRHS

OFELI::DC2DT3, [217](#)
 OFELI::DC2DT6, [221](#)
 OFELI::DC3DAT3, [223](#)
 OFELI::DC3DT4, [227](#)
 OFELI::Elas2DQ4, [268](#)
 OFELI::Elas2DT3, [272](#)
 OFELI::Elas3DH8, [274](#)
 OFELI::Elas3DT4, [276](#)
 OFELI::Equa.Laplace, [291](#)
 OFELI::Equa.Porous, [294](#)
 OFELI::Equa.Therm, [299](#)
 OFELI::Laplace1DL2, [361](#)
 OFELI::Laplace1DL3, [363](#)
 OFELI::Laplace2DT3, [365](#)
 OFELI::Laplace2DT6, [367](#)
 OFELI::WaterPorous2D, [591](#)

BoundarySideLoop

Finite Element Mesh, [86](#)

Brick, [207](#)

OFELI::Brick, [208](#)

build

OFELI::Bar2DL2, [194](#)
 OFELI::EC2D1T3, [254](#)
 OFELI::Equa.Laplace, [291](#)
 OFELI::Equa.Porous, [294](#), [295](#)
 OFELI::Equa.Therm, [299](#), [300](#)
 OFELI::LaplaceDG2DP1, [370](#)
 OFELI::NSP2DQ41, [463](#)

buildEigen

OFELI::Beam3DL2, [198](#)
 OFELI::Laplace1DL2, [360](#)
 OFELI::Laplace2DT3, [365](#)

OFELI::Laplace2DT6, [367](#)

CAPACITY

OFELI, [136](#)

CATCH_EXCEPTION

Utilities, [39](#)

CG

Solver, [107](#), [108](#)

CG.SOLVER

OFELI, [138](#)

CGS

Solver, [109](#), [110](#)

CGS.SOLVER

OFELI, [138](#)

CONSISTENT_CAPACITY

OFELI, [136](#)

CONSISTENT_MASS

OFELI, [136](#)

CONTACT

OFELI, [137](#)

CONTACT_BC

OFELI, [138](#)

CONTACT_M

OFELI, [138](#)

CONTACT_S

OFELI, [138](#)

CONVECTION

OFELI, [136](#)

CRANK_NICOLSON

OFELI, [137](#)

Capacity

OFELI::DC1DL2, [212](#)
 OFELI::DC2DT3, [215](#)
 OFELI::DC2DT6, [220](#)
 OFELI::DC3DAT3, [223](#)
 OFELI::DC3DT4, [226](#)
 OFELI::Equa.Therm, [299](#)

check

OFELI, [161](#)
 OFELI::Material, [405](#)
 OFELI::Triang3, [554](#)

check_error

OFELI::FMM2D, [320](#)
 OFELI::FMM3D, [322](#)
 OFELI::FMMSolver, [324](#)

checkSturm

OFELI::EigenProblemSolver, [265](#)

Circle, [209](#)

OFELI::Circle, [209](#)

clear

Utilities, [65](#)

Code

Finite Element Mesh, [90](#), [91](#)

Conservation Law Equations, [22](#)

- Contact
 - OFELI::Elas2DT3, [272](#)
- ContactPressure
 - OFELI::Elas2DT3, [272](#)
- Contains
 - OFELI::Element, [282](#), [283](#)
 - OFELI::Side, [513](#)
- contains
 - OFELI::IPF, [355](#)
- Convection
 - OFELI::DC1DL2, [212](#)
 - OFELI::DC2DT3, [215](#), [216](#)
 - OFELI::DC2DT6, [220](#)
 - OFELI::DC3DT4, [226](#), [227](#)
- Converged
 - Global Variables, [80](#)
- Coord
 - Finite Element Mesh, [90](#)
- createBoundarySideList
 - OFELI::Mesh, [427](#)
- createInternalSideList
 - OFELI::Mesh, [427](#)
- CurlEdgeSh
 - OFELI::Tetra4, [540](#)
- DC1DL2, [210](#)
 - OFELI::DC1DL2, [211](#)
- DC2DT3, [213](#)
 - OFELI::DC2DT3, [214](#), [215](#)
- DC2DT6, [218](#)
 - OFELI::DC2DT6, [219](#)
- DC3DAT3, [221](#)
 - OFELI::DC3DAT3, [222](#)
- DC3DT4, [224](#)
 - OFELI::DC3DT4, [225](#)
- DENSE
 - OFELI, [138](#)
- DEVIATORIC
 - OFELI, [136](#)
- DG, [228](#)
 - OFELI::DG, [228](#)
- DGElementAssembly
 - OFELI::Equation, [308](#)
- DIAG_PREC
 - OFELI, [138](#)
- DIAGONAL
 - OFELI, [138](#)
- DIFFUSION
 - OFELI, [136](#)
- DILATATION
 - OFELI, [136](#)
- DILU_PREC
 - OFELI, [138](#)
- DIRECT_SOLVER
 - OFELI, [138](#)
- dLine
 - OFELI::Figure, [318](#)
- DMatrix
 - OFELI::DMatrix, [231](#), [232](#)
- DMatrix< T_ >, [229](#)
- DOF
 - OFELI::Edge, [258](#)
 - OFELI::Node, [458](#)
 - OFELI::Side, [510](#)
- DP1toP1
 - OFELI::Reconstruction, [505](#)
- DSMatrix
 - OFELI::DSMatrix, [247](#), [248](#)
- DSMatrix< T_ >, [245](#)
- DSh
 - OFELI::Line2, [381](#)
 - OFELI::Line3, [382](#)
 - OFELI::Penta6, [486](#)
 - OFELI::Tetra4, [541](#)
 - OFELI::Triang3, [554](#)
 - OFELI::Triang6S, [556](#)
- Deactivate
 - OFELI, [159](#)
- Deform
 - OFELI::Mesh, [432](#)
- DeformMesh
 - Finite Element Mesh, [92](#)
- Delete
 - OFELI::Mesh, [429](#), [430](#)
- DeleteElement
 - OFELI::Mesh, [429](#)
- DeleteNode
 - OFELI::Mesh, [429](#)
- DeleteSide
 - OFELI::Mesh, [429](#)
- Deviator
 - OFELI::Elas2DT3, [271](#)
- DiagBC
 - OFELI::Equation, [303](#)
- DiagPrescribe
 - OFELI, [148](#)
 - OFELI::SkMatrix, [520](#)
- Diffusion
 - OFELI::DC1DL2, [212](#)
 - OFELI::DC2DT3, [215](#)
 - OFELI::DC2DT6, [220](#)
 - OFELI::DC3DAT3, [223](#)
 - OFELI::DC3DT4, [226](#)
- Dilatation
 - OFELI::Elas2DT3, [272](#)
- Discrepancy
 - Utilities, [52](#)
- Distance

Utilities, [48](#), [52](#)
 Domain, [240](#)
 OFELI::Domain, [242](#)
 Dot
 Utilities, [65](#)
 Vector and Matrix, [71](#), [75](#)
 E2T
 OFELI::PhaseChange, [487](#)
 EC2D1T3, [253](#)
 OFELI::EC2D1T3, [254](#)
 EC2D2T3, [255](#)
 OFELI::EC2D2T3, [256](#)
 EIGEN
 OFELI, [137](#)
 ELECTRIC
 OFELI, [136](#)
 EQ_CONSTRAINT
 OFELI::LPSolver, [401](#)
 ESTIM_ND_JUMP
 OFELI::Estimator, [311](#)
 ESTIM_ZZ
 OFELI::Estimator, [311](#)
 EXTERNAL_BOUNDARY
 OFELI::Side, [510](#)
 Edge, [256](#)
 OFELI::Edge, [258](#)
 EdgeList, [259](#)
 EdgeLoop
 Finite Element Mesh, [86](#)
 EdgeSh
 OFELI::Tetra4, [540](#)
 EdgesAreDOF
 OFELI::Mesh, [432](#)
 EigenProblemSolver, [260](#)
 OFELI::EigenProblemSolver, [262](#), [263](#)
 Elas2DQ4, [266](#)
 OFELI::Elas2DQ4, [267](#)
 Elas2DT3, [269](#)
 OFELI::Elas2DT3, [271](#)
 Elas3DH8, [273](#)
 OFELI::Elas3DH8, [274](#)
 Elas3DT4, [275](#)
 OFELI::Elas3DT4, [276](#)
 Electric
 OFELI::EC2D1T3, [255](#)
 Electromagnetics, [23](#)
 Element, [277](#)
 OFELI::Element, [280](#)
 element_assembly
 General Purpose Equations, [18–20](#)
 ElementAssembly
 OFELI::Equation, [306](#), [307](#), [309](#)
 ElementList, [285](#)

ElementLoop
 Finite Element Mesh, [85](#)
 ElementNodeCoordinates
 OFELI::Equation, [306](#)
 ElementNodeVector
 OFELI::Equation, [304](#), [305](#)
 ElementNodeVectorSingleDOF
 OFELI::Equation, [304](#)
 ElementSideVector
 OFELI::Equation, [305](#)
 ElementVector
 OFELI::Equation, [305](#)
 ElementsAreDOF
 OFELI::Mesh, [432](#)
 Ellipse, [286](#)
 OFELI::Ellipse, [287](#)
 EnthalpyToTemperature
 OFELI::PhaseChange, [487](#)
 Equa_Electromagnetics< T_, NEN_, NEE_, NSN_, NSE_ >, [287](#)
 Equa_Fluid
 OFELI::Equa_Fluid, [290](#)
 Equa_Fluid< T_, NEN_, NEE_, NSN_, NSE_ >, [288](#)
 Equa_Laplace
 OFELI::Equa_Laplace, [291](#)
 Equa_Laplace< T_, NEN_, NEE_, NSN_, NSE_ >, [290](#)
 Equa_Porous
 OFELI::Equa_Porous, [294](#)
 Equa_Porous< T_, NEN_, NEE_, NSN_, NSE_ >, [292](#)
 Equa_Solid
 OFELI::Equa_Solid, [296](#)
 Equa_Solid< T_, NEN_, NEE_, NSN_, NSE_ >, [295](#)
 Equa_Therm
 OFELI::Equa_Therm, [298](#)
 Equa_Therm< T_, NEN_, NEE_, NSN_, NSE_ >, [297](#)
 Equal
 Utilities, [65](#)
 Equation
 OFELI::Equation, [302](#), [303](#)
 Equation< T_, NEN_, NEE_, NSN_, NSE_ >, [300](#)
 Estimator, [310](#)
 OFELI::Estimator, [312](#)
 EstimatorType
 OFELI::Estimator, [311](#)
 eval
 OFELI::FMM2D, [320](#)
 OFELI::FMM3D, [322](#)
 execute
 OFELI::FastMarching2D, [315](#)

- ExtendSpeed
 - OFELI::FMM2D, 320
 - OFELI::FMM3D, 322
 - OFELI::FMMSolver, 324
- FE_2D_3N
 - OFELI, 137
- FE_2D_4N
 - OFELI, 137
- FE_2D_6N
 - OFELI, 137
- FE_3D_4N
 - OFELI, 137
- FE_3D_8N
 - OFELI, 137
- FE_3D_AXI3N
 - OFELI, 137
- FEShape, 315
 - OFELI::FEShape, 316
- FEType
 - OFELI, 137
- FIRST_ORDER_METHOD
 - OFELI::Muscl, 441
- FMM2D, 318
 - OFELI::FMM2D, 319, 320
- FMM3D, 320
 - OFELI::FMM3D, 321
- FMMSolver, 322
 - OFELI::FMMSolver, 323
- FORWARD_EULER
 - OFELI, 137
- Factor
 - OFELI::LocalMatrix, 393
- FactorAndSolve
 - OFELI::LocalMatrix, 393
 - OFELI::Matrix, 412, 413
- FastMarching2D, 314
 - OFELI::FastMarching2D, 314
- Figure, 317
- Finite Element Mesh, 81
 - ActiveElementLoop, 85
 - BoundaryNodeLoop, 86
 - BoundarySideLoop, 86
 - Code, 90, 91
 - Coord, 90
 - DeformMesh, 92
 - EdgeLoop, 86
 - ElementLoop, 85
 - GRAPH_MEMORY, 85
 - getMaxElementMeasure, 96
 - getMaxSideMeasure, 96
 - getMaxSize, 95
 - getMeanElementMeasure, 97
 - getMeanSideMeasure, 97
 - getMinElementMeasure, 95
 - getMinSideMeasure, 96
 - getMinSize, 95
 - Label, 88, 89
 - MeshToMesh, 92–94
 - NodeInElement, 98
 - NodeInSide, 98
 - NodeLabel, 89, 90
 - NodeLoop, 86
 - operator<<, 87, 88, 99
 - operator-, 87
 - operator==, 91, 92
 - operator&&, 86
 - operator||, 87
 - setBoundaryNodeCodes, 98
 - setNodeCodes, 97
 - SideInElement, 99
 - SideLoop, 85
 - TheEdge, 85
 - TheElement, 85
 - TheNode, 85
 - theNodeLabel, 86
 - TheSide, 85
- Fluid Dynamics, 24
- Forward
 - OFELI::ICPG1D, 336
 - OFELI::ICPG2DT, 341
 - OFELI::LCL1D, 373
 - OFELI::LCL2DT, 376
 - OFELI::LCL3DT, 379
- Funct, 324
 - OFELI::Funct, 325
- Function
 - OFELI::MyNLAS, 447
- GAUSS_LEGENDRE
 - OFELI, 139
- GE_CONSTRAINT
 - OFELI::LPSolver, 401
- GMRES_SOLVER
 - OFELI, 138
- GMRes
 - Solver, 111, 112
- GRADIENT
 - OFELI::OptSolver, 475
- GRAPH_MEMORY
 - Finite Element Mesh, 85
- GS
 - Solver, 113
- Gauss, 326
 - OFELI::Gauss, 327
- genMesh
 - OFELI::Domain, 243
- General Purpose Equations, 17

- element_assembly, 18–20
 - side_assembly, 20, 21
- get
 - OFELI, 142, 143, 153
 - OFELI::Domain, 243
 - OFELI::IPF, 355–357
 - OFELI::Mesh, 425, 426
 - OFELI::NLASSolver, 455
 - OFELI::Prescription, 501
 - OFELI::SkMatrix, 522
 - OFELI::SkSMatrix, 531
- getActiveElement
 - OFELI::Mesh, 434
- getAllEdges
 - OFELI::Mesh, 428
- getAllSides
 - OFELI::Mesh, 427
- getArray
 - OFELI::DMatrix, 240
- getArraySize
 - OFELI::IPF, 356
- getAuxFile
 - OFELI::IPF, 358
- getAverage
 - OFELI::Vect, 582
- getB1
 - OFELI::BiotSavart, 202
- getB2
 - OFELI::BiotSavart, 201
- getB3
 - OFELI::BiotSavart, 201
- getBC
 - OFELI::IPF, 352
- getBC1
 - OFELI::BiotSavart, 202
- getBC2
 - OFELI::BiotSavart, 202
- getBC3
 - OFELI::BiotSavart, 202
- getBCFile
 - OFELI::IPF, 357
- getBF
 - OFELI::IPF, 352
- getBFFFile
 - OFELI::IPF, 357
- getBamg
 - Utilities, 55
- getBoundaryNodes
 - OFELI::Mesh, 427
- getBoundarySides
 - OFELI::Mesh, 427
- getCode
 - OFELI, 158, 159
 - OFELI::Edge, 259
 - OFELI::Node, 458
 - OFELI::Side, 511
- getColHeight
 - OFELI::SkMatrix, 519
 - OFELI::SkSMatrix, 528
- getCollnd
 - OFELI, 152
- getColumn
 - OFELI::DMatrix, 233
 - OFELI::DSMatrix, 248, 249
- getComplex
 - OFELI::IPF, 355
- getComplexPar
 - OFELI::IPF, 354
- getCoord
 - OFELI::Node, 459
- getCurl
 - OFELI::Vect, 581
- getDOFType
 - OFELI::Vect, 573
- getData
 - OFELI::IPF, 353
- getDerivative
 - OFELI, 143
- getDet
 - OFELI::FEShape, 316
- getDiag
 - OFELI::Matrix, 408
- getDisp
 - OFELI::Beam3DL2, 197
- getDivergence
 - OFELI::Vect, 582
- getDouble
 - OFELI::IPF, 354, 355
- getDoublePar
 - OFELI::IPF, 353
- getEasymesh
 - Utilities, 55
- getEdgeLabel
 - OFELI::Mesh, 434
- getEigenVector
 - OFELI::EigenProblemSolver, 265
- getElementLabel
 - OFELI::Mesh, 434
- getElementNeighborElements
 - OFELI::Mesh, 428
- getElementWiseIndex
 - OFELI::Estimator, 313
- getEquation
 - OFELI::MyOpt, 449
- getFFT
 - OFELI::Vect, 589
- getFirstSideLabel
 - OFELI::Partition, 484

- getGambit
 - Utilities, [56](#)
- getGmsh
 - Utilities, [56](#)
- getGradient
 - OFELI::Vect, [581](#)
- getInit
 - OFELI::IPF, [352](#)
- getInitFile
 - OFELI::IPF, [357](#)
- getInnerProduct
 - OFELI::LocalMatrix, [394](#)
- getIntPar
 - OFELI::IPF, [353](#)
- getInteger
 - OFELI::IPF, [354](#)
- getInternalEnergy
 - OFELI::ICPG1D, [336](#)
- getInterpolate
 - OFELI::Line2, [381](#)
- getInvFFT
 - OFELI::Vect, [589](#)
- getLevel
 - OFELI::Node, [459](#)
- getList
 - OFELI::Mesh, [433](#)
- getLocal
 - OFELI::LocalVect, [398](#)
- getLocalPoint
 - OFELI::FEShape, [316](#), [317](#)
- getMach
 - OFELI::ICPG1D, [336](#)
- getMatlab
 - Utilities, [57](#)
- getMaxElementMeasure
 - Finite Element Mesh, [96](#)
- getMaxSideMeasure
 - Finite Element Mesh, [96](#)
- getMaxSize
 - Finite Element Mesh, [95](#)
- getMaxTime
 - OFELI::IPF, [353](#)
- getMeanElementMeasure
 - Finite Element Mesh, [97](#)
- getMeanSideMeasure
 - Finite Element Mesh, [97](#)
- getMeasure
 - OFELI::Element, [284](#)
 - OFELI::Side, [512](#)
- getMesh
 - OFELI::AbsEqua, [189](#)
 - Utilities, [54](#)
- getMeshFile
 - OFELI::IPF, [357](#)
- getMinElementMeasure
 - Finite Element Mesh, [95](#)
- getMinSideMeasure
 - Finite Element Mesh, [96](#)
- getMinSize
 - Finite Element Mesh, [95](#)
- getMomentum
 - OFELI::ICPG1D, [336](#)
- getName
 - OFELI::Material, [405](#)
- getNbAcc
 - OFELI::OptSolver, [481](#)
- getNbBoundarySides
 - OFELI::Mesh, [431](#)
- getNbConnectInSubMesh
 - OFELI::Partition, [484](#)
- getNbConnectOutSubMesh
 - OFELI::Partition, [485](#)
- getNbInternalSides
 - OFELI::Mesh, [431](#)
- getNbIter
 - OFELI::IPF, [353](#)
- getNbNeigEl
 - OFELI::Node, [459](#)
- getNbNeigElements
 - OFELI::Element, [283](#)
- getNbOutOfBounds
 - OFELI::OptSolver, [481](#)
- getNbSteps
 - OFELI::IPF, [353](#)
- getNeigEl
 - OFELI::Node, [459](#)
- getNeighborElement
 - OFELI::Element, [283](#)
 - OFELI::Side, [512](#)
- getNetgen
 - Utilities, [57](#)
- getNodeLabel
 - OFELI::Edge, [259](#)
 - OFELI::Mesh, [434](#)
- getNodeLabelInMesh
 - OFELI::Partition, [484](#)
- getNodeLabelInSubMesh
 - OFELI::Partition, [483](#)
- getNodeNeighborElements
 - OFELI::Mesh, [428](#)
- getNodeWiseIndex
 - OFELI::Estimator, [313](#)
- getNorm1
 - OFELI::Vect, [573](#)
- getNorm2
 - OFELI::Vect, [574](#)
- getNormMax
 - OFELI::Vect, [574](#)

- getNormal
 - OFELI::Side, 512
- getNy
 - OFELI, 158
- getNz
 - OFELI, 158
- getObjective
 - OFELI::LPSolver, 403
- getOtherNeighborElement
 - OFELI::Side, 512
- getOutput
 - OFELI::IPF, 352
- getP
 - OFELI::ICPG2DT, 342
- getPlot
 - OFELI::IPF, 352
- getPlotFile
 - OFELI::IPF, 357
- getPointDoublePar
 - OFELI::IPF, 353
- getPrescriptionFile
 - OFELI::IPF, 358
- getProject
 - OFELI::IPF, 357
- getR
 - OFELI::ICPG2DT, 342
- getRefCoord
 - OFELI::Line2, 381
- getRestartFile
 - OFELI::IPF, 357
- getRow
 - OFELI::DMatrix, 233
 - OFELI::DSMatrix, 249
- getSCurl
 - OFELI::Vect, 582
- getSF
 - OFELI::IPF, 352
- getSFFile
 - OFELI::IPF, 357
- getSave
 - OFELI::IPF, 352
- getSaveFile
 - OFELI::IPF, 357
- getSecondSideLabel
 - OFELI::Partition, 484
- getSideLabel
 - OFELI::Mesh, 434
- getSideWiseIndex
 - OFELI::Estimator, 313
- getSignedDistance
 - OFELI::Brick, 208
 - OFELI::Circle, 210
 - OFELI::Ellipse, 287
 - OFELI::Figure, 318
 - OFELI::Polygon, 495
 - OFELI::Rectangle, 507
 - OFELI::Sphere, 533
 - OFELI::Triangle, 557
- getSolution
 - OFELI::MeshAdapt, 438
 - OFELI::OptSolver, 481
- getSolutionBB
 - OFELI::MeshAdapt, 438
- getSolutionbb
 - OFELI::MeshAdapt, 438
- getSoundSpeed
 - OFELI::ICPG1D, 336
- getStresses
 - OFELI::Bar2DL2, 194
- getString
 - OFELI::IPF, 354
- getStringPar
 - OFELI::IPF, 353
- getSubMesh
 - OFELI::Partition, 484
- getTemperature
 - OFELI::OptSolver, 481
- getTetgen
 - Utilities, 58
- getTime
 - OFELI::Timer, 542
- getTimeDerivative
 - OFELI::ODESolver, 472, 473
- getTimeStep
 - OFELI::IPF, 353
- getTolerance
 - OFELI::IPF, 353
- getTotalEnergy
 - OFELI::ICPG1D, 336
- getTriangle
 - Utilities, 58
- getUnitNormal
 - OFELI::Element, 284
 - OFELI::Side, 512
- getV
 - OFELI::ICPG2DT, 342
- getValue
 - OFELI, 143, 145
- getWNorm2
 - OFELI::Vect, 574
- getXYZ
 - OFELI::Node, 459
- Global Variables, 78
 - Converged, 80
 - InitPetsc, 80
 - MaxNbIterations, 79
 - NbTimeSteps, 79
 - theEdge, 79

- theElement, 78
- theFinalTime, 80
- theIteration, 79
- theNode, 78
- theSide, 79
- theStep, 79
- theTime, 80
- theTimeStep, 80
- theTolerance, 80
- Verbosity, 79
- Grad
 - OFELI::DC2DT3, 217
 - OFELI::DC3DAT3, 224
 - OFELI::DC3DT4, 227
 - OFELI::Hexa8, 333
 - OFELI::Quad4, 503
 - OFELI::Triang3, 554
- Gradient
 - OFELI::MyNLA, 447
 - OFELI::MyOpt, 449
- Grid, 328
 - OFELI, 155, 156
- HEAT_FLUX
 - OFELI, 137
- HEAT_SOURCE
 - OFELI, 136
- HEUN
 - OFELI, 137
- HLL_SOLVER
 - OFELI::Muscl, 442
- HLLC_SOLVER
 - OFELI::Muscl, 442
- Heat Transfer, 29
- HelmholtzBT3, 330
 - OFELI::HelmholtzBT3, 331
- Hexa8, 331
- ICPG1D, 333
 - OFELI::ICPG1D, 335
- ICPG2DT, 338
 - OFELI::ICPG2DT, 340
- ICPG3DT, 342
 - OFELI::ICPG3DT, 344, 345
- IDENT_PREC
 - OFELI, 138
- IDENTITY
 - OFELI, 138
- ILU_PREC
 - OFELI, 138
- INTERNAL_BOUNDARY
 - OFELI::Side, 510
- INTERNAL_SIDE
 - OFELI::Side, 510
- IOField, 347
 - OFELI, 139, 140
- IPF, 349
 - OFELI::IPF, 352
- Imag
 - Vector and Matrix, 75
- InitPetsc
 - Global Variables, 80
- Initialize
 - OFELI::Muscl2DT, 445
- Input/Output, 30
 - MAX_ARRAY_SIZE, 30
 - MAX_INPUT_STRING_LENGTH, 30
 - MAX_NB_PAR, 30
- insertBC
 - OFELI::Vect, 579, 580
- insertCircle
 - OFELI::Domain, 244
- insertLine
 - OFELI::Domain, 244
- insertRequiredEdge
 - OFELI::Domain, 245
- insertRequiredVertex
 - OFELI::Domain, 245
- insertSubDomain
 - OFELI::Domain, 245
- insertVertex
 - OFELI::Domain, 243
- IntegND
 - OFELI::EC2D1T3, 255
- Integration, 345
 - OFELI::Integration, 346
- IntegrationScheme
 - OFELI, 138
- Interface Problems, 25
- Invert
 - OFELI::LocalMatrix, 394
- isActive
 - OFELI, 160
- isCloseTo
 - OFELI::Point, 491
- isFactorized
 - OFELI::Matrix, 413
- isGrid
 - OFELI::Vect, 573
- IsIn
 - OFELI::Element, 285
- isOnBoundary
 - OFELI::Edge, 259
 - OFELI::Element, 284
 - OFELI::Node, 459
 - OFELI::Side, 512
- Iter
 - OFELI, 160

Iter< T_ >, 358
 Iteration
 OFELI, 138
 IterationLoop
 Solver, 104

 Jacobi
 Solver, 113
 JouleHeating
 OFELI::DC2DT3, 218

 LCL1D, 370
 LCL2DT, 374
 OFELI::LCL2DT, 375
 LCL3DT, 376
 OFELI::LCL3DT, 378
 LCapacity
 OFELI::DC1DL2, 211
 OFELI::DC2DT3, 215
 OFELI::DC2DT6, 220
 OFELI::DC3DAT3, 222
 OFELI::DC3DT4, 226
 OFELI::Equa_Therm, 298
 LE_CONSTRAINT
 OFELI::LPSolver, 401
 LEAP_FROG
 OFELI, 137
 LEFT_RECTANGLE
 OFELI, 139
 LF_SOLVER
 OFELI::Muscl, 442
 LMass
 OFELI::Bar2DL2, 194
 OFELI::Elas2DT3, 271
 OFELI::Equa_Solid, 296
 LOAD
 OFELI, 136
 LORENTZ_FORCE
 OFELI, 137
 LPSolver, 400
 OFELI::LPSolver, 401
 LUMPED_CAPACITY
 OFELI, 136
 LUMPED_MASS
 OFELI, 136
 Label
 Finite Element Mesh, 88, 89
 Laplace equation, 26
 Laplace1D
 OFELI, 147, 153
 Laplace1DL2, 359
 OFELI::Laplace1DL2, 360
 Laplace1DL3, 361
 OFELI::Laplace1DL3, 362, 363

Laplace2D
 OFELI, 148
 Laplace2DT3, 363
 OFELI::Laplace2DT3, 364, 365
 Laplace2DT6, 366
 OFELI::Laplace2DT6, 367
 LaplaceDG2DP1, 368
 OFELI::LaplaceDG2DP1, 369
 Limiter
 OFELI::Muscl, 441
 Line2, 379
 OFELI::Line2, 380
 Line3, 381
 LinearExchange
 OFELI::DC2DT3, 216
 LinearSolver
 OFELI::LinearSolver, 384–386
 LinearSolver< T_ >, 382
 LocalMatrix
 OFELI::LocalMatrix, 390
 LocalMatrix< T_, NR_, NC_ >, 388
 LocalNodeVector
 OFELI::Equation, 304
 LocalVect
 OFELI::LocalVect, 396
 LocalVect< T_, N_ >, 394
 Localize
 OFELI::LocalMatrix, 391
 OFELI::LocalVect, 398

 MAGNETIC
 OFELI, 136
 MASS
 OFELI, 136
 MAX_ARRAY_SIZE
 Input/Output, 30
 MAX_INPUT_STRING_LENGTH
 Input/Output, 30
 MAX_LIMITER
 OFELI::Muscl, 441
 MAX_NB_INPUT_FIELDS
 Solver, 103
 MAX_NB_MESHES
 Solver, 103
 MAX_NB_PAR
 Input/Output, 30
 MAX_SOLVER
 OFELI::Muscl, 442
 MID_RECTANGLE
 OFELI, 139
 MINMOD_LIMITER
 OFELI::Muscl, 441
 MOBILITY
 OFELI, 136

MULTI_SLOPE_M_METHOD
 OFELI::Muscl, [441](#)
 MULTI_SLOPE_Q_METHOD
 OFELI::Muscl, [441](#)
 Magnetic
 OFELI::EC2D1T3, [254](#)
 Mass
 OFELI::Bar2DL2, [194](#)
 OFELI::Elas2DT3, [271](#)
 OFELI::Equa_Solid, [297](#)
 Material, [403](#)
 OFELI::Material, [405](#)
 Matrix
 OFELI::Matrix, [408](#)
 Matrix< T_ >, [405](#)
 MatrixType
 OFELI, [137](#)
 MaxNbIterations
 Global Variables, [79](#)
 Media
 OFELI::Elas2DT3, [271](#)
 OFELI::Elas3DT4, [276](#)
 Mesh, [415](#)
 OFELI::Mesh, [421–424](#)
 MeshAdapt, [434](#)
 OFELI::MeshAdapt, [437](#)
 MeshToMesh
 Finite Element Mesh, [92–94](#)
 Method
 OFELI::Muscl, [441](#)
 Modulus
 Vector and Matrix, [75](#)
 Mult
 OFELI, [150](#)
 OFELI::DMatrix, [235](#)
 OFELI::LocalMatrix, [393](#)
 OFELI::SkMatrix, [519](#)
 OFELI::SkSMatrix, [527](#)
 MultAdd
 OFELI, [150, 151](#)
 OFELI::DMatrix, [234, 235](#)
 OFELI::DSMatrix, [251](#)
 OFELI::LocalMatrix, [392](#)
 OFELI::SkMatrix, [518, 519](#)
 OFELI::SkSMatrix, [527](#)
 OFELI::Vect, [582](#)
 MultAddScal
 OFELI::LocalMatrix, [392](#)
 Muscl, [439](#)
 Muscl1D, [443](#)
 Muscl2DT, [444](#)
 Muscl3DT, [445](#)
 MyNLAS, [446](#)
 OFELI::MyNLAS, [447](#)

MyOpt, [448](#)
 OFELI::MyOpt, [448](#)
 NELDER_MEAD
 OFELI::OptSolver, [476](#)
 NEWMARK
 OFELI, [137](#)
 NEWTON
 OFELI::OptSolver, [476](#)
 NLASSolver, [449](#)
 OFELI::NLASSolver, [451, 452](#)
 NONE
 OFELI, [137](#)
 NORM1
 OFELI, [185](#)
 NORM2
 OFELI, [185](#)
 NORM_MAX
 OFELI, [185](#)
 NSP2DQ41, [461](#)
 OFELI::NSP2DQ41, [462](#)
 NbTimeSteps
 Global Variables, [79](#)
 Node, [455](#)
 OFELI::Node, [457](#)
 NodeInElement
 Finite Element Mesh, [98](#)
 NodeInSide
 Finite Element Mesh, [98](#)
 NodeLabel
 Finite Element Mesh, [89, 90](#)
 NodeList, [459](#)
 NodeLoop
 Finite Element Mesh, [86](#)
 NodesAreDOF
 OFELI::Mesh, [432](#)
 Norm
 OFELI::Vect, [573](#)
 NormType
 OFELI, [185](#)
 Normalize
 OFELI::Point, [490](#)
 Nrm2
 Utilities, [65](#)
 NumberEquations
 OFELI::Mesh, [427](#)
 OBJECTIVE
 OFELI::LPSolver, [401](#)
 ODESolver, [463](#)
 OFELI::ODESolver, [466](#)
 OFELI, [117, 163](#)
 A, [139](#)
 AB2, [137](#)

ADAMS.BASHFORTH, 137
 add, 152
 Analysis, 137
 Axy, 151, 154
 b, 139
 BACKWARD_EULER, 137
 BAND, 138
 BCType, 138
 BDF2, 137
 BICG_SOLVER, 138
 BICG_STAB_SOLVER, 138
 BOUNDARY_TRACTION, 136
 BUILTIN, 137
 BUOYANCY, 137
 CAPACITY, 136
 CG_SOLVER, 138
 CGS_SOLVER, 138
 CONSISTENT_CAPACITY, 136
 CONSISTENT_MASS, 136
 CONTACT, 137
 CONTACT_BC, 138
 CONTACT_M, 138
 CONTACT_S, 138
 CONVECTION, 136
 CRANK_NICOLSON, 137
 check, 161
 DENSE, 138
 DEVIATORIC, 136
 DIAG_PREC, 138
 DIAGONAL, 138
 DIFFUSION, 136
 DILATATION, 136
 DILU_PREC, 138
 DIRECT_SOLVER, 138
 Deactivate, 159
 DiagPrescribe, 148
 EIGEN, 137
 ELECTRIC, 136
 FE_2D_3N, 137
 FE_2D_4N, 137
 FE_2D_6N, 137
 FE_3D_4N, 137
 FE_3D_8N, 137
 FE_3D_AXI3N, 137
 FEType, 137
 FORWARD_EULER, 137
 GAUSS_LEGENDRE, 139
 GMRES_SOLVER, 138
 get, 142, 143, 153
 getCode, 158, 159
 getCollnd, 152
 getDerivative, 143
 getNy, 158
 getNz, 158
 getValue, 143, 145
 Grid, 155, 156
 HEAT_FLUX, 137
 HEAT_SOURCE, 136
 HEUN, 137
 IDENT_PREC, 138
 IDENTITY, 138
 ILU_PREC, 138
 IOField, 139, 140
 IntegrationScheme, 138
 isActive, 160
 Iter, 160
 Iteration, 138
 LEAP_FROG, 137
 LEFT_RECTANGLE, 139
 LOAD, 136
 LORENTZ_FORCE, 137
 LUMPED_CAPACITY, 136
 LUMPED_MASS, 136
 Laplace1D, 147, 153
 Laplace2D, 148
 MAGNETIC, 136
 MASS, 136
 MID_RECTANGLE, 139
 MOBILITY, 136
 MatrixType, 137
 Mult, 150
 MultAdd, 150, 151
 NEWMARK, 137
 NONE, 137
 NORM1, 185
 NORM2, 185
 NORM_MAX, 185
 NormType, 185
 OPTIMIZATION, 137
 open, 140
 operator*, 150
 operator*=: 150, 154
 operator(), 149, 154
 operator=, 152, 154
 operator[], 150
 PDE_Terms, 136
 PERIODIC_A, 138
 PERIODIC_B, 138
 Preconditioner, 138
 Prev, 139
 put, 142
 RIGHT_RECTANGLE, 139
 RK3_TVD, 137
 RK4, 137
 RUNGE_KUTTA, 137
 SIMPSON, 139
 SKYLINE, 138
 SLIP, 138

- SPARSE, 138
- SSOR.PREC, 138
- STATIONARY, 137
- STEADY_STATE, 137
- STIFFNESS, 136
- SYMMETRIC, 138
- saveGMSH, 143
- set, 151
- setCode, 158
- setDomain, 157
- setFile, 143
- setGraph, 149
- setMesh, 148
- setMeshFile, 140
- setN, 158
- setSize, 149, 154
- setSolver, 152
- setXMax, 157
- setXMin, 156
- solve, 152, 155
- SpMatrix, 145–147
- TMult, 151
- TRANSIENT, 137
- TRANSIENT.ONE.STEP, 137
- TRAPEZOIDAL, 139
- TRIDIAGONAL, 138
- TimeScheme, 137
- TrMatrix, 153
- UNSYMMETRIC, 138
- VISCOSITY, 136
- WNORM1, 185
- WNORM2, 185
- OFELI::AbsEqua
 - getMesh, 189
 - setLinearSolver, 190
 - setMatrixType, 191
 - setSolver, 189
 - solveLinearSystem, 191
- OFELI::BMatrix
 - Axpy, 205
 - BMatrix, 204
 - operator*=, 206
 - operator(), 205
 - operator+=, 206
 - operator=, 206
 - setLU, 206
 - setSize, 205
 - solve, 206, 207
- OFELI::Bar2DL2
 - Bar2DL2, 192, 194
 - build, 194
 - getStresses, 194
 - LMass, 194
 - Mass, 194
 - Stiffness, 194
- OFELI::Beam3DL2
 - AxialForce, 197
 - Beam3DL2, 196, 197
 - BendingMoment, 198
 - buildEigen, 198
 - getDisp, 197
 - set, 197
 - ShearForce, 198
 - TwistingMoment, 198
- OFELI::BiotSavart
 - BiotSavart, 199, 200
 - getB1, 202
 - getB2, 201
 - getB3, 201
 - getBC1, 202
 - getBC2, 202
 - getBC3, 202
 - run, 203
 - setBoundary, 201
 - setCurrentDensity, 200
 - setMagneticInduction, 201
 - setPermeability, 201
- OFELI::Brick
 - Brick, 208
 - getSignedDistance, 208
 - operator+=, 208
 - setBoundingBox, 208
- OFELI::Circle
 - Circle, 209
 - getSignedDistance, 210
 - operator+=, 210
- OFELI::DC1DL2
 - BodyRHS, 212
 - Capacity, 212
 - Convection, 212
 - DC1DL2, 211
 - Diffusion, 212
 - LCapacity, 211
 - setInput, 213
- OFELI::DC2DT3
 - BodyRHS, 216
 - BoundaryRHS, 217
 - Capacity, 215
 - Convection, 215, 216
 - DC2DT3, 214, 215
 - Diffusion, 215
 - Grad, 217
 - JouleHeating, 218
 - LCapacity, 215
 - LinearExchange, 216
 - Periodic, 217
 - setInput, 217
- OFELI::DC2DT6

- BodyRHS, [221](#)
- BoundaryRHS, [221](#)
- Capacity, [220](#)
- Convection, [220](#)
- DC2DT6, [219](#)
- Diffusion, [220](#)
- LCapacity, [220](#)
- OFELI::DC3DAT3
 - BodyRHS, [223](#)
 - BoundaryRHS, [223](#)
 - Capacity, [223](#)
 - DC3DAT3, [222](#)
 - Diffusion, [223](#)
 - Grad, [224](#)
 - LCapacity, [222](#)
- OFELI::DC3DT4
 - BodyRHS, [227](#)
 - BoundaryRHS, [227](#)
 - Capacity, [226](#)
 - Convection, [226](#), [227](#)
 - DC3DT4, [225](#)
 - Diffusion, [226](#)
 - Grad, [227](#)
 - LCapacity, [226](#)
 - Periodic, [227](#)
- OFELI::DG
 - DG, [228](#)
- OFELI::DMatrix
 - add, [235](#)
 - Axpy, [235](#), [236](#)
 - DMatrix, [231](#), [232](#)
 - getArray, [240](#)
 - getColumn, [233](#)
 - getRow, [233](#)
 - Mult, [235](#)
 - MultAdd, [234](#), [235](#)
 - operator*=, [240](#)
 - operator(), [237](#)
 - operator+=, [240](#)
 - operator-=, [240](#)
 - operator=, [239](#), [240](#)
 - reset, [234](#)
 - set, [234](#)
 - setColumn, [234](#)
 - setDiag, [232](#)
 - setLU, [237](#)
 - setQR, [236](#)
 - setRow, [234](#)
 - setSize, [232](#), [233](#)
 - setTransLU, [237](#)
 - setTransQR, [236](#)
 - solve, [238](#), [239](#)
 - solveQR, [236](#)
 - solveTrans, [238](#), [239](#)
 - solveTransQR, [237](#)
 - TMult, [235](#)
- OFELI::DSMatrix
 - add, [250](#)
 - Axpy, [251](#), [252](#)
 - DSMatrix, [247](#), [248](#)
 - getColumn, [248](#), [249](#)
 - getRow, [249](#)
 - MultAdd, [251](#)
 - operator(), [250](#)
 - operator+=, [251](#)
 - operator-=, [251](#)
 - set, [248](#)
 - setColumn, [250](#)
 - setDiag, [250](#)
 - setLDLt, [251](#)
 - setRow, [249](#)
 - setSize, [248](#)
 - solve, [252](#)
 - TMult, [251](#)
- OFELI::Domain
 - Domain, [242](#)
 - genMesh, [243](#)
 - get, [243](#)
 - insertCircle, [244](#)
 - insertLine, [244](#)
 - insertRequiredEdge, [245](#)
 - insertRequiredVertex, [245](#)
 - insertSubDomain, [245](#)
 - insertVertex, [243](#)
 - operator*=, [243](#)
 - setOutputFile, [245](#)
- OFELI::EC2D1T3
 - build, [254](#)
 - EC2D1T3, [254](#)
 - Electric, [255](#)
 - IntegND, [255](#)
 - Magnetic, [254](#)
 - setData, [254](#)
- OFELI::EC2D2T3
 - EC2D2T3, [256](#)
- OFELI::Edge
 - DOF, [258](#)
 - Edge, [258](#)
 - getCode, [259](#)
 - getNodeLabel, [259](#)
 - isOnBoundary, [259](#)
 - operator(), [259](#)
 - setCode, [259](#)
 - setDOF, [258](#)
- OFELI::EdgeList
 - selectCode, [260](#)
 - unselectCode, [260](#)
- OFELI::EigenProblemSolver

- Assembly, [264](#)
- checkSturm, [265](#)
- EigenProblemSolver, [262](#), [263](#)
- getEigenvector, [265](#)
- run, [264](#)
- runSubSpace, [265](#)
- SAssembly, [264](#)
- setMatrix, [263](#), [264](#)
- setPDE, [264](#)
- setSubspaceDimension, [265](#)
- setTolerance, [265](#)
- OFELI::Elas2DQ4
 - BodyRHS, [268](#)
 - BoundaryRHS, [268](#)
 - Elas2DQ4, [267](#)
 - PlaneStrain, [268](#)
 - PlaneStress, [268](#)
 - Strain, [268](#)
 - Stress, [268](#), [269](#)
- OFELI::Elas2DT3
 - BodyRHS, [272](#)
 - BoundaryRHS, [272](#)
 - Contact, [272](#)
 - ContactPressure, [272](#)
 - Deviator, [271](#)
 - Dilatation, [272](#)
 - Elas2DT3, [271](#)
 - LMass, [271](#)
 - Mass, [271](#)
 - Media, [271](#)
 - Periodic, [273](#)
 - Reaction, [272](#)
 - Strain, [273](#)
 - Stress, [273](#)
- OFELI::Elas3DH8
 - BodyRHS, [275](#)
 - BoundaryRHS, [274](#)
 - Elas3DH8, [274](#)
- OFELI::Elas3DT4
 - BodyRHS, [276](#)
 - BoundaryRHS, [276](#)
 - Elas3DT4, [276](#)
 - Media, [276](#)
- OFELI::Element
 - Add, [281](#), [282](#)
 - Contains, [282](#), [283](#)
 - Element, [280](#)
 - getMeasure, [284](#)
 - getNbNeigElements, [283](#)
 - getNeighborElement, [283](#)
 - getUnitNormal, [284](#)
 - IsIn, [285](#)
 - isOnBoundary, [284](#)
 - operator(), [282](#), [284](#)
 - Replace, [281](#)
 - set, [282](#)
 - setChild, [284](#)
 - setCode, [281](#), [282](#)
 - setDOF, [282](#)
 - setLabel, [280](#)
 - setSide, [284](#)
- OFELI::ElementList
 - selectLevel, [286](#)
 - unselectCode, [286](#)
- OFELI::Ellipse
 - Ellipse, [287](#)
 - getSignedDistance, [287](#)
 - operator+=, [287](#)
- OFELI::Equa.Fluid
 - Equa.Fluid, [290](#)
- OFELI::Equa.Laplace
 - BodyRHS, [291](#)
 - BoundaryRHS, [291](#)
 - build, [291](#)
 - Equa.Laplace, [291](#)
- OFELI::Equa.Porous
 - BodyRHS, [294](#)
 - BoundaryRHS, [294](#)
 - build, [294](#), [295](#)
 - Equa.Porous, [294](#)
 - run, [295](#)
- OFELI::Equa.Solid
 - Equa.Solid, [296](#)
 - LMass, [296](#)
 - Mass, [297](#)
- OFELI::Equa.Therm
 - BodyRHS, [299](#)
 - BoundaryRHS, [299](#)
 - build, [299](#), [300](#)
 - Capacity, [299](#)
 - Equa.Therm, [298](#)
 - LCapacity, [298](#)
 - setStab, [298](#)
- OFELI::Equation
 - AxbAssembly, [310](#)
 - DGElementAssembly, [308](#)
 - DiagBC, [303](#)
 - ElementAssembly, [306](#), [307](#), [309](#)
 - ElementNodeCoordinates, [306](#)
 - ElementNodeVector, [304](#), [305](#)
 - ElementNodeVectorSingleDOF, [304](#)
 - ElementSideVector, [305](#)
 - ElementVector, [305](#)
 - Equation, [302](#), [303](#)
 - LocalNodeVector, [304](#)
 - setMaterialProperty, [310](#)
 - SideAssembly, [309](#), [310](#)
 - SideNodeCoordinates, [306](#)

- SideNodeVector, 304
- SideSideVector, 304
- SideVector, 306
- updateBC, 303
- OFELI::Estimator
 - ESTIM_ND_JUMP, 311
 - ESTIM_ZZ, 311
 - Estimator, 312
 - EstimatorType, 311
 - getElementWiseIndex, 313
 - getNodeWiseIndex, 313
 - getSideWiseIndex, 313
 - setSolution, 313
 - setType, 313
- OFELI::FEShape
 - FEShape, 316
 - getDet, 316
 - getLocalPoint, 316, 317
 - Sh, 316
- OFELI::FMM2D
 - check_error, 320
 - eval, 320
 - ExtendSpeed, 320
 - FMM2D, 319, 320
- OFELI::FMM3D
 - check_error, 322
 - eval, 322
 - ExtendSpeed, 322
 - FMM3D, 321
- OFELI::FMMSolver
 - check_error, 324
 - ExtendSpeed, 324
 - FMMSolver, 323
- OFELI::FastMarching2D
 - execute, 315
 - FastMarching2D, 314
- OFELI::Figure
 - dLine, 318
 - getSignedDistance, 318
- OFELI::Funct
 - Funct, 325
 - operator=, 326
- OFELI::Gauss
 - Gauss, 327
 - setTriangle, 328
- OFELI::HelmholtzBT3
 - HelmholtzBT3, 331
- OFELI::Hexa8
 - atGauss, 333
 - Grad, 333
 - setLocal, 332
- OFELI::ICPG1D
 - Forward, 336
 - getInternalEnergy, 336
 - getMach, 336
 - getMomentum, 336
 - getSoundSpeed, 336
 - getTotalEnergy, 336
 - ICPG1D, 335
 - setBC, 337, 338
 - setInOutflowBC, 338
 - setInitialCondition, 337
- OFELI::ICPG2DT
 - Forward, 341
 - getP, 342
 - getR, 342
 - getV, 342
 - ICPG2DT, 340
 - setBC, 341, 342
 - setReconstruction, 341
 - setSolver, 341
- OFELI::ICPG3DT
 - ICPG3DT, 344, 345
 - setReconstruction, 345
- OFELI::IPF
 - contains, 355
 - get, 355–357
 - getArraySize, 356
 - getAuxFile, 358
 - getBC, 352
 - getBCFile, 357
 - getBF, 352
 - getBFFFile, 357
 - getComplex, 355
 - getComplexPar, 354
 - getData, 353
 - getDouble, 354, 355
 - getDoublePar, 353
 - getInit, 352
 - getInitFile, 357
 - getIntPar, 353
 - getInteger, 354
 - getMaxTime, 353
 - getMeshFile, 357
 - getNbIter, 353
 - getNbSteps, 353
 - getOutput, 352
 - getPlot, 352
 - getPlotFile, 357
 - getPointDoublePar, 353
 - getPrescriptionFile, 358
 - getProject, 357
 - getRestartFile, 357
 - getSF, 352
 - getSFFFile, 357
 - getSave, 352
 - getSaveFile, 357
 - getString, 354

- getStringPar, 353
- getTimeStep, 353
- getTolerance, 353
- IPF, 352
- OFELI::Integration
 - Integration, 346
 - run, 347
 - setFunction, 346
 - setQuadrilateral, 347
 - setScheme, 346
 - setTriangle, 347
- OFELI::Iter
 - setMaxIter, 359
 - setTolerance, 359
 - setVerbose, 359
- OFELI::LCL1D
 - Forward, 373
 - runOneTimeStep, 373
 - setBC, 373
 - setInitialCondition, 372, 373
 - setVelocity, 373
- OFELI::LCL2DT
 - Forward, 376
 - LCL2DT, 375
 - runOneTimeStep, 375
 - setBC, 375, 376
 - setInitialCondition, 375
 - setVelocity, 376
- OFELI::LCL3DT
 - Forward, 379
 - LCL3DT, 378
 - setBC, 378
 - setInitialCondition, 378
 - setVelocity, 379
- OFELI::LPSolver
 - EQ_CONSTRAINT, 401
 - GE_CONSTRAINT, 401
 - getObjective, 403
 - LE_CONSTRAINT, 401
 - LPSolver, 401
 - OBJECTIVE, 401
 - run, 402
 - set, 402
 - setSize, 402
 - Setting, 401
- OFELI::Laplace1DL2
 - BodyRHS, 361
 - BoundaryRHS, 361
 - buildEigen, 360
 - Laplace1DL2, 360
 - setBoundaryCondition, 361
 - setTraction, 361
- OFELI::Laplace1DL3
 - BodyRHS, 363
 - BoundaryRHS, 363
 - Laplace1DL3, 362, 363
 - setTraction, 363
- OFELI::Laplace2DT3
 - BodyRHS, 365
 - BoundaryRHS, 365
 - buildEigen, 365
 - Laplace2DT3, 364, 365
 - Post, 366
- OFELI::Laplace2DT6
 - BodyRHS, 367
 - BoundaryRHS, 367
 - buildEigen, 367
 - Laplace2DT6, 367
- OFELI::LaplaceDG2DP1
 - build, 370
 - LaplaceDG2DP1, 369
 - run, 370
 - set, 369, 370
 - Smooth, 370
- OFELI::Line2
 - DSh, 381
 - getInterpolate, 381
 - getRefCoord, 381
 - Line2, 380
 - Sh, 381
- OFELI::Line3
 - DSh, 382
- OFELI::LinearSolver
 - LinearSolver, 384–386
 - set, 387
 - setMatrix, 386
 - setMaxIter, 386
 - setSolver, 387
 - solve, 387, 388
- OFELI::LocalMatrix
 - Factor, 393
 - FactorAndSolve, 393
 - getInnerProduct, 394
 - Invert, 394
 - LocalMatrix, 390
 - Localize, 391
 - Mult, 393
 - MultAdd, 392
 - MultAddScal, 392
 - operator*, 392
 - operator*=, 392
 - operator(), 391
 - operator+=, 391, 392
 - operator-=, 392
 - operator/=: 392
 - operator=, 391
 - solve, 393
 - Symmetrize, 393

- OFELI::LocalVect
 - getLocal, 398
 - LocalVect, 396
 - Localize, 398
 - operator*=, 399
 - operator(), 399
 - operator+=, 399
 - operator,, 400
 - operator=, 399
 - operator/ =, 400
 - operator=, 399
 - operator[], 399
- OFELI::Material
 - check, 405
 - getName, 405
 - Material, 405
 - set, 405
- OFELI::Matrix
 - Assembly, 410
 - Axpy, 408
 - FactorAndSolve, 412, 413
 - getDiag, 408
 - isFactorized, 413
 - Matrix, 408
 - operator*=, 415
 - operator(), 413, 414
 - operator+=, 414, 415
 - operator-=, 414, 415
 - operator=, 414
 - operator[], 414
 - Prescribe, 410, 411
 - PrescribeSide, 412
 - reset, 408
 - set, 413
 - setDiagonal, 410
 - solve, 412
- OFELI::Mesh
 - Add, 425, 428
 - AddMidNodes, 431
 - createBoundarySideList, 427
 - createInternalSideList, 427
 - Deform, 432
 - Delete, 429, 430
 - DeleteElement, 429
 - DeleteNode, 429
 - DeleteSide, 429
 - EdgesAreDOF, 432
 - ElementsAreDOF, 432
 - get, 425, 426
 - getActiveElement, 434
 - getAllEdges, 428
 - getAllSides, 427
 - getBoundaryNodes, 427
 - getBoundarySides, 427
 - getEdgeLabel, 434
 - getElementLabel, 434
 - getElementNeighborElements, 428
 - getList, 433
 - getNbBoundarySides, 431
 - getNbInternalSides, 431
 - getNodeLabel, 434
 - getNodeNeighborElements, 428
 - getSideLabel, 434
 - Mesh, 421–424
 - NodesAreDOF, 432
 - NumberEquations, 427
 - operator*=, 425
 - put, 433
 - Refine, 434
 - RenumberEdge, 430
 - RenumberElement, 430
 - RenumberNode, 430
 - RenumberSide, 430
 - Reorder, 428
 - Rescale, 431
 - save, 433
 - set, 431, 432
 - setDOFSupport, 426
 - setDim, 425
 - setList, 430, 431
 - setMaterial, 428
 - setNbDOFPerNode, 426
 - setPointInDomain, 426
 - SidesAreDOF, 432
- OFELI::MeshAdapt
 - getSolution, 438
 - getSolutionBB, 438
 - getSolutionbb, 438
 - MeshAdapt, 437
 - run, 439
 - saveMbb, 438
 - setMaxNbVertices, 437
 - setNoKeep, 438
 - setNoScaling, 438
 - setRatio, 437
 - setRelaxation, 437
 - setTheta, 438
- OFELI::Muscl
 - FIRST_ORDER_METHOD, 441
 - HLL_SOLVER, 442
 - HLLC_SOLVER, 442
 - LF_SOLVER, 442
 - Limiter, 441
 - MAX_LIMITER, 441
 - MAX_SOLVER, 442
 - MINMOD_LIMITER, 441
 - MULTI_SLOPE_M_METHOD, 441
 - MULTI_SLOPE_Q_METHOD, 441

- Method, [441](#)
- ROE_SOLVER, [442](#)
- RUSANOV_SOLVER, [442](#)
- SUPERBEE_LIMITER, [441](#)
- setCFL, [442](#)
- setLimiter, [443](#)
- setMethod, [443](#)
- setReconstruction, [442](#)
- setReferenceLength, [442](#)
- setTimeStep, [442](#)
- setVerbose, [442](#)
- SolverType, [441](#)
- VANALBADA_LIMITER, [441](#)
- VANLEER_LIMITER, [441](#)
- VFROE_SOLVER, [442](#)
- OFELI::Muscl2DT
 - Initialize, [445](#)
 - setReconstruction, [445](#)
- OFELI::Muscl3DT
 - setReconstruction, [446](#)
- OFELI::MyNLAS
 - Function, [447](#)
 - Gradient, [447](#)
 - MyNLAS, [447](#)
- OFELI::MyOpt
 - getEquation, [449](#)
 - Gradient, [449](#)
 - MyOpt, [448](#)
 - Objective, [449](#)
 - setEquation, [449](#)
- OFELI::NLASSolver
 - get, [455](#)
 - NLASSolver, [451](#), [452](#)
 - setDf, [454](#)
 - setFunction, [452](#)
 - setGradient, [452](#), [454](#)
 - setInitial, [454](#), [455](#)
 - setMaxIter, [452](#)
 - setPDE, [454](#)
 - setTolerance, [452](#)
 - setf, [454](#)
- OFELI::NSP2DQ41
 - build, [463](#)
 - NSP2DQ41, [462](#)
 - Periodic, [463](#)
 - runOneTimeStep, [463](#)
 - setInput, [462](#)
 - setPenalty, [462](#)
- OFELI::Node
 - DOF, [458](#)
 - getCode, [458](#)
 - getCoord, [459](#)
 - getLevel, [459](#)
 - getNbNeigEl, [459](#)
 - getNeigEl, [459](#)
 - getXYZ, [459](#)
 - isOnBoundary, [459](#)
 - Node, [457](#)
 - setCode, [457](#), [458](#)
 - setCoord, [458](#)
 - setDOF, [458](#)
 - setLevel, [459](#)
 - setOnBoundary, [458](#)
- OFELI::NodeList
 - selectCode, [460](#)
 - selectCoordinate, [461](#)
 - unselectCode, [460](#)
- OFELI::ODESolver
 - getTimeDerivative, [472](#), [473](#)
 - ODESolver, [466](#)
 - run, [472](#)
 - runOneTimeStep, [472](#)
 - seODEVectors, [470](#)
 - set, [466](#)
 - setCoef, [466](#), [467](#)
 - setConstantMatrix, [471](#)
 - setDF, [468](#)
 - setF, [467](#)
 - setInitial, [468](#), [469](#)
 - setInitialRHS, [469](#)
 - setLinear, [467](#)
 - setLinearSolver, [471](#)
 - setMatrices, [470](#)
 - setMaxIter, [472](#)
 - setNbEq, [466](#)
 - setNewmarkParameters, [471](#)
 - setNonConstantMatrix, [471](#)
 - setRHS, [471](#)
 - setRK4RHS, [468](#)
 - setTolerance, [472](#)
 - setdFdt, [468](#)
- OFELI::OptSolver
 - GRADIENT, [475](#)
 - getNbAcc, [481](#)
 - getNbOutOfBounds, [481](#)
 - getSolution, [481](#)
 - getTemperature, [481](#)
 - NELDER_MEAD, [476](#)
 - NEWTON, [476](#)
 - OptMethod, [475](#)
 - OptSolver, [476](#)
 - run, [481](#)
 - SIMULATED_ANNEALING, [476](#)
 - setBC, [478](#)
 - setEqConstraint, [479](#)
 - setGradient, [478](#)
 - setHessian, [478](#)
 - setIneqConstraint, [478](#)

- setLowerBound, 479
- setLowerBounds, 479
- setObjective, 478
- setOptClass, 479
- setOptMethod, 476
- setSAOpt, 480
- setTolerance, 480
- setUpperBound, 479
- setUpperBounds, 479
- TRUNCATED_NEWTON, 475
- OFELI::Partition
 - getFirstSideLabel, 484
 - getNbConnectInSubMesh, 484
 - getNbConnectOutSubMesh, 485
 - getNodeLabelInMesh, 484
 - getNodeLabelInSubMesh, 483
 - getSecondSideLabel, 484
 - getSubMesh, 484
 - Partition, 483
 - put, 485
- OFELI::Penta6
 - DSh, 486
 - Penta6, 486
 - setLocal, 486
- OFELI::PhaseChange
 - E2T, 487
 - EnthalpyToTemperature, 487
- OFELI::Point
 - isCloseTo, 491
 - Normalize, 490
 - operator!=, 490
 - operator*=: 490
 - operator(), 489
 - operator+=, 490
 - operator,, 491
 - operator-=, 490
 - operator/=: 490
 - operator=, 490
 - operator==, 490
 - operator[], 489, 490
 - Point, 489
- OFELI::Point2D
 - operator!=, 494
 - operator*=: 494
 - operator(), 493
 - operator+=, 493
 - operator-=, 493
 - operator/=: 494
 - operator=, 493
 - operator==, 494
 - operator[], 493
 - Point2D, 493
- OFELI::Polygon
 - getSignedDistance, 495
 - operator+=, 495
 - Polygon, 495
 - setVertices, 495
- OFELI::Prec
 - Prec, 496, 497
 - setMatrix, 499
 - setType, 498
 - solve, 499
 - TransSolve, 499, 500
- OFELI::Prescription
 - get, 501
 - Prescription, 500
- OFELI::Quad4
 - atGauss, 503
 - Grad, 503
 - Quad4, 503
 - setLocal, 503
- OFELI::Reconstruction
 - DP1toP1, 505
 - P0toP1, 504
- OFELI::Rectangle
 - getSignedDistance, 507
 - operator+=, 507
 - Rectangle, 506
 - setBoundingBox, 507
- OFELI::Side
 - Add, 511
 - Contains, 513
 - DOF, 510
 - EXTERNAL_BOUNDARY, 510
 - getCode, 511
 - getMeasure, 512
 - getNeighborElement, 512
 - getNormal, 512
 - getOtherNeighborElement, 512
 - getUnitNormal, 512
 - INTERNAL_BOUNDARY, 510
 - INTERNAL_SIDE, 510
 - isOnBoundary, 512
 - operator(), 512
 - set, 511
 - setChild, 513
 - setCode, 511
 - setDOF, 511
 - Side, 510
 - SideType, 510
- OFELI::SideList
 - selectCode, 514
 - unselectCode, 514
- OFELI::SkMatrix
 - add, 519
 - Axpy, 518
 - DiagPrescribe, 520
 - get, 522

- getColHeight, 519
- Mult, 519
- MultAdd, 518, 519
- operator*=, 521
- operator(), 519, 520
- operator+=, 520, 521
- operator=, 520
- set, 518
- setDOF, 517
- setLU, 521
- setMesh, 517
- setSkyline, 517
- SkMatrix, 516, 517
- solve, 521
- TMult, 519
- TMultAdd, 518
- OFELI::SkSMatrix
 - add, 527
 - Axpy, 526
 - get, 531
 - getColHeight, 528
 - Mult, 527
 - MultAdd, 527
 - operator*=, 528
 - operator(), 528
 - operator+=, 528
 - operator=, 528
 - set, 526
 - setLDLt, 528
 - setMesh, 526
 - setSkyline, 526
 - SkSMatrix, 524, 525
 - solve, 529
 - solveLDLt, 529
 - TMult, 527
- OFELI::Sphere
 - getSignedDistance, 533
 - operator+=, 533
 - Sphere, 532
- OFELI::SteklovPoincare2DBE
 - run, 538
 - setExterior, 538
 - setMesh, 538
 - SteklovPoincare2DBE, 537, 538
- OFELI::TINS2DT3S
 - setInput, 550
 - TINS2DT3S, 549, 550
- OFELI::TINS3DT4S
 - setInput, 552
 - TINS3DT4S, 551
- OFELI::Tetra4
 - CurlEdgeSh, 540
 - DSh, 541
 - EdgeSh, 540
 - Sh, 540
- OFELI::TimeStepping
 - Assembly, 548
 - run, 548
 - runOneTimeStep, 548
 - SAssembly, 548
 - set, 544
 - setBC, 546
 - setConstantMatrix, 547
 - setInitial, 545
 - setInitialRHS, 546
 - setLinearSolver, 545, 547
 - setNLTerm, 547
 - setNLTerm0, 547
 - setNewmarkParameters, 546
 - setNonConstantMatrix, 547
 - setPDE, 545
 - setRHS, 546
 - setRK3_TVDRHS, 545
 - setRK4RHS, 545
 - TimeStepping, 544
- OFELI::Timer
 - getTime, 542
 - Start, 542
 - Started, 542
 - Stop, 542
- OFELI::Triang3
 - check, 554
 - DSh, 554
 - Grad, 554
 - Sh, 553
 - Triang3, 553
- OFELI::Triang6S
 - atMidEdges, 556
 - DSh, 556
 - setLocal, 556
 - Sh, 555
 - Triang6S, 555
- OFELI::Triangle
 - getSignedDistance, 557
 - operator+=, 558
 - Triangle, 557
- OFELI::Vect
 - add, 583
 - Assembly, 580, 581
 - Axpy, 582
 - getAverage, 582
 - getCurl, 581
 - getDOFType, 573
 - getDivergence, 582
 - getFFT, 589
 - getGradient, 581
 - getInvFFT, 589
 - getNorm1, 573

- getNorm2, [574](#)
- getNormMax, [574](#)
- getSCurl, [582](#)
- getWNorm2, [574](#)
- insertBC, [579](#), [580](#)
- isGrid, [573](#)
- MultAdd, [582](#)
- Norm, [573](#)
- operator*=, [587](#)
- operator(), [584](#), [585](#)
- operator+=, [587](#)
- operator,, [589](#)
- operator-=, [587](#)
- operator/=, [587](#)
- operator=, [585](#)
- push_back, [587](#)
- removeBC, [578](#)
- resize, [572](#)
- select, [570](#)
- set, [570](#), [571](#), [583](#)
- setDG, [573](#)
- setDOFType, [572](#)
- setIJK, [574](#)
- setMesh, [572](#)
- setNodeBC, [574](#)–[576](#)
- setSideBC, [575](#)–[578](#)
- setSize, [572](#)
- setUniform, [585](#)
- transferBC, [579](#)
- Vect, [567](#)–[569](#)
- WithMesh, [573](#)
- OFELI::WaterPorous2D
 - BodyRHS, [591](#)
 - BoundaryRHS, [591](#)
 - setCoef, [591](#)
 - WaterPorous2D, [591](#)
- OFELI::triangle
 - triangle, [559](#)
- OFELI_E
 - Utilities, [38](#)
- OFELI_EPSMCH
 - Utilities, [38](#)
- OFELI_GAUSS2
 - Utilities, [38](#)
- OFELI_IMAG
 - Utilities, [39](#)
- OFELI_ONEOVERPI
 - Utilities, [38](#)
- OFELI_PI
 - Utilities, [38](#)
- OFELI_SIXTH
 - Utilities, [38](#)
- OFELI_SQRT2
 - Utilities, [38](#)
- OFELI_SQRT3
 - Utilities, [38](#)
- OFELI_THIRD
 - Utilities, [38](#)
- OFELI_TOLERANCE
 - Utilities, [39](#)
- OFELI_TWELVETH
 - Utilities, [38](#)
- OFELIException, [473](#)
- OPTIMIZATION
 - OFELI, [137](#)
- Objective
 - OFELI::MyOpt, [449](#)
- open
 - OFELI, [140](#)
- operator!=
 - OFELI::Point, [490](#)
 - OFELI::Point2D, [494](#)
- operator<
 - Utilities, [48](#)
- operator<<
 - Finite Element Mesh, [87](#), [88](#), [99](#)
 - Solver, [116](#)
 - Utilities, [39](#), [40](#), [48](#), [52](#)
 - Vector and Matrix, [72](#)–[74](#), [76](#)
- operator>>
 - Vector and Matrix, [76](#)
- operator*
 - OFELI, [150](#)
 - OFELI::LocalMatrix, [392](#)
 - Utilities, [46](#), [47](#), [50](#), [51](#)
 - Vector and Matrix, [69](#)–[76](#)
- operator*=
 - OFELI, [150](#), [154](#)
 - OFELI::BMatrix, [206](#)
 - OFELI::DMatrix, [240](#)
 - OFELI::Domain, [243](#)
 - OFELI::LocalMatrix, [392](#)
 - OFELI::LocalVect, [399](#)
 - OFELI::Matrix, [415](#)
 - OFELI::Mesh, [425](#)
 - OFELI::Point, [490](#)
 - OFELI::Point2D, [494](#)
 - OFELI::SkMatrix, [521](#)
 - OFELI::SkSMatrix, [528](#)
 - OFELI::Vect, [587](#)
- operator()
 - OFELI, [149](#), [154](#)
 - OFELI::BMatrix, [205](#)
 - OFELI::DMatrix, [237](#)
 - OFELI::DSMatrix, [250](#)
 - OFELI::Edge, [259](#)
 - OFELI::Element, [282](#), [284](#)
 - OFELI::LocalMatrix, [391](#)

- OFELI::LocalVect, 399
- OFELI::Matrix, 413, 414
- OFELI::Point, 489
- OFELI::Point2D, 493
- OFELI::Side, 512
- OFELI::SkMatrix, 519, 520
- OFELI::SkSMatrix, 528
- OFELI::Vect, 584, 585
- operator+
 - Utilities, 45, 49
 - Vector and Matrix, 70, 71, 74
- operator+=
 - OFELI::BMatrix, 206
 - OFELI::Brick, 208
 - OFELI::Circle, 210
 - OFELI::DMatrix, 240
 - OFELI::DSMatrix, 251
 - OFELI::Ellipse, 287
 - OFELI::LocalMatrix, 391, 392
 - OFELI::LocalVect, 399
 - OFELI::Matrix, 414, 415
 - OFELI::Point, 490
 - OFELI::Point2D, 493
 - OFELI::Polygon, 495
 - OFELI::Rectangle, 507
 - OFELI::SkMatrix, 520, 521
 - OFELI::SkSMatrix, 528
 - OFELI::Sphere, 533
 - OFELI::Triangle, 558
 - OFELI::Vect, 587
- operator,
 - OFELI::LocalVect, 400
 - OFELI::Point, 491
 - OFELI::Vect, 589
- operator-
 - Finite Element Mesh, 87
 - Utilities, 45, 46, 49, 50
 - Vector and Matrix, 70, 71, 74
- operator-=
 - OFELI::DMatrix, 240
 - OFELI::DSMatrix, 251
 - OFELI::LocalMatrix, 392
 - OFELI::LocalVect, 399
 - OFELI::Matrix, 414, 415
 - OFELI::Point, 490
 - OFELI::Point2D, 493
 - OFELI::Vect, 587
- operator/
 - Utilities, 47, 51
 - Vector and Matrix, 70, 71, 75
- operator/=
 - OFELI::LocalMatrix, 392
 - OFELI::LocalVect, 400
 - OFELI::Point, 490
 - OFELI::Point2D, 494
 - OFELI::Vect, 587
- operator==
 - Finite Element Mesh, 91, 92
 - OFELI::Point, 490
 - OFELI::Point2D, 494
 - Utilities, 44, 48
- operator&&
 - Finite Element Mesh, 86
- operator[]
 - OFELI, 150
 - OFELI::LocalVect, 399
 - OFELI::Matrix, 414
 - OFELI::Point, 489, 490
 - OFELI::Point2D, 493
- operator| |
 - Finite Element Mesh, 87
- OptMethod
 - OFELI::OptSolver, 475
- OptSolver, 473
 - OFELI::OptSolver, 476
- P0toP1
 - OFELI::Reconstruction, 504
- PDE_Terms
 - OFELI, 136
- PERIODIC_A
 - OFELI, 138
- PERIODIC_B
 - OFELI, 138
- Partition, 481
 - OFELI::Partition, 483
- Penta6, 485
 - OFELI::Penta6, 486
- Periodic
 - OFELI::DC2DT3, 217
 - OFELI::DC3DT4, 227
 - OFELI::Elas2DT3, 273
 - OFELI::NSP2DQ41, 463
- PhaseChange, 487
- Physical properties of media, 77

PlaneStrain
 OFELI::Elas2DQ4, 268
 PlaneStress
 OFELI::Elas2DQ4, 268
 Point
 OFELI::Point, 489
 Point< T_ >, 488
 Point2D
 OFELI::Point2D, 493
 Point2D< T_ >, 491
 Polygon, 494
 OFELI::Polygon, 495
 Porous Media problems, 27
 Post
 OFELI::Laplace2DT3, 366
 Prec
 OFELI::Prec, 496, 497
 Prec< T_ >, 495
 Preconditioner
 OFELI, 138
 Prescribe
 OFELI::Matrix, 410, 411
 PrescribeSide
 OFELI::Matrix, 412
 Prescription, 500
 OFELI::Prescription, 500
 Prev
 OFELI, 139
 push.back
 OFELI::Vect, 587
 put
 OFELI, 142
 OFELI::Mesh, 433
 OFELI::Partition, 485

 qksort
 Utilities, 63, 64
 Quad4, 502
 OFELI::Quad4, 503
 QuickSort
 Utilities, 63

 RIGHT_RECTANGLE
 OFELI, 139
 RK3_TVD
 OFELI, 137
 RK4
 OFELI, 137
 ROE_SOLVER
 OFELI::Muscl, 442
 RUNGE_KUTTA
 OFELI, 137
 RUSANOV_SOLVER
 OFELI::Muscl, 442

Reaction
 OFELI::Elas2DT3, 272
 Real
 Vector and Matrix, 75
 Reconstruction, 504
 Rectangle, 505
 OFELI::Rectangle, 506
 Refine
 OFELI::Mesh, 434
 removeBC
 OFELI::Vect, 578
 RenumberEdge
 OFELI::Mesh, 430
 RenumberElement
 OFELI::Mesh, 430
 RenumberNode
 OFELI::Mesh, 430
 RenumberSide
 OFELI::Mesh, 430
 Reorder
 OFELI::Mesh, 428
 Replace
 OFELI::Element, 281
 Rescale
 OFELI::Mesh, 431
 reset
 OFELI::DMatrix, 234
 OFELI::Matrix, 408
 resize
 OFELI::Vect, 572
 Richardson
 Solver, 114
 run
 OFELI::BiotSavart, 203
 OFELI::EigenProblemSolver, 264
 OFELI::Equa_Porous, 295
 OFELI::Integration, 347
 OFELI::LPSolver, 402
 OFELI::LaplaceDG2DP1, 370
 OFELI::MeshAdapt, 439
 OFELI::ODESolver, 472
 OFELI::OptSolver, 481
 OFELI::SteklovPoincare2DBE, 538
 OFELI::TimeStepping, 548
 runOneTimeStep
 OFELI::LCL1D, 373
 OFELI::LCL2DT, 375
 OFELI::NSP2DQ41, 463
 OFELI::ODESolver, 472
 OFELI::TimeStepping, 548
 runSubSpace
 OFELI::EigenProblemSolver, 265

 SAssembly

OFELI::EigenProblemSolver, 264
 OFELI::TimeStepping, 548
 SIMPSON
 OFELI, 139
 SIMULATED_ANNEALING
 OFELI::OptSolver, 476
 SKYLINE
 OFELI, 138
 SLIP
 OFELI, 138
 SPARSE
 OFELI, 138
 SSOR
 Solver, 115
 SSOR_PREC
 OFELI, 138
 STATIONARY
 OFELI, 137
 STEADY_STATE
 OFELI, 137
 STIFFNESS
 OFELI, 136
 SUPERBEE_LIMITER
 OFELI::Muscl, 441
 SYMMETRIC
 OFELI, 138
 save
 OFELI::Mesh, 433
 saveBamg
 Utilities, 62
 saveField
 Utilities, 40, 41
 saveGMSH
 OFELI, 143
 saveGmsh
 Utilities, 44, 60
 saveGnuplot
 Utilities, 41, 42, 60
 saveMatlab
 Utilities, 60
 saveMbb
 OFELI::MeshAdapt, 438
 saveMesh
 Utilities, 59
 saveTecplot
 Utilities, 42, 61
 saveVTK
 Utilities, 43, 61
 Scale
 Utilities, 64
 Schur
 Solver, 115
 seODEVectors
 OFELI::ODESolver, 470

select
 OFELI::Vect, 570
 selectCode
 OFELI::EdgeList, 260
 OFELI::NodeList, 460
 OFELI::SideList, 514
 selectCoordinate
 OFELI::NodeList, 461
 selectLevel
 OFELI::ElementList, 286
 set
 OFELI, 151
 OFELI::Beam3DL2, 197
 OFELI::DMatrix, 234
 OFELI::DSMatrix, 248
 OFELI::Element, 282
 OFELI::LPSolver, 402
 OFELI::LaplaceDG2DP1, 369, 370
 OFELI::LinearSolver, 387
 OFELI::Material, 405
 OFELI::Matrix, 413
 OFELI::Mesh, 431, 432
 OFELI::ODESolver, 466
 OFELI::Side, 511
 OFELI::SkMatrix, 518
 OFELI::SkSMatrix, 526
 OFELI::TimeStepping, 544
 OFELI::Vect, 570, 571, 583
 setBC
 OFELI::ICPG1D, 337, 338
 OFELI::ICPG2DT, 341, 342
 OFELI::LCL1D, 373
 OFELI::LCL2DT, 375, 376
 OFELI::LCL3DT, 378
 OFELI::OptSolver, 478
 OFELI::TimeStepping, 546
 setBoundary
 OFELI::BiotSavart, 201
 setBoundaryCondition
 OFELI::Laplace1DL2, 361
 setBoundaryNodeCodes
 Finite Element Mesh, 98
 setBoundingBox
 OFELI::Brick, 208
 OFELI::Rectangle, 507
 setCFL
 OFELI::Muscl, 442
 setChild
 OFELI::Element, 284
 OFELI::Side, 513
 setCode
 OFELI, 158
 OFELI::Edge, 259
 OFELI::Element, 281, 282

OFELI::Node, [457](#), [458](#)
 OFELI::Side, [511](#)
 setCoef
 OFELI::ODESolver, [466](#), [467](#)
 OFELI::WaterPorous2D, [591](#)
 setColumn
 OFELI::DMatrix, [234](#)
 OFELI::DSMatrix, [250](#)
 setConstantMatrix
 OFELI::ODESolver, [471](#)
 OFELI::TimeStepping, [547](#)
 setCoord
 OFELI::Node, [458](#)
 setCurrentDensity
 OFELI::BiotSavart, [200](#)
 setDF
 OFELI::ODESolver, [468](#)
 setDG
 OFELI::Vect, [573](#)
 setDOF
 OFELI::Edge, [258](#)
 OFELI::Element, [282](#)
 OFELI::Node, [458](#)
 OFELI::Side, [511](#)
 OFELI::SkMatrix, [517](#)
 setDOFSupport
 OFELI::Mesh, [426](#)
 setDOFType
 OFELI::Vect, [572](#)
 setData
 OFELI::EC2D1T3, [254](#)
 setDf
 OFELI::NLASSolver, [454](#)
 setDiag
 OFELI::DMatrix, [232](#)
 OFELI::DSMatrix, [250](#)
 setDiagonal
 OFELI::Matrix, [410](#)
 setDim
 OFELI::Mesh, [425](#)
 setDomain
 OFELI, [157](#)
 setEqConstraint
 OFELI::OptSolver, [479](#)
 setEquation
 OFELI::MyOpt, [449](#)
 setExterior
 OFELI::SteklovPoincare2DBE, [538](#)
 setF
 OFELI::ODESolver, [467](#)
 setFile
 OFELI, [143](#)
 setFunction
 OFELI::Integration, [346](#)

OFELI::NLASSolver, [452](#)
 setGradient
 OFELI::NLASSolver, [452](#), [454](#)
 OFELI::OptSolver, [478](#)
 setGraph
 OFELI, [149](#)
 setHessian
 OFELI::OptSolver, [478](#)
 setIJK
 OFELI::Vect, [574](#)
 setInOutflowBC
 OFELI::ICPG1D, [338](#)
 setIneqConstraint
 OFELI::OptSolver, [478](#)
 setInitial
 OFELI::NLASSolver, [454](#), [455](#)
 OFELI::ODESolver, [468](#), [469](#)
 OFELI::TimeStepping, [545](#)
 setInitialCondition
 OFELI::ICPG1D, [337](#)
 OFELI::LCL1D, [372](#), [373](#)
 OFELI::LCL2DT, [375](#)
 OFELI::LCL3DT, [378](#)
 setInitialRHS
 OFELI::ODESolver, [469](#)
 OFELI::TimeStepping, [546](#)
 setInput
 OFELI::DC1DL2, [213](#)
 OFELI::DC2DT3, [217](#)
 OFELI::NSP2DQ41, [462](#)
 OFELI::TINS2DT3S, [550](#)
 OFELI::TINS3DT4S, [552](#)
 setLDLt
 OFELI::DSMatrix, [251](#)
 OFELI::SkSMMatrix, [528](#)
 setLU
 OFELI::BMatrix, [206](#)
 OFELI::DMatrix, [237](#)
 OFELI::SkMatrix, [521](#)
 setLabel
 OFELI::Element, [280](#)
 setLevel
 OFELI::Node, [459](#)
 setLimiter
 OFELI::Muscl, [443](#)
 setLinear
 OFELI::ODESolver, [467](#)
 setLinearSolver
 OFELI::AbsEqua, [190](#)
 OFELI::ODESolver, [471](#)
 OFELI::TimeStepping, [545](#), [547](#)
 setList
 OFELI::Mesh, [430](#), [431](#)
 setLocal

OFELI::Hexa8, 332
 OFELI::Penta6, 486
 OFELI::Quad4, 503
 OFELI::Triang6S, 556
 setLowerBound
 OFELI::OptSolver, 479
 setLowerBounds
 OFELI::OptSolver, 479
 setMagneticInduction
 OFELI::BiotSavart, 201
 setMaterial
 OFELI::Mesh, 428
 setMaterialProperty
 OFELI::Equation, 310
 setMatrices
 OFELI::ODESolver, 470
 setMatrix
 OFELI::EigenProblemSolver, 263, 264
 OFELI::LinearSolver, 386
 OFELI::Prec, 499
 setMatrixType
 OFELI::AbsEqua, 191
 setMaxIter
 OFELI::Iter, 359
 OFELI::LinearSolver, 386
 OFELI::NLASSolver, 452
 OFELI::ODESolver, 472
 setMaxNbVertices
 OFELI::MeshAdapt, 437
 setMesh
 OFELI, 148
 OFELI::SkMatrix, 517
 OFELI::SkSMatrix, 526
 OFELI::SteklovPoincare2DBE, 538
 OFELI::Vect, 572
 setMeshFile
 OFELI, 140
 setMethod
 OFELI::Muscl, 443
 setN
 OFELI, 158
 setNLTerm
 OFELI::TimeStepping, 547
 setNLTerm0
 OFELI::TimeStepping, 547
 setNbDOFPerNode
 OFELI::Mesh, 426
 setNbEq
 OFELI::ODESolver, 466
 setNewmarkParameters
 OFELI::ODESolver, 471
 OFELI::TimeStepping, 546
 setNoKeep
 OFELI::MeshAdapt, 438

setNoScaling
 OFELI::MeshAdapt, 438
 setNodeBC
 OFELI::Vect, 574–576
 setNodeCodes
 Finite Element Mesh, 97
 setNonConstantMatrix
 OFELI::ODESolver, 471
 OFELI::TimeStepping, 547
 setObjective
 OFELI::OptSolver, 478
 setOnBoundary
 OFELI::Node, 458
 setOptClass
 OFELI::OptSolver, 479
 setOptMethod
 OFELI::OptSolver, 476
 setOutputFile
 OFELI::Domain, 245
 setPDE
 OFELI::EigenProblemSolver, 264
 OFELI::NLASSolver, 454
 OFELI::TimeStepping, 545
 setPenalty
 OFELI::NSP2DQ41, 462
 setPermeability
 OFELI::BiotSavart, 201
 setPointInDomain
 OFELI::Mesh, 426
 setQR
 OFELI::DMatrix, 236
 setQuadrilateral
 OFELI::Integration, 347
 setRHS
 OFELI::ODESolver, 471
 OFELI::TimeStepping, 546
 setRK3_TVDRHS
 OFELI::TimeStepping, 545
 setRK4RHS
 OFELI::ODESolver, 468
 OFELI::TimeStepping, 545
 setRatio
 OFELI::MeshAdapt, 437
 setReconstruction
 OFELI::ICPG2DT, 341
 OFELI::ICPG3DT, 345
 OFELI::Muscl, 442
 OFELI::Muscl2DT, 445
 OFELI::Muscl3DT, 446
 setReferenceLength
 OFELI::Muscl, 442
 setRelaxation
 OFELI::MeshAdapt, 437
 setRow

- OFELI::DMatrix, 234
- OFELI::DSMatrix, 249
- setSAOpt
 - OFELI::OptSolver, 480
- setScheme
 - OFELI::Integration, 346
- setSide
 - OFELI::Element, 284
- setSideBC
 - OFELI::Vect, 575–578
- setSize
 - OFELI, 149, 154
 - OFELI::BMatrix, 205
 - OFELI::DMatrix, 232, 233
 - OFELI::DSMatrix, 248
 - OFELI::LPSolver, 402
 - OFELI::Vect, 572
- setSkyline
 - OFELI::SkMatrix, 517
 - OFELI::SkSMatrix, 526
- setSolution
 - OFELI::Estimator, 313
- setSolver
 - OFELI, 152
 - OFELI::AbsEqua, 189
 - OFELI::ICPG2DT, 341
 - OFELI::LinearSolver, 387
- setStab
 - OFELI::Equa_Therm, 298
- setSubspaceDimension
 - OFELI::EigenProblemSolver, 265
- setTheta
 - OFELI::MeshAdapt, 438
- setTimeStep
 - OFELI::Muscl, 442
- setTolerance
 - OFELI::EigenProblemSolver, 265
 - OFELI::Iter, 359
 - OFELI::NLASSolver, 452
 - OFELI::ODESolver, 472
 - OFELI::OptSolver, 480
- setTraction
 - OFELI::Laplace1DL2, 361
 - OFELI::Laplace1DL3, 363
- setTransLU
 - OFELI::DMatrix, 237
- setTransQR
 - OFELI::DMatrix, 236
- setTriangle
 - OFELI::Gauss, 328
 - OFELI::Integration, 347
- setType
 - OFELI::Estimator, 313
 - OFELI::Prec, 498
- setUniform
 - OFELI::Vect, 585
- setUpperBound
 - OFELI::OptSolver, 479
- setUpperBounds
 - OFELI::OptSolver, 479
- setVelocity
 - OFELI::LCL1D, 373
 - OFELI::LCL2DT, 376
 - OFELI::LCL3DT, 379
- setVerbose
 - OFELI::Iter, 359
 - OFELI::Muscl, 442
- setVertices
 - OFELI::Polygon, 495
- setXMax
 - OFELI, 157
- setXMin
 - OFELI, 156
- setdFdt
 - OFELI::ODESolver, 468
- setf
 - OFELI::NLASSolver, 454
- Setting
 - OFELI::LPSolver, 401
- Sh
 - OFELI::FEShape, 316
 - OFELI::Line2, 381
 - OFELI::Tetra4, 540
 - OFELI::Triang3, 553
 - OFELI::Triang6S, 555
- Shape Function, 100
- ShearForce
 - OFELI::Beam3DL2, 198
- Side, 507
 - OFELI::Side, 510
- side_assembly
 - General Purpose Equations, 20, 21
- SideAssembly
 - OFELI::Equation, 309, 310
- SideInElement
 - Finite Element Mesh, 99
- SideList, 513
- SideLoop
 - Finite Element Mesh, 85
- SideNodeCoordinates
 - OFELI::Equation, 306
- SideNodeVector
 - OFELI::Equation, 304
- SideSideVector
 - OFELI::Equation, 304
- SideType
 - OFELI::Side, 510
- SideVector

OFELI::Equation, 306
 SidesAreDOF
 OFELI::Mesh, 432
 SkMatrix
 OFELI::SkMatrix, 516, 517
 SkMatrix< T_ >, 514
 SkSMatrix
 OFELI::SkSMatrix, 524, 525
 SkSMatrix< T_ >, 522
 Smooth
 OFELI::LaplaceDG2DP1, 370
 Solid Mechanics, 28
 solve
 OFELI, 152, 155
 OFELI::BMatrix, 206, 207
 OFELI::DMatrix, 238, 239
 OFELI::DSMatrix, 252
 OFELI::LinearSolver, 387, 388
 OFELI::LocalMatrix, 393
 OFELI::Matrix, 412
 OFELI::Prec, 499
 OFELI::SkMatrix, 521
 OFELI::SkSMatrix, 529
 solveLDLt
 OFELI::SkSMatrix, 529
 solveLinearSystem
 OFELI::AbsEqua, 191
 solveQR
 OFELI::DMatrix, 236
 solveTrans
 OFELI::DMatrix, 238, 239
 solveTransQR
 OFELI::DMatrix, 237
 Solver, 101
 BiCG, 104, 105
 BiCGStab, 105, 106
 CG, 107, 108
 CGS, 109, 110
 GMRes, 111, 112
 GS, 113
 IterationLoop, 104
 Jacobi, 113
 MAX_NB.INPUT_FIELDS, 103
 MAX_NB.MESHES, 103
 operator<<, 116
 Richardson, 114
 SSOR, 115
 Schur, 115
 TimeLoop, 103
 SolverType
 OFELI::Muscl, 441
 SpMatrix
 OFELI, 145–147
 SpMatrix< T_ >, 533

Sphere, 531
 OFELI::Sphere, 532
 SqrDistance
 Utilities, 47, 51
 Start
 OFELI::Timer, 542
 Started
 OFELI::Timer, 542
 SteklovPoincare2DBE, 536
 OFELI::SteklovPoincare2DBE, 537, 538
 Stiffness
 OFELI::Bar2DL2, 194
 Stop
 OFELI::Timer, 542
 Strain
 OFELI::Elas2DQ4, 268
 OFELI::Elas2DT3, 273
 Stress
 OFELI::Elas2DQ4, 268, 269
 OFELI::Elas2DT3, 273
 Symmetrize
 OFELI::LocalMatrix, 393
 TINS2DT3S, 548
 OFELI::TINS2DT3S, 549, 550
 TINS3DT4S, 550
 OFELI::TINS3DT4S, 551
 TMult
 OFELI, 151
 OFELI::DMatrix, 235
 OFELI::DSMatrix, 251
 OFELI::SkMatrix, 519
 OFELI::SkSMatrix, 527
 TMultAdd
 OFELI::SkMatrix, 518
 TRANSIENT
 OFELI, 137
 TRANSIENT_ONE_STEP
 OFELI, 137
 TRAPEZOIDAL
 OFELI, 139
 TRIDIAGONAL
 OFELI, 138
 TRUNCATED_NEWTON
 OFELI::OptSolver, 475
 Tabulation, 538
 Tetra4, 539
 TheEdge
 Finite Element Mesh, 85
 theEdge
 Global Variables, 79
 TheElement
 Finite Element Mesh, 85
 theElement

- Global Variables, 78
- theFinalTime
 - Global Variables, 80
- theIteration
 - Global Variables, 79
- TheNode
 - Finite Element Mesh, 85
- theNode
 - Global Variables, 78
- theNodeLabel
 - Finite Element Mesh, 86
- TheSide
 - Finite Element Mesh, 85
- theSide
 - Global Variables, 79
- theStep
 - Global Variables, 79
- theTime
 - Global Variables, 80
- theTimeStep
 - Global Variables, 80
- theTolerance
 - Global Variables, 80
- TimeLoop
 - Solver, 103
- TimeScheme
 - OFELI, 137
- TimeStepping, 542
 - OFELI::TimeStepping, 544
- Timer, 541
- TrMatrix
 - OFELI, 153
- TrMatrix< T_ >, 559
- TransSolve
 - OFELI::Prec, 499, 500
- transferBC
 - OFELI::Vect, 579
- Triang3, 552
 - OFELI::Triang3, 553
- Triang6S, 554
 - OFELI::Triang6S, 555
- Triangle, 556
 - OFELI::Triangle, 557
- triangle, 558
 - OFELI::triangle, 559
- TwistingMoment
 - OFELI::Beam3DL2, 198
- UNSYMMETRIC
 - OFELI, 138
- unselectCode
 - OFELI::EdgeList, 260
 - OFELI::ElementList, 286
 - OFELI::NodeList, 460
- OFELI::SideList, 514
- updateBC
 - OFELI::Equation, 303
- Utilities, 31
 - areClose, 47
 - Axpy, 64, 65
 - BSpline, 62
 - banner, 63
 - CATCH_EXCEPTION, 39
 - clear, 65
 - Discrepancy, 52
 - Distance, 48, 52
 - Dot, 65
 - Equal, 65
 - getBamg, 55
 - getEasymesh, 55
 - getGambit, 56
 - getGmsh, 56
 - getMatlab, 57
 - getMesh, 54
 - getNetgen, 57
 - getTetgen, 58
 - getTriangle, 58
 - Nrm2, 65
 - OFELI_E, 38
 - OFELI_EPSMCH, 38
 - OFELI_GAUSS2, 38
 - OFELI_IMAG, 39
 - OFELI_ONEOVERPI, 38
 - OFELI_PI, 38
 - OFELI_SIXTH, 38
 - OFELI_SQRT2, 38
 - OFELI_SQRT3, 38
 - OFELI_THIRD, 38
 - OFELI_TOLERANCE, 39
 - OFELI_TWELVETH, 38
 - operator<, 48
 - operator<<, 39, 40, 48, 52
 - operator*, 46, 47, 50, 51
 - operator+, 45, 49
 - operator-, 45, 46, 49, 50
 - operator/, 47, 51
 - operator==, 44, 48
 - qksort, 63, 64
 - QuickSort, 63
 - saveBamg, 62
 - saveField, 40, 41
 - saveGmsh, 44, 60
 - saveGnuplot, 41, 42, 60
 - saveMatlab, 60
 - saveMesh, 59
 - saveTecplot, 42, 61
 - saveVTK, 43, 61
 - Scale, 64

- SqrDistance, [47](#), [51](#)
- VLG, [39](#)
- Xpy, [64](#)
- VANALBADA_LIMITER
 - OFELI::Muscl, [441](#)
- VANLEER_LIMITER
 - OFELI::Muscl, [441](#)
- VFROE_SOLVER
 - OFELI::Muscl, [442](#)
- VISCOSITY
 - OFELI, [136](#)
- VLG
 - Utilities, [39](#)
- Vect
 - OFELI::Vect, [567–569](#)
- Vect< T_ >, [561](#)
- Vector and Matrix, [66](#)
 - Dot, [71](#), [75](#)
 - Imag, [75](#)
 - Modulus, [75](#)
 - operator<<, [72–74](#), [76](#)
 - operator>>, [76](#)
 - operator*, [69–76](#)
 - operator+, [70](#), [71](#), [74](#)
 - operator-, [70](#), [71](#), [74](#)
 - operator/, [70](#), [71](#), [75](#)
 - Real, [75](#)
- Verbosity
 - Global Variables, [79](#)
- WNORM1
 - OFELI, [185](#)
- WNORM2
 - OFELI, [185](#)
- WaterPorous2D, [589](#)
 - OFELI::WaterPorous2D, [591](#)
- WithMesh
 - OFELI::Vect, [573](#)
- Xpy
 - Utilities, [64](#)